

## RF EXPOSURE EVALUATION

|                            |   |  |
|----------------------------|---|--|
| <b>Product Name</b>        | : | <b>HeroGoGo Hero Camera</b>  |
| <b>Model Name</b>          | : | <b>HeroGoGo 1, HeroGoGo 1S</b>   |
| <b>FCC ID</b>              | : | <b>2APORHEROGOGO</b>   |
| <b>Specification</b>       | : | <b>802.11b/g/n HT20/n HT40</b>   |
| <b>Operation Frequency</b> | : | <b>2412-2462MHz for 802.11b/g;<br/>2412-2462MHz for 802.11n(HT20);<br/>2422-2452MHz for 802.11n(HT40);</b> |
| <b>Number of Channel</b>   | : | <b>11 channels for 802.11b/g;<br/>11 channels for 802.11n(HT20);<br/>7 channels for 802.11n(HT40);</b>     |
| <b>Antenna Type</b>        | : | <b>Internal PCB Antenna</b>  |
| <b>Antenna Gain</b>        | : | <b>2 dBi</b>   |
| <b>Type of Modulation</b>  | : | <b>DSSS with DBPSK/DQPSK/CCK for 802.11b;<br/>OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;</b>           |
| <b>Power supply</b>        | : | <b>DC 3.8V, 1100mAh Battery</b>  |
| <b>Hardware Version</b>    | : | <b>zhuban_v3_0_20170928</b>  |
| <b>Software Version</b>    | : | <b>2.1.5.3.20180327</b>  |
| <b>Device category</b>     | : | <b>Portable (&lt;20cm separation)</b>  |

## Standard Requirement

According to § 1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See KDB 447498 D01 General RF Exposure Guidance v06, section 4. 3. 1.

According to § 1.1310 and § 2.1091 RF exposure is calculated.

### Limits for General Population/Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength(V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (minutes) |
|-----------------------|------------------------------|-------------------------------|-------------------------------------|--------------------------|
| 0.3-1.34              | 614                          | 1.63                          | *(100)                              | 30                       |
| 1.34-30               | 824/f                        | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |
| 30-300                | 27.5                         | 0.073                         | 0.2                                 | 30                       |
| 300-1500              | /                            | /                             | f/1500                              | 30                       |
| 1500-100,000          | /                            | /                             | 1.0                                 | 30                       |

F=Frequency in MHz

\*=Plane-wave equivalent power density

## Evaluation Method

The 1-g and 10-g SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances  $\leq 50\text{mm}$  are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})]*[\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g SAR extremity SAR, where}$

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison.

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50\text{mm}$  and for transmission frequencies between 100MHz and 6GHz. When the minimum test separation distance is  $<5\text{mm}$ , a distance of 5mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

## Test Result

### Conducted Power Results

| Test Mode    | Channel | Frequency (MHz) | Power (dBm) | Power Tune Up (dBm) |
|--------------|---------|-----------------|-------------|---------------------|
| 802.11b      | Low     | 2412            | 7.27        | 7.0±1               |
|              | Middle  | 2437            | 8.41        | 7.5±1               |
|              | High    | 2462            | 8.09        | 8.0±1               |
| 802.11g      | Low     | 2412            | 7.95        | 7.0±1               |
|              | Middle  | 2437            | 8.58        | 8.0±1               |
|              | High    | 2462            | 7.44        | 6.5±1               |
| 802.11n HT20 | Low     | 2412            | 9.15        | 8.5±1               |
|              | Middle  | 2437            | 8.63        | 8.0±1               |
|              | High    | 2462            | 8.49        | 8.0±1               |
| 802.11n HT40 | Low     | 2422            | 8.46        | 8.0±1               |
|              | Middle  | 2437            | 8.61        | 8.5±1               |
|              | High    | 2452            | 8.67        | 8.5±1               |

### Evaluation Results

| Test Mode    | Frequency (MHz) | Antenna Distance (mm) | RF output power (including tune-up tolerance) |      | SAR Test Exclusion Threshold | Limits | SAR Test Exclusion |
|--------------|-----------------|-----------------------|---|------|------------------------------|--------|--------------------|
|              |                 |                       | dBm   | mW   |                              |        |                    |
| 802.11b      | 2412            | Low                   | 8.0   | 6.31 | 1.95983                      | 3.0    | Yes                |
|              | 2437            | Middle                | 8.5   | 7.08 | 2.21033                      | 3.0    | Yes                |
|              | 2462            | High                  | 9.0   | 7.94 | 2.49272                      | 3.0    | Yes                |
| 802.11g      | 2412            | Low                   | 8.0   | 6.31 | 1.95983                      | 3.0    | Yes                |
|              | 2437            | Middle                | 9.0   | 7.94 | 2.48003                      | 3.0    | Yes                |
|              | 2462            | High                  | 7.5   | 5.62 | 1.76471                      | 3.0    | Yes                |
| 802.11n HT20 | 2412            | Low                   | 9.5   | 8.91 | 2.76834                      | 3.0    | Yes                |
|              | 2437            | Middle                | 9.0   | 7.94 | 2.48003                      | 3.0    | Yes                |
|              | 2462            | High                  | 9.0   | 7.94 | 2.49272                      | 3.0    | Yes                |
| 802.11n HT40 | 2422            | Low                   | 9.0   | 7.94 | 2.47239                      | 3.0    | Yes                |
|              | 2437            | Middle                | 9.5   | 8.91 | 2.78264                      | 3.0    | Yes                |
|              | 2452            | High                  | 9.5   | 8.91 | 2.79120                      | 3.0    | Yes                |



PRECISE TESTING

#### Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

Signature

A handwritten signature in black ink that reads "Holly Cao".

Client's signature: Holly Cao

Client's name / title: QA Manager

Date: 2018-05-29