



CTC Laboratories, Inc.

2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China

Tel: +86-755- 27521059 Fax: +86-755- 27521011 Http://www.sz-ctc.com.cn

RF Exposure Evaluation

FCC ID: 2APPZ-J4G

According to KDB447498 D01 General RF Exposure Guidance v06, Clause 4.3.1(a)

EUT Specification

EUT	IP Phone
Model/Type reference:	J4G
Listed Model(s):	N/A
Frequency band (Operating)	☒ BT: 2.402GHz ~ 2.480GHz ☐ BLE: 2.402GHz ~ 2.480GHz ☐ WLAN: 2.412GHz ~ 2.462GHz ☐ Others
Device category	☐ Portable (<20cm separation) ☐ Mobile (<5mm separation) ☒ fixed (>20cm separation) ☐ Others
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Antenna gain (Max)	2.8dBi

Limit

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{f_{(\text{GHz})}} \right] \leq 3.0$$

Where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz

-Power and distance are rounded to the nearest mW and mm before calculation

-The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

CTC Laboratories, Inc.

2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn



For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn

**Measurement Result**

Type	Channel frequency (MHz)	Max. Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Calculation Value	Threshold Value	Result
GFSK	2402	3.75	3±1	4	1.484	3.0	PASS
	2441	3.87	3±1	4	1.496	3.0	
	2480	4.32	4±1	5	1.898	3.0	
π /4-DQPSK	2402	3.74	3±1	4	1.484	3.0	
	2441	3.85	3±1	4	1.496	3.0	
	2480	4.32	4±1	5	1.898	3.0	
8-DPSK	2402	3.77	3±1	4	1.484	3.0	
	2441	3.86	3±1	4	1.496	3.0	
	2480	4.31	4±1	5	1.898	3.0	

Note

For a more detailed features description, please refer to the RF Test Report.

*****THE END*****