

SPECIFICATION FOR APPROVAL

CUSTOMER: **Shenzhen Aodehong Electronic Technology Co., Ltd.**

CUST P/N:

FINE P/N:

G4511-6.5uH single-coil 0.08*105P*12TS

DESC:

Φ 43.5MMX5.0MMX0.8MM dual slot

DATE:

2022/11/01

Version:

A.0

PREPARED BY	CHECKED BY	APPROVED BY	CUSTOMER APPROVE
黃燕铭	宁元安	黃锦华	

Shenzhen Songdao Technology Co., Ltd.

Factory Address: 8th Floor, Building 2, No. 123 Sanjia High tech Industrial Park, Junfa
3rd Road, Dongkeng Town, Dongguan

TEL: 13728755750

FAX: 0755-84526500


E-mail: 506388681@qq.com

Rev.	Before Change	After Change	Change Date	Approved By
A.0	New issue	----	2018/07/24	黃锦华

SPECIFICATION

DESC	Φ 13.5x39-6.5uH-0.08x105P-20mm-43.5C	Rev: A.0	CUST:	XXX
			CUST P/N:	

一、DIMENSION:(mm)




A	43.5.0±0.5
B	39±1
C	13.5±0.5
D	20±2
E	3±2
F	2±0.2

Remark:

1. Cross over outgoing line;
2. Outgoing line position wrapping 8mm(ref)width high-temperature adhesive paper 1-2Ts;
3. Coil with circular hard magnetic plate and slot, Magnetic plate size: 43.5±0.5mm, Inner hole: 5.3mm, Thickness: 0.8±0.2 mm, Adhesive.

二、SCHEMATIC DIAGRAM:



三、Winding Specification:

NO.	TERMINAL	WIRE	Turns	Winding Direction
1	S F	Wrapped wire 0.08*105P	12Ts	CCW

四、ELECTRICAL CHARACTERISTICS:

TEMPERATURE:25±10°C, RELATIVE HUMIDITY:65±20%

NO.	ITEM	TERMINAL	SPECIFICATION	TEST FREQUENCY	TEST EQUIPMENTS
1	IND.	S-F	3.8uH ±20% Individual coil	100KHz/1.0V	LCZ METER 1062B
2	IND.	S-F	6.5uH ±10% add magnetic plate	100KHz/1.0V	LCZ METER 1062B
3	Q value	S-F	≥55		
4	DCR	S-F	≤48mΩ		LCZ METER 502B

PREPARED BY/DATE

黃燕铭 2022/11/01

CHECKED BY/DATE

黃锦华 2022/11/01