


FCC MPE TEST REPORT

Project Number : EA1804C-091
Test Report Number : TR-W1806-006
Type of Equipment : Digital Smart Door Lock Set
Model Name : GKW-2000D
FCC ID : 2APR8-GKW2000D
ISED Cert. Number : 24013-GKW2000D
Multiple Model Name : N/A
Applicant : Guardtec
Address : #1203-1204, Hansin IT Tower, 272 Digital-ro, Guro-gu, Seoul, Korea 08389
Manufacturer : Guardtec
Address : #1203-1204, Hansin IT Tower, 272 Digital-ro, Guro-gu, Seoul, Korea 08389
Regulation : FCC Part 15 Subpart C Section 15.247, IC RSS-247 Issue2
Total page of Report : 5 Pages
Date of Receipt : 2018-04-26
Date of Issue : 2018-06-12
Test Result : PASS

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Prepared by Song, In-young / Senior Engineer  2018-06-12
Signature Date

Reviewed by Choi, Yeong-min / Technical Manager  2018-06-12
Signature Date

CONTENTS

	Page
1. EUT (EQUIPMENT UNDER TEST)	4
2. TEST RESULT	5

Release Control Record

Issue Report No.	Issued Date	Revisions	Effect Section
TR-W1806-006	2018-06-12	Initial Release	All

1. EUT (Equipment Under Test)

1.1 General Description

The Guardtec, Model GKW-2000D (referred to as the EUT in this report) is a Digital Smart Door Lock Set. The EUT is a device for transferring Bluetooth signal to an Smart phone through wireless communication.

1.2 RF Output Power

Operating Mode	Channel	Frequency (MHz)	Conducted Output Power (dBm)
Bluetooth LE	Middle	2 440	-6.73

2. TEST RESULT

2.1 Bluetooth LE

According to FCC KDB 447498 D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \times [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,

where,

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to two decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

For the present device, the conducted output power is -6.73 dBm at Middle Channel

So, max. power of channel, including tune-up tolerance = 0.21 mW

min. test separation distance = 50 mm

$f(\text{GHz}) = 2.44$

$(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \times [\sqrt{f(\text{GHz})}]$

$= (0.21 / 50) \times (\sqrt{2.44}) = 0.01 \leq 3.00$

Hence the SAR Exclusion Threshold condition is satisfied and the SAR evaluation for general population exposure conditions is not required.