

Maximum Permissible Exposure Evaluation

FCC ID: 2APRB-T8204-W

1. Client Information

Applicant	:	Guangzhou Juan Intelligent Tech Joint Stock Co.,Ltd
Address	:	No.2 Plant, West of Shanxi country, Dashi street, Panyu District, Guangzhou City, China
Manufacturer	:	Guangzhou Juan Intelligent Tech Joint Stock Co.,Ltd
Address	:	No.2 Plant, West of Shanxi country, Dashi street, Panyu District, Guangzhou City, China

2. General Description of EUT

EUT Name	:	Net video recorder with touch screen	
Models No.	:	T8204-W, see Note(1)	
Model Different	:	All these models are the same PCB, layout and electrical circuit, the only difference is model or color.	
Product Description	:	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz 802.11n (HT40): 2422MHz~2452MHz
		RF Output Power:	wlan0: 802.11b: 12.58dBm 802.11g: 8.43dBm 802.11n (HT20): 8.80dBm 802.11n (HT40): 6.73dBm wlan1: 802.11b: 10.12dBm 802.11g: 9.84dBm 802.11n (HT20): 8.58dBm 802.11n (HT40): 6.71dBm
		Antenna Gain:	4dBi External Antenna
		Modulation Type:	802.11b: DSSS(CCK, DQPSK, DBPSK) 802.11g/n: OFDM(BPSK,QPSK,16QAM, 64QAM)
Power Supply	:	AC/DC adapter(Model:MX12L1-0502500U): Input:AC100-240V, 0.35A, 50/60Hz Output: DC 5V 2.5A	
Software Version	:	3.0.3.20	
Hardware Version	:	Hi3536D_V103_ZX	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

Note:

(1) models**Models No.**

T8208-W, WRM2-KIT02, ZR04JT, M0719HN4-W, M0719HN4-B, C2019HN4-W- II , C2019HN4-W, M074JN2-W, M074JN2-B, 1PJ2-2019W- II , 1PJ2-2019W, MWM730, NVR-SD6400NM-W-TU, SM-W4CHNVR-7IN-JA, WD-W4CHNVR-7IN-JA, M0719HN8-W, M0719HN8-B, LCD-KIT-2MP, D5309HN4-W, D5309HN8-W, M1011HN4-W, M1011HN8-W, M1560HN8-W, JA-T6204-W

MPE Calculations for WIFI

1. Antenna Gain:

External Antenna: 4dBi.

2. EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3. Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=(PG)/4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

4. Test Result:

Worst Maximum MPE Result										
ANT	Mode	Freq. (MHz)	Conducted Power(max) (dBm) [P]	Tune up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/ cm ²) [S]	Power Density Limit (mW/ cm ²)	Result
ANT 1	B	2412	12.58	12±1	13	4	20	0.00997	1	PASS
		2437	11.76	11±1	12			0.00792		
		2462	11.65	11±1	12			0.00792		
	G	2412	8.43	8±1	9			0.00397		
		2437	8.42	8±1	9			0.00397		
		2462	8.07	8±1	9			0.00397		
	N20	2412	8.48	8±1	9			0.00397		
		2437	8.8	8±1	9			0.00397		
		2462	8.6	8±1	9			0.00397		
	N40	2422	6.68	6±1	7			0.00250		
		2437	6.73	6±1	7			0.00250		
		2452	6.61	6±1	7			0.00250		
ANT 2	B	2412	10.12	10±1	11	4	20	0.00629	1	PASS
		2437	9.14	9±1	10			0.00500		
		2462	8.00	8±1	9			0.00397		
	G	2412	9.84	9±1	10			0.00500		
		2437	9.33	9±1	10			0.00500		
		2462	7.96	7±1	8			0.00315		
	N20	2412	8.58	8±1	9			0.00397		
		2437	7.99	8±1	9			0.00397		
		2462	7.09	7±1	8			0.00315		
	N40	2422	6.71	6±1	7			0.00250		
		2437	6.32	6±1	7			0.00250		
		2452	5.87	6±1	7			0.00250		
Max Power Density(mW/ cm ²)			Power Density _{ant 1} + Power Density _{ant 2} =0.00997+0.00629=0.01626							
Note: wlan0 is ANT1 wlan1 is ANT2 RF Output power specifies that Maximum Conducted Peak Output Power.										

5. Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

For 802.11b/g/n:2412~2462 MHz

MPE limit S: 1mW/ cm²

The MPE is calculated as $0.01626 \text{ mW} / \text{cm}^2 < \text{limit } 1 \text{ mW} / \text{cm}^2$. So, RF exposure limit warning or SAR test are not required.

The EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47 CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.

Note

For a more detailed features description, please refer to the RF Test Report.

-----END OF REPORT-----