

FCC ID: 2APRZ-MAXWELL RF Exposure (DTS, DSS) test report modification cross comparison chart

FCC ID	2APRZ-MAXWELL		
Equipment Class	RF Exposure (DTS, DSS)		
Radio Function	BLE, BT		
Report No.	BTL-FCCP-3-2209T130		
Modified Page Number	1, 3 and 4; Total 3 page.		
Modified	Original	Note	
 <p>Report No.: BTL-FCCP-3-2209T130</p> <h3>FCC SAR Exclusion Report</h3> <p>FCC ID: 2APRZ-MAXWELL</p> <p>Report No. : BTL-FCCP-3-2209T130 Equipment : Maxwell headset Model Name : Maxwell Brand Name : Audeze LLC Applicant : Audeze LLC Address : 3410 S Susan St, Santa Ana, CA 92704 USA</p> <p>FCC Rule Part(s) : 47 CFR § 2.1093 KDB 447498 D04 Interim General RF Exposure Guidance v01 FCC Guidelines for Human Exposure IEEE C95.1</p> <p>Date of Receipt : 2022/10/4 Date of Test : 2022/10/4~ 2022/11/9 Issued Date : 2023/3/24</p> <p>The above equipment has been tested and found in compliance with the requirement of the above standards by BTL Inc.</p> <p>Prepared by : <u>Eric Lee</u> Eric Lee, Engineer</p> <p>Approved by : <u>Jerry Chang</u> Jerry Chang, Supervisor</p> <p>BTL Inc. No.18, Ln. 171, Sec. 2, Jiuzong Rd., Neihu Dist., Taipei City 114, Taiwan Tel: +886-2-2657-3299 Fax: +886-2-2657-3331 Web: www.newbtl.com Service mail: btl_qa@newbtl.com</p> <p>Project No.: 2209T130 Page 1 of 4 Report Version: R01</p>	 <p>Report No.: BTL-FCCP-3-2209T130</p> <h3>FCC SAR Exclusion Report</h3> <p>FCC ID: 2APRZ-MAXWELL</p> <p>Report No. : BTL-FCCP-3-2209T130 Equipment : Maxwell headset Model Name : Maxwell Brand Name : Audeze LLC Applicant : Audeze LLC Address : 3410 S Susan St, Santa Ana, CA 92704 USA</p> <p>FCC Rule Part(s) : FCC CFR Title 47, Part 2, Subpart J (§2.1093) KDB 447498 D04 General RF Exposure Guidance v01</p> <p>Date of Receipt : 2022/10/4 Date of Test : 2022/10/4~ 2022/11/9 Issued Date : 2022/11/30</p> <p>The above equipment has been tested and found in compliance with the requirement of the above standards by BTL Inc.</p> <p>Prepared by : <u>Eric Lee</u> Eric Lee, Engineer</p> <p>Approved by : <u>Jerry Chang</u> Jerry Chang, Supervisor</p> <p>BTL Inc. No.18, Ln. 171, Sec. 2, Jiuzong Rd., Neihu Dist., Taipei City 114, Taiwan Tel: +886-2-2657-3299 Fax: +886-2-2657-3331 Web: www.newbtl.com Service mail: btl_qa@newbtl.com</p> <p>Project No.: 2209T130 Page 1 of 4 Report Version: R00</p>	<p>On page 1,</p> <ol style="list-style-type: none"> the FCC Rule Part description is modified; the Issued Date is updated, and the Report Version is updated to R01 on every page due to this modification. 	

FCC ID: 2APRZ-MAXWELL RF Exposure (DTS, DSS) test report modification cross comparison chart

FCC ID	2APRZ-MAXWELL																																	
Equipment Class	RF Exposure (DTS, DSS)																																	
Radio Function	BLE, BT																																	
Report No.	BTL-FCCP-3-2209T130																																	
Modified Page Number	1, 3 and 4; Total 3 page.																																	
Modified	Original			Note																														
 <p>Report No.: BTL-FCCP-3-2209T130</p> <p>REVISION HISTORY</p> <table border="1"> <thead> <tr> <th>Report No.</th><th>Version</th><th>Description</th><th>Issued Date</th><th>Note</th></tr> </thead> <tbody> <tr> <td>BTL-FCCP-3-2209T130</td><td>R00</td><td>Original Report</td><td>2022/11/30</td><td>Invalid</td></tr> <tr> <td>BTL-FCCP-3-2209T130</td><td>R01</td><td>Revised report to address TAF Audit's comments.</td><td>2023/3/24</td><td>Valid</td></tr> </tbody> </table> <p>Project No.: 2209T130 Page 3 of 4 Report Version: R01</p>	Report No.	Version	Description	Issued Date	Note	BTL-FCCP-3-2209T130	R00	Original Report	2022/11/30	Invalid	BTL-FCCP-3-2209T130	R01	Revised report to address TAF Audit's comments.	2023/3/24	Valid	 <p>Report No.: BTL-FCCP-3-2209T130</p> <p>REVISION HISTORY</p> <table border="1"> <thead> <tr> <th>Report No.</th><th>Version</th><th>Description</th><th>Issued Date</th><th>Note</th></tr> </thead> <tbody> <tr> <td>BTL-FCCP-3-2209T130</td><td>R00</td><td>Original Report</td><td>2022/11/30</td><td>Invalid</td></tr> <tr> <td colspan="5"></td></tr> </tbody> </table> <p>Project No.: 2209T130 Page 3 of 4 Report Version: R00</p>			Report No.	Version	Description	Issued Date	Note	BTL-FCCP-3-2209T130	R00	Original Report	2022/11/30	Invalid						On page 3, in the Report REVISION HISTORY , a Version R01 description is added due to this modification.
Report No.	Version	Description	Issued Date	Note																														
BTL-FCCP-3-2209T130	R00	Original Report	2022/11/30	Invalid																														
BTL-FCCP-3-2209T130	R01	Revised report to address TAF Audit's comments.	2023/3/24	Valid																														
Report No.	Version	Description	Issued Date	Note																														
BTL-FCCP-3-2209T130	R00	Original Report	2022/11/30	Invalid																														

FCC ID: 2APRZ-MAXWELL RF Exposure (DTS, DSS) test report modification cross comparison chart

FCC ID	2APRZ-MAXWELL																																																																					
Equipment Class	RF Exposure (DTS, DSS)																																																																					
Radio Function	BLE, BT																																																																					
Report No.	BTL-FCCP-3-2209T130																																																																					
Modified Page Number	1, 3 and 4; Total 3 page.																																																																					
Modified	Original	Note																																																																				
<p>BTL</p> <p>Report No.: BTL-FCCP-3-2209T130</p> <p>According to KDB 447498 D04 Interim General RF Exposure Guidance v01</p> <p>This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). Pth is given by Formula</p> $P_{th} (\text{mW}) = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$ <p>where</p> $x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$ $P_{th} (\text{mW}) = ERP_{20 \text{ cm}} (\text{mW}) = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$ <p>Evaluation Facility: No. 68-1, Ln. 169, Sec. 2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan (FCC DN: TW0659) <input checked="" type="checkbox"/> SAR01</p> <p>Table for Filed Antenna:</p> <table border="1"> <thead> <tr> <th>Ant.</th><th>Manufacturer</th><th>Model number</th><th>Type</th><th>Connector</th><th>Frequency (MHz)</th><th>Gain (dB)</th></tr> </thead> <tbody> <tr> <td>1</td><td>Ampacs Corporation</td><td>Maxwell_RX_Printed_ANT</td><td>PIFA</td><td>N/A</td><td>2400-2485</td><td>0.5</td></tr> </tbody> </table> <p>Note: The above Antenna information are derived from the antenna data sheet provided by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.</p> <p>Maximum RF output power:</p> <table border="1"> <thead> <tr> <th>Mode</th><th>Maximum Output Power (dBm)</th><th>Tolerance (dB)</th><th>Maximum Tune-up Power (dBm)</th></tr> </thead> <tbody> <tr> <td>BT / BLE</td><td>3.8</td><td>+/- 0.5</td><td>4.3</td></tr> </tbody> </table> <p>Therefore RF Exposure Evaluation:</p> <table border="1"> <thead> <tr> <th>Distance (mm)</th><th>Frequency (MHz)</th><th>Maximum Tune-up Power (dBm)</th><th>Maximum Tune-up Power (mW)</th><th>SAR Exclusion Threshold (mW)</th><th>Test Required</th></tr> </thead> <tbody> <tr> <td>5.00</td><td>2480</td><td>4.30</td><td>2.69</td><td>2.72</td><td>No</td></tr> </tbody> </table> <p>Therefore, standalone SAR measurements are not required for both head and body.</p> <p>End of Test Report</p>	Ant.	Manufacturer	Model number	Type	Connector	Frequency (MHz)	Gain (dB)	1	Ampacs Corporation	Maxwell_RX_Printed_ANT	PIFA	N/A	2400-2485	0.5	Mode	Maximum Output Power (dBm)	Tolerance (dB)	Maximum Tune-up Power (dBm)	BT / BLE	3.8	+/- 0.5	4.3	Distance (mm)	Frequency (MHz)	Maximum Tune-up Power (dBm)	Maximum Tune-up Power (mW)	SAR Exclusion Threshold (mW)	Test Required	5.00	2480	4.30	2.69	2.72	No	<p>BTL</p> <p>Report No.: BTL-FCCP-3-2209T130</p> <p>According to KDB 447498 D04 Interim General RF Exposure Guidance v01</p> <p>This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). Pth is given by Formula</p> $P_{th} (\text{mW}) = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$ <p>where</p> $x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$ $P_{th} (\text{mW}) = ERP_{20 \text{ cm}} (\text{mW}) = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$ <p>Table for Filed Antenna:</p> <table border="1"> <thead> <tr> <th>Ant.</th><th>Manufacturer</th><th>Model number</th><th>Type</th><th>Connector</th><th>Frequency (MHz)</th><th>Gain (dB)</th></tr> </thead> <tbody> <tr> <td>1</td><td>Ampacs Corporation</td><td>Maxwell_RX_Printed_ANT</td><td>PIFA</td><td>N/A</td><td>2400-2485</td><td>0.5</td></tr> </tbody> </table> <p>Note: The above Antenna information are derived from the antenna data sheet provided by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.</p> <p>Maximum RF output power:</p> <table border="1"> <thead> <tr> <th>Mode</th><th>Maximum Output Power (dBm)</th><th>Tolerance (dB)</th><th>Maximum Tune-up Power (dBm)</th></tr> </thead> <tbody> <tr> <td>BT / BLE</td><td>3.8</td><td>+/- 0.5</td><td>4.3</td></tr> </tbody> </table> <p>Therefore RF Exposure Evaluation:</p> <table border="1"> <thead> <tr> <th>Distance (mm)</th><th>Frequency (MHz)</th><th>Maximum Tune-up Power (dBm)</th><th>Maximum Tune-up Power (mW)</th><th>SAR Exclusion Threshold (mW)</th><th>Test Required</th></tr> </thead> <tbody> <tr> <td>5.00</td><td>2480</td><td>4.30</td><td>2.69</td><td>2.72</td><td>No</td></tr> </tbody> </table> <p>Therefore, standalone SAR measurements are not required for both head and body.</p> <p>End of Test Report</p>	Ant.	Manufacturer	Model number	Type	Connector	Frequency (MHz)	Gain (dB)	1	Ampacs Corporation	Maxwell_RX_Printed_ANT	PIFA	N/A	2400-2485	0.5	Mode	Maximum Output Power (dBm)	Tolerance (dB)	Maximum Tune-up Power (dBm)	BT / BLE	3.8	+/- 0.5	4.3	Distance (mm)	Frequency (MHz)	Maximum Tune-up Power (dBm)	Maximum Tune-up Power (mW)	SAR Exclusion Threshold (mW)	Test Required	5.00	2480	4.30	2.69	2.72	No	<p>On page 4, the calculation facility address is added.</p>
Ant.	Manufacturer	Model number	Type	Connector	Frequency (MHz)	Gain (dB)																																																																
1	Ampacs Corporation	Maxwell_RX_Printed_ANT	PIFA	N/A	2400-2485	0.5																																																																
Mode	Maximum Output Power (dBm)	Tolerance (dB)	Maximum Tune-up Power (dBm)																																																																			
BT / BLE	3.8	+/- 0.5	4.3																																																																			
Distance (mm)	Frequency (MHz)	Maximum Tune-up Power (dBm)	Maximum Tune-up Power (mW)	SAR Exclusion Threshold (mW)	Test Required																																																																	
5.00	2480	4.30	2.69	2.72	No																																																																	
Ant.	Manufacturer	Model number	Type	Connector	Frequency (MHz)	Gain (dB)																																																																
1	Ampacs Corporation	Maxwell_RX_Printed_ANT	PIFA	N/A	2400-2485	0.5																																																																
Mode	Maximum Output Power (dBm)	Tolerance (dB)	Maximum Tune-up Power (dBm)																																																																			
BT / BLE	3.8	+/- 0.5	4.3																																																																			
Distance (mm)	Frequency (MHz)	Maximum Tune-up Power (dBm)	Maximum Tune-up Power (mW)	SAR Exclusion Threshold (mW)	Test Required																																																																	
5.00	2480	4.30	2.69	2.72	No																																																																	