



MPE REPORT

FCC ID: 2APSD-IGM4

Date of issue: Apr. 12, 2021

Report number: MTi20081916-5E3

Sample description: Mortise 2+

Model(s): IGM4

Applicant: igloocompany Pte Ltd

Address: 67 Ayer Rajah Crescent #03-25/26 Singapore Singapore

Date of test: Nov. 19, 2020 to Dec. 01, 2020

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

This test report is valid for the tested samples only. It cannot be reproduced except in full without prior written consent of Shenzhen Microtest Co., Ltd.

Tel:(86-755)88850135

Fax: (86-755) 88850136

Web: <http://www.mtitest.com>

E-mail: mti@51mti.com

Address: 101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China.



TEST RESULT CERTIFICATION	
Applicant's name:	igloocompany Pte Ltd
Address:	67 Ayer Rajah Crescent #03-25/26 Singapore Singapore
Manufacture's name:	SOLITY CO., LTD
Address:	#103 Yangcheon Venture town 267, Sinjeong-ro, Yangcheon-gu, Seoul, Korea 08079
Product name:	Mortise 2+
Trademark:	igloohome
Model and/or type reference:	IGM4
Serial model:	N/A
RF exposure procedures:	KDB 447498 D01 v06

This device described above has been tested by Shenzhen Microtest Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by:

Danny Xu

Dec. 01, 2020

Reviewed by:

Leo Su

Apr. 12, 2021

Approved by:

Tom Xue

Apr. 12, 2021



RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1415926

R= distance between observation point and center of the radiator in cm(20cm)

Pd the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.



Measurement Result

BLE:

Operation Frequency: BLE: 2402-2480MHz,

Power density limited: 1mW/ cm²

Antenna Type: PCB Antenna;

BT antenna gain: 0dBi

R=20cm

mW=10^(dBm/10)

antenna gain Numeric=10^(dBi/10)= 10^(0/10)=1.00

Channel Freq. (MHz)	modulation	conducted power	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
		(dBm)		tune-up power (dBm)	(mW)	(dBi)	Numeric		
2402	GFSK	-6.283	(-6)±1	-5	0.316	0	1.00	0.0001	1
2440		-6.154	(-6)±1	-5	0.316	0	1.00	0.0001	1
2480		-6.469	(-6)±1	-5	0.316	0	1.00	0.0001	1

Conclusion:

For the max result: 0.0001≤ 1.0 for 1g SAR, No SAR is required.

----END OF REPORT----