

# Inverted F Antenna Specification

## Summary

|                      |                                                        |          |          |          |          |          |
|----------------------|--------------------------------------------------------|----------|----------|----------|----------|----------|
| ITEM                 | ANT SPEC                                               |          |          |          |          |          |
| Model Name           | 2.4G ANT                                               |          |          |          |          |          |
| Center Frequency     | Horizontal                                             |          |          | Vertical |          |          |
|                      | 2400MHz                                                | 2400MHz  | 2500MHz  | 2400MHz  | 2400MHz  | 2500MHz  |
|                      | -1.73dBi                                               | -0.84dBi | -0.68dBi | -6.15dBi | -3.70dBi | -2.32dBi |
| MAX. Gain            | -0.68dBi                                               |          |          |          |          |          |
| Polarization         | Horizontal and Vertical                                |          |          |          |          |          |
| Azimuth Beam Pattern | Omni-directional                                       |          |          |          |          |          |
| Impedance            | 50 Ohm                                                 |          |          |          |          |          |
| Antenna Length       | 38.20mm                                                |          |          |          |          |          |
| Manufacture          | Qingtian Zteng Metal Jewelry CO.,LTD                   |          |          |          |          |          |
| Address              | NO.7 Industrial Area,Wenxi Town, Lishui City, Zhejiang |          |          |          |          |          |


## Antenna Photo



Horizontal: 2400 MHz 2450 MHz 2500 MHz

Power (dBm)

Max: 0 Min: -40 Scale: 5/div




| Frequency<br>(MHz) | Gain(dB)  |          |          |
|--------------------|-----------|----------|----------|
|                    | Max       | Min      | Avg      |
| 2400               | -1.73178  | -30.0815 | -8.48713 |
| 2450               | -0.845801 | -38.5605 | -7.88012 |
| 2500               | -0.685586 | -24.0318 | -6.79139 |

Vertical: 2400 MHz 2450 MHz 2500 MHz

Power (dBm)

Max: 0 Min: -30 Scale: 5/div



| Frequency<br>(MHz) | Gain(dB) |          |          |
|--------------------|----------|----------|----------|
|                    | Max      | Min      | Avg      |
| 2400               | -6.1530  | -24.1420 | -13.0295 |
| 2450               | -3.7054  | -26.5836 | -10.6700 |
| 2500               | -2.32122 | -30.4301 | -9.70536 |

ANT Test Labs: Attestation of Global Compliance Co., Ltd.