

FCC PART 15E TEST REPORT FOR CERTIFICATION
On Behalf of

Hunan Greatwall Computer System Co., Ltd

8"Android Tablet

Model Number: 100011885

FCC ID: 2APUQW829

Prepared for:	Hunan Greatwall Computer System Co., Ltd
	Hu'nan Greatwall Industrial Park,Xiangyun Middle Rd.,Tianyuan Dist.,
	Zhuzhou, Hu'nan
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	


Report Number:	ESTE-R2004081
Date of Test:	Apr. 16~May. 14, 2020
Date of Report:	May. 15, 2020

TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION.....	3
1. GENERAL INFORMATION.....	5
1.1. Description of Device (EUT)	5
1.1. Difference between Model Numbers.....	6
1.2. The antenna information for EUT	6
2. SUMMARY OF TEST	7
2.1. Summary of test result.....	7
2.2. Test Facilities	8
2.3. Measurement uncertainty for EST Technology Co., Ltd.	9
2.4. Assistant equipment used for test	9
2.5. Block Diagram	9
2.6. Test Mode.....	10
2.7. Channel List	12
2.8. Power Setting of Test Software.....	13
2.9. Duty Cycle of Test Signal	14
2.10. Test Equipment List	18
3. 6dB BANDWIDTH & 26dB BANDWIDTH & 99% OCCUPIED BANDWIDTH.....	20
3.1. Limit	20
3.2. Test Setup.....	20
3.3. Spectrum Analyzer Setting.....	20
3.4. Test Procedure	21
3.5. Test Result	21
3.6. Test Result	22
3.7. Test Result	24
4. MAXIMUM CONDUCTED OUTPUT POWER	45
4.1. Limit	45
4.2. Test Setup.....	45
4.3. Test Procedure	45
4.4. Test Result	46
5. PEAK POWER SPECTRAL DENSITY	48
5.1. Limit	48
5.2. Test Setup.....	48
5.3. Spectrum Analyzer Setting.....	48
5.4. Test Procedure	48
5.5. Test Result	48
6. UNWANTED EMISSIONS AND BAND EDGE	63
6.1. Limit	63
6.2. Test Setup.....	64
6.3. Spectrum Analyzer Setting.....	65
6.4. Test Procedure	66
6.5. Test Result	67
7. FREQUENCY STABILITY	120
7.1. Limit	120
7.2. Test Setup.....	120

- 7.3. Spectrum Analyzer Setting..... 120
- 7.4. Test Procedure..... 121
- 7.5. Test Result..... 122
- 8. AC POWER LINE CONDUCTED EMISSIONS126
 - 8.1. Limit 126
 - 8.2. Test Setup 126
 - 8.3. Spectrum Analyzer Setting..... 126
 - 8.4. Test Procedure..... 126
 - 8.5. Test Result..... 127
- 9. ANTENNA REQUIREMENTS.....131
 - 9.1. Limit 131
 - 9.2. Test Result..... 131
- 10. TEST SETUP PHOTO.....132
- 11. EUT PHOTO.....134

EST Technology Co., Ltd.

Applicant:	Hunan Greatwall Computer System Co., Ltd		
Address:	Hu'nan Greatwall Industrial Park,Xiangyun Middle Rd.,Tianyuan Dist., Zhuzhou, Hu'nan		
Manufacturer:	Hunan Greatwall Computer System Co.,Ltd		
Address:	Hu'nan Greatwall Industrial Park,Xiangyun Middle Rd.,Tianyuan Dist.,Zhuzhou, Hu'nan		
E.U.T:	8"Android Tablet		
Model Number:	100011885		
Power Supply:	DC 5V From Adapter Input AC 100-240V~50/60Hz DC 3.8V From Battery		
Trade Name:	onn.	Serial No.:	-----
Date of Receipt:	Apr. 15, 2020	Date of Test:	Apr. 16~May. 14, 2020
Test Specification:	FCC Part 15 Subpart E 15.407 ANSI C63.10:2013 FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01 FCC KDB 662911 D01 Multiple Transmitter Output v02r01		
Test Result:	The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC Rules and Regulations Part 15 Subpart E requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.		
Prepared by:	Reviewed by:	Date: May 15, 2020	
		 Approved by: 	
Ring / Assistant	Seven / Engineer	Iceman Hu / Manager	
Other Aspects:	None.		
Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested			
This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.			

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

FCC ID	:	2APUQW829
Product Name	:	8"Android Tablet
Model Number	:	100011885
Software Version	:	F732M.Q0.V3.18.CC-V03.8168.64-7420
Hardware Version	:	F732U2.0
Operation frequency	:	U-NII-1: 5150 MHz~5250 MHz U-NII-2A: 5250 MHz~5350 MHz U-NII-2C: 5470 MHz~5725 MHz U-NII-3: 5725 MHz~5850 MHz
Number of channel	:	U-NII-1: IEEE 802.11a / n HT20 / ac VHT20: 4 Channels; IEEE 802.11n HT40 / ac VHT40: 2 Channels; IEEE 802.11ac VHT80: 1 Channel. U-NII-2A: IEEE 802.11a / n HT20 / ac VHT20: 4 Channels; IEEE 802.11n HT40 / ac VHT40: 2 Channels; IEEE 802.11ac VHT80: 1 Channel. U-NII-2C: IEEE 802.11a / n HT20 / ac VHT20: 11 Channels; IEEE 802.11n HT40 / ac VHT40: 5 Channels; IEEE 802.11ac VHT80: 2 Channel. U-NII-3: IEEE 802.11a / n HT20 / ac VHT20: 5 Channels; IEEE 802.11n HT40 / ac VHT40: 2 Channels; IEEE 802.11ac VHT80: 1 Channel.
Modulation	:	OFDM(QPSK, BPSK, 16-QAM, 64-QAM,256-QAM)
Transmit Data Rate	:	IEEE 802.11a: 54, 48, 36, 24, 18, 12, 9, 6Mbps; IEEE 802.11n: up 150Mbps; IEEE 802.11ac: up to 433.3Mbps;
Channels Spacing	:	IEEE 802.11a: 20MHz; IEEE 802.11n HT20: 20MHz; IEEE 802.11n HT40: 40MHz; IEEE 802.11ac VHT20: 20MHz; IEEE 802.11ac VHT40: 40MHz; IEEE 802.11ac VHT80: 80MHz;

Transmit Power	:	U-NII-1	IEEE 802.11a: 11.79dBm IEEE 802.11n HT20: 11.63dBm IEEE 802.11n HT40: 11.05dBm IEEE 802.11ac VHT20: 11.7dBm IEEE 802.11ac VHT40: 11.16dBm IEEE 802.11ac VHT80: 10.93dBm
		U-NII-2A	IEEE 802.11a: 11.86dBm IEEE 802.11n HT20: 11.76dBm IEEE 802.11n HT40: 11.08dBm IEEE 802.11ac VHT20: 11.31dBm IEEE 802.11ac VHT40: 11.08dBm IEEE 802.11ac VHT80: 10.91dBm
		U-NII-2C	IEEE 802.11a: 10.75dBm IEEE 802.11n HT20: 10.57dBm IEEE 802.11n HT40: 10.01dBm IEEE 802.11ac VHT20: 10.1dBm IEEE 802.11ac VHT40: 9.94dBm IEEE 802.11ac VHT80: 9.47dBm
		U-NII-3	IEEE 802.11a: 9.85dBm IEEE 802.11n HT20: 9.83dBm IEEE 802.11n HT40: 8.88dBm IEEE 802.11ac VHT20: 9.17dBm IEEE 802.11ac VHT40: 8.89dBm IEEE 802.11ac VHT80: 8.46dBm
Sample Type	:	Prototype production	

Note:

For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

1.1. Difference between Model Numbers

Model Number	main board	DDR	EMMC
100011885	A	RS512M32LZ4D2ANP_75BT 2G/4die 3733Mbps 10*14.5mm FBGA200 RS	MEMA032G 32GB 1.8V/HS400/EMMC5.1 200MHz 153-FBGA ISOCOM
	2	MDXC1016G-M2 2GB(512*32) 3200Mbps 10*14.5mm FBGA200 FORESEE	LTMZ0007HF-DAB1-SM Leahkinn
	3	RS512M32LM4D2BDS-53BT 2GB(512*32) 3200Mbps 10*14.5mm FBGA200 RS	EMMC32G-TA28 32GB 1.8V 200MHz 153-FBGA Kingston

Note: Default is A mainboard, reported to the DDR and EMMC combination for 2 and 3

1.2. The antenna information for EUT

Ant No.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Internal	N/A	2.2

2. SUMMARY OF TEST

2.1. Summary of test result

Report Section	Description of Test Item	FCC Standard Section	Results
3	6dB Bandwidth & 26dB Bandwidth & 99% Occupied Bandwidth	15.407(a) 15.407(e)	PASS
4	Maximum Conducted Output Power	15.407(a)	PASS
5	Peak Power Spectral Density	15.407(a)	PASS
6	Unwanted Emissions and Band Edge	15.205 15.209 15.407(b)	PASS
7	Frequency Stability	15.407(g)	PASS
8	AC Power Line Conducted Emissions	15.207 15.407(b)(6)	PASS
9	Antenna Requirement	15.203	PASS

Note:

(1) "N/A" denotes test is not applicable in this test report

2.2. Test Facilities

EMC Lab	: Certificated by CNAS, CHINA Registration No.: L5288 Date of registration: November 13, 2017 Certificated by FCC, USA Designation Number: CN1215 Test Firm Registration Number: 722932 Date of registration: November 21, 2017 Certificated by A2LA, USA Registration No.: 4366.01 Date of registration: November 07, 2017 Certificated by Industry Canada CAB identifier No.: CN0035 Date of registration: January 04, 2019 Certificated by VCCI, Japan Registration No.: R-13663; C-14103 Date of registration: July 25, 2017 This Certificate is valid until: July 24, 2020 Certificated by TUV Rheinland, Germany Registration No.: UA 50413872 0001 Date of registration: July 31, 2018 Certificated by TUV/PS, Shenzhen Registration No.: SCN1017 Date of registration: January 27, 2011 Certificated by Intertek ETL SEMKO Registration No.: 2011-RTL-L2-64 Date of registration: April 28, 2011 Certificated by Nemko, Hong Kong Registration No.: 175193 Date of registration: May 4, 2011
Name of Firm	: EST Technology Co., Ltd.
Site Location	: Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China

2.3. Measurement uncertainty for EST Technology Co., Ltd.

Test Item	Uncertainty
Uncertainty for Conduction emission test	2.54dB
Uncertainty for Radiation Emission test (30MHz-1GHz)	3.62
Uncertainty for Radiation Emission test (1GHz to 18GHz)	4.86
Uncertainty for spurious emissions test (18GHz to 40GHz)	4.67
Uncertainty for radio frequency	7×10^{-8}
Uncertainty for conducted RF Power	0.20dB
Uncertainty for Power density test	0.26dB
Temperature	$\pm 0.6^{\circ}\text{C}$
Humidity	$\pm 4.0\%$
Volatage DC	$\pm 1.0\%$
Volatage (AC, <10KHz)	$\pm 1.5\%$

Note:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.


2.4. Assistant equipment used for test

Item	Equipment	Brand	Model Name/Type No.	FCC ID	Series No.
A	Adapter	onn	BSY01J3050200U U	-	-

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	1m	DC Cable

2.5. Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 (or 1.5) meter high above ground.



2.6. Test Mode

Pre-scan has been combined all possible modulations and data rates to determine the worst case test mode, the worst case test mode was selected for the final test as listed below.

Test Item	Test Mode	Channel	Modulation	Data rate
6dB Bandwidth	IEEE 802.11a	149/157/165	OFDM	6Mbps
	IEEE 802.11n HT20	149/157/165	OFDM	MCS0
	IEEE 802.11n HT40	151/159	OFDM	MCS0
	IEEE 802.11ac VHT20	149/157/165	OFDM	MCS0
	IEEE 802.11ac VHT40	151/159	OFDM	MCS0
	IEEE 802.11ac VHT80	155	OFDM	MCS0
26dB Bandwidth	IEEE 802.11a	36/40/48/52/60/64/100/116/140	OFDM	6Mbps
	IEEE 802.11n HT20	36/40/48/52/60/64/100/116/140	OFDM	MCS0
	IEEE 802.11n HT40	38/46/54/62/102/114/134	OFDM	MCS0
	IEEE 802.11ac VHT20	36/40/48/52/60/64/100/116/140	OFDM	MCS0
	IEEE 802.11ac VHT40	38/46/54/62/102/114/134	OFDM	MCS0
	IEEE 802.11ac VHT80	42/58/106/122	OFDM	MCS0
99% Occupied Bandwidth	IEEE 802.11a	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	6Mbps
	IEEE 802.11n HT20	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	MCS0
	IEEE 802.11n HT40	38/46/54/62/102/114/134/151/159	OFDM	MCS0
	IEEE 802.11ac VHT20	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	MCS0
	IEEE 802.11ac VHT40	38/46/54/62/102/114/134/151/159	OFDM	MCS0
	IEEE 802.11ac VHT80	42/58/106/122/155	OFDM	MCS0
Maximum Conducted Output Power	IEEE 802.11a	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	6Mbps
	IEEE 802.11n HT20	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	MCS0
	IEEE 802.11n HT40	38/46/54/62/102/114/134/151/159	OFDM	MCS0
	IEEE 802.11ac VHT20	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	MCS0
	IEEE 802.11ac VHT40	38/46/54/62/102/114/134/151/159	OFDM	MCS0
	IEEE 802.11ac VHT80	42/58/106/122/155	OFDM	MCS0

Peak Power Spectral Density	IEEE 802.11a	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	6Mbps
	IEEE 802.11n HT20	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	MCS0
	IEEE 802.11n HT40	38/46/54/62/102/114/134/151/159	OFDM	MCS0
	IEEE 802.11ac VHT20	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	MCS0
	IEEE 802.11ac VHT40	38/46/54/62/102/114/134/151/159	OFDM	MCS0
	IEEE 802.11ac VHT80	42/58/106/122/155	OFDM	MCS0
Unwanted Emissions and Band Edge(Above 1GHz)	IEEE 802.11a	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	6Mbps
	IEEE 802.11n HT20	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	MCS0
	IEEE 802.11n HT40	38/46/54/62/102/114/134/151/159	OFDM	MCS0
	IEEE 802.11ac VHT20	36/40/48/52/60/64/100/116/140/149/157/165	OFDM	MCS0
	IEEE 802.11ac VHT40	38/46/54/62/102/114/134/151/159	OFDM	MCS0
	IEEE 802.11ac VHT80	42/58/106/122/155	OFDM	MCS0
Unwanted Emissions Below 1GHz	IEEE 802.11a	100	OFDM	6Mbps
Frequency Stability	Unmodulation	36/64/100/149	N/A	N/A
AC Power Line Conducted Emissions	IEEE 802.11a	100	OFDM	6Mbps

Note:

1. In radiated measurement, the EUT had been pre-scan on the positioned of each 3 axis(X,Y,Z), the worst case was found when positioned on **X-plane**.

2.7. Channel List

Band	Mode	Channel	Frequency (MHz)
U-NII-1	IEEE 802.11a & n HT20 & ac VHT20	36	5180
		40	5200
		44	5220
		48	5240
	IEEE 802.11n HT40 & ac VHT40	38	5190
		46	5230
	IEEE 802.11ac VHT80	42	5210
U-NII-2A	IEEE 802.11a & n HT20 & ac VHT20	52	5260
		56	5280
		60	5300
		64	5320
	IEEE 802.11n HT40 & ac VHT40	54	5270
		62	5310
	IEEE 802.11ac VHT80	58	5290
U-NII-2C	IEEE 802.11a & n HT20 & ac VHT20	100	5500
		104	5520
		108	5540
		112	5560
		116	5580
		120	5600
		124	5620
		128	5640
		132	5660
		136	5680
		140	5700
	IEEE 802.11n HT40 & ac VHT40	102	5510
		110	5550
		118	5590
		126	5630
		134	5670
	IEEE 802.11ac VHT80	106	5530
		122	5610
U-NII-3	IEEE 802.11a & n HT20 & ac VHT20	149	5745
		153	5765
		157	5785
		161	5805
		165	5825
	IEEE 802.11n HT40 & ac VHT40	151	5755
		159	5795
	IEEE 802.11ac VHT80	155	5775

2.8. Power Setting of Test Software

Software Name	N/A		
U-NII-1			
Frequency(MHz)	5180	5200	5240
IEEE 802.11a Setting	Default	Default	Default
IEEE 802.11n HT20 Setting	Default	Default	Default
IEEE 802.11ac VHT20 Setting	Default	Default	Default
Frequency(MHz)	5190	5230	
IEEE 802.11n HT40 Setting	Default	Default	
IEEE 802.11ac VHT40 Setting	Default	Default	
Frequency(MHz)	5210		
IEEE 802.11ac VHT80 Setting	Default		
U-NII-2A			
Frequency(MHz)	5260	5300	5320
IEEE 802.11a Setting	Default	Default	Default
IEEE 802.11n HT20 Setting	Default	Default	Default
IEEE 802.11ac VHT20 Setting	Default	Default	Default
Frequency(MHz)	5270	5310	
IEEE 802.11n HT40 Setting	Default	Default	
IEEE 802.11ac VHT40 Setting	Default	Default	
Frequency(MHz)	5290		
IEEE 802.11ac VHT80 Setting	Default		
U-NII-2C			
Frequency(MHz)	5500	5580	5700
IEEE 802.11a Setting	Default	Default	Default
IEEE 802.11n HT20 Setting	Default	Default	Default
IEEE 802.11ac VHT20 Setting	Default	Default	Default
Frequency(MHz)	5510	5590	5670
IEEE 802.11n HT40 Setting	Default	Default	Default
IEEE 802.11ac VHT40 Setting	Default	Default	Default
Frequency(MHz)	5530	5610	
IEEE 802.11ac VHT80 Setting	Default	Default	
U-NII-3			
Frequency(MHz)	5745	5785	5825
IEEE 802.11a Setting	Default	Default	Default
IEEE 802.11n HT20 Setting	Default	Default	Default
IEEE 802.11ac VHT20 Setting	Default	Default	Default
Frequency(MHz)	5755	5795	
IEEE 802.11n HT40 Setting	Default	Default	
IEEE 802.11ac VHT40 Setting	Default	Default	
Frequency(MHz)	5775		
IEEE 802.11ac VHT80 Setting	Default		


2.9. Duty Cycle of Test Signal

Temperature	23℃	Relative Humidity		55%	Test Voltage		120V/60Hz
Mode	Frequency (MHz)	On time (ms)	Total Time (ms)	Duty Cycle (%)	Duty Factor (dB)	1/T (Hz)	VBW Setting (Hz)
IEEE 802.11a	5180	1.41159	1.44638	97.88	0.09	712	708
IEEE 802.11n HT20	5180	1.30725	1.34493	97.43	0.11	759	765
IEEE 802.11n HT40	5190	0.65507	0.68986	97.45	0.11	752	1527
IEEE 802.11ac VHT20	5180	1.32174	1.35942	95.06	0.22	1493	757
IEEE 802.11ac VHT40	5190	0.66087	0.69855	95.03	0.22	1503	1513
IEEE 802.11ac VHT80	5210	0.33043	0.36232	89.76	0.47	3026	3026


Note:

1. Duty Cycle=On Time/Total Time×100%.
2. Duty Factor=10×LOG(1/Duty Cycle).
3. If duty cycle <98 %, the conducted average output power and average power spectral density should be add duty factor.
4. If duty cycle ≥98 %,the EUT is consider to be transmitting continuously,the conducted average output power and average power spectral density no need to add duty factor.
5. The on-time time is transmission duration(T).
6. The VBW Setting is use for RMS measurement in Unwanted Emissions and Band Edge(Above 1GHz) Test.


IEEE 802.11a 5180MHz




IEEE 802.11n HT20 5180MHz




IEEE 802.11n HT40 5190MHz




IEEE 802.11ac VHT20 5180MHz



IEEE 802.11ac VHT40 5190MHz



IEEE 802.11ac VHT80 5210MHz



2.10. Test Equipment List

For AC power conducted emissions test						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESHS30	EST-E001	LISAI	June 14,19	1 Year
Artificial Mains Network	Rohde & Schwarz	ENV216	EST-E002	LISAI	June 14,19	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	EST-E078	LISAI	June 14,19	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

For radiated emissions test(9KHz-30MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	EST-E047	LISAI	June 14,19	1 Year
Active Loop Antenna	SCHWARZB ECK	FMZB 1519B	EST-E054	LISAI	June 14,19	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
9kHz-30MHz Cable	N/A	EST-001	N/A	N/A	N/A	N/A

For radiated emissions test(30MHz-1000MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	EST-E047	LISAI	June 14,19	1 Year
Bilog Antenna	Teseq	CBL 6111D	EST-E034	LISAI	June 14,19	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
30-1000MHz Cable	N/A	EST-002	N/A	N/A	N/A	N/A

For radiated emissions test(Above 1000MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Horn Antenna	SCHWARZB ECK	BBHA 9120 D	EST-E031	LISAI	June 14,19	1 Year
Signal Amplifier	SCHWARZB ECK	BBV9718	EST-E032	LISAI	June 14,19	1 Year
Spectrum Analyzer	Rohde & Schwarz	FSV40	EST-E069	LISAI	June 14,19	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
Above 1GHz Cable	N/A	EST-003	N/A	N/A	N/A	N/A


For connect EUT antenna terminal test						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
TS 8997	Rohde & Schwarz	/	/	/	/	/
Open Switch and Control Unit	Rohde & Schwarz	OSP-B157WB	EST-E036	LISAI	June 14,19	1 Year
Signal and Spectrum Analyzer	Rohde & Schwarz	FSV	EST-E037	LISAI	June 14,19	1 Year
Signal Generator	Rohde & Schwarz	SMB100A	EST-E038	LISAI	June 14,19	1 Year
Vector Signal Generator	Rohde & Schwarz	SMBV100A	EST-E039	LISAI	June 14,19	1 Year
Test Software	Rohde & Schwarz	WMS32	V10.50.00	N/A	N/A	N/A
Temperature controller	Terchy	MHQ	EST-E101	LISAI	June 14,19	1 Year

3. 6dB BANDWIDTH & 26dB BANDWIDTH & 99% OCCUPIED BANDWIDTH

3.1. Limit

Band	Frequency (MHz)	Test Item	Limit
U-NII-1	5150-5250	26dB Bandwidth&99% Occupied Bandwidth	N/A
U-NII-2A	5250-5350	26dB Bandwidth&99% Occupied Bandwidth	N/A
U-NII-2C	5470-5725	26dB Bandwidth&99% Occupied Bandwidth	N/A
U-NII-3	5725-5850	6dB Bandwidth&99% Occupied Bandwidth	6dB Bandwidth $\geq$ 500KHz

3.2. Test Setup



3.3. Spectrum Analyzer Setting

6dB Bandwidth	
Spectrum Parameters	Setting
RBW	100KHz
VBW	300KHz
Span	40MHz(20MHz Bandwidth mode) 60MHz(40MHz Bandwidth mode) 120MHz(80MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

26dB Bandwidth	
Spectrum Parameters	Setting
RBW	approximately 1% of the emission bandwidth
VBW	>RBW
Span	40MHz(20MHz Bandwidth mode) 60MHz(40MHz Bandwidth mode) 120MHz(80MHz Bandwidth mode)
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

99% Occupied Bandwidth	
Spectrum Parameters	Setting
RBW	1% to 5% of the OBW
VBW	approximately three times the RBW
Span	between 1.5 times and 5.0 times the OBW
Sweep Time	Auto
Detector	Peak
Trace Mode	Max Hold

3.4. Test Procedure

For 26dB Bandwidth Measurement :

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 3.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

For 6dB Bandwidth Measurement :

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 3.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

For 99% Occupied Bandwidth Measurement :

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 3.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, use the 99% power bandwidth function to measure bandwidth.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

3.5. Test Result

Temperature	27°C	Relative Humidity	54%	Test Voltage	120V/60Hz
-------------	------	-------------------	-----	--------------	-----------

3.6. Test Result

BAND	Test Mode	Fre (MHz)	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Calculate Power Limit (W)	Calculate Power Limit (dBm)
U-NII-1	IEEE 802.11a	5180	20.087	16.729		
		5200	20.318	16.556		
		5240	20.203	16.729		
	IEEE 802.11n HT20	5180	20.608	17.656		
		5200	20.666	17.771		
		5240	20.55	17.771		
	IEEE 802.11ac VHT20	5180	20.55	17.713		
		5200	20.666	17.656		
		5240	20.55	17.656		
	IEEE 802.11n HT40	5190	41.071	36.932		
		5230	40.724	36.816		
	IEEE 802.11ac VHT40	5190	41.245	36.585		
		5230	41.158	36.700		
	IEEE 802.11ac VHT80	5210	81.27	75.369		
U-NII-2A	IEEE 802.11a	5260	20.145	16.556	0.2500	23.98
		5300	20.145	16.556	0.2500	23.98
		5320	20.087	16.845	0.2500	23.98
	IEEE 802.11n HT20	5260	20.608	17.713	0.2500	23.98
		5300	20.55	17.656	0.2500	23.98
		5320	20.608	17.771	0.2500	23.98
	IEEE 802.11ac VHT20	5260	20.608	17.713	0.2500	23.98
		5300	20.434	17.656	0.2500	23.98
		5320	20.492	17.713	0.2500	23.98
	IEEE 802.11n HT40	5270	41.071	36.700	0.2500	23.98
		5310	41.158	36.816	0.2500	23.98
	IEEE 802.11ac VHT40	5270	40.984	36.585	0.2500	23.98
		5310	40.984	36.585	0.2500	23.98
	IEEE 802.11ac VHT80	5290	81.62	75.369	0.2500	23.98
U-NII-2C	IEEE 802.11a	5500	20.26	16.614	0.2500	23.98
		5580	20.087	16.614	0.2500	23.98
		5700	20.203	16.729	0.2500	23.98
	IEEE 802.11n HT20	5500	20.666	17.713	0.2500	23.98
		5580	20.434	17.713	0.2500	23.98
		5700	20.55	17.829	0.2500	23.98
	IEEE 802.11ac VHT20	5500	20.434	17.713	0.2500	23.98
		5580	20.608	17.771	0.2500	23.98
		5700	20.608	17.656	0.2500	23.98
	IEEE 802.11n HT40	5510	40.55	36.816	0.2500	23.98
		5590	44.197	36.816	0.2500	23.98
		5670	41.158	36.816	0.2500	23.98
	IEEE 802.11ac VHT40	5510	41.071	36.585	0.2500	23.98
		5590	41.071	36.700	0.2500	23.98
		5670	41.158	36.585	0.2500	23.98
	IEEE 802.11ac VHT80	5530	81.45	75.369	0.2500	23.98
		5610	81.27	75.369	0.2500	23.98

Temperature	23℃	Relative Humidity	55%	Test Voltage	120V/60Hz	
6dB Bandwidth&99% Occupied Bandwidth						
BAND	Test Mode	Frequency (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	6dB BW Min Limit (MHz)	Result
U-NII-3	IEEE 802.11a	5745	15.128	16.845	0.5	PASS
		5785	15.342	16.614	0.5	PASS
		5825	15.142	16.903	0.5	PASS
	IEEE 802.11n HT20	5745	15.368	17.771	0.5	PASS
		5785	15.342	17.771	0.5	PASS
		5825	15.435	17.771	0.5	PASS
	IEEE 802.11ac VHT20	5745	15.315	17.598	0.5	PASS
		5785	15.142	17.598	0.5	PASS
		5825	15.941	17.656	0.5	PASS
	IEEE 802.11n HT40	5755	35.122	36.816	0.5	PASS
		5795	35.122	36.816	0.5	PASS
	IEEE 802.11ac VHT40	5755	35.122	36.585	0.5	PASS
		5795	35.122	36.585	0.5	PASS
	IEEE 802.11ac VHT80	5775	75.142	75.369	0.5	PASS

Note :

For Band U-NII-2A and U-NII-2C,the maximum conducted output power limit is 250mw or $11+10 \times \log B$, which is lesser,where B is the 26dB Bandwidth in MHz.So in this section,the maximum conducted output power limit can calculate with 26dB Bandwidth.

3.7. Test Result

U-NII-1 IEEE 802.11a 5180MHz

26dB Bandwidth




99% Occupied Bandwidth



U-NII-1 IEEE 802.11a 5200MHz

26dB Bandwidth




99% Occupied Bandwidth




U-NII-1 IEEE 802.11a 5240MHz

26dB Bandwidth




99% Occupied Bandwidth



U-NII-1 IEEE 802.11n HT20 5180MHz**26dB Bandwidth****99% Occupied Bandwidth****U-NII-1 IEEE 802.11n HT20 5200MHz****26dB Bandwidth****99% Occupied Bandwidth****U-NII-1 IEEE 802.11n HT20 5240MHz****26dB Bandwidth****99% Occupied Bandwidth**

U-NII-1 IEEE 802.11ac VHT20 5180MHz

26dB Bandwidth




99% Occupied Bandwidth




U-NII-1 IEEE 802.11ac VHT20 5200MHz

26dB Bandwidth




99% Occupied Bandwidth







U-NII-1 IEEE 802.11ac VHT20 5240MHz


26dB Bandwidth



99% Occupied Bandwidth




U-NII-1 IEEE 802.11n HT40 5190MHz**26dB Bandwidth****99% Occupied Bandwidth****U-NII-1 IEEE 802.11n HT40 5230MHz****26dB Bandwidth****99% Occupied Bandwidth****U-NII-1 IEEE 802.11ac VHT40 5190MHz****26dB Bandwidth****99% Occupied Bandwidth**



U-NII-2A IEEE 802.11a 5260MHz

26dB Bandwidth




99% Occupied Bandwidth



U-NII-2A IEEE 802.11a 5300MHz

26dB Bandwidth




99% Occupied Bandwidth






U-NII-2A IEEE 802.11a 5320MHz

26dB Bandwidth




99% Occupied Bandwidth



U-NII-2A IEEE 802.11n HT20 5260MHz**26dB Bandwidth****99% Occupied Bandwidth****U-NII-2A IEEE 802.11n HT20 5300MHz****26dB Bandwidth****99% Occupied Bandwidth****U-NII-2A IEEE 802.11n HT20 5320MHz****26dB Bandwidth****99% Occupied Bandwidth**

U-NII-2A IEEE 802.11ac VHT20 5260MHz

26dB Bandwidth



99% Occupied Bandwidth




U-NII-2A IEEE 802.11ac VHT20 5300MHz

26dB Bandwidth




99% Occupied Bandwidth







U-NII-2A IEEE 802.11ac VHT20 5320MHz

26dB Bandwidth



99% Occupied Bandwidth





U-NII-2A IEEE 802.11n HT40 5270MHz**26dB Bandwidth****99% Occupied Bandwidth****U-NII-2A IEEE 802.11n HT40 5310MHz****26dB Bandwidth****99% Occupied Bandwidth****U-NII-2A IEEE 802.11ac VHT40 5270MHz****26dB Bandwidth****99% Occupied Bandwidth**

U-NII-2A IEEE 802.11ac VHT40 5310MHz

26dB Bandwidth



99% Occupied Bandwidth



U-NII-2A IEEE 802.11ac VHT80 5290MHz

26dB Bandwidth

99% Occupied Bandwidth



U-NII-2C IEEE 802.11a 5500MHz

26dB Bandwidth




99% Occupied Bandwidth



U-NII-2C IEEE 802.11a 5580MHz

26dB Bandwidth




99% Occupied Bandwidth






U-NII-2C IEEE 802.11a 5700MHz

26dB Bandwidth




99% Occupied Bandwidth



U-NII-2C IEEE 802.11n HT20 5500MHz**26dB Bandwidth****99% Occupied Bandwidth****U-NII-2C IEEE 802.11n HT20 5580MHz****26dB Bandwidth****99% Occupied Bandwidth****U-NII-2C IEEE 802.11n HT20 5700MHz****26dB Bandwidth****99% Occupied Bandwidth**

U-NII-2C IEEE 802.11ac VHT20 5500MHz

26dB Bandwidth




99% Occupied Bandwidth



U-NII-2C IEEE 802.11ac VHT20 5580MHz

26dB Bandwidth




99% Occupied Bandwidth








U-NII-2C IEEE 802.11ac VHT20 5700MHz


26dB Bandwidth




99% Occupied Bandwidth




U-NII-2C IEEE 802.11n HT40 5510MHz**26dB Bandwidth****99% Occupied Bandwidth****U-NII-2C IEEE 802.11n HT40 5590MHz****26dB Bandwidth****99% Occupied Bandwidth****U-NII-2C IEEE 802.11n HT40 5670MHz****26dB Bandwidth****99% Occupied Bandwidth**





U-NII-3 IEEE 802.11a 5745MHz

6dB Bandwidth




99% Occupied Bandwidth



U-NII-3 IEEE 802.11a 5785MHz

6dB Bandwidth




99% Occupied Bandwidth








U-NII-3 IEEE 802.11a 5825MHz

6dB Bandwidth




99% Occupied Bandwidth




U-NII-3 IEEE 802.11n HT20 5745MHz**6dB Bandwidth****99% Occupied Bandwidth****U-NII-3 IEEE 802.11n HT20 5785MHz****6dB Bandwidth****99% Occupied Bandwidth****U-NII-3 IEEE 802.11n HT20 5825MHz****6dB Bandwidth****99% Occupied Bandwidth**

U-NII-3 IEEE 802.11ac VHT20 5745MHz

6dB Bandwidth




99% Occupied Bandwidth




U-NII-3 IEEE 802.11ac VHT20 5785MHz

6dB Bandwidth




99% Occupied Bandwidth







U-NII-3 IEEE 802.11ac VHT20 5825MHz


6dB Bandwidth



99% Occupied Bandwidth



U-NII-3 IEEE 802.11n HT40 5755MHz**6dB Bandwidth****99% Occupied Bandwidth****U-NII-3 IEEE 802.11n HT40 5795MHz****6dB Bandwidth****99% Occupied Bandwidth****U-NII-3 IEEE 802.11ac VHT40 5755MHz****6dB Bandwidth****99% Occupied Bandwidth**



4. MAXIMUM CONDUCTED OUTPUT POWER


4.1. Limit

Band	EUT Type	Limit
U-NII-1	Outdoor Access Point	1W(30dBm) (Max. e.i.r.p $\leq$ 125mW at any elevation angle above 30 degrees as measured from the horizon)
	Indoor Access Point	1W(30dBm)
	Fixed point-to-point Access Point	1W(30dBm)
	Mobile and Portable Client Device	250mW(23.98dBm)
U-NII-2A	All Device	250mW(23.98dBm) or 11dBm+10 log B, Which is lesser. (B is 26dB Bandwidth in MHz)
U-NII-2C	All Device	250mW(23.98dBm) or 11dBm+10 log B, Which is lesser. (B is 26dB Bandwidth in MHz)
U-NII-3	All Device	1W(30dBm)

Note:

For the Band U-NII-2A and U-NII-2C, the maximum conducted output power limit calculate result refer to section 3.5.

4.2. Test Setup



4.3. Test Procedure

- Connect EUT antenna terminal to the OSP-B157WB with RF cable.
- Set the EUT transmit continuously with maximum output power.
- Through the test software in TS 8897 to control a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.

4.4. Test Result

Temperature	23℃	Relative Humidity		55%	Test Voltage	120V/60Hz
BAND	Test Mode	Frequency (MHz)	Conducted AVG Output Power (dBm)	Conducted AVG Output Power (W)	Limit (dBm)	Result
U-NII-1	IEEE 802.11a	5180	11.78	0.0151	23.98	PASS
		5200	11.46	0.0140	23.98	PASS
		5240	11.79	0.0151	23.98	PASS
	IEEE 802.11n HT20	5180	11.62	0.0145	23.98	PASS
		5200	11.33	0.0136	23.98	PASS
		5240	11.63	0.0145	23.98	PASS
	IEEE 802.11ac VHT20	5180	11.70	0.0148	23.98	PASS
		5200	11.02	0.0126	23.98	PASS
		5240	11.26	0.0134	23.98	PASS
	IEEE 802.11n HT40	5190	11.05	0.0127	23.98	PASS
		5230	10.88	0.0123	23.98	PASS
	IEEE 802.11ac VHT40	5190	11.16	0.0131	23.98	PASS
		5230	10.88	0.0122	23.98	PASS
	IEEE 802.11ac VHT80	5210	10.93	0.0124	23.98	PASS
U-NII-2A	IEEE 802.11a	5260	11.86	0.0153	23.98	PASS
		5300	11.68	0.0147	23.98	PASS
		5320	11.76	0.0150	23.98	PASS
	IEEE 802.11n HT20	5260	11.76	0.0150	23.98	PASS
		5300	11.53	0.0142	23.98	PASS
		5320	11.54	0.0143	23.98	PASS
	IEEE 802.11ac VHT20	5260	11.31	0.0135	23.98	PASS
		5300	11.04	0.0127	23.98	PASS
		5320	11.15	0.0130	23.98	PASS
	IEEE 802.11n HT40	5270	11.08	0.0128	23.98	PASS
		5310	10.96	0.0125	23.98	PASS
	IEEE 802.11ac VHT40	5270	11.05	0.0127	23.98	PASS
		5310	11.01	0.0126	23.98	PASS
	IEEE 802.11ac VHT80	5290	10.91	0.0123	23.98	PASS

BAND	Test Mode	Frequency (MHz)	Conducted AVG Output Power (dBm)	Conducted AVG Output Power (W)	Limit (dBm)	Result
U-NII-2C	IEEE 802.11a	5500	10.75	0.0119	23.98	PASS
		5580	10.70	0.0118	23.98	PASS
		5700	9.39	0.0087	23.98	PASS
	IEEE 802.11n HT20	5500	10.57	0.0114	23.98	PASS
		5580	10.52	0.0113	23.98	PASS
		5700	9.23	0.0084	23.98	PASS
	IEEE 802.11ac VHT20	5500	10.05	0.0101	23.98	PASS
		5580	10.10	0.0102	23.98	PASS
		5700	8.69	0.0074	23.98	PASS
	IEEE 802.11n HT40	5510	10.01	0.0100	23.98	PASS
		5670	9.50	0.0089	23.98	PASS
	IEEE 802.11ac VHT40	5510	9.94	0.0099	23.98	PASS
		5670	9.62	0.0092	23.98	PASS
	IEEE 802.11ac VHT80	5530	9.41	0.0087	23.98	PASS
		5610	9.47	0.0089	23.98	
U-NII-3	IEEE 802.11a	5745	9.85	0.0097	30.00	PASS
		5785	8.25	0.0067	30.00	PASS
		5825	9.07	0.0081	30.00	PASS
	IEEE 802.11n HT20	5745	9.83	0.0096	30.00	PASS
		5785	8.59	0.0072	30.00	PASS
		5825	9.40	0.0087	30.00	PASS
	IEEE 802.11ac VHT20	5745	9.17	0.0083	30.00	PASS
		5785	8.04	0.0064	30.00	PASS
		5825	8.79	0.0076	30.00	PASS
	IEEE 802.11n HT40	5755	8.88	0.0077	30.00	PASS
		5795	8.34	0.0068	30.00	PASS
	IEEE 802.11ac VHT40	5755	8.89	0.0077	30.00	PASS
		5795	8.33	0.0068	30.00	PASS
	IEEE 802.11ac VHT80	5775	8.46	0.0070	30.00	PASS

5. PEAK POWER SPECTRAL DENSITY

5.1. Limit

Band	EUT Type	Limit
U-NII-1	Outdoor Access Point	17dBm/MHz
	Indoor Access Point	17dBm/MHz
	Fixed point-to-point Access Point	17dBm/MHz
	Mobile and Portable Client Device	11dBm/MHz
U-NII-2A	All Device	11dBm/MHz
U-NII-2C	All Device	11dBm/MHz
U-NII-3	All Device	30dBm/500KHz

5.2. Test Setup



5.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	1MHz(For U-NII-1&U-NII-2A&U-NII-2C) 500KHz(For U-NII-3)
VBW	3MHz(For U-NII-1&U-NII-2A&U-NII-2C) 2MHz(For U-NII-3)
Span	encompass the entire 26 dB EBW or 99% OBW of the signal
Sweep Time	Auto
Number of Sweep Point	$\geq 2 \times \text{SPAN/RBW}$
Detector	RMS(power averaging)
Trace Average	≥ 100 traces

5.4. Test Procedure

- Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- Spectrum analyzer setting parameters in accordance with section 5.3.
- Set the EUT transmit continuously with maximum output power.
- Allow trace to stabilize, use the marker-to-peak function to set the marker to the average of the emission.
- If the duty cycle of test signal $< 98\%$, the result = max measured value + $10 \times \log(1/\text{duty cycle})$;
If the duty cycle of test signal $\geq 98\%$, the result = max measured value.
- Repeat above procedures until all modes and channels were measured.
- Record the results in the test report.


5.5. Test Result

Temperature	23°C	Relative Humidity	55%	Test Voltage	120V/60Hz
-------------	------	-------------------	-----	--------------	-----------


BAND	Test Mode	Fre (MHz)	Power Density (dBm/MHz)	Duty Factor (dB)	Total Power Density (dBm/MHz)	Limit (dBm/MHz)	Result
U-NII-1	IEEE 802.11a	5180	7.31	0.11	7.42	11.00	PASS
		5200	6.15	0.11	6.26	11.00	PASS
		5240	6.24	0.11	6.35	11.00	PASS
	IEEE 802.11n HT20	5180	5.85	0.12	5.97	11.00	PASS
		5200	5.40	0.12	5.52	11.00	PASS
		5240	6.38	0.12	6.50	11.00	PASS
	IEEE 802.11ac VHT20	5180	5.57	0.12	5.69	11.00	PASS
		5200	5.20	0.12	5.32	11.00	PASS
		5240	5.41	0.12	5.53	11.00	PASS
	IEEE 802.11n HT40	5190	3.17	0.22	3.39	11.00	PASS
		5230	3.24	0.22	3.46	11.00	PASS
	IEEE 802.11ac VHT40	5190	2.71	0.24	2.95	11.00	PASS
		5230	2.56	0.24	2.80	11.00	PASS
	IEEE 802.11ac VHT80	5210	-0.34	0.40	0.06	11.00	PASS
U-NII-2A	IEEE 802.11a	5260	6.39	0.11	6.50	11.00	PASS
		5300	6.90	0.11	7.01	11.00	PASS
		5320	7.82	0.11	7.93	11.00	PASS
	IEEE 802.11n HT20	5260	5.53	0.12	5.65	11.00	PASS
		5300	5.75	0.12	5.87	11.00	PASS
		5320	6.24	0.12	6.36	11.00	PASS
	IEEE 802.11ac VHT20	5260	6.06	0.12	6.18	11.00	PASS
		5300	5.86	0.12	5.98	11.00	PASS
		5320	6.83	0.12	6.95	11.00	PASS
	IEEE 802.11n HT40	5270	3.54	0.22	3.76	11.00	PASS
		5310	3.67	0.22	3.89	11.00	PASS
	IEEE 802.11ac VHT40	5270	2.53	0.24	2.77	11.00	PASS
		5310	3.38	0.24	3.62	11.00	PASS
	IEEE 802.11ac VHT80	5290	0.00	0.40	0.40	11.00	PASS
U-NII-2C	IEEE 802.11a	5500	5.27	0.11	5.38	11.00	PASS
		5580	3.68	0.11	3.79	11.00	PASS
		5700	4.97	0.11	5.08	11.00	PASS
	IEEE 802.11n HT20	5500	5.10	0.12	5.22	11.00	PASS
		5580	4.43	0.12	4.55	11.00	PASS
		5700	5.35	0.12	5.47	11.00	PASS
	IEEE 802.11ac VHT20	5500	4.66	0.12	4.78	11.00	PASS
		5580	4.12	0.12	4.24	11.00	PASS
		5700	4.95	0.12	5.07	11.00	PASS
	IEEE 802.11n HT40	5510	1.49	0.22	1.71	11.00	PASS
		5590	0.50	0.22	0.72	11.00	PASS
		5670	0.50	0.22	1.68	11.00	PASS
	IEEE 802.11ac VHT40	5510	1.44	0.24	0.71	11.00	PASS
		5590	0.47	0.24	-1.30	11.00	PASS
		5670	0.47	0.24	-1.82	11.00	PASS
	IEEE 802.11ac VHT80	5530	-1.70	0.40	5.38	11.00	PASS
		5610	-2.22	0.40	3.79	11.00	PASS

BAND	Test Mode	Fre (MHz)	Power Density (dBm/500KHz)	Duty Factor (dB)	Total Power Density (dBm/500KHz)	Limit (dBm/500KHz)	Result
U-NII-3	IEEE 802.11a	5745	5.51	0.11	5.62	30.00	PASS
		5785	4.64	0.11	4.75	30.00	PASS
		5825	3.47	0.11	3.58	30.00	PASS
	IEEE 802.11n HT20	5745	5.10	0.12	5.22	30.00	PASS
		5785	4.00	0.12	4.12	30.00	PASS
		5825	3.01	0.12	3.13	30.00	PASS
	IEEE 802.11ac VHT20	5745	4.99	0.12	5.11	30.00	PASS
		5785	4.13	0.12	4.25	30.00	PASS
		5825	3.02	0.12	3.14	30.00	PASS
	IEEE 802.11n HT40	5755	2.43	0.22	2.65	30.00	PASS
		5795	1.23	0.22	1.45	30.00	PASS
	IEEE 802.11ac VHT40	5755	1.91	0.24	2.15	30.00	PASS
		5795	0.85	0.24	1.09	30.00	PASS
	IEEE 802.11ac VHT80	5775	-1.53	0.40	-1.13	30.00	PASS


U-NII-1 IEEE 802.11a 5180MHz




U-NII-1 IEEE 802.11a 5200MHz



U-NII-1 IEEE 802.11a 5240MHz



U-NII-1 IEEE 802.11n HT20 5180MHz




U-NII-1 IEEE 802.11n HT20 5200MHz




U-NII-1 IEEE 802.11n HT20 5240MHz




U-NII-1 IEEE 802.11ac VHT20 5180MHz



U-NII-1 IEEE 802.11ac VHT20 5200MHz



U-NII-1 IEEE 802.11ac VHT20 5240MHz



U-NII-1 IEEE 802.11n HT40 5190MHz





U-NII-1 IEEE 802.11n HT40 5230MHz



U-NII-1 IEEE 802.11ac VHT40 5190MHz






U-NII-2A IEEE 802.11a 5260MHz



U-NII-2A IEEE 802.11a 5300MHz



U-NII-2A IEEE 802.11a 5320MHz



U-NII-2A IEEE 802.11n HT20 5260MHz








U-NII-2A IEEE 802.11n HT20 5300MHz




U-NII-2A IEEE 802.11n HT20 5320MHz




U-NII-2A IEEE 802.11ac VHT20 5260MHz**U-NII-2A IEEE 802.11ac VHT20 5300MHz****U-NII-2A IEEE 802.11ac VHT20 5320MHz****U-NII-2A IEEE 802.11n HT40 5270MHz****U-NII-2A IEEE 802.11n HT40 5310MHz****U-NII-2A IEEE 802.11ac VHT40 5270MHz**




U-NII-2C IEEE 802.11a 5500MHz




U-NII-2C IEEE 802.11a 5580MHz



U-NII-2C IEEE 802.11a 5700MHz



U-NII-2C IEEE 802.11n HT20 5500MHz




U-NII-2C IEEE 802.11n HT20 5580MHz



U-NII-2C IEEE 802.11n HT20 5700MHz





U-NII-2C IEEE 802.11ac VHT40 5510MHz




U-NII-2C IEEE 802.11ac VHT40 5590MHz




U-NII-2C IEEE 802.11ac VHT40 5670MHz




U-NII-2C IEEE 802.11ac VHT80 5530MHz




U-NII-2C IEEE 802.11ac VHT80 5610MHz




U-NII-3 IEEE 802.11a 5745MHz




U-NII-3 IEEE 802.11a 5785MHz



U-NII-3 IEEE 802.11a 5825MHz



U-NII-3 IEEE 802.11n HT20 5745MHz




U-NII-3 IEEE 802.11n HT20 5785MHz



U-NII-3 IEEE 802.11n HT20 5825MHz




U-NII-3 IEEE 802.11ac VHT20 5745MHz



U-NII-3 IEEE 802.11ac VHT20 5785MHz




U-NII-3 IEEE 802.11ac VHT20 5825MHz



U-NII-3 IEEE 802.11n HT40 5755MHz





U-NII-3 IEEE 802.11n HT40 5795MHz



U-NII-3 IEEE 802.11ac VHT40 5755MHz





6. UNWANTED EMISSIONS AND BAND EDGE

6.1. Limit

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

The unwanted emissions which fall in Restricted bands shall not exceed the field strength levels specified in the following table:

15.209 Radiated emission limits

Frequency (MHz)	Field Strength(μ V/m)	Distance(m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

15.205 Restricted frequency band


MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

Note:

1. $\text{dB}\mu\text{V/m} = 20 \log(\mu\text{V/m})$
2. Above 1GHz the formula is used to convert the EIRP to field strength

$$E[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] - 20 \log(d[\text{m}]) + 104.77,$$
 where E is field strength and d is distance at which the field strength limit is specified in the applicable requirements.
 for example, 3m field strength($\text{dB}\mu\text{V/m}$)= $\text{EIRP} - 20 \log(3) + 104.77 = \text{EIRP} + 95.2$

6.2. Test Setup



6.3. Spectrum Analyzer Setting

For 9KHz-150KHz

Spectrum Parameters	Setting
RBW	300Hz(for Peak&AVG)/CISPR 200Hz(for QP)
VBW	300Hz(for Peak&AVG)/CISPR 200Hz(for QP)
Start frequency	9KHz
Stop frequency	150KHz
Sweep Time	Auto
Detector	PEAK/QP/AVG
Trace Mode	Max Hold

Note : For 9KHz-90KHz&110KHz-150KHz,the detector is average,other frequency is CISPR QP detector.

For 150KHz-30MHz

Spectrum Parameters	Setting
RBW	9KHz
VBW	9KHz
Start frequency	150KHz
Stop frequency	30MHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

Note : For 150KHz-490KHz,the detector is average,other frequency is CISPR QP detector.

For 30MHz-1GHz

Spectrum Parameters	Setting
RBW	120KHz
VBW	300KHz
Start frequency	30MHz
Stop frequency	1GHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

For Above 1GHz

Spectrum Parameters	Setting	
RBW	1MHz	
VBW	PEAK Measurement	AVG Measurement
	3MHz	Duty cycle $\geq 98\%$, VBW=10Hz Duty cycle $< 98\%$, VBW $\geq 1/T$ Video bandwidth mode=RMS (power averaging)
Start frequency	1GHz	
Stop frequency	40GHz	
Sweep Time	Auto	
Detector	PEAK	
Trace Mode	Max Hold	

Note : T is the on-time time of the duty cycle,when EUT transmit continuously with maximum output power,unit is seconds. reference section 2.7 for the on-time time.

6.4. Test Procedure


- a. EUT was placed on a turn table, which is 0.8 meter high above ground for below 1GHz test, and which is 1.5 meter high above ground for above 1GHz test.
- b. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower.
- c. Set the EUT transmit continuously with maximum output power.
- d. The turn table can rotate 360 degrees to determine the position of the maximum emission level.
- e. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.
- f. Spectrum analyzer setting parameters in accordance with section 6.3.
- g. Repeat above procedures until all channels were measured.
- h. Record the results in the test report.

6.5. Test Result

Radiated Emissions Below 1GHz

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan,Guangdong,China
Tel:+86-769-83081888
Fax:+86-769-83081878



Site no. : 3# 966 Chamber Data no. : 73
Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL
Limit : FCC PART 15 B(3M)
Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
Engineer : Frank
EUT : 8"Android Tablet
Power : DCSV From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : TX Mode

Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
30.00	18.40	0.14	2.63	21.17	40.00	18.83	QP
88.20	8.90	0.79	8.83	18.52	43.50	24.98	QP
139.61	12.50	1.03	10.37	23.90	43.50	19.60	QP
159.01	11.30	1.14	10.86	23.30	43.50	20.20	QP
294.81	13.50	1.83	8.68	24.01	46.00	21.99	QP
916.58	24.00	3.99	6.26	34.25	46.00	11.75	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 74

File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (78)

Date: 2020-04-18



Site no. : 3# 966 Chamber Data no. : 74
 Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Frank
 EUT : 8"Android Tablet
 Power : DC5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode

Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
39.70	12.20	0.22	14.49	26.91	40.00	13.09	QP
51.34	7.90	0.31	12.59	20.80	40.00	19.20	QP
88.20	8.90	0.79	11.04	20.73	43.50	22.77	QP
159.98	11.30	1.14	13.84	26.28	43.50	17.22	QP
184.23	9.26	1.22	9.01	19.49	43.50	24.01	QP
916.58	24.00	3.99	7.04	35.03	46.00	10.97	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Mainboard Model No.: MDXC1016G-M2 2GB & LTMZ0007HF-DAB1-SM


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 85

File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (94)

Date: 2020-05-14



Site no. : 1# 966 Chamber Data no. : 85
 Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6'; Humi:56%; Press:101.52kPa
 Engineer : Frank
 EUT : 8"Android Tablet
 Power : DC5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 MDXC1016G-M2 2GB
 LTMZ0007HF-DAB1-SM

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	32.9100	16.20	0.16	5.13	21.49	40.00	18.51	QP
2	125.0600	11.50	0.95	7.75	20.20	43.50	23.30	QP
3	150.2800	11.60	1.09	10.00	22.69	43.50	20.81	QP
4	763.3200	22.43	3.59	1.13	27.15	46.00	18.85	QP
5	829.2800	23.39	3.72	2.10	29.21	46.00	16.79	QP
6	960.2300	24.70	4.61	1.98	31.29	54.00	22.71	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 86

File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (94)

Date: 2020-05-14



Site no. : 1# 966 Chamber Data no. : 86
 Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6'; Humi:56%; Press:101.52kPa
 Engineer : Frank
 EUT : 8"Android Tablet
 Power : DC5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 MDXC1016G-M2 2GB
 LTMZ0007HF-DAB1-SM

Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1 149.3100	11.62	1.09	6.66	19.37	43.50	24.13	QP
2 274.4400	12.42	1.75	7.17	21.34	46.00	24.66	QP
3 816.6700	23.27	3.70	2.47	29.44	46.00	16.56	QP
4 878.7500	23.81	3.89	2.62	30.32	46.00	15.68	QP
5 916.5800	24.00	3.99	3.43	31.42	46.00	14.58	QP
6 960.2300	24.70	4.61	4.89	34.20	54.00	19.80	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Mainboard Model No.: RS512M32LM4D2BDS-53BT 2GB & EMMC32G-TA28 32GB


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 93

File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (94)

Date: 2020-05-14




Site no. : 1# 966 Chamber Data no. : 93
 Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6'; Humi:56%; Press:101.52kPa
 Engineer : Frank
 EUT : 8"Android Tablet
 Power : DC5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 RS512M32LM4D2BDS-53BT 2GB
 EMMC32G-TA28 32GB

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.0000	18.40	0.14	7.90	26.44	40.00	13.56	QP
2	139.6100	12.50	1.03	9.17	22.70	43.50	20.80	QP
3	159.9800	11.30	1.14	9.49	21.93	43.50	21.57	QP
4	584.8400	20.15	2.93	4.26	27.34	46.00	18.66	QP
5	916.5800	24.00	3.99	2.66	30.65	46.00	15.35	QP
6	960.2300	24.70	4.61	4.53	33.84	54.00	20.16	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



Site no. : 1# 966 Chamber Data no. : 94
 Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:23.6';Humi:56%;Press:101.52kPa
 Engineer : Frank
 EUT : 8"Android Tablet
 Power : DC5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 RS512M32LM4D2BDS-53BT 2GB
 EMMC32G-TA28 32GB

Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1 139.6100	12.50	1.03	5.28	18.81	43.50	24.69	QP
2 266.6800	13.30	1.72	7.07	22.09	46.00	23.91	QP
3 690.5700	21.61	3.20	3.27	28.08	46.00	17.92	QP
4 825.4000	23.35	3.71	2.75	29.81	46.00	16.19	QP
5 922.4000	24.02	4.04	3.62	31.68	46.00	14.32	QP
6 960.2300	24.70	4.61	4.16	33.47	54.00	20.53	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Note:

1. The amplitude of 9KHz to 30MHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.
2. All channels had been pre-test, only the worst case was reported.

Radiated Emissions Above 1G


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 47

File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (78)

Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 47
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCCPART 15E PEAK NII
 Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
 Engineer : Seven
 EUT : 8"Android Tablet
 Power : DC5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : IEEE 802.11a TX 5180MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5180.00	32.20	3.52	34.63	76.67	77.76	68.20	-9.56	Peak
2	8021.00	36.90	5.80	34.89	33.35	41.16	68.20	27.04	Peak
3	10360.00	39.27	5.99	34.31	28.98	39.93	68.20	28.27	Peak
4	15042.00	40.86	6.78	34.59	31.45	44.50	68.20	23.70	Peak
5	15540.00	40.31	6.46	34.39	28.02	40.40	74.00	33.60	Peak
6	17830.00	47.54	8.13	34.32	21.56	42.91	74.00	31.09	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 48 File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 48
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5180MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5180.00	32.20	3.52	34.63	79.13	80.22	68.20	-12.02	Peak
2	10112.00	39.02	5.92	34.24	33.44	44.14	68.20	24.06	Peak
3	10360.00	39.27	5.99	34.31	28.24	39.19	68.20	29.01	Peak
4	14532.00	40.99	6.89	34.46	30.34	43.76	68.20	24.44	Peak
5	15540.00	40.31	6.46	34.39	27.93	40.31	74.00	33.69	Peak
6	17983.00	48.76	8.23	34.30	20.71	43.40	74.00	30.60	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 49 File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 49
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5200MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5200.00	32.24	3.53	34.62	78.93	80.08	68.20	-11.88	Peak
2	6304.00	33.88	4.56	34.45	37.09	41.08	68.20	27.12	Peak
3	10400.00	39.31	5.99	34.32	26.30	37.28	68.20	30.92	Peak
4	14634.00	40.97	6.88	34.49	29.39	42.75	68.20	25.45	Peak
5	15600.00	40.24	6.53	34.36	27.55	39.96	74.00	34.04	Peak
6	18000.00	48.90	8.24	34.30	20.38	43.22	74.00	30.78	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 50 File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 50
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5200MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5200.00	32.24	3.53	34.62	76.39	77.54	68.20	-9.34	Peak
2	8021.00	36.90	5.80	34.89	34.41	42.22	68.20	25.98	Peak
3	10400.00	39.31	5.99	34.32	29.96	40.94	68.20	27.26	Peak
4	14005.00	41.10	6.53	34.30	30.02	43.35	68.20	24.85	Peak
5	15600.00	40.24	6.53	34.36	28.64	41.05	74.00	32.95	Peak
6	17830.00	47.54	8.13	34.32	22.02	43.37	74.00	30.63	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 51 File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 51
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5240MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5240.00	32.31	3.55	34.61	76.01	77.26	68.20	-9.06	Peak
2	7987.00	36.90	5.80	34.90	32.63	40.43	68.20	27.77	Peak
3	10480.00	39.39	6.02	34.35	27.71	38.77	68.20	29.43	Peak
4	14566.00	40.99	6.89	34.47	28.80	42.21	68.20	25.99	Peak
5	15720.00	40.10	6.65	34.31	28.20	40.64	74.00	33.36	Peak
6	17966.00	48.63	8.22	34.30	19.52	42.07	74.00	31.93	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 52 File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 52
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5240MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5240.00	32.31	3.55	34.61	78.71	79.96	68.20	-11.76	Peak
2	7902.00	36.88	5.71	34.89	33.96	41.66	68.20	26.54	Peak
3	10480.00	39.39	6.02	34.35	30.21	41.27	68.20	26.93	Peak
4	14447.00	41.01	6.86	34.43	29.86	43.30	68.20	24.90	Peak
5	15720.00	40.10	6.65	34.31	29.95	42.39	74.00	31.61	Peak
6	17813.00	47.41	8.12	34.32	22.23	43.44	74.00	30.56	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 53 File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 53
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5260MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5260.00	32.39	3.57	34.59	75.84	77.21	68.20	-9.01	Peak
2	8021.00	36.90	5.80	34.89	33.07	40.88	68.20	27.32	Peak
3	10520.00	39.43	6.02	34.36	28.94	40.03	68.20	28.17	Peak
4	14651.00	40.97	6.87	34.49	29.50	42.85	68.20	25.35	Peak
5	15780.00	40.05	6.69	34.29	25.91	38.36	74.00	35.64	Peak
6	17881.00	47.95	8.16	34.31	20.72	42.52	74.00	31.48	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 54 File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 54
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5260MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5260.00	32.39	3.57	34.59	77.40	78.77	68.20	-10.57	Peak
2	9976.00	38.87	5.88	34.20	32.80	43.35	68.20	24.85	Peak
3	10520.00	39.43	6.02	34.36	29.08	40.17	68.20	28.03	Peak
4	14549.00	40.99	6.89	34.46	30.12	43.54	68.20	24.66	Peak
5	15780.00	40.05	6.69	34.29	27.04	39.49	74.00	34.51	Peak
6	18000.00	48.90	8.24	34.30	19.24	42.08	74.00	31.92	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 55 File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 55
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5300MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5300.00	32.46	3.59	34.58	75.09	76.56	68.20	-8.36	Peak
2	9993.00	38.90	5.89	34.20	31.42	42.01	68.20	26.19	Peak
3	10600.00	39.51	6.04	34.38	28.35	39.52	68.20	28.68	Peak
4	14583.00	40.98	6.89	34.47	29.89	43.29	68.20	24.91	Peak
5	15900.00	39.91	6.81	34.24	24.89	37.37	74.00	36.63	Peak
6	17473.00	44.70	7.89	34.35	25.37	43.61	68.20	24.59	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 56 File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 56
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5300MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5300.00	32.46	3.59	34.58	78.58	80.05	68.20	-11.85	Peak
2	8072.00	36.90	5.73	34.87	31.42	39.18	74.00	34.82	Peak
3	10600.00	39.51	6.04	34.38	27.98	39.15	68.20	29.05	Peak
4	15076.00	40.82	6.76	34.57	28.64	41.65	68.20	26.55	Peak
5	15900.00	39.91	6.81	34.24	22.31	34.79	74.00	39.21	Peak
6	17949.00	48.49	8.21	34.31	20.40	42.79	74.00	31.21	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 57 File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 57
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5320MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5320.00	32.50	3.60	34.57	74.93	76.46	68.20	-8.26	Peak
2	9993.00	38.90	5.89	34.20	32.95	43.54	68.20	24.66	Peak
3	10640.00	39.54	6.04	34.39	29.65	40.84	74.00	33.16	Peak
4	14107.00	41.08	6.61	34.33	31.53	44.89	68.20	23.31	Peak
5	15960.00	39.84	6.88	34.21	27.49	40.00	74.00	34.00	Peak
6	18000.00	48.90	8.24	34.30	21.81	44.65	74.00	29.35	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 58 File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 58
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5320MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5320.00	32.50	3.60	34.57	75.56	77.09	68.20	-8.89	Peak
2	8038.00	36.90	5.78	34.88	33.07	40.87	74.00	33.13	Peak
3	10640.00	39.54	6.04	34.39	29.36	40.55	74.00	33.45	Peak
4	14974.00	40.91	6.82	34.59	29.98	43.12	68.20	25.08	Peak
5	15960.00	39.84	6.88	34.21	25.29	37.80	74.00	36.20	Peak
6	17677.00	46.32	8.03	34.33	26.25	46.27	68.20	21.93	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 59 File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 59
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5500MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5500.00	32.90	3.71	34.50	74.77	76.88	68.20	-8.68	Peak
2	9823.00	38.56	5.76	34.23	33.42	43.51	68.20	24.69	Peak
3	11000.00	39.90	6.11	34.50	29.14	40.65	74.00	33.35	Peak
4	15076.00	40.82	6.76	34.57	30.21	43.22	68.20	24.98	Peak
5	16500.00	40.36	7.12	34.30	26.57	39.75	68.20	28.45	Peak
6	17813.00	47.41	8.12	34.32	21.10	42.31	74.00	31.69	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 60 File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 60
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5500MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5500.00	32.90	3.71	34.50	77.37	79.48	68.20	-11.28	Peak
2	10095.00	39.00	5.92	34.23	31.59	42.28	68.20	25.92	Peak
3	11000.00	39.90	6.11	34.50	28.68	40.19	74.00	33.81	Peak
4	15110.00	40.79	6.73	34.56	30.07	43.03	68.20	25.17	Peak
5	16500.00	40.36	7.12	34.30	26.87	40.05	68.20	28.15	Peak
6	17915.00	48.22	8.18	34.31	22.97	45.06	74.00	28.94	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 61 File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 61
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5580MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5580.00	32.89	3.79	34.47	77.49	79.70	68.20	-11.50	Peak
2	10333.00	39.24	5.98	34.30	33.33	44.25	68.20	23.95	Peak
3	11160.00	39.90	6.12	34.55	28.57	40.04	74.00	33.96	Peak
4	15059.00	40.84	6.77	34.58	30.31	43.34	68.20	24.86	Peak
5	16740.00	40.62	7.26	34.35	26.69	40.22	68.20	27.98	Peak
6	17983.00	48.76	8.23	34.30	21.29	43.98	74.00	30.02	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 62 File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 62
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5580MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5580.00	32.89	3.79	34.47	74.32	76.53	68.20	-8.33	Peak
2	9891.00	38.69	5.81	34.22	33.84	44.12	68.20	24.08	Peak
3	11160.00	39.90	6.12	34.55	30.69	42.16	74.00	31.84	Peak
4	14600.00	40.98	6.88	34.48	30.30	43.68	68.20	24.52	Peak
5	16740.00	40.62	7.26	34.35	26.38	39.91	68.20	28.29	Peak
6	18000.00	48.90	8.24	34.30	22.41	45.25	74.00	28.75	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 63 File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 63
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5700MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5700.00	32.86	3.94	34.42	74.03	76.41	68.20	-8.21	Peak
2	9823.00	38.56	5.76	34.23	29.38	39.47	68.20	28.73	Peak
3	11400.00	39.90	6.14	34.62	24.38	35.80	74.00	38.20	Peak
4	14634.00	40.97	6.88	34.49	27.80	41.16	68.20	27.04	Peak
5	17100.00	41.71	7.52	34.39	22.78	37.62	68.20	30.58	Peak
6	17813.00	47.41	8.12	34.32	23.65	44.86	74.00	29.14	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 64 File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 64
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5700MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5700.00	32.86	3.94	34.42	78.44	80.82	68.20	-12.62	Peak
2	9942.00	38.80	5.85	34.21	32.69	43.13	68.20	25.07	Peak
3	11400.00	39.90	6.14	34.62	27.93	39.35	74.00	34.65	Peak
4	14957.00	40.91	6.82	34.58	30.89	44.04	68.20	24.16	Peak
5	17100.00	41.71	7.52	34.39	24.22	39.06	68.20	29.14	Peak
6	17932.00	48.36	8.20	34.31	22.08	44.33	74.00	29.67	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 65 File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (78) Date: 2020-04-24




Site no. : 1# 966 Chamber Data no. : 65
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5745MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	3057.00	28.63	2.26	34.41	46.16	42.64	68.20	25.56	Peak
2	5745.00	32.85	4.00	34.40	77.15	79.60	68.20	-11.40	Peak
3	10282.00	39.19	5.96	34.29	31.42	42.28	68.20	25.92	Peak
4	11490.00	39.90	6.15	34.65	27.24	38.64	74.00	35.36	Peak
5	15127.00	40.77	6.72	34.55	30.76	43.70	68.20	24.50	Peak
6	17235.00	42.80	7.65	34.38	22.58	38.65	68.20	29.55	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



Site no. : 1# 966 Chamber Data no. : 66
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5745MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5745.00	32.85	4.00	34.40	79.99	82.44	68.20	-14.24	Peak
2	9925.00	38.76	5.84	34.21	32.73	43.12	68.20	25.08	Peak
3	11490.00	39.90	6.15	34.65	27.57	38.97	74.00	35.03	Peak
4	14991.00	40.90	6.81	34.59	31.37	44.49	68.20	23.71	Peak
5	17235.00	42.80	7.65	34.38	24.16	40.23	68.20	27.97	Peak
6	18000.00	48.90	8.24	34.30	21.81	44.65	74.00	29.35	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 67 File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (78) Date: 2020-04-24



Site no. : 1# 966 Chamber Data no. : 67
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5785MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5785.00	32.84	4.05	34.39	75.01	77.51	68.20	-9.31	Peak
2	9891.00	38.69	5.81	34.22	35.52	45.80	68.20	22.40	Peak
3	11570.00	39.90	6.12	34.67	29.06	40.41	74.00	33.59	Peak
4	15093.00	40.81	6.74	34.57	33.60	46.58	68.20	21.62	Peak
5	17355.00	43.75	7.77	34.36	26.18	43.34	68.20	24.86	Peak
6	17660.00	46.19	8.02	34.33	25.51	45.39	68.20	22.81	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 68 File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (78) Date: 2020-04-24



Site no. : 1# 966 Chamber Data no. : 68
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5785MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5785.00	32.84	4.05	34.39	78.85	81.35	68.20	-13.15	Peak
2	9993.00	38.90	5.89	34.20	35.27	45.86	68.20	22.34	Peak
3	11570.00	39.90	6.12	34.67	28.94	40.29	74.00	33.71	Peak
4	14685.00	40.96	6.87	34.50	32.12	45.45	68.20	22.75	Peak
5	17355.00	43.75	7.77	34.36	23.70	40.86	68.20	27.34	Peak
6	17796.00	47.27	8.11	34.32	22.96	44.02	74.00	29.98	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878


Data: 69 File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (78) Date: 2020-04-24



Site no. : 1# 966 Chamber Data no. : 69
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5825MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5825.00	32.83	4.11	34.37	75.45	78.02	68.20	-9.82	Peak
2	9891.00	38.69	5.81	34.22	30.53	40.81	68.20	27.39	Peak
3	11650.00	39.90	6.08	34.69	24.35	35.64	74.00	38.36	Peak
4	15059.00	40.84	6.77	34.58	28.77	41.80	68.20	26.40	Peak
5	17475.00	44.70	7.89	34.35	25.18	43.42	68.20	24.78	Peak
6	17864.00	47.82	8.15	34.31	25.10	46.76	74.00	27.24	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.



Site no. : 1# 966 Chamber Data no. : 70
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCCPART 15E PEAK NII
 Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
 Engineer : Seven
 EUT : 8"Android Tablet
 Power : DC5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : IEEE 802.11a TX 5825MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5825.00	32.83	4.11	34.37	74.71	77.28	68.20	-9.08	Peak
2	10690.00	39.59	6.05	34.41	33.40	44.63	74.00	29.37	Peak
3	11650.00	39.90	6.08	34.69	27.12	38.41	74.00	35.59	Peak
4	15127.00	40.77	6.72	34.55	31.76	44.70	68.20	23.50	Peak
5	17475.00	44.70	7.89	34.35	23.65	41.89	68.20	26.31	Peak
6	17762.00	47.00	8.09	34.32	22.87	43.64	74.00	30.36	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Note:

1. The amplitude of 18GHz to 40GHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.
2. All test mode had been pre-test, only Low/Middle/High Channel of the worst case modulation mode was reported

Radiated Band Edge


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 31

File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (78)

Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 31
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCCPART 15E PEAK NII
 Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
 Engineer : Seven
 EUT : 8"Android Tablet
 Power : DC5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : IEEE 802.11a TX 5180MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5150.00	32.13	3.50	34.64	41.66	42.65	68.20	25.55	Peak
2	5181.80	32.20	3.52	34.63	82.54	83.63	68.20	-15.43	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 32 File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 32
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5180MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5150.00	32.13	3.50	34.64	41.68	42.67	68.20	25.53	Peak
2	5181.80	32.20	3.52	34.63	84.99	86.08	68.20	-17.88	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 33

File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (78)

Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 33
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCCPART 15E PEAK NII
 Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
 Engineer : Seven
 EUT : 8"Android Tablet
 Power : DC5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : IEEE 802.11a TX 5240MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5237.75	32.31	3.55	34.61	84.09	85.34	68.20	-17.14	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 34 File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 34
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5240MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5237.75	32.31	3.55	34.61	82.83	84.08	68.20	-15.88	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878


Data: 35 File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 35
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5260MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5258.70	32.39	3.57	34.59	83.72	85.09	68.20	-16.89	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.



Site no. : 1# 966 Chamber Data no. : 36
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5260MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	5258.70	32.39	3.57	34.59	81.80	83.17	68.20	-14.97	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 37 File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 37
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5320MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5318.90	32.50	3.60	34.57	81.95	83.48	68.20	-15.28	Peak
2	5350.00	32.57	3.62	34.56	41.71	43.34	68.20	24.86	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 38 File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 38
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5320MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5322.15	32.50	3.60	34.57	81.00	82.53	68.20	-14.33	Peak
2	5350.00	32.57	3.62	34.56	41.51	43.14	68.20	25.06	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 39 File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 39
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5500MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5470.00	32.83	3.69	34.51	42.85	44.86	68.20	23.34	Peak
2	5501.28	32.90	3.71	34.50	81.29	83.40	68.20	-15.20	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 40 File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 40
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5500MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5470.00	32.83	3.69	34.51	42.14	44.15	68.20	24.05	Peak
2	5499.12	32.90	3.71	34.50	83.02	85.13	68.20	-16.93	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 41 File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (78) Date: 2020-04-23



Site no. : 1# 966 Chamber Data no. : 41
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5700MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	5700.66	32.86	3.96	34.42	83.76	86.16	68.20	-17.96	Peak
2	5725.00	32.86	3.98	34.41	41.74	44.17	68.20	24.03	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 42 File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (78) Date: 2020-04-23




Site no. : 1# 966 Chamber Data no. : 42
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5700MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5697.74	32.86	3.94	34.42	82.52	84.90	68.20	-16.70	Peak
2	5725.00	32.86	3.98	34.41	40.53	42.96	68.20	25.24	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878




Site no. : 1# 966 Chamber Data no. : 43
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCCPART 15E PEAK NII
 Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
 Engineer : Seven
 EUT : 8"Android Tablet
 Power : DC5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : IEEE 802.11a TX 5745MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	5744.80	32.85	4.00	34.40	85.77	88.22	68.20	-20.02	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



Site no. : 1# 966 Chamber Data no. : 44
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5745MHz


	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5746.40	32.85	4.00	34.40	81.65	84.10	68.20	-15.90	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 45 File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (78) Date: 2020-04-24




Site no. : 1# 966 Chamber Data no. : 45
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCCPART 15E PEAK NII
Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
Engineer : Seven
EUT : 8"Android Tablet
Power : DC5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : IEEE 802.11a TX 5825MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5826.60	32.83	4.11	34.37	79.86	82.43	68.20	-14.23	Peak
2	5850.00	32.83	4.13	34.36	42.21	44.81	68.20	23.39	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology



Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878







Site no. : 1# 966 Chamber Data no. : 46
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCCPART 15E PEAK NII
 Env. / Ins. : Temp:27.3';Humi:54%;Press:101.52kPa
 Engineer : Seven
 EUT : 8"Android Tablet
 Power : DC5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : IEEE 802.11a TX 5825MHz



	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	5825.90	32.83	4.11	34.37	84.10	86.67	68.20	-18.47	Peak
2	5850.00	32.83	4.13	34.36	44.68	47.28	68.20	20.92	Peak



Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.














18000MHz-40000MHz

Pass


Note: The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

7. FREQUENCY STABILITY

7.1. Limit

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the operational description.

7.2. Test Setup



7.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	10KHz
VBW	10KHz
Span	200KHz
Sweep Time	Auto
Detector	PEAK
Trace Mode	Max Hold

7.4. Test Procedure

For measurement frequency stability under temperature variation :

- a. Supply the EUT with a nominal ac voltage or install a new or fully charged battery in the EUT.
- b. Turn the EUT OFF and place it inside the environmental temperature chamber.
- c. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- d. Spectrum analyzer setting parameters in accordance with section 7.3.
- e. Set the temperature control on the chamber to the Specified temperature and allow the oscillator heater and the chamber temperature to stabilize.
- f. Turn the EUT ON with the rated voltage, and the EUT transmit continuously with maximum output power.
- g. Record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized.
- h. Repeat step d through step f to measured the temperature form -20°C to $+50^{\circ}\text{C}$ in 10°C steps.

For frequency stability under voltage variation:

- a. Supply the EUT with a nominal ac voltage or install a new or fully charged battery in the EUT.
- b. Turn the EUT OFF and place it inside the environmental temperature chamber.
- c. Connect EUT antenna terminal to the spectrum analyzer with RF cable.
- d. Spectrum analyzer setting parameters in accordance with section 7.3.
- e. Unless otherwise specified, set the temperature control on the chamber to the ambient room temperature ($+15^{\circ}\text{C}$ to $+25^{\circ}\text{C}$) and allow the oscillator heater and the chamber temperature to stabilize.
- f. Turn the EUT ON with the rated voltage, and the EUT transmit continuously with maximum output power.
- g. Record the operating frequency.
- h. Repeat step d through step f to measured the varied from 85% to 115% of the rated voltage.

7.5. Test Result

Frequency (MHz)	Voltage (V)	Temperature (°C)	Time (minutes)	Measurement Value (MHz)	Frequency Error (ppm)
5180	120	50	0	5180.0023000	0.44
			2	5180.0078000	1.51
			5	5180.0020000	0.39
			10	5180.0032100	0.62
	120	40	0	5180.0044000	0.85
			2	5180.0044000	0.85
			5	5180.0044000	0.85
			10	5180.0054000	1.04
	120	30	0	5180.0054000	1.04
			2	5180.0054000	1.04
			5	5180.0045700	0.88
			10	5180.0038000	0.73
	120	20	0	5180.0037000	0.71
			2	5180.0024800	0.48
			5	5180.3300000	63.71
			10	5180.0014700	0.28
	120	10	0	5180.0013100	0.25
			2	5180.0046100	0.89
			5	5180.0044300	0.86
			10	5180.0000000	0.00
	120	0	0	5180.0090000	1.74
			2	5180.0070000	1.35
			5	5180.0070000	1.35
			10	5180.0070000	1.35
	120	-10	0	5180.0070000	1.35
			2	5180.0060000	1.16
			5	5180.0060000	1.16
			10	5180.0060000	1.16
	120	-20	0	5180.0060000	1.16
			2	5180.0038700	0.75
			5	5180.0030000	0.58
			10	5180.0028700	0.55
	120	20	/	5180.0020000	0.39
	102	20	/	5180.0024700	0.48
	138	20	/	5180.0024700	0.48
	MAX Frquency Error(ppm)				63.71

Frequency (MHz)	Voltage (V)	Temperature (°C)	Time (minutes)	Measurement Value (MHz)	Frequency Error (ppm)
5320	120	50	0	5320.0085000	1.60
			2	5320.0087000	1.64
			5	5320.0015400	0.29
			10	5320.0018400	0.35
	120	40	0	5320.0045410	0.85
			2	5320.0044000	0.83
			5	5320.0044000	0.83
			10	5320.0044000	0.83
	120	30	0	5320.0044000	0.83
			2	5320.0047000	0.88
			5	5320.0041400	0.78
			10	5320.0074100	1.39
	120	20	0	5320.0082000	1.54
			2	5320.0042400	0.80
			5	5320.0035400	0.67
			10	5320.0024100	0.45
	120	10	0	5320.0053400	1.00
			2	5320.0045400	0.85
			5	5320.0054100	1.02
			10	5320.0054400	1.02
	120	0	0	5320.0045400	0.85
			2	5320.0025400	0.48
			5	5320.0025400	0.48
			10	5320.0035400	0.67
	120	-10	0	5320.0035400	0.67
			2	5320.0035400	0.67
			5	5320.0035400	0.67
			10	5320.0035400	0.67
	120	-20	0	5320.0075400	1.42
			2	5320.0075450	1.42
			5	5320.0071210	1.34
			10	5320.0001752	0.03
	120	20	/	5320.0081210	1.53
	102	20	/	5320.0082100	1.54
	138	20	/	5320.0087857	1.65
MAX Frquency Error(ppm)					1.65

Frequency (MHz)	Voltage (V)	Temperature (°C)	Time (minutes)	Measurement Value (MHz)	Frequency Error (ppm)
5500	120	50	0	5500.0021500	0.39
			2	5500.0021500	0.39
			5	5500.0021500	0.39
			10	5500.0021500	0.39
	120	40	0	5500.0021500	0.39
			2	5500.0021210	0.39
			5	5500.0024540	0.45
			10	5500.0027870	0.51
	120	30	0	5500.0031200	0.57
			2	5500.0034540	0.63
			5	5500.0011210	0.20
			10	5500.0014700	0.27
	120	20	0	5500.0014700	0.27
			2	5500.0017027	0.31
			5	5500.0018772	0.34
			10	5500.0020517	0.37
	120	10	0	5500.0022262	0.40
			2	5500.0041000	0.75
			5	5500.0037400	0.68
			10	5500.0031210	0.57
	120	0	0	5500.0026747	0.49
			2	5500.0021852	0.40
			5	5500.0016957	0.31
			10	5500.0012062	0.22
	120	-10	0	5500.0064100	1.17
			2	5500.0063500	1.15
			5	5500.0065400	1.19
			10	5500.0067300	1.22
	120	-20	0	5500.0069200	1.26
			2	5500.0071100	1.29
			5	5500.0052100	0.95
			10	5500.0042000	0.76
	120	20	/	5500.0012540	0.23
	102	20	/	5500.0021200	0.39
	138	20	/	5500.0037200	0.68
MAX Frquency Error(ppm)					1.29

Frequency (MHz)	Voltage (V)	Temperature (°C)	Time (minutes)	Measurement Value (MHz)	Frequency Error (ppm)
5745	120	50	0	5745.0014700	0.26
			2	5745.0075000	1.31
			5	5745.0041000	0.71
			10	5745.0069867	1.22
	120	40	0	5745.0083017	1.45
			2	5745.0096167	1.67
			5	5745.0010932	0.19
			10	5745.0012247	0.21
	120	30	0	5745.0013562	0.24
			2	5745.0014877	0.26
			5	5745.0016192	0.28
			10	5745.0035700	0.62
	120	20	0	5745.0015400	0.27
			2	5745.0017800	0.31
			5	5745.0068700	1.20
			10	5745.0068700	1.20
	120	10	0	5745.0010263	0.18
			2	5745.0012808	0.22
			5	5745.0015353	0.27
			10	5745.0017898	0.31
	120	0	0	5745.0084500	1.47
			2	5745.0088500	1.54
			5	5745.0092500	1.61
			10	5745.0096500	1.68
	120	-10	0	5745.0078500	1.37
			2	5745.0034000	0.59
			5	5745.0045300	0.79
			10	5745.0056600	0.99
	120	-20	0	5745.0067900	1.18
			2	5745.0079200	1.38
			5	5745.0034000	0.59
			10	5745.0098700	1.72
	120	20	/	5745.0016340	0.28
	102	20	/	5745.0022810	0.40
	138	20	/	5745.0029280	0.51
MAX Frquency Error(ppm)					1.72

8. AC POWER LINE CONDUCTED EMISSIONS


8.1. Limit

Frequency			Maximum RF Line Voltage	
			Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz	~	500kHz	66 ~ 56*	56 ~ 46*
500kHz	~	5MHz	56	46
5MHz	~	30MHz	60	50

Notes:

1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

8.2. Test Setup



8.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	9KHz
VBW	9KHz
Start frequency	150KHz
Stop frequency	30MHz
Sweep Time	Auto
Detector	QP/AVG
Trace Mode	Max Hold


8.4. Test Procedure

- The EUT was placed on a non-metallic table, 80cm above the ground plane.
- The EUT Power connected to the power mains through a line impedance stabilization network.
- Provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs).
- Set the EUT transmit continuously with maximum output power.
- Spectrum analyzer setting parameters in accordance with section 8.3.
- The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Test.
- Record the results in the test report.

8.5. Test Result

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
0.15	9.62	9.69	2.03	21.34	55.82	34.48	Average
0.15	9.62	9.69	20.31	39.62	65.82	26.20	QP
0.18	9.69	9.77	1.46	20.92	54.46	33.54	Average
0.18	9.69	9.77	19.35	38.81	64.46	25.65	QP
0.20	9.69	9.77	0.69	20.15	53.54	33.39	Average
0.20	9.69	9.77	17.75	37.21	63.54	26.33	QP
0.51	9.78	9.92	0.43	20.13	46.00	25.87	Average
0.51	9.78	9.92	12.44	32.14	56.00	23.86	QP
0.67	9.75	9.92	5.58	25.25	46.00	20.75	Average
0.67	9.75	9.92	19.64	39.31	56.00	16.69	QP
1.07	9.67	9.94	0.63	20.24	46.00	25.76	Average
1.07	9.67	9.94	9.41	29.02	56.00	26.98	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 60

File: \\Emc-ce-1\Test data\2020\RFIC\CHANGCHENG.EM6 (64)

Date: 2020-04-17



Trace: 59

Site no. : 844 Shield Room Data no. : 60
Dis. / Ant. : -----antenna Ant. pol. : LINE
Limit : FCC PART 15B QP
Env. / Ins. : Temp:23.5'C Humi:58% Press:101.50kPa
Engineer : Zero
EUT : 8"Android Tablet
Power : DC 5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : TX Mode

Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
0.15	9.79	9.69	4.91	24.39	55.82	31.43	Average
0.15	9.79	9.69	20.92	40.40	65.82	25.42	QP
0.20	9.80	9.77	5.26	24.83	53.54	28.71	Average
0.20	9.80	9.77	18.35	37.92	63.54	25.62	QP
0.41	9.84	9.92	4.00	23.76	47.73	23.97	Average
0.41	9.84	9.92	16.12	35.88	57.73	21.85	QP
0.53	9.93	9.92	5.38	25.23	46.00	20.77	Average
0.53	9.93	9.92	18.42	38.27	56.00	17.73	QP
0.66	9.82	9.92	13.11	32.85	46.00	13.15	Average
0.66	9.82	9.92	28.12	47.86	56.00	8.14	QP
1.06	9.79	9.94	4.44	24.17	46.00	21.83	Average
1.06	9.79	9.94	18.54	38.27	56.00	17.73	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 62

File: \\Emc-ce-1\Test data\2020\RFIC\CHANGCHENG.EM6 (64)

Date: 2020-04-17



Trace: 61

Site no. : 844 Shield Room Data no. : 62
Dis. / Ant. : -----antenna Ant. pol. : LINE
Limit : FCC PART 15B QP
Env. / Ins. : Temp:23.5'C Humi:58% Press:101.50kPa
Engineer : Zero
EUT : 8"Android Tablet
Power : DC 5V From Adapter Input AC 240V/60Hz
M/N : 100011885
Test Mode : TX Mode

Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
0.24	9.70	9.92	5.98	25.60	52.17	26.57	Average
0.24	9.70	9.92	18.86	38.48	62.17	23.69	QP
0.67	9.82	9.92	11.65	31.39	46.00	14.61	Average
0.67	9.82	9.92	26.66	46.40	56.00	9.60	QP
0.91	9.79	9.94	6.02	25.75	46.00	20.25	Average
0.91	9.79	9.94	20.09	39.82	56.00	16.18	QP
1.41	9.79	9.95	4.12	23.86	46.00	22.14	Average
1.41	9.79	9.95	19.19	38.93	56.00	17.07	QP
2.01	9.80	9.96	3.97	23.73	46.00	22.27	Average
2.01	9.80	9.96	18.90	38.66	56.00	17.34	QP
3.31	9.86	9.98	3.73	23.57	46.00	22.43	Average
3.31	9.86	9.98	16.68	36.52	56.00	19.48	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 64

File: \\Emc-ce-1\Test data\2020\RFIC\CHANGCHENG.EM6 (64)

Date: 2020-04-17



Trace: 63

Site no. : 844 Shield Room Data no. : 64
 Dis. / Ant. : -----antenna Ant. pol. : NEUTRAL
 Limit : FCC PART 15B QP
 Env. / Ins. : Temp:23.5'C Humi:58% Press:101.50kPa
 Engineer : Zero
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 240V/60Hz
 M/N : 100011885
 Test Mode : TX Mode

Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
0.16	9.62	9.69	0.16	19.47	55.30	35.83	Average
0.16	9.62	9.69	15.65	34.96	65.30	30.34	QP
0.26	9.71	9.92	1.14	20.77	51.34	30.57	Average
0.26	9.71	9.92	11.35	30.98	61.34	30.36	QP
0.68	9.75	9.92	5.31	24.98	46.00	21.02	Average
0.68	9.75	9.92	18.34	38.01	56.00	17.99	QP
1.50	9.68	9.96	0.37	20.01	46.00	25.99	Average
1.50	9.68	9.96	10.40	30.04	56.00	25.96	QP
2.00	9.68	9.96	0.53	20.17	46.00	25.83	Average
2.00	9.68	9.96	10.49	30.13	56.00	25.87	QP
2.62	9.80	9.97	0.60	20.37	46.00	25.63	Average
2.62	9.80	9.97	12.24	32.01	56.00	23.99	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

9. ANTENNA REQUIREMENTS

9.1. Limit


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

9.2. Test Result


The antennas used for this product is internal antenna ,so compliance with antenna requirements.
(Please refer to the EUT photo for details)

10. TEST SETUP PHOTO


Conducted Test



Radiated Test (Below 1GHz)



Radiated Test (Above 1GHz)





11. EUT PHOTO



External Photos
M/N: 100011885




External Photos
M/N: 100011885




External Photos
M/N: 100011885




Power Supply



Internal Photos
M/N: 100011885




Internal Photos
M/N: 100011885




Internal Photos
M/N: 100011885




Internal Photos
M/N: 100011885



Internal Photos
M/N: 100011885



Mainboard Model No.: MDXC1016G-M2 2GB & LTMZ0007HF-DAB1-SM



Mainboard Model No.: RS512M32LM4D2BDS-53BT 2GB & EMMC32G-TA28 32GB

End of Test Report