

FCC PART 15C TEST REPORT FOR CERTIFICATION
On Behalf of

Hunan Greatwall Computer System Co., Ltd

8"Android Tablet

Model Number: 100011885

FCC ID: 2APUQW829


Prepared for:	Hunan Greatwall Computer System Co., Ltd
	Hu'nan Greatwall Industrial Park,Xiangyun Middle Rd., Tianyuan
	Dist., Zhuzhou, Hu'nan
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
	Tel: 86-769-83081888-808

Report Number:	ESTE-R2004080-1
Date of Test:	Aug. 13~Sep. 01, 2020
Date of Report:	Sep. 02, 2020

TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION.....	3
1. GENERAL INFORMATION.....	4
1.1. Description of Device (EUT)	4
1.2. Difference between Model Numbers.....	4
1.3. Antenna Information	4
2. SUMMARY OF TEST	5
2.1. Summary of test result.....	5
2.2. Test Facilities	6
2.3. Measurement uncertainty	7
2.4. Assistant equipment used for test.....	7
2.5. Block Diagram	7
2.6. Test Mode.....	8
2.7. Power Setting of Test Software.....	9
2.8. Channel List	9
2.9. Test Equipment List	10
3. RADIATED SPURIOUS EMISSIONS AND BAND EDGE	11
3.1. Limit	11
3.2. Test setup.....	12
3.3. Spectrum Analyzer Setting.....	13
3.4. Test Procedure.....	14
3.5. Test Result.....	15
4. AC POWER LINE CONDUCTED EMISSIONS	21
4.1. Limit	21
4.2. Test Setup.....	21
4.3. Spectrum Analyzer Setting.....	21
4.4. Test Procedure.....	21
4.5. Test Result.....	22
5. TEST SETUP PHOTO	34
6. EUT PHOTO.....	36

EST Technology Co., Ltd.

Applicant:	Hunan Greatwall Computer System Co., Ltd		
Address:	Hu'nan Greatwall Industrial Park, Xiangyun Middle Rd., Tianyuan Dist., Zhuzhou, Hu'nan		
Manufacturer:	Hunan Greatwall Computer System Co., Ltd		
Address:	Hu'nan Greatwall Industrial Park, Xiangyun Middle Rd., Tianyuan Dist., Zhuzhou, Hu'nan		
E.U.T:	8" Android Tablet		
Model Number:	100011885		
Power Supply:	DC 5V From Adapter Input AC 100-240V~50/60Hz DC 3.8V From Battery		
Trade Name:	onn.	Serial No.:	-----
Date of Receipt:	Aug. 13, 2020	Date of Test:	Aug. 13~Sep. 01, 2020
Test Specification:	FCC Part 15 Subpart C (15.247) ANSI C63.10:2013 FCC KDB 558074 D01 15.247 Meas Guidance v05r02 FCC KDB 662911 D01 Multiple Transmitter Output v02r01		
Test Result:	The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC Rules and Regulations Part 15 Subpart C requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.		
Prepared by:		Reviewed by:	Date: Sep. 02, 2020
 _____ Ring Yang / Assistant		 _____ Seven Wang / Engineer	 _____ Iceman Hu / Manager
Other Aspects: Because only the replace the power management chip PMU and add supply power, so just re-tested spurious emissions(30-1000MHz) 、conducted Emissions, other test item needn't re-tested, test data refer to test report " ESTE-R2004080"			
Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested			
This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.			

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Product Name	:	8"Android Tablet
Model Number	:	100011885
Software Version	:	F732M.Q0.V3.18.CC-V03.8168.64-7420
Hardware Version	:	F732U2.0
Operation frequency	:	2412MHz~2462MHz 2422MHz~2452MHz
Number of channel	:	IEEE 802.11b: 11 Channels IEEE 802.11g: 11 Channels IEEE 802.11n HT20: 11 Channels
Max Output Power (PEAK)	:	IEEE 802.11b: 18.41dBm IEEE 802.11g: 21.48dBm IEEE 802.11n HT20: 21.56dBm IEEE 802.11n HT40: 21.2dBm
Modulation Type	:	IEEE 802.11b mode: DSSS(CCK,QPSK, BPSK) IEEE 802.11g mode: OFDM (BPSK/QPSK/16QAM/64QAM) IEEE 802.11n mode: OFDM (BPSK/QPSK/16QAM/64QAM)
Sample Type	:	Prototype production

Note:

For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

1.2. Difference between Model Numbers

Model Number	main board	DDR	EMMC	MPU
100011885	1	RS512M32LZ4D2ANP_75BT 2G/4die 3733Mbps 10*14.5mm FBGA200 RS	MEMA032G 32GB 1.8V/HS400/EMMC5.1 200MHz 153-FBGA ISOCOM	MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJP
	2	MDXC1016G-M2 2GB(512*32) 3200Mbps 10*14.5mm FBGA200 FORESEE	LTMZ0007HF-DAB1-SM Leahkinn	
	3	RS512M32LM4D2BDS-53BT 2GB(512*32) 3200Mbps 10*14.5mm FBGA200 RS	EMMC32G-TA28 32GB 1.8V 200MHz 153-FBGA Kingston	

Note: Default is A mainboard, reported to the DDR,EMMC and MPU combination for 2 and 3

1.3. Antenna Information

Ant No.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Internal	N/A	2.2

2. SUMMARY OF TEST

2.1. Summary of test result

Report Section	Description of Test Item	FCC Standard Section	Results
3	6dB Bandwidth	15.247(a)(2)	N/A
4	Maximum Peak Output Power	15.247(b)(3)	N/A
5	Power Spectral Density	15.247(e)	N/A
6	Conducted Band Edge	15.247(d)	N/A
7	Conducted Spurious Emissions	15.247(d)	N/A
8	Radiated Spurious Emissions and Band Edge	15.205 15.209 15.247(d)	PASS
9	AC Power Line Conducted Emissions	15.207	PASS
10	Antenna Requirement	15.203	N/A

Note:

(1) “N/A” denotes test is not applicable in this test report

2.2. Test Facilities

EMC Lab

: Certificated by CNAS, CHINA
Registration No.: L5288
This Certificate is valid until: November 12, 2023

Certificated by FCC, USA
Designation Number: CN1215
This Certificate is valid until: January 31, 2022

Certificated by A2LA, USA
Registration No.: 4366.01
This Certificate is valid until: January 31, 2022

Certificated by Industry Canada
CAB identifier No.: CN0035
This Certificate is valid until: January 31, 2022

Certificated by VCCI, Japan
Registration No.: C-14103; T-20073; R-13663;
R-20103; G-20097
Date of registration: Apr. 20, 2020
This Certificate is valid until: Apr. 19, 2023

Certificated by TUV Rheinland, Germany
Registration No.: UA 50413872 0001
Date of registration: July 31, 2018

Certificated by Intertek
Registration No.: 2011-RTL-L2-64
Date of registration: November 08, 2018

Name of Firm : EST Technology Co., Ltd.

Site Location : Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China

2.3. Measurement uncertainty

Test Item	Uncertainty
Uncertainty for Conduction emission test	$\pm 3.48\text{dB}$
Uncertainty for spurious emissions test (30MHz-1GHz)	$\pm 4.60\text{ dB(Polarize: H)}$
	$\pm 4.68\text{ dB(Polarize: V)}$
Uncertainty for spurious emissions test (1GHz to 25GHz)	$\pm 4.96\text{dB}$
Uncertainty for radio frequency	7×10^{-8}
Uncertainty for conducted RF Power	0.20dB
Uncertainty for Power density test	0.26dB

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.


2.4. Assistant equipment used for test

Item	Equipment	Brand	Model Name/Type No.	FCC ID	Series No.
A	Adapter	omn	GDA0101H-U0500200	N/A	N/A

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	1m	DC Cable

2.5. Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 (or 1.5) meter high above ground. EUT was beset into 2.4G WIFI test mode by software before test.



(EUT: 8"Android Tablet)

2.6. Test Mode

The test mode was selected for the final test as listed below.

Test Item	Mode	Date Rate	Test Channel
Radiated Spurious Emissions(Below 1GHz)	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
	IEEE 802.11n HT40	MCS0	Low/Middle/High
AC Power Line Conducted Emissions	IEEE 802.11b	1Mbps	Low/Middle/High
	IEEE 802.11g	6Mbps	Low/Middle/High
	IEEE 802.11n HT20	MCS0	Low/Middle/High
	IEEE 802.11n HT40	MCS0	Low/Middle/High

Note:

1. In radiated measurement, the EUT had been pre-scan on the positioned of each 3 axis(X,Y,Z), the worst case was found when positioned on **X-plane**.

2.7. Power Setting of Test Software

Software Name	N/A		
Frequency(MHz)	2412	2437	2462
IEEE 802.11b Setting	Default	Default	Default
IEEE 802.11g Setting	Default	Default	Default
IEEE 802.11n HT20 Setting	Default	Default	Default
Frequency(MHz)	2422	2437	2452
IEEE 802.11n HT40 Setting	Default	Default	Default

2.8. Channel List

IEEE 802.11b/802.11g/802.11n HT20					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462
2	2417	7	2442		
3	2422	8	2447		
4	2427	9	2452		
5	2432	10	2457		
IEEE 802.11n HT40					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	6	2437	9	2452
4	2427	7	2442		
5	2432	8	2447		

2.9. Test Equipment List

For conducted emission test						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESHS30	EST-E001	LISAI	June 13,20	1 Year
Artificial Mains Network	Rohde & Schwarz	ENV216	EST-E002	LISAI	June 13,20	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	EST-E078	LISAI	June 13,20	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

For radiated emissions test (30MHz-1000MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	EST-E047	LISAI	June 13,20	1 Year
Bilog Antenna	Teseq	CBL 6111D	EST-E034	LISAI	June 13,20	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
30-1000MHz Cable	N/A	EST-002	N/A	N/A	N/A	N/A

For radiated emission test(Above 1000MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Horn Antenna	SCHWARZB ECK	BBHA9120D	EST-E031	LISAI	June 13,20	1 Year
Signal Amplifier	SCHWARZB ECK	BBV9718	EST-E032	LISAI	June 13,20	1 Year
Spectrum Analyzer	Rohde &Schwarz	FSV40	EST-E069	LISAI	June 13,20	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
Above 1GHz Cable	N/A	EST-003	N/A	N/A	N/A	N/A

3. RADIATED SPURIOUS EMISSIONS AND BAND EDGE

3.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)


15.209 Limit

Frequency (MHz)	Field Strength(μ V/m)	Distance(m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Note:

- (1) Emission level $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$.
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

3.2. Test setup



3.3. Spectrum Analyzer Setting

For 9KHz-150KHz

Spectrum Parameters	Setting
RBW	300Hz(for Peak&AVG)/CISPR 200Hz(for QP)
VBW	300Hz(for Peak&AVG)/CISPR 200Hz(for QP)
Start frequency	9KHz
Stop frequency	150KHz
Sweep Time	Auto
Detector	PEAK/QP/AVG
Trace Mode	Max Hold

For 150KHz-30MHz

Spectrum Parameters	Setting
RBW	9KHz
VBW	9KHz
Start frequency	150KHz
Stop frequency	30MHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

For 30MHz-1GHz

Spectrum Parameters	Setting
RBW	120KHz
VBW	300KHz
Start frequency	30MHz
Stop frequency	1GHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

For Above 1GHz

Spectrum Parameters	Setting
RBW	1MHz
VBW	PEAK Measurement
	3MHz
	AVG Measurement
	Duty cycle $\geq 98\%$, VBW=10Hz
	Duty cycle $< 98\%$, VBW $\geq 1/T$
Start frequency	1GHz
Stop frequency	25GHz
Sweep Time	Auto
Detector	PEAK
Trace Mode	Max Hold

Note :

1. T is the on-time time of the duty cycle,when EUT transmit continuously with maximum output power,unit is seconds. reference section 2.8 for the on-time time.

3.4. Test Procedure

- a. EUT was placed on a turn table, which is 0.8 meter high above ground for below 1GHz test, and which is 1.5 meter high above ground for above 1GHz test.
- b. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower.
- c. Set the EUT transmit continuously with maximum output power.
- d. The turn table can rotate 360 degrees to determine the position of the maximum emission level.
- e. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.
- f. Spectrum analyzer setting parameters in accordance with section 8.3.
- g. Repeat above procedures until all channels were measured.
- h. Record the results in the test report.

Note:


1. For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.
2. The frequency 2412MHz/2422MHz/2437MHz/2452MHz/2462MHz are fundamental frequency, which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.

3.5. Test Result

Radiated Emissions Below 1GHz

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



Site no. : 3# 966 Chamber Data no. : 95
 Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:25.2'; Humi:56%; Press:101.52kPa
 Engineer : Blank
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:RS512M32LZ4D2ANP_75BT 2G
 EMMC:MEMA032G 32GB 1.8V
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJF

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	30.000	18.40	0.14	2.39	20.93	40.00	19.07	QP
2	80.440	7.60	0.68	8.17	16.45	40.00	23.55	QP
3	139.610	12.50	1.03	3.23	16.76	43.50	26.74	QP
4	731.310	21.71	3.55	3.47	28.73	46.00	17.27	QP
5	856.440	23.67	3.73	2.70	30.10	46.00	15.90	QP
6	947.620	24.56	4.49	1.95	31.00	46.00	15.00	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 96

File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (118)

Date: 2020-08-24



Site no. : 3# 966 Chamber Data no. : 96
Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL
Limit : FCC PART 15 B(3M)
Env. / Ins. : Temp:25.2';Humi:56%;Press:101.52kPa
Engineer : Blank
EUT : 8"Android Tablet
Power : DC 5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : TX Mode
DDR:RS512M32L24D2ANP_75BT 2G
EMMC:MEMA032G 32GB 1.8V
MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	38.730	12.50	0.20	10.17	22.87	40.00	17.13	QP
2	159.980	11.30	1.14	9.70	22.14	43.50	21.36	QP
3	531.490	18.85	2.79	6.34	27.98	46.00	18.02	QP
4	603.270	20.46	2.99	6.44	29.89	46.00	16.11	QP
5	730.340	21.70	3.56	4.77	30.03	46.00	15.97	QP
6	951.500	24.62	4.54	4.48	33.64	46.00	12.36	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 103

File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (118)

Date: 2020-08-24



Site no. : 3# 966 Chamber Data no. : 103
 Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:25.2'; Humi:56%; Press:101.52kPa
 Engineer : Blank
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:MDXC1016G-M2 2GB
 EMMC:LTM20007HF-DAB1-SM
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.970	17.60	0.14	2.52	20.26	40.00	19.74	QP
2	86.260	8.50	0.76	8.51	17.77	40.00	22.23	QP
3	190.050	8.90	1.24	8.76	18.90	43.50	24.60	QP
4	714.820	21.70	3.39	3.11	28.20	46.00	17.80	QP
5	827.340	23.37	3.71	3.05	30.13	46.00	15.87	QP
6	948.590	24.58	4.51	2.22	31.31	46.00	14.69	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 104

File: \\Emc-966-1\test data\2020\RFIC\CHANGCHENG\100011885.EM6 (118)

Date: 2020-08-24




Site no. : 3# 966 Chamber Data no. : 104
 Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:25.2'; Humi:56%; Press:101.52kPa
 Engineer : Blank
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:MDXC1016G-M2 2GB
 EMMC:LTM20007HF-DAB1-SM
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.970	17.60	0.14	6.56	24.30	40.00	15.70	QP
2	48.430	9.50	0.28	13.56	23.34	40.00	16.66	QP
3	160.950	11.14	1.15	13.45	25.74	43.50	17.76	QP
4	744.890	21.80	3.66	2.21	27.67	46.00	18.33	QP
5	856.440	23.67	3.73	2.57	29.97	46.00	16.03	QP
6	953.440	24.64	4.60	2.19	31.43	46.00	14.57	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

Data: 111 File: \\Emc-966-1\\test data\\2020\\RF\\C\\CHANGCHENG\\100011885.EM6 (118) Date: 2020-08-25



Site no. : 3# 966 Chamber Data no. : 111
Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL
Limit : FCC PART 15 B(3M)
Env. / Ins. : Temp:25.2';Humi:56%;Press:101.52kPa
Engineer : Blank
EUT : 8"Android Tablet
Power : DC 5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : TX Mode
DDR:RS512M32LM4D2BDS-53BT 2GB
EMMC:EMMC32G-TA28 32GB
MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP


	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	38.730	12.50	0.20	11.00	23.70	40.00	16.30	QP
2	166.770	10.18	1.19	7.43	18.80	43.50	24.70	QP
3	531.490	18.85	2.79	3.33	24.97	46.00	21.03	QP
4	824.430	23.35	3.72	2.17	29.24	46.00	16.76	QP
5	888.450	23.88	3.89	2.59	30.36	46.00	15.64	QP
6	943.740	24.48	4.42	2.32	31.22	46.00	14.78	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 112 File: \\Emc-966-1\\test data\\2020\\RFIC\\CHANGCHENG\\100011885.EM6 (118)
Date: 2020-08-25



Site no. : 3# 966 Chamber Data no. : 112
Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL
Limit : FCC PART 15 B(3M)
Env. / Ins. : Temp:25.2'; Humi:56%; Press:101.52kPa
Engineer : Blank
EUT : 8"Android Tablet
Power : DC 5V From Adapter Input AC 120V/60Hz
M/N : 100011885
Test Mode : TX Mode
DDR:RS512M32LM4D2BDS-53BT 2GB
EMMC:EMMC32G-TA28 32GB
MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Remark
1	64.920	5.50	0.48	12.86	18.84	40.00	21.16	QP
2	80.440	7.60	0.68	10.77	19.05	40.00	20.95	QP
3	233.700	10.78	1.55	7.23	19.56	46.00	26.44	QP
4	685.720	21.64	3.20	3.16	28.00	46.00	18.00	QP
5	793.390	22.76	3.55	7.08	33.39	46.00	12.61	QP
6	825.400	23.35	3.71	4.26	31.32	46.00	14.68	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

Note:

- The amplitude of 9KHz to 30MHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.
- All channels had been pre-test, only the worst case was reported.

4. AC POWER LINE CONDUCTED EMISSIONS


4.1. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note:

1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

4.2. Test Setup



4.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	9KHz
VBW	9KHz
Start frequency	150KHz
Stop frequency	30MHz
Sweep Time	Auto
Detector	QP/AVG
Trace Mode	Max Hold

4.4. Test Procedure

- a. The EUT was placed on a non-metallic table, 80cm above the ground plane.
- b. The EUT Power connected to the power mains through a line impedance stabilization network.
- c. Provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs).
- d. Set the EUT transmit continuously with maximum output power.
- e. Spectrum analyzer setting parameters in accordance with section 9.3.
- f. The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Test.
- g. Record the results in the test report.

4.5. Test Result


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 162

File: \\Emc-ce-1\Test data\2020\RFIC\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 161

Site no : 844 Shield Room Data no. : 162
 Env. / Ins. : Temp:23.5'C Humi:58% Press:101.50kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 240V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:RS512M32LZ4D2ANP_75BT 2G
 EMMC:MEMA032G 32GB 1.8V
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.3019	9.63	9.92	9.78	29.33	50.19	20.86	Average
2	0.3019	9.63	9.92	17.94	37.49	60.19	22.70	QP
3	0.4193	9.64	9.92	17.00	36.56	47.46	10.90	Average
4	0.4193	9.64	9.92	22.24	41.80	57.46	15.66	QP
5	0.4564	9.65	9.92	19.30	38.87	46.76	7.89	Average
6	0.4564	9.65	9.92	25.44	45.01	56.76	11.75	QP
7	0.4994	9.65	9.92	13.57	33.14	46.01	12.87	Average
8	0.4994	9.65	9.92	20.73	40.30	56.01	15.71	QP
9	0.7630	9.70	9.93	9.01	28.64	46.00	17.36	Average
10	0.7630	9.70	9.93	18.35	37.98	56.00	18.02	QP
11	0.8393	9.70	9.93	8.80	28.43	46.00	17.57	Average
12	0.8393	9.70	9.93	15.48	35.11	56.00	20.89	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 164

File: \\Emc-ce-1\Test data\2020\RFIC\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 163

Site no : 844 Shield Room Data no. : 164
 Env. / Ins. : Temp:23.5'C Humi:58% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 240V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:RS512M32LZ4D2ANP_75BT 2G
 EMMC:MEMA032G 32GB 1.8V
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.2987	9.72	9.92	2.84	22.48	50.28	27.80	Average
2	0.2987	9.72	9.92	13.94	33.58	60.28	26.70	QP
3	0.3771	9.72	9.92	4.07	23.71	48.34	24.63	Average
4	0.3771	9.72	9.92	17.36	37.00	58.34	21.34	QP
5	0.4193	9.72	9.92	10.59	30.23	47.46	17.23	Average
6	0.4193	9.72	9.92	22.67	42.31	57.46	15.15	QP
7	0.4564	9.72	9.92	13.37	33.01	46.76	13.75	Average
8	0.4564	9.72	9.92	24.66	44.30	56.76	12.46	QP
9	0.4994	9.72	9.92	5.45	25.09	46.01	20.92	Average
10	0.4994	9.72	9.92	17.59	37.23	56.01	18.78	QP
11	0.8393	9.72	9.93	4.60	24.25	46.00	21.75	Average
12	0.8393	9.72	9.93	16.70	36.35	56.00	19.65	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 166

File: \\Emc-ce-1\Test data\2020\RFIC\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 165

Site no : 844 Shield Room Data no. : 166
 Env. / Ins. : Temp:23.5'C Humi:58% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:RS512M32LZ4D2ANP_75BT 2G
 EMMC:MEMA032G 32GB 1.8V
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJP

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.3321	9.72	9.92	1.42	21.06	49.40	28.34	Average
2	0.3321	9.72	9.92	14.57	34.21	59.40	25.19	QP
3	0.4193	9.72	9.92	10.16	29.80	47.46	17.66	Average
4	0.4193	9.72	9.92	24.25	43.89	57.46	13.57	QP
5	0.4637	9.72	9.92	10.06	29.70	46.63	16.93	Average
6	0.4637	9.72	9.92	22.42	42.06	56.63	14.57	QP
7	0.5101	9.72	9.92	2.87	22.51	46.00	23.49	Average
8	0.5101	9.72	9.92	13.95	33.59	56.00	22.41	QP
9	0.8850	9.72	9.93	1.66	21.31	46.00	24.69	Average
10	0.8850	9.72	9.93	14.79	34.44	56.00	21.56	QP
11	1.0997	9.72	9.94	-0.56	19.10	46.00	26.90	Average
12	1.0997	9.72	9.94	14.59	34.25	56.00	21.75	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 168

File: \\Emc-ce-1\Test data\2020\RFIC\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 167

Site no : 844 Shield Room Data no. : 168
 Env. / Ins. : Temp:23.5'C Humi:58% Press:101.50kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:RS512M32LZ4D2ANP_75BT 2G
 EMMC:MEMA032G 32GB 1.8V
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.3338	9.63	9.92	6.22	25.77	49.35	23.58	Average
2	0.3338	9.63	9.92	15.46	35.01	59.35	24.34	QP
3	0.4215	9.64	9.92	15.73	35.29	47.42	12.13	Average
4	0.4215	9.64	9.92	21.86	41.42	57.42	16.00	QP
5	0.4637	9.65	9.92	13.67	33.24	46.63	13.39	Average
6	0.4637	9.65	9.92	22.78	42.35	56.63	14.28	QP
7	0.5074	9.65	9.92	10.66	30.23	46.00	15.77	Average
8	0.5074	9.65	9.92	19.78	39.35	56.00	16.65	QP
9	0.8850	9.72	9.93	5.97	25.62	46.00	20.38	Average
10	0.8850	9.72	9.93	15.85	35.50	56.00	20.50	QP
11	1.3029	9.77	9.94	4.82	24.53	46.00	21.47	Average
12	1.3029	9.77	9.94	15.94	35.65	56.00	20.35	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 194

File: \\Emc-ce-1\Test data\2020\RFIC\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 193

Site no : 844 Shield Room Data no. : 194
 Env. / Ins. : Temp:23.5'C Humi:58% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 240V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:MDXC1016G-M2 2GB
 EMMC:LTM20007HF-DAB1-SM
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.1685	9.73	9.69	7.47	26.89	55.03	28.14	Average
2	0.1685	9.73	9.69	27.55	46.97	65.03	18.06	QP
3	0.3832	9.72	9.92	5.40	25.04	48.21	23.17	Average
4	0.3832	9.72	9.92	17.78	37.42	58.21	20.79	QP
5	0.4215	9.72	9.92	8.61	28.25	47.42	19.17	Average
6	0.4215	9.72	9.92	18.84	38.48	57.42	18.94	QP
7	0.4637	9.72	9.92	11.84	31.48	46.63	15.15	Average
8	0.4637	9.72	9.92	22.93	42.57	56.63	14.06	QP
9	0.5074	9.72	9.92	5.26	24.90	46.00	21.10	Average
10	0.5074	9.72	9.92	15.76	35.40	56.00	20.60	QP
11	0.8438	9.72	9.93	2.03	21.68	46.00	24.32	Average
12	0.8438	9.72	9.93	14.85	34.50	56.00	21.50	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 196

File: \\Emc-ce-1\Test data\2020\RFIC\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 195

Site no : 844 Shield Room Data no. : 196
 Env. / Ins. : Temp:23.5'C Humi:58% Press:101.50kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 240V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:MDXC1016G-M2 2GB
 EMMC:LTM20007HF-DAB1-SM
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.3019	9.63	9.92	9.89	29.44	50.19	20.75	Average
2	0.3019	9.63	9.92	19.36	38.91	60.19	21.28	QP
3	0.3832	9.64	9.92	10.38	29.94	48.21	18.27	Average
4	0.3832	9.64	9.92	17.54	37.10	58.21	21.11	QP
5	0.4215	9.64	9.92	16.38	35.94	47.42	11.48	Average
6	0.4215	9.64	9.92	21.66	41.22	57.42	16.20	QP
7	0.4637	9.65	9.92	17.72	37.29	46.63	9.34	Average
8	0.4637	9.65	9.92	23.95	43.52	56.63	13.11	QP
9	0.5020	9.65	9.92	12.47	32.04	46.00	13.96	Average
10	0.5020	9.65	9.92	20.87	40.44	56.00	15.56	QP
11	0.8438	9.71	9.93	9.73	29.37	46.00	16.63	Average
12	0.8438	9.71	9.93	16.42	36.06	56.00	19.94	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 198

File: \\Emc-ce-1\Test data\2020\RFIC\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 197

Site no : 844 Shield Room Data no. : 198
 Env. / Ins. : Temp:23.5'C Humi:58% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:MDXC1016G-M2 2GB
 EMMC:LTM20007HF-DAB1-SM
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.1740	9.73	9.77	5.21	24.71	54.77	30.06	Average
2	0.1740	9.73	9.77	23.26	42.76	64.77	22.01	QP
3	0.3356	9.72	9.92	1.14	20.78	49.31	28.53	Average
4	0.3356	9.72	9.92	14.35	33.99	59.31	25.32	QP
5	0.4260	9.72	9.92	8.52	28.16	47.33	19.17	Average
6	0.4260	9.72	9.92	21.48	41.12	57.33	16.21	QP
7	0.4686	9.72	9.92	9.45	29.09	46.54	17.45	Average
8	0.4686	9.72	9.92	22.59	42.23	56.54	14.31	QP
9	0.5101	9.72	9.92	2.87	22.51	46.00	23.49	Average
10	0.5101	9.72	9.92	13.95	33.59	56.00	22.41	QP
11	0.8944	9.72	9.94	-1.05	18.61	46.00	27.39	Average
12	0.8944	9.72	9.94	13.77	33.43	56.00	22.57	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 200

File: \\Emc-ce-1\Test data\2020\RFIC\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 199

Site no : 844 Shield Room Data no. : 200
 Env. / Ins. : Temp:23.5'C Humi:58% Press:101.50kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:MDXC1016G-M2 2GB
 EMMC:LTM20007HF-DAB1-SM
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.1806	9.62	9.77	8.74	28.13	54.46	26.33	Average
2	0.1806	9.62	9.77	23.58	42.97	64.46	21.49	QP
3	0.3286	9.63	9.92	6.45	26.00	49.49	23.49	Average
4	0.3286	9.63	9.92	15.74	35.29	59.49	24.20	QP
5	0.4193	9.64	9.92	14.82	34.38	47.46	13.08	Average
6	0.4193	9.64	9.92	20.64	40.20	57.46	17.26	QP
7	0.4637	9.65	9.92	10.08	29.65	46.63	16.98	Average
8	0.4637	9.65	9.92	21.75	41.32	56.63	15.31	QP
9	0.5101	9.65	9.92	9.26	28.83	46.00	17.17	Average
10	0.5101	9.65	9.92	19.37	38.94	56.00	17.06	QP
11	0.8850	9.72	9.93	3.17	22.82	46.00	23.18	Average
12	0.8850	9.72	9.93	16.46	36.11	56.00	19.89	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 226

File: \\Emc-ce-1\Test data\2020\RFIC\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 225

Site no : 844 Shield Room Data no. : 226
 Env. / Ins. : Temp:23.5'C Humi:58% Press:101.50kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 240V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:RS512M32LM4D2BDS-53BT 2GB
 EMMC:EMMC32G-TA28 32GB
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.3100	9.63	9.92	12.27	31.82	49.97	18.15	Average
2	0.3100	9.63	9.92	18.47	38.02	59.97	21.95	QP
3	0.3832	9.64	9.92	12.96	32.52	48.21	15.69	Average
4	0.3832	9.64	9.92	18.13	37.69	58.21	20.52	QP
5	0.4237	9.64	9.92	16.33	35.89	47.37	11.48	Average
6	0.4237	9.64	9.92	22.46	42.02	57.37	15.35	QP
7	0.4612	9.65	9.92	18.09	37.66	46.67	9.01	Average
8	0.4612	9.65	9.92	25.37	44.94	56.67	11.73	QP
9	0.4941	9.65	9.92	14.24	33.81	46.10	12.29	Average
10	0.4941	9.65	9.92	20.46	40.03	56.10	16.07	QP
11	0.8438	9.71	9.93	9.80	29.44	46.00	16.56	Average
12	0.8438	9.71	9.93	16.26	35.90	56.00	20.10	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 228

File: \\Emc-ce-1\Test data\2020\RFIC\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 227

Site no : 844 Shield Room Data no. : 228
 Env. / Ins. : Temp:23.5'C Humi:58% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 240V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:RS512M32LM4D2BDS-53BT 2GB
 EMMC:EMMC32G-TA28 32GB
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.3067	9.72	9.92	2.92	22.56	50.06	27.50	Average
2	0.3067	9.72	9.92	16.73	36.37	60.06	23.69	QP
3	0.3832	9.72	9.92	3.72	23.36	48.21	24.85	Average
4	0.3832	9.72	9.92	16.67	36.31	58.21	21.90	QP
5	0.4215	9.72	9.92	9.09	28.73	47.42	18.69	Average
6	0.4215	9.72	9.92	19.35	38.99	57.42	18.43	QP
7	0.4612	9.72	9.92	12.97	32.61	46.67	14.06	Average
8	0.4612	9.72	9.92	22.74	42.38	56.67	14.29	QP
9	0.4941	9.72	9.92	5.18	24.82	46.10	21.28	Average
10	0.4941	9.72	9.92	16.26	35.90	56.10	20.20	QP
11	0.8438	9.72	9.93	4.32	23.97	46.00	22.03	Average
12	0.8438	9.72	9.93	16.48	36.13	56.00	19.87	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 230

File: \\Emc-ce-1\Test data\2020\RFIC\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 229

Site no : 844 Shield Room Data no. : 230
 Env. / Ins. : Temp:23.5'C Humi:58% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:RS512M32LM4D2BDS-53BT 2GB
 EMMC:EMMC32G-TA28 32GB
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJF

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.1641	9.73	9.69	1.89	21.31	55.25	33.94	Average
2	0.1641	9.73	9.69	17.72	37.14	65.25	28.11	QP
3	0.3410	9.72	9.92	1.54	21.18	49.18	28.00	Average
4	0.3410	9.72	9.92	14.37	34.01	59.18	25.17	QP
5	0.4215	9.72	9.92	11.25	30.89	47.42	16.53	Average
6	0.4215	9.72	9.92	21.36	41.00	57.42	16.42	QP
7	0.4637	9.72	9.92	10.05	29.69	46.63	16.94	Average
8	0.4637	9.72	9.92	22.34	41.98	56.63	14.65	QP
9	0.5020	9.72	9.92	3.00	22.64	46.00	23.36	Average
10	0.5020	9.72	9.92	15.34	34.98	56.00	21.02	QP
11	0.8850	9.72	9.93	1.47	21.12	46.00	24.88	Average
12	0.8850	9.72	9.93	15.53	35.18	56.00	20.82	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 232

File: \\Emc-ce-1\Test data\2020\RFIC\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 231



Site : 844 Shield Room Data no. : 232
 Env. / Ins. : Temp:23.5'C Humi:58% Press:101.50kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:RS512M32LM4D2BDS-53BT 2GB
 EMMC:EMMC32G-TA28 32GB
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJP

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.3428	9.63	9.92	7.46	27.01	49.13	22.12	Average
2	0.3428	9.63	9.92	15.36	34.91	59.13	24.22	QP
3	0.4215	9.64	9.92	16.76	36.32	47.42	11.10	Average
4	0.4215	9.64	9.92	22.63	42.19	57.42	15.23	QP
5	0.4612	9.65	9.92	14.47	34.04	46.67	12.63	Average
6	0.4612	9.65	9.92	23.57	43.14	56.67	13.53	QP
7	0.5020	9.65	9.92	10.08	29.65	46.00	16.35	Average
8	0.5020	9.65	9.92	19.39	38.96	56.00	17.04	QP
9	0.8850	9.72	9.93	5.93	25.58	46.00	20.42	Average
10	0.8850	9.72	9.93	15.84	35.49	56.00	20.51	QP
11	1.3029	9.77	9.94	4.14	23.85	46.00	22.15	Average
12	1.3029	9.77	9.94	15.27	34.98	56.00	21.02	QP


Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.

5. TEST SETUP PHOTO

Conducted Test



Radiated Test (Below 1GHz)





6. EUT PHOTO



External Photos
M/N: 100011885



External Photos
M/N: 100011885



External Photos
M/N: 100011885



Power Supply



Power Supply




Mainboard Model No.: RS512M32LZ4D2ANP_75BT 2G & MEMA032G 32GB 1.8V

Internal Photos


M/N: 100011885



Internal Photos
M/N: 100011885




Internal Photos
M/N: 100011885





Mainboard Model No.: MDXC1016G-M2 2GB & LTMZ0007HF-DAB1-SM

Internal Photos

M/N: 100011885





Internal Photos
M/N: 100011885





Mainboard Model No.: RS512M32LM4D2BDS-53BT 2GB & EMMC32G-TA28 32GB

Internal Photos

M/N: 100011885



Internal Photos
M/N: 100011885



End of Test Report