

10 Appendix A - General Product Information

Radiofrequency radiation exposure evaluation

This exposure evaluation is intended for **FCC ID: 2APUWPR**

According to KDB 447498 D01v06 section 4.3.1, For frequencies between 100 MHz to 6GHz and test separation distances \leq 50 mm, the Numeric threshold is determined as:

Step a)

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR

>> The fundamental frequency of the EUT is 2457MHz,

the test separation distance is \leq 50mm.

(Manufacturer specified the separation distance is: 5mm)

Step b)

>> Numeric threshold (2457MHz), mW / 5mm * $\sqrt{2.457\text{GHz}}$ \leq 3.0

Numeric threshold (2457MHz) \leq 9.569mW

>> The power (measured + tune up tolerance) of EUT at 2457MHz is: 0.08mW

Which is smaller than the Numeric threshold.

Therefore, the device is exempt from stand-alone SAR test requirements.


Power calculation (According to C63.10 chapter 9.5)

	Value	Unit
Field Strength Measured (E)	88.77	$\text{dB}\mu\text{V/m}$
Measurement Distance (D)	3	m
Equivalent Isotropically Radiated Power (E.I.R.P in dBm)	-11.16	dBm
Equivalent Isotropically Radiated Power (E.I.R.P in mW)	0.08	mW

Remark: EIRP = E + 20log(D) -104.7


(According to C63.10 chapter 9.5)

Reviewed by:



Eric LI
EMC Project Manager

Prepared by:

Hosea CHAN
EMC Project Engineer