

Report No.: SHEM200900783902

Page: 1 of 8

1 Cover Page

RF MPE REPORT

Application No.: SHEM2009007839CR

FCC ID: 2APV2-CSW2H

Applicant: Hangzhou Ezviz Software Co., Ltd.

Address of Applicant: Room 302, Unit B, Building 2,399 Danfeng Road, Binjiang

District, Hangzhou, Zhejiang

Manufacturer: Hangzhou Ezviz Software Co., Ltd.

Address of Manufacturer: Room 302, Unit B, Building 2,399 Danfeng Road, Binjiang

District, Hangzhou, Zhejiang

Equipment Under Test (EUT):

EUT Name: Smart Home Camera Base Station

Model No.: CS-W2H

Standard(s): FCC Rules 47 CFR §2.1091

KDB447498 D01 General RF Exposure Guidance v06

Date of Receipt: 2020-09-16

Date of Test: 2020-09-17 to 2020-10-09

Date of Issue: 2020-10-13

Test Result: Pass*

parlan 2han

Parlam Zhan E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.



pprovals in writing.

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and

NC.588 West Jindu Road, Songjiang District, Shanghai, China 201612 t(86-21) 61915666 f(86-21) 6191567 www.sgsgroup.com.cn 中国・上海・松江区金都西路588号 邮编: 201612 t(86-21) 61915666 f(86-21) 61915678 e sgs.china@sgs.com

^{*} In the configuration tested, the EUT complied with the standards specified above.



Report No.: SHEM200900783902

Page: 2 of 8

Revision Record						
Version Description Date Remark						
00	Original	2020-10-13	/			

Authorized for issue by:		
	Michael Mil	
	Micheal Niu / Project Engineer	
	Parlam Zhan	
	Parlam Zhan / Reviewer	



Report No.: SHEM200900783902

Page: 3 of 8

2 Contents

			age
1	COV	/ER PAGE	1
2	CON	ITENTS	3
3	GEN	IERAL INFORMATION	4
	3.1	GENERAL DESCRIPTION OF E.U.T.	4
	3.2	TECHNICAL SPECIFICATIONS	4
	3.3	TEST LOCATION	5
	3.4	TEST FACILITY	5
4	TES	T STANDARDS AND LIMITS	6
	4.1	FCC RADIOFREQUENCY RADIATION EXPOSURE LIMITS:	6
5	MEA	ASUREMENT AND CALCULATION	7
	5.1	MAXIMUM TRANSMIT POWER	7
	5.2	MPE CALCULATION	8



Report No.: SHEM200900783902

Page: 4 of 8

3 General Information

3.1 General Description of E.U.T.

Power supply:	DC 12V By adapter
	Adapter
	MODEL: ADS-12FG-12N 12012EPCU
	INPUT:100-240V~,50/60Hz
	OUTPUT:DC12V,1A

3.2 Technical Specifications

2.4GHz

2.40112	
Antenna Gain:	Ant 1:3.1dBi,
	Ant 2:3.1dBi
	Directional gain:6.11dBi
Antenna Type:	PIFA Antenna
Channel Spacing:	5MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK)
	802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels:	802.11b/g/n(HT20):11
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz



Report No.: SHEM200900783902

Page: 5 of 8

3.3 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted.

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L4354)

CNAS has accredited Compliance Certification Services (Kunshan) Inc. to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• A2LA (Certificate No. 2541.01)

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

• FCC (Designation Number: CN1172)

Compliance Certification Services Inc. has been recognized as an accredited testing laboratory. Designation Number: CN1172.

ISED (CAB identifier: CN0072)

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

CAB Identifier: CN0072.

VCCI (Member No.: 1938)

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-1600, C-1707, T-1499, G-10216 respectively.



Report No.: SHEM200900783902

Page: 6 of 8

4 Test Standards and Limits

4.1 FCC Radiofrequency radiation exposure limits:

According to §1.1310, the limit for general population/uncontrolled exposures

Frequency	Power density(mW/cm ²)	Averaging time(minutes)
300MHz~1.5GHz	f/1500	30
1.5GHz~100GHz	1.0	30



Report No.: SHEM200900783902

Page: 7 of 8

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report SHEM200900783901

Test Mode	Channel	Antenna 1 Power[dBm]	Antenna 2 Power[dBm]	MIMO Power[dBm]	Antenna 1 Power[mW]	Antenna 2 Power[mW]	MIMO Power[mW]
11B	2412	17.18	18.77	NA	52.24	75.34	N/A
11B	2437	17.46	18.44	NA	55.72	69.82	N/A
11B	2462	17.32	18.18	NA	53.95	65.77	N/A
11G	2412	18.42	17.06	NA	69.50	50.82	N/A
11G	2437	18.01	15.62	NA	63.24	36.48	N/A
11G	2462	18.84	16.19	NA	76.56	41.59	N/A
11N20MIMO	2412	15.14	13.22	17.30	32.66	20.99	53.70
11N20MIMO	2437	14.44	12.03	16.41	27.80	15.96	43.75
11N20MIMO	2462	14.46	12.48	16.59	27.93	17.70	45.60



Report No.: SHEM200900783902

Page: 8 of 8

5.2 MPE Calculation

According to the formula $S=P/4\pi R^2$, we can calculate S which is MPE.

Note:

- 1) P (mW)
- 2) R = distance to the center of radiation of antenna (in meter) = 20cm
- 3) MPE limit = 1mW/cm²

For 2.4G WiFi -Antenna1:

The max. antenna gain is

3.1 dBi

Max. Conducted Power P(mW)	Gain in Linear Scale G	Operation Distance R(cm)	Power Density (mW/cm ²)	Limit (mW/cm²)	Result
76.56	2.042	20	0.03110	1	Pass

For 2.4G WiFi -Antenna2:

The max. antenna gain is 3.1 dBi

Max. Conducted Power P(mW)	Gain in Linear Scale G	Operation Distance R(cm)	Power Density (mW/cm²)	Limit (mW/cm ²)	Result
75.34	2.042	20	0.03060	1	Pass

In MIMO mode:

The max. antenna gain is 6.11 dBi

-						
	Max. Conducted Power P(mW)	Gain in Linear Scale G	Operation Distance R(cm)	Power Density (mW/cm²)	Limit (mW/cm²)	Result
	53.7	4.083	20	0.04362	1	Pass

according to the KDB447498 section 7.2 determine the device is exclusion from SAR test.

-- End of the Report--