



FCC PART 15.247 TEST REPORT

For

Bolt Modus Corp

Oficina N.33 Edificio Ofidepositos Central, Calidonia - Distrito Federal, Panama

FCC ID: 2APW4LIV1S

Report Type: Original Report	Product Type: Mobile Phone
Report Number: RSZ201224001-00C	
Report Date: 2021-01-22	
Reviewed By: RF Engineer	Nancy Wang 
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “★”.

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk “*”. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE	7
DUTY CYCLE	7
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	9
TEST EQUIPMENT LIST	10
FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE	11
APPLICABLE STANDARD	11
FCC §15.203 - ANTENNA REQUIREMENT.....	12
APPLICABLE STANDARD	12
ANTENNA CONNECTOR CONSTRUCTION	12
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	13
APPLICABLE STANDARD	13
EUT SETUP	13
EMI TEST RECEIVER SETUP.....	13
TEST PROCEDURE	13
CORRECTED FACTOR & MARGIN CALCULATION	14
TEST DATA	14
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	17
APPLICABLE STANDARD	17
EUT SETUP	17
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	18
TEST PROCEDURE	18
CORRECTED AMPLITUDE & MARGIN CALCULATION	18
TEST DATA	18
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	27
APPLICABLE STANDARD	27
TEST PROCEDURE	27
TEST DATA	27
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	28
APPLICABLE STANDARD	28
TEST PROCEDURE	28
TEST DATA	28

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	29
APPLICABLE STANDARD	29
TEST PROCEDURE	29
TEST DATA	29
FCC §15.247(e) - POWER SPECTRAL DENSITY	30
APPLICABLE STANDARD	30
TEST PROCEDURE	30
TEST DATA	30
APPENDIX Wi-Fi.....	31
APPENDIX A: DTS BANDWIDTH	31
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	35
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER (PEAK)	39
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER (AVERAGE)	39
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	40
APPENDIX E: BAND EDGE MEASUREMENTS.....	44
APPENDIX F: DUTY CYCLE	46
APPENDIX BLE.....	48
APPENDIX A: DTS BANDWIDTH	48
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	50
APPENDIX C: MAXIMUM CONDUCTED PEAK OUTPUT POWER.....	52
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	53
APPENDIX E: BAND EDGE MEASUREMENTS.....	55
APPENDIX F: DUTY CYCLE	56

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Mobile Phone
Tested Model	LIV 1S
Frequency Range	BLE: 2402-2480MHz Wi-Fi: 2412-2472MHz
Maximum Conducted Peak Output Power	BLE: -4.39dBm(LE 1M) Wi-Fi: 12.91dBm(802.11b), 11.55dBm(802.11g), 10.32dBm(802.11n-HT20)
Modulation Technique	BLE: GFSK Wi-Fi: DSSS, OFDM
Antenna Specification*	Internal Antenna:1.47dBi(provided by the applicant)
Voltage Range	DC 3.8V from battery or DC 5.0V from adapter
Date of Test	2020-12-31 to 2021-01-17
Sample number	RSZ201224001-RF-S1(Assigned by BACL, Shenzhen)
Received date	2020-12-24
Sample/EUT Status	Good condition
Adapter information	Model: CLIV1S Input: AC 100-264V,0.25A~50/60Hz Output: DC 5.0V, 0.7A

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.73dB
RF conducted test with spectrum		±1.6dB
AC Power Lines Conducted Emissions		±1.95dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±1 °C
Humidity		±6%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g and 802.11n-HT20 mode, 13 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	12	2467
6	2437	13	2472
7	2442	/	/

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 7 and 13

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

No software was use to the EUT tested. The power level was provided by the applicant.

The device was tested with the worst case was performed as below:

Mode	Data rate	Power level*		
		Low channel	Middle channel	High channel
802.11b	1 Mbps	15	15	15
802.11g	6 Mbps	10	10	10
802.11n-HT20	MCS0	12	12	12
BLE	Default	Default	Default	Default

The worse-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rated bandwidths, and modulations.

Duty cycle

Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-Shielding Detachable USB Cable	1.0	EUT	Adapter

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2020/08/04	2021/08/03
Rohde & Schwarz	LISN	ENV216	101613	2020/08/04	2021/08/03
Rohde & Schwarz	Transient Limitor	ESH3Z2	DE25985	2020/11/29	2021/11/28
Unknown	CE Cable	CE Cable	UF A210B-1-0720-504504	2020/11/29	2021/11/28
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
Radiated Emission Test					
R&S	EMI Test Receiver	ESR3	102455	2020/08/04	2021/08/03
Sonoma instrument	Pre-amplifier	310 N	186238	2020/08/04	2021/08/03
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2020/12/22	2023/12/21
Unknown	Cable 2	RF Cable 2	F-03-EM197	2020/11/29	2021/11/28
Unknown	Cable	Chamber Cable 1	F-03-EM236	2020/11/29	2021/11/28
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR
Rohde & Schwarz	Spectrum Analyzer	FSV40-N	102259	2020/08/04	2021/08/03
COM-POWER	Pre-amplifier	PA-122	181919	2020/11/29	2021/11/28
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2020/11/29	2021/11/28
Sunol Sciences	Horn Antenna	DRH-118	A052604	2020/12/22	2023/12/21
Insulated Wire Inc.	RF Cable	SPS-2503-3150	02222010	2020/11/29	2021/11/28
Unknown	RF Cable	W1101-EQ1 OUT	F-19-EM005	2020/11/29	2021/11/28
SNSD	Band Reject filter	BSF2402-2480MN-0898-001	2.4G filter	2020/04/20	2021/04/19
Ducommun Technologies	Horn antenna	ARH-4223-02	1007726-021304	2020/12/06	2021/12/05
RF Conducted Test					
Tonscend Corporation	RF control Unit	JS0806-2	19D8060154	2020/08/04	2021/08/03
Rohde & Schwarz	Signal and Spectrum Analyzer	FSV40	101473	2020/08/04	2021/08/03
Unknown	RF Cable	Unknown	2301 276	2020/11/29	2021/11/28

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE**Applicable Standard**

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Measurement Result**For BLE:**

Mode	Frequency (MHz)	Max Tune-up Conducted Power (dBm)	Max Tune-up Conducted Power (mW)	Calculated Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
BLE	2480	-4.0	0.4	5	0.13	3.0	Yes

Result: No SAR test is required.

For Wi-Fi:

Wi-Fi: please refer to the report number: RSZ201224001-SA.

Result: Compliance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


Antenna Connector Construction

The EUT has an internal antenna arrangement which was permanently attached for BLE and Wi-Fi. The antenna gain is 1.47dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS**Applicable Standard**

FCC§15.207

EUT Setup

Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$


Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	65 %
ATM Pressure:	101.0 kPa

The testing was performed by Haiguo Li on 2021-01-09.


EUT operation mode: Transmitting (worst case at 802.11b mode, low channel)

AC 120V/60 Hz, Line**Final Result 1**

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.170501	51.6	9.000	L1	19.9	13.3	64.9
0.178500	53.4	9.000	L1	19.9	11.2	64.6
0.181500	50.3	9.000	L1	19.9	14.1	64.4
0.229500	45.6	9.000	L1	19.8	16.9	62.5
0.233500	47.0	9.000	L1	19.8	15.3	62.3
0.293500	42.8	9.000	L1	19.7	17.6	60.4

Final Result 2

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.170501	32.9	9.000	L1	19.9	22.0	54.9
0.178500	34.6	9.000	L1	19.9	20.0	54.6
0.181500	32.7	9.000	L1	19.9	21.7	54.4
0.229500	26.7	9.000	L1	19.8	25.8	52.5
0.233500	27.8	9.000	L1	19.8	24.5	52.3
0.293500	25.5	9.000	L1	19.7	24.9	50.4

AC 120V/60 Hz, Neutral**Final Result 1**



Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.157500	43.1	9.000	N	19.8	22.5	65.6
0.173500	52.1	9.000	N	19.8	12.7	64.8
0.181500	48.2	9.000	N	19.8	16.2	64.4
0.217500	37.8	9.000	N	19.8	25.1	62.9
0.237500	43.0	9.000	N	19.8	19.2	62.2
0.285500	39.1	9.000	N	19.7	21.6	60.7

Final Result 2

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.174000	32.9	9.000	N	19.8	21.9	54.8
0.238000	26.5	9.000	N	19.8	25.7	52.2
0.346000	30.1	9.000	N	19.8	19.0	49.1
0.410000	20.7	9.000	N	19.8	26.9	47.6
0.522000	20.7	9.000	N	19.8	25.3	46.0
0.746000	21.5	9.000	N	19.8	24.5	46.0

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data


Environmental Conditions

Temperature:	22.2~23 °C
Relative Humidity:	40~51 %
ATM Pressure:	101.0 kPa

The testing was performed by Holland Yang on 2021-01-11 for below 1GHz and Leven Gan on 2021-01-10 for above 1GHz.

EUT operation mode: Transmitting

30 MHz~1 GHz: (worst case at 802.11b mode, low channel)



Final Result

Frequency (MHz)	QuasiPeak (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
30.353025	18.27	40.00	21.73	360.0	H	311.0	-4.7
36.148250	16.37	40.00	23.63	200.0	V	0.0	-8.1
40.099000	14.79	40.00	25.21	251.0	V	0.0	-10.6
46.432375	12.80	40.00	27.20	123.0	V	0.0	-14.8
151.903250	16.52	43.50	26.98	227.0	H	86.0	-11.0
709.745875	21.00	46.00	25.00	187.0	H	190.0	-1.0

1 GHz-25 GHz (Wi-Fi):**802.11b Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2389.42	28.45	PK	139	1.9	H	36.23	64.68	74	9.32
2389.42	14.64	Ave.	139	1.9	H	36.23	50.87	54	3.13
2484.17	28.51	PK	119	1.5	H	36.70	65.21	74	8.79
2484.17	14.72	Ave.	119	1.5	H	36.70	51.42	54	2.58
4824.00	48.75	PK	121	1.2	H	6.28	55.03	74	18.97
4824.00	44.70	Ave.	121	1.2	H	6.28	50.98	54	3.02
Middle Channel (2442MHz)									
4884.00	47.34	PK	117	1.9	H	6.76	54.10	74	19.90
4884.00	42.12	Ave.	117	1.9	H	6.76	48.88	54	5.12
High Channel (2472 MHz)									
2388.48	28.45	PK	37	1.7	H	36.23	64.68	74	9.32
2388.48	14.68	Ave.	37	1.7	H	36.23	50.91	54	3.09
2483.62	29.08	PK	80	1.6	H	36.70	65.78	74	8.22
2483.62	15.70	Ave.	80	1.6	H	36.70	52.40	54	1.60
4944.00	47.76	PK	96	1.9	H	6.76	54.52	74	19.48
4944.00	39.34	Ave.	96	1.9	H	6.76	46.10	54	7.90

802.11g Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2389.65	29.22	PK	179	1.1	H	31.87	61.09	74	12.91
2389.65	15.21	Ave.	179	1.1	H	31.87	47.08	54	6.92
2484.36	28.91	PK	70	2.1	H	32.13	61.04	74	12.96
2484.36	15.17	Ave.	70	2.1	H	32.13	47.30	54	6.70
4824.00	44.53	PK	304	1.8	H	6.28	50.81	74	23.19
4824.00	30.96	Ave.	304	1.8	H	6.28	37.24	54	16.76
Middle Channel (2442MHz)									
4884.00	44.86	PK	148	2.4	H	6.76	51.62	74	22.38
4884.00	31.43	Ave.	148	2.4	H	6.76	38.19	54	15.81
High Channel (2472 MHz)									
2387.41	28.94	PK	248	1.6	H	31.87	60.81	74	13.19
2387.41	15.16	Ave.	248	1.6	H	31.87	47.03	54	6.97
2483.70	37.45	PK	294	1.5	H	32.13	69.58	74	4.42
2483.70	18.76	Ave.	294	1.5	H	32.13	50.89	54	3.11
4944.00	44.99	PK	183	2.5	H	6.76	51.75	74	22.25
4944.00	31.51	Ave.	183	2.5	H	6.76	38.27	54	15.73

802.11n-HT20 Mode:

Low Channel (2412 MHz)									
2389.16	29.14	PK	8	1.5	H	31.87	61.01	74	12.99
2389.16	15.27	Ave.	8	1.5	H	31.87	47.14	54	6.86
2484.43	28.93	PK	131	1.7	H	32.13	61.06	74	12.94
2484.43	15.25	Ave.	131	1.7	H	32.13	47.38	54	6.62
4824.00	44.69	PK	224	1.9	H	6.28	50.97	74	23.03
4824.00	31.35	Ave.	224	1.9	H	6.28	37.63	54	16.37
Middle Channel (2442MHz)									
4884.00	44.93	PK	39	1.2	H	6.76	51.69	74	22.31
4884.00	31.65	Ave.	39	1.2	H	6.76	38.41	54	15.59
High Channel (2472 MHz)									
2385.59	28.89	PK	44	1.9	H	31.87	60.76	74	13.24
2385.59	15.24	Ave.	44	1.9	H	31.87	47.11	54	6.89
2483.77	37.04	PK	203	2.2	H	32.13	69.17	74	4.83
2483.77	18.73	Ave.	203	2.2	H	32.13	50.86	54	3.14
4944.00	44.63	PK	170	1.8	H	6.76	51.39	74	22.61
4944.00	31.34	Ave.	170	1.8	H	6.76	38.10	54	15.90

1 GHz-25 GHz (BLE):

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2402 MHz)									
2389.42	28.96	PK	163	1.9	H	31.87	60.83	74	13.17
2389.42	15.12	Ave.	163	1.9	H	31.87	46.99	54	7.01
2485.16	28.81	PK	335	2.0	H	32.13	60.94	74	13.06
2485.16	15.09	Ave.	335	2.0	H	32.13	47.22	54	6.78
4804.00	44.75	PK	14	2.5	H	6.28	51.03	74	22.97
4804.00	30.84	Ave.	14	2.5	H	6.28	37.12	54	16.88
Middle Channel (2440 MHz)									
4880.00	44.81	PK	112	1.4	H	6.76	51.57	74	22.43
4880.00	30.96	Ave.	112	1.4	H	6.76	37.72	54	16.28
High Channel (2480 MHz)									
2388.14	28.95	PK	190	2.3	H	31.87	60.82	74	13.18
2388.14	15.11	Ave.	190	2.3	H	31.87	46.98	54	7.02
2484.28	29.17	PK	48	1.1	H	32.13	61.30	74	12.70
2484.28	15.15	Ave.	48	1.1	H	32.13	47.28	54	6.72
4960.00	45.14	PK	98	1.8	H	6.80	51.94	74	22.06
4960.00	31.22	Ave.	98	1.8	H	6.80	38.02	54	15.98

Note:


Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading


Margin = Limit - Corrected. Amplitude

The other spurious emission which is 20dB to the limit was not recorded.

Pre-scan with 802.11b mode, low channel
Horizontal





Date: 10.JAN.2021 19:59:39




Date: 10.JAN.2021 20:44:42


Vertical



Pre-scan for Average Horizontal




Date: 10.JAN.2021 20:05:31




Date: 10.JAN.2021 20:49:02

Vertical



Date: 10.JAN.2021 20:14:13




Date: 10.JAN.2021 20:55:48

FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH**Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

**Test Data****Environmental Conditions**

Temperature:	24.6 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Bravos Zhao from 2020-12-31 to 2021-01-01.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.


FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	24.6 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Bravos Zhao from 2020-12-31 to 2021-01-01.

EUT operation mode: Transmitting


Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

**Test Data****Environmental Conditions**

Temperature:	24.6 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Bravos Zhao from 2020-12-31 to 2021-01-01.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.


FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	24.6 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Bravos Zhao from 2020-12-31 to 2021-01-17.

EUT operation mode: Transmitting


Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.

APPENDIX Wi-Fi**Appendix A: DTS Bandwidth
Test Result**


Test Mode	Antenna	Channel	DTS BW [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	9.120	0.5	PASS
		2442	9.120	0.5	PASS
		2472	9.120	0.5	PASS
11G	Ant1	2412	16.400	0.5	PASS
		2442	16.440	0.5	PASS
		2472	16.440	0.5	PASS
11N20SISO	Ant1	2412	17.680	0.5	PASS
		2442	17.680	0.5	PASS
		2472	17.640	0.5	PASS

Test Graphs


11B_Ant1_2412




11B_Ant1_2442



11B_Ant1_2472




11G_Ant1_2412




Date: 31.DEC.2020 23:53:53

11G_Ant1_2442




Date: 1.JAN.2021 00:25:48

11G_Ant1_2472




Date: 1.JAN.2021 00:02:47

11N20SISO_Ant1_2412




Date: 1.JAN.2021 00:04:33

11N20SISO_Ant1_2442



Date: 1.JAN.2021 00:06:12

11N20SISO_Ant1_2472



Date: 1.JAN.2021 00:10:47

**Appendix B: Occupied Channel Bandwidth
Test Result**


Test Mode	Antenna	Channel	OCB [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	11.828	---	PASS
		2442	11.788	---	PASS
		2472	11.628	---	PASS
11G	Ant1	2412	17.942	---	PASS
		2442	17.942	---	PASS
		2472	18.302	---	PASS
11N20SISO	Ant1	2412	18.621	---	PASS
		2442	18.581	---	PASS
		2472	18.541	---	PASS

Test Graphs


11B_Ant1_2412



11B_Ant1_2442



11B_Ant1_2472




11G_Ant1_2412




Date: 1.JAN.2021 00:33:04

11G_Ant1_2442



Date: 1.JAN.2021 00:33:50

11G_Ant1_2472



Date: 1.JAN.2021 00:34:30

11N20SISO_Ant1_2412



11N20SISO_Ant1_2442



11N20SISO_Ant1_2472



Appendix C: Maximum conducted output power (Peak)**Test Result**

Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	12.64	<=30	PASS
		2442	11.44	<=30	PASS
		2472	12.91	<=30	PASS
11G	Ant1	2412	8.48	<=30	PASS
		2442	10.04	<=30	PASS
		2472	11.55	<=30	PASS
11N20SISO	Ant1	2412	8.96	<=30	PASS
		2442	8.92	<=30	PASS
		2472	10.32	<=30	PASS


Appendix C: Maximum conducted output power (Average)**Test Result**


Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	11.79	<=30	PASS
		2442	9.54	<=30	PASS
		2472	10.94	<=30	PASS
11G	Ant1	2412	5.42	<=30	PASS
		2442	5.04	<=30	PASS
		2472	6.64	<=30	PASS
11N20SISO	Ant1	2412	3.73	<=30	PASS
		2442	3.68	<=30	PASS
		2472	5.27	<=30	PASS


**Appendix D: Maximum power spectral density
Test Result**

Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	0.12	<=8	PASS
		2442	-0.76	<=8	PASS
		2472	0.26	<=8	PASS
11G	Ant1	2412	-22.66	<=8	PASS
		2442	-21.21	<=8	PASS
		2472	-19.1	<=8	PASS
11N20SISO	Ant1	2412	-22.4	<=8	PASS
		2442	-22.69	<=8	PASS
		2472	-20.37	<=8	PASS

Test Graphs









Appendix E: Band edge measurements Test Graphs

11B_Ant1_Low_2412



Date: 31.DEC.2020 23:49:36

11B_Ant1_High_2472




Date: 31.DEC.2020 23:52:54

11G_Ant1_Low_2412



Date: 31.DEC.2020 23:54:29

11G Ant1_High_2472



Date: 1.JAN.2021 00:03:23

11N20SISO_Ant1_Low_2412



Date: 1.JAN.2021 00:05:09

11N20SISO_Ant1_High_2472




Date: 1.JAN.2021 00:11:23

**Appendix F: Duty Cycle
Test Result**

Test Mode	Antenna	Channel	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
11B	Ant1	2442	8.38	8.46	99.05
11G	Ant1	2442	1.37	1.45	94.48
11N20SISO	Ant1	2442	1.28	1.36	94.12


Test Graphs

11B_Ant1_2442




Date: 31.DEC.2020 23:50:59

11G_Ant1_2442



Date: 1.JAN.2021 00:25:40

11N20SISO_Ant1_2442




Date: 1.JAN.2021 00:06:04

APPENDIX BLE**Appendix A: DTS Bandwidth
Test Result**

Test Mode	Antenna	Channel	DTS BW [MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.672	0.5	PASS
		2440	0.668	0.5	PASS
		2480	0.668	0.5	PASS


Test Graphs

BLE_1M_Ant1_2402




Date: 31.DEC.2020 23:43:41

BLE_1M_Ant1_2440



Date: 31.DEC.2020 23:44:54

BLE_1M_Ant1_2480



Date: 31.DEC.2020 23:46:09

**Appendix B: Occupied Channel Bandwidth
Test Result**

Test Mode	Antenna	Channel	OCB [MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.023	---	PASS
		2440	1.023	---	PASS
		2480	1.027	---	PASS

Test Graphs

BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



BLE_1M_Ant1_2480



**Appendix C: Maximum conducted Peak output power
Test Result**


Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	-4.39	<=30	PASS
		2440	-5.10	<=30	PASS
		2480	-6.77	<=30	PASS

**Appendix D: Maximum power spectral density
Test Result**


Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-20.65	<=8	PASS
		2440	-21.64	<=8	PASS
		2480	-23.61	<=8	PASS

Test Graphs


BLE_1M_Ant1_2402




BLE_1M_Ant1_2440



BLE_1M_Ant1_2480




Appendix E: Band edge measurements Test Graphs



Appendix F: Duty Cycle Test Result

Test Mode	Antenna	Channel	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
BLE_1M	Ant1	2440	1.63	1.87	87.17

Test Graphs



***** END OF REPORT *****