

Appendix A

RF Test Data for BT(BLE) (Conducted Measurement)

Product Name: Mobile Phone

Trade Mark: Krip

Test Model: K5b

FCC ID: 2APX7K5B


Environmental Conditions

Temperature:	24.5° C
Relative Humidity:	60%
ATM Pressure:	100.0 kPa
Test Engineer:	Gary Qian
Supervised by:	Eden Hu


1.6dB Bandwidth


Test Mode	Test Channel	Ant	EBW[MHz]	Limit	Verdict
BLE	2402	Ant1	0.502	0.5	PASS
BLE	2440	Ant1	0.501	0.5	PASS
BLE	2480	Ant1	0.505	0.5	PASS

6dB Bandwidth_BLE_2402_Ant1



6dB Bandwidth_BLE_2440_Ant1






2.Occupied Bandwidth

Test Mode	Test Channel	Ant	OBW[MHz]	Limit[MHz]	Verdict
-----------	--------------	-----	----------	------------	---------


3.Maximum peak conducted output power

Test Mode	Test Channel	Ant	Power[dBm]	Limit[dBm]	Verdict
BLE	2402	Ant1	-3.445	30	PASS
BLE	2440	Ant1	-3.528	30	PASS
BLE	2480	Ant1	-3.723	30	PASS


Maximum peak conducted output power_BLE_2402_Ant1



Maximum peak conducted output power_BLE_2440_Ant1




Maximum peak conducted output power_BLE_2480_Ant1




4.Maximum Peak power spectral density

Test Mode	Test Channel	Ant	PSD[dBm/3KHz]	Limit[dBm/3KHz]	Verdict
BLE	2402	Ant1	-20.133	8.00	PASS
BLE	2440	Ant1	-20.285	8.00	PASS
BLE	2480	Ant1	-20.475	8.00	PASS


Maximum Peak power spectral density_BLE_2402_Ant1



Maximum Peak power spectral density_BLE_2440_Ant1




Maximum Peak power spectral density_BLE_2480_Ant1




5.Band-edge for RF Conducted Emissions

Type	Carrier Frequency(MHz)	Frequency(MHz)	Carrier Frequency Power [dBm]	Bandedge Peak(dBm)	Upper limit(dBm)	Conclusion
BLE	2402	2400	-3.606	-62.31	-23.606	Pass
BLE	2480	2483.5	-3.89	-62.78	-23.89	Pass

Band-edge for RF Conducted Emissions_BLE_2402_Ant1





Band-edge for RF Conducted Emissions_BLE_2480_Ant1





6.RF Conducted Spurious Emissions



RF Conducted Spurious Emissions_BLE_2440_Ant1



RF Conducted Spurious Emissions_BLE_2480_Ant1




7.Restrict-band band-edge measurements


Type	Carrier Frequency (MHz)	Frequency(MHz)	Gain	Ground Factor	Peak Value(dBm)	E [dBuV/m]	Limit [dBuV/m]	Conclusion
1DH5	2402	2310	2.00	0.00	-52.14	45.06	74	Pass
1DH5	2480	2483.5	2.00	0.00	-51.19	46.01	74	Pass

Type	Carrier Frequency (MHz)	Frequency(MHz)	Gain	Ground Factor	Average Value(dBm)	E [dBuV/m]	Limit [dBuV/m]	Conclusion
1DH5	2402	2310	2.00	0.00	-59.86	37.34	54	Pass
1DH5	2480	2483.5	2.00	0.00	-59.31	37.89	54	Pass

Restrict-band band-edge measurements_BLE_2402_Ant1_PEAK



Restrict-band band-edge measurements_BLE_2402_Ant1_AV



Restrict-band band-edge measurements_BLE_2480_Ant1_PEAK

8.Duty Cycle

Test Mode	Test Channel	Ant	Duty Cycle[%]	Verdict
BLE	2402	Ant1	85.45	PASS

Duty Cycle_BLE_2402_Ant1

