



FCC PART 15.407

TEST REPORT

For

KRIPTO MOBILE CORPORATION

7236 NW 31ST ST., MIAMI Florida United States

FCC ID: 2APX7K650A

Report Type: Original Report	Product Type: Mobile phone
Report Number: RSZ190115002-00E	
Report Date: 2019-02-28	
Simon Wang <i>Simon wang</i>	
Reviewed By: RF Engineer	
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”.

The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY.....	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	10
SUPPORT EQUIPMENT LIST AND DETAILS	10
EXTERNAL I/O CABLE.....	10
BLOCK DIAGRAM OF TEST SETUP	11
SUMMARY OF TEST RESULTS.....	12
TEST EQUIPMENT LIST	13
FCC §1.1307(b) & §2.1093 - RF EXPOSURE INFORMATION	15
APPLICABLE STANDARD	15
TEST RESULT	15
FCC §15.203 – ANTENNA REQUIREMENT	16
APPLICABLE STANDARD	16
ANTENNA CONNECTOR CONSTRUCTION	16
FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS	17
APPLICABLE STANDARD	17
EUT SETUP.....	17
EMI TEST RECEIVER SETUP.....	17
TEST PROCEDURE	17
TEST RESULTS SUMMARY	18
TEST DATA	18
§15.205 & §15.209 & §15.407(B) (1), (4), (6), (7) – UNDESIRABLE EMISSION	21
APPLICABLE STANDARD	21
EUT SETUP	21
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	22
TEST PROCEDURE	22
CORRECTED AMPLITUDE & MARGIN CALCULATION	23
TEST RESULTS SUMMARY	23
TEST DATA	23
§15.407(B) (1), (4) –OUT OF BAND EMISSION	30
APPLICABLE STANDARD	30
TEST PROCEDURE	30
TEST DATA	30
FCC §15.407(a) (1) –EMISSION BANDWIDTH.....	37
APPLICABLE STANDARD	37

TEST PROCEDURE	37
TEST DATA	37
FCC §15.407(a) (1) (3) – CONDUCTED TRANSMITTER OUTPUT POWER	46
APPLICABLE STANDARD	46
TEST PROCEDURE	46
TEST DATA	47
FCC §15.407(a) (1) (3) - POWER SPECTRAL DENSITY	48
APPLICABLE STANDARD	48
TEST PROCEDURE	48
TEST DATA	49

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Mobile phone
Tested Model	K65
Frequency Range	5G WI-FI: 5150-5250 MHz
Transmit Power	5150-5250 MHz: 10.29dBm (802.11a), 10.66dBm(802.11n20), 9.96 dBm(802.11n40), 10.67dBm (802.11ac20), 10.13dBm(802.11 ac40), 9.54 dBm(802.11 ac80)
Modulation Technique	WIFI: DSSS, OFDM
Antenna Specification	Internal antenna: 1.5dBi
Voltage Range	DC 3.85V from battery or DC 5.0V from adapter
Date of Test	Jan 22, 2019~ Feb 25, 2019
Sample serial number	190115002
Received date	2019-01-15
Sample/EUT Status	Good condition
Adapter information	Model: C650 Input: AC 100-240V, 50/60Hz, 0.5A Output: DC 5V, 1.5A

Objective

This type approval report is prepared on behalf of *KRIPTO MOBILE CORPORATION* in accordance with Part 2-Subpart J, Part 15-Subparts A and E of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS&DSS, FCC Part 22H&24E&27 PCE and FCC Part 15B JBP submissions with FCC ID: 2APX7K650A.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.5dB
RF conducted test with spectrum		±1.5dB
AC Power Lines Conducted Emissions		±1.95dB
Radiated Emissions	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±3 °C
Humidity		±6%
Supply voltages		±0.4%

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer.

The device support 802.11a/n20/n40/ac20/ac40/ac80 modes.

For 5150-5250MHz Band, 7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
38	5190	46	5230
40	5200	48	5240
42	5210	/	/


EUT Exercise Software

CMD command was made to the EUT tested. Test frequencies and power level were configured as below:

U-NII	Mode	Channel Number	Frequency (MHz)	Rate (Mbps)	Power Level
5150 – 5250MHz	802.11 a	CH36	5180	6	14
		CH40	5200	6	14
		CH48	5240	6	14
	802.11 n20	CH36	5180	MCS0	14
		CH40	5200	MCS0	14
		CH48	5240	MCS0	14
	802.11 n40	CH38	5190	MCS0	13
		CH46	5230	MCS0	13
	802.11 ac20	CH36	5180	MCS0	14
		CH40	5200	MCS0	14
		CH48	5240	MCS0	14
	802.11 ac40	CH38	5190	MCS0	13
		CH46	5230	MCS0	13
	802.11 ac80	CH42	5210	MCS0	13


Duty cycle
5150-5250 MHz

802.11a mode




Date: 22.JAN.2019 20:56:04

802.11n20 mode




Date: 22.JAN.2019 20:54:25

802.11n40 Mode




Date: 22.JAN.2019 20:53:55

802.11ac20 Mode




Date: 22.JAN.2019 20:55:26

802.11ac40 Mode



Date: 22.JAN.2019 20:53:28

802.11ac80 Mode



Date: 22.JAN.2019 20:52:37

Band	Duty Cycle (%)	T(ms)	1/T(kHz)	VBW Setting	10log(1/x)
802.11a	100	-	-	10Hz	-
802.11n20	100	-	-	10Hz	-
802.11n40	100	-	-	10Hz	-
802.11ac20	100	-	-	10Hz	-
802.11ac40	100	-	-	10Hz	-
802.11ac80	100	-	-	10Hz	-

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From/Port	To
Un-shielding Un-detachable DC Cable	1.5	EUT	Adapter

Block Diagram of Test Setup

For conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§ 1.1307 , §2.1093	RF Exposure (SAR)	Compliance*
§15.203	Antenna Requirement	Compliance
§15.407(b)(6)& §15.207(a)	Conducted Emissions	Compliance
§15.205& §15.209 &§15.407(b) (1), (4),(7)	Undesirable Emission& Restricted Bands	Compliance
§15.407(b) (1),(4)	Out Of Band Emission	Compliance
§15.407(a) (1), (5),(e)	Emission Bandwidth	Compliance
§15.407(a)(1),(3)	Conducted Transmitter Output Power	Compliance
§15.407 (a)(1),(3)	Power Spectral Density	Compliance

Note: Compliance*: Please refer to SAR report released by BACL, report number: RSZ190115002-20A

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
AC Line Conducted test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2018-07-11	2019-07-11
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2018-12-21	2019-12-21
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2018-11-12	2019-11-12
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
Unknown	Conducted Emission Cable	78652	UF A210B-1-0720-504504	2018-11-12	2019-11-12
Radiated Emission Test					
A.H.System	Horn Antenna	SAS-200/571	135	2018-09-01	2021-08-31
Rohde & Schwarz	Signal Analyzer	FSEM	845987/005	2018-06-23	2019-06-23
Agilent	Spectrum Analyzer	8564E	3943A01781	2019-01-04	2020-01-04
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
COM-POWER	Pre-amplifier	PA-122	181919	2018-11-12	2019-11-12
Sonoma instrument	Amplifier	310N	186238	2018-11-12	2019-11-12
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2019-01-11	2020-01-11
UTiFLEX MICRO-C0AX	RF Cable	UFA147A-2362-100100	MFR64639 231029-003	2018-07-11	2021-07-10
Ducommun technologies	RF Cable	104PEA	218124002	2018-11-12	2019-11-12
Ducommun technologies	RF Cable	RG-214	1	2018-11-19	2019-05-21
Ducommun technologies	RF Cable	RG-214	2	2018-11-12	2019-11-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-04	2017-12-29	2020-12-28
Ducommun Technologies	Horn Antenna	ARH-2823-02	1007726-04	2016-11-18	2019-11-18
Ducommun Technologies	Pre-amplifier	ALN-22093530-01	991373-01	2018-08-03	2019-08-03

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSU26	200120	2018-12-24	2019-12-24
Agilent	USB Wideband Power Meter	U2021XA	MY54250003	2018-06-23	2019-06-23
Ducommun technologies	RF Cable	RG-214	3	Each Time	
WEINSCHTEL	3dB Attenuator	6231	666	Each Time	

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307(b) & §2.1093 - RF EXPOSURE INFORMATION

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliance, please refer to the SAR report: RSZ190115002-20A.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.407 (a), if the transmitting antennas of directional gain greater than 6dBi are used, the transmit power and power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 1.5 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207, §15.407(b) (6)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level complies with the limit if

$$L_m + U_{(L_m)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BACL, $U_{(L_m)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.


Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Haiguo Li on 2019-01-23.

EUT operation mode: Transmitting (worst case is 802.11a mode 5240 MHz)

AC 120V/60 Hz, Line:

Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.150000	54.7	19.8	66.0	11.3	QP
0.177500	50.7	19.8	64.6	13.9	QP
0.209500	47.6	19.7	63.2	15.6	QP
0.214501	50.3	19.7	63.0	12.7	QP
0.233500	47.5	19.7	62.3	14.8	QP
0.305350	44.3	19.8	60.1	15.8	QP
0.150000	41.6	19.8	56.0	14.4	Ave.
0.177500	34.1	19.8	54.6	20.5	Ave.
0.209500	35.4	19.7	53.2	17.8	Ave.
0.214501	37.7	19.7	53.0	15.3	Ave.
0.233500	35.6	19.7	52.3	16.7	Ave.
0.305350	36.3	19.8	50.1	13.8	Ave.

AC120V, 60 Hz, Neutral:

Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.157500	53.7	19.7	65.6	11.9	QP
0.165500	54.6	19.7	65.2	10.6	QP
0.189500	50.5	19.7	64.1	13.6	QP
0.209500	49.0	19.7	63.2	14.2	QP
0.305350	46.7	19.8	60.1	13.4	QP
0.313230	45.6	19.8	59.9	14.3	QP
0.157500	36.0	19.7	55.6	19.6	Ave.
0.165500	36.5	19.7	55.2	18.7	Ave.
0.189500	37.5	19.7	54.1	16.6	Ave.
0.209500	36.6	19.7	53.2	16.6	Ave.
0.305350	41.8	19.8	50.1	8.3	Ave.
0.313230	40.9	19.8	49.9	9.0	Ave.

Note:

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

§15.205 & §15.209 & §15.407(B) (1), (4), (6), (7) – UNDESIRABLE EMISSION**Applicable Standard**

FCC §15.407 (b) (1), (4), (6), (7); §15.209; §15.205;


(b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.


Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209.

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site ,The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC 15.209 and FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Radiated Spurious Emission

During the radiated emission test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all the installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz, peak and Average detection modes for frequencies above 1GHz.

According to ANSI C63.10-2013,9.4: For field strength measurements made at other than the distance at which the applicable limit is specified,extrapolate the measured field strength to the field strength at the distance specified by the limit using an inverse distance correction factor (20 dB/decade of distance). In some cases, a different distance correction factor may be required;

$$E_{\text{SpecLimit}} = E_{\text{Meas}} + 20 \log \left(\frac{d_{\text{Meas}}}{d_{\text{SpecLimit}}} \right)$$

where

$E_{\text{SpecLimit}}$	is the field strength of the emission at the distance specified by the limit, in dB μ V/m
E_{Meas}	is the field strength of the emission at the measurement distance, in dB μ V/m
d_{Meas}	is the measurement distance, in m
$d_{\text{SpecLimit}}$	is the distance specified by the limit, in m

So the extrapolation factor of 1m is $20 \cdot \log(1/3) = -9.5$ dB

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{\text{lim}} + U_{\text{cispr}}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.


Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Tracy Hu on 2019-02-25.

EUT operation mode: Transmitting

30 MHz – 1 GHz: (worst case is 802.11a mode 5240 MHz)

Frequency (MHz)	Corrected Amplitude (dBμV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
48.362625	28.49	109.0	V	0.0	-18.9	40.00	11.51
51.399625	30.70	101.0	V	357.0	-19.7	40.00	9.30
331.158750	27.79	108.0	H	169.0	-10.8	46.00	18.21
349.306625	28.66	102.0	H	279.0	-10.8	46.00	17.34
837.695125	29.43	108.0	H	340.0	5.7	46.00	16.57
957.980750	31.04	320.0	V	208.0	9.3	46.00	14.96

30 MHz ~ 40 GHz:**5150-5250 MHz:**

Frequency (MHz)	Receiver		Turntable	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBµV/m)	FCC Part 15.407/205/209	
	Reading (dBµV)	PK/QP/Ave.	Degree	Height (m)	Polar (H / V)			Limit (dBµV/m)	Margin (dB)
802.11a									
5180 MHz									
5149.90	34.94	PK	355	2.2	V	41.60	76.54	83.5	6.96
5149.90	14.25	Ave.	355	2.2	V	41.60	55.85	63.5	7.65
5350.00	27.89	PK	307	2.4	V	42.06	69.95	83.5	13.55
5350.00	13.80	Ave.	307	2.4	V	42.06	55.86	63.5	7.64
10360.00	40.56	PK	283	2.2	V	21.69	62.25	77.7	15.45
5200 MHz									
10400.00	39.20	PK	235	1.1	H	21.79	60.99	77.7	16.71
5240 MHz									
5150.00	27.64	PK	158	1.9	V	41.43	69.07	83.5	14.43
5150.00	13.85	Ave.	158	1.9	V	41.43	55.28	63.5	8.22
5350.00	27.74	PK	164	1.8	V	42.06	69.80	83.5	13.70
5350.00	13.87	Ave.	164	1.8	V	42.06	55.93	63.5	7.57
10480.00	40.02	PK	239	2.3	V	21.79	61.81	77.7	15.89
802.11n20									
5180 MHz									
5145.00	33.22	PK	290	2.2	V	41.60	74.82	83.5	8.68
5145.00	13.89	Ave.	290	2.2	V	41.60	55.49	63.5	8.01
5350.00	27.64	PK	248	1.3	V	42.06	69.70	83.5	13.80
5350.00	13.70	Ave.	248	1.3	V	42.06	55.76	63.5	7.74
10360.00	40.33	PK	304	2.2	V	21.69	62.02	77.7	15.68
5200 MHz									
10400.00	40.36	PK	153	2.4	V	21.79	62.15	77.7	15.55
5240 MHz									
5150.00	27.40	PK	136	1.0	V	41.43	68.83	83.5	14.67
5150.00	13.93	Ave.	136	1.0	V	41.43	55.36	63.5	8.14
5350.00	27.10	PK	356	2.3	V	42.06	69.16	83.5	14.34
5350.00	13.57	Ave.	356	2.3	V	42.06	55.63	63.5	7.87
10480.00	40.10	PK	283	1.3	V	21.49	61.59	77.7	16.11
802.11n40									
5190 MHz									
5149.00	34.45	PK	59	1.3	V	41.60	76.05	83.5	7.45
5149.00	14.05	Ave.	59	1.3	V	41.60	55.65	63.5	7.85
5350.00	27.64	PK	248	1.4	V	42.06	69.70	83.5	13.80
5350.00	13.78	Ave.	248	1.4	V	42.06	55.84	63.5	7.66
10380.00	39.79	PK	183	2.1	V	21.69	61.48	77.7	16.22
5230 MHz									
5150.00	27.80	PK	68	1.2	V	41.43	69.23	83.5	14.27
5150.00	13.76	Ave.	68	1.2	V	41.43	55.19	63.5	8.31
5350.00	27.52	PK	335	2.3	V	42.06	69.58	83.5	13.92
5350.00	13.65	Ave.	335	2.3	V	42.06	55.71	63.5	7.79
10460.00	40.13	PK	230	1.3	V	21.39	61.52	77.7	16.18

Frequency (MHz)	Receiver		Turntable	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	FCC Part 15.407/205/209	
	Reading (dBμV)	PK/QP/Ave.	Degree	Height (m)	Polar (H / V)			Limit (dBμV/m)	Margin (dB)
802.11ac20									
5180 MHz									
5148.98	32.42	PK	118	2.2	V	41.60	74.02	83.5	9.48
5148.98	13.96	Ave.	118	2.2	V	41.60	55.56	63.5	7.94
5350.00	27.54	PK	314	2.1	V	42.06	69.60	83.5	13.90
5350.00	13.70	Ave.	314	2.1	V	42.06	55.76	63.5	7.74
10360.00	40.50	PK	87	2.0	V	21.69	62.19	77.7	15.51
5200 MHz									
10400.00	39.95	PK	327	1.2	V	21.79	61.74	77.7	15.96
5240 MHz									
5150.00	27.64	PK	195	2.0	V	41.43	69.07	83.5	14.43
5150.00	13.78	Ave.	195	2.0	V	41.43	55.21	63.5	8.29
5350.00	27.59	PK	137	1.1	V	42.06	69.65	83.5	13.85
5350.00	13.65	Ave.	137	1.1	V	42.06	55.71	63.5	7.79
10480.00	40.74	PK	321	2.0	V	21.49	62.23	77.7	15.47
802.11ac40									
5190 MHz									
5146.20	33.76	PK	163	1.8	V	41.60	75.36	83.5	8.14
5146.20	13.97	Ave.	163	1.8	V	41.60	55.57	63.5	7.93
5350.00	27.84	PK	50	1.9	V	42.06	69.90	83.5	13.60
5350.00	13.89	Ave.	50	1.9	V	42.06	55.95	63.5	7.55
10380.00	40.35	PK	162	2.4	V	21.69	62.04	77.7	15.66
5230 MHz									
5150.00	27.94	PK	55	2.0	V	41.43	69.37	83.5	14.13
5150.00	13.86	Ave.	55	2.0	V	41.43	55.29	63.5	8.21
5350.00	27.45	PK	60	2.4	V	42.06	69.51	83.5	13.99
5350.00	13.65	Ave.	60	2.4	V	42.06	55.71	63.5	7.79
10460.00	40.17	PK	174	1.8	V	21.39	61.56	77.7	16.14
802.11ac80									
5210 MHz									
5143.00	33.70	PK	139	2.3	V	41.60	75.30	83.5	8.20
5143.00	13.95	Ave.	139	2.3	V	41.60	55.55	63.5	7.95
5350.00	27.84	PK	170	1.2	V	42.06	69.90	83.5	13.60
5350.00	13.76	Ave.	170	1.2	V	42.06	55.82	63.5	7.68
10420.00	40.63	PK	293	1.1	V	21.79	62.42	77.7	15.28

Note: For the band edge of 5150-5250MHz band testing, the amplifier had been use.

Note:

Corrected Amplitude = Corrected Factor + Reading



Corrected Factor=Antenna factor (RX) + Cable Loss – Amplifier Factor

Margin = Limit- Corr. Amplitude



All other spurious emissions are 20 dB below the limit or are on the system noise floor level.

Peak


Pre-scan with 802.11a 5240MHz
Horizontal




Vertical



Average Horizontal



Vertical



§15.407(B) (1), (4) –OUT OF BAND EMISSION


Applicable Standard

FCC §15.407 (b) (1), (4);

For transmitters operating in the 5.15–5.25 GHz band: all emissions outside of the 5.15–5.35 GHz band shall not exceed an EIRP of –27dBm/MHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. The Resolution bandwidth is set to 1MHz, The Video bandwidth is set to ≥ 1 MHz, report the peak value out of the operating band.
3. Repeat above procedures until all frequencies measured were complete.
4. when necessary, provided the measured energy is integrated to show the total power over 1 MHz.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Tracy Hu on 2019-01-22.


EUT operation mode: Transmitting

5150 – 5250 MHz:

Testing Mode	Left band edge (dBm/MHz)	Right band edge (dBm/MHz)	Limit (dBm/MHz)
802.11a	-38.11	-44.66	-27
802.11n20	-38.18	-45.34	-27
802.11n40	-29.25	-45.98	-27
802.11ac20	-41.14	-46.18	-27
802.11ac40	-34.21	-46.68	-27
802.11ac80	-36.56	-50.72	-27


Note: For 5150-5250MHz band, the limit is EIRP, so the antenna gain had been adding to the plots.

802.11a mode, Band Edge, Left Side




Date: 22.JAN.2019 19:48:08

802.11a mode, Band Edge, Right Side




Date: 22.JAN.2019 19:48:54

802.11n20 mode, Band Edge, Left Side




Date: 22.JAN.2019 19:40:57

802.11n20 mode, Band Edge, Right Side




Date: 22.JAN.2019 19:41:52

802.11n40 mode, Band Edge, Left Side




Date: 22.JAN.2019 19:34:32

802.11n40 mode, Band Edge, Right Side




Date: 22.JAN.2019 19:33:18

802.11ac20 mode, Band Edge, Left Side




Date: 22.JAN.2019 19:45:02

802.11ac20 mode, Band Edge, Right Side




Date: 22.JAN.2019 19:44:25

802.11ac40 mode, Band Edge, Left Side




Date: 22.JAN.2019 19:29:35

802.11ac40 mode, Band Edge, Right Side




Date: 22.JAN.2019 19:32:06

802.11ac80 mode, Band Edge, Left Side



Date: 22.JAN.2019 20:30:29

802.11ac80 mode, Band Edge, Right Side



Date: 22.JAN.2019 20:31:00

FCC §15.407(a) (1) –EMISSION BANDWIDTH

Applicable Standard

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

Test Procedure

1. Emission Bandwidth (EBW)

- a) Set RBW = approximately 1% of the emission bandwidth.
- b) Set the VBW > RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa


The testing was performed by Tracy Hu on 2019-01-22.

EUT operation mode: Transmitting


Test Result: Pass; please refer to the following tables and plots.

5150 MHz - 5250 MHz:


Frequency (MHz)	26 dB Bandwidth (MHz)	99% Bandwidth (MHz)	Remark
802.11a			No transmitted signal in the 99% bandwidth extends into the U-NII-2A band
5180	20.06	16.60	
5200	20.13	16.60	
5240	20.19	16.60	
802.11n20			
5180	20.51	17.63	
5200	20.32	17.63	
5240	20.45	17.63	
802.11n40			
5190	41.03	36.28	
5230	41.41	36.15	
802.11ac20			
5180	20.51	17.63	
5200	20.51	17.69	
5240	20.58	17.69	
802.11ac40			
5190	41.03	36.28	
5230	41.15	36.15	
802.11ac80			
5210	80.77	75.38	

802.11a mode, 26 dB Emissions & 99% Occupied Bandwidth, 5180 MHz


Date: 22.JAN.2019 20:37:34

802.11a mode, 26 dB Emissions & 99% Occupied Bandwidth, 5200 MHz

Date: 22.JAN.2019 20:39:30


802.11a mode, 26 dB Emissions & 99% Occupied Bandwidth, 5240 MHz

Date: 22.JAN.2019 20:41:49

802.11n20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5180 MHz


Date: 22.JAN.2019 20:23:58

802.11n20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5200 MHz




Date: 22.JAN.2019 20:25:27


802.11n20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5240 MHz



Date: 22.JAN.2019 20:27:01


802.11n40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5190 MHz

Date: 22.JAN.2019 19:58:19

802.11n40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5230 MHz


Date: 22.JAN.2019 20:00:12

802.11ac20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5180 MHz




Date: 22.JAN.2019 20:16:44


802.11ac20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5200 MHz




Date: 22.JAN.2019 20:18:13

802.11ac20 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5240 MHz


Date: 22.JAN.2019 20:22:09

802.11ac40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5190 MHz

Date: 22.JAN.2019 20:04:33

802.11ac40 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5230 MHz

Date: 22.JAN.2019 20:07:42

802.11ac80 mode, 26 dB Emissions & 99% Occupied Bandwidth, 5210 MHz

Date: 22.JAN.2019 20:34:17


FCC §15.407(a) (1) (3) – CONDUCTED TRANSMITTER OUTPUT POWER**Applicable Standard**

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Tracy Hu on 2019-01-22.

EUT operation mode: Transmitting

Test Result: Pass

Please refer to the following tables.

5150 MHz – 5250 MHz

Frequency (MHz)	Conducted Output Power (dBm)	Limit (dBm)
802.11a		
5180	10.29	24
5200	10.32	
5240	10.63	
802.11n20		
5180	10.43	24
5200	10.66	
5240	10.26	
802.11n40		
5190	9.87	24
5230	9.96	
802.11ac20		
5180	10.11	24
5200	10.67	
5240	10.52	
802.11ac40		
5190	9.87	24
5230	10.13	
802.11ac80		
5210	9.54	24

FCC §15.407(a) (1) (3) - POWER SPECTRAL DENSITY

Applicable Standard

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 kHz bandwidth, the following adjustments to the procedures apply:

- a) Set $RBW \geq 1/T$, where T is defined in section II.B.1.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10 \log (500 \text{ kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ kHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10 \log (1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa

The testing was performed by Tracy Hu on 2019-01-22.

EUT operation mode: Transmitting


Test Result: Pass

Please refer to the following tables and plots.

5150 MHz – 5250 MHz


Frequency (MHz)	Power Spectral Density (dBm/MHz)	Limit (dBm/MHz)
802.11a		
5180	-2.82	11
5200	-2.75	
5240	-2.23	
802.11n20		
5180	-2.68	11
5200	-2.42	
5240	-2.68	
802.11n40		
5190	-5.48	11
5230	-5.54	
802. 11ac20		
5180	-2.72	11
5200	-2.56	
5240	-2.68	
802. 11ac40		
5190	-5.90	11
5230	-5.35	
802. 11ac80		
5210	-8.98	11

802.11a mode, Power Spectral Density, 5180 MHz




Date: 22.JAN.2019 20:45:14

802.11a mode, Power Spectral Density, 5200 MHz




Date: 22.JAN.2019 20:44:55

802.11a mode, Power Spectral Density, 5240 MHz




Date: 22.JAN.2019 20:44:16

802.11n20 mode, Power Spectral Density, 5180 MHz




Date: 22.JAN.2019 20:45:42

802.11n20 mode, Power Spectral Density, 5200 MHz




Date: 22.JAN.2019 20:46:19

802.11n20 mode, Power Spectral Density, 5240 MHz




Date: 22.JAN.2019 20:46:38

802.11n40 mode, Power Spectral Density, 5190 MHz




Date: 22.JAN.2019 20:49:56

802.11n40 mode, Power Spectral Density, 5230 MHz




Date: 22.JAN.2019 20:50:17

802.11ac20 mode, Power Spectral Density, 5180 MHz




Date: 22.JAN.2019 20:47:37


802.11ac20 mode, Power Spectral Density, 5200 MHz



Date: 22.JAN.2019 20:48:10


802. 11ac20 mode, Power Spectral Density, 5240 MHz

Date: 22.JAN.2019 20:48:29

802. 11ac40 mode, Power Spectral Density, 5190 MHz


Date: 22.JAN.2019 20:49:07

802.11ac40 mode, Power Spectral Density, 5230 MHz



Date: 22.JAN.2019 20:49:31

802.11ac80 mode, Power Spectral Density, 5210 MHz



Date: 22.JAN.2019 20:51:10

***** END OF REPORT *****