

# FCC REPORT

**Applicant:** JINAN WANBIN IMPORT&EXPORT TRADE CO.,LTD

**Address of Applicant:** Suite 3-101, Building No.18, Spring Garden, Happy Street 25-27-29, Huaiyin District, Jinan City, Shandong Province, China

**Manufacturer/Factory:** JINAN WANBIN IMPORT&EXPORT TRADE CO.,LTD

**Address of Manufacturer/Factory:** Suite 3-101, Building No.18, Spring Garden, Happy Street 25-27-29, Huaiyin District, Jinan City, Shandong Province, China

## Equipment Under Test (EUT)

**Product Name:** Tyre Pressure Sensors ( TPMS Sensors)

**Model No.:** WBE-A

**FCC ID:** 2APXO-WBEA

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart C Section 15.231

**Date of sample receipt:** May 18, 2018

**Date of Test:** May 18-22, 2018

**Date of report issued:** May 23, 2018

**Test Result :** PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

A handwritten signature in black ink, appearing to read "Robinson Lo". To the left of the signature is a circular blue stamp with the text "GTS" in the center, surrounded by "GLOBAL UNITED TECHNOLOGY SERVICES CO., LTD." and "FCC ID: 2APXO-WBEA".

**Laboratory Manager**

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

## 2 Version

Version No.	Date	Description
01	May 23, 2018	Original

Prepared By:




Date:

May 23, 2018

Project Engineer

Check By:



Date:

May 23, 2018

Reviewer

### 3 Contents

	Page
1 COVER PAGE .....	1
2 VERSION .....	2
3 CONTENTS .....	3
4 TEST SUMMARY .....	4
4.1 MEASUREMENT UNCERTAINTY .....	4
5 GENERAL INFORMATION .....	5
5.1 GENERAL DESCRIPTION OF EUT .....	5
5.2 TEST MODE .....	6
5.3 DESCRIPTION OF SUPPORT UNITS .....	6
5.4 TEST FACILITY .....	6
5.5 TEST LOCATION .....	6
5.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER .....	6
5.7 ADDITIONAL INSTRUCTIONS .....	6
6 TEST INSTRUMENTS LIST .....	7
7 TEST RESULTS AND MEASUREMENT DATA .....	8
7.1 ANTENNA REQUIREMENT .....	8
7.2 RADIATED EMISSION METHOD .....	9
7.2.1 Field Strength of The Fundamental Signal .....	12
7.2.2 Spurious emissions .....	13
7.3 20DB OCCUPY BANDWIDTH .....	18
7.4 DWELL TIME .....	19
8 TEST SETUP PHOTO .....	21
9 EUT CONSTRUCTIONAL DETAILS .....	22

## 4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
Field strength of the fundamental signal	15.231 (e)	Pass
Spurious emissions	15.231 (e)/15.209	Pass
20dB Bandwidth	15.231 (c)	Pass
Dwell time	15.231 (e)	Pass

Pass: The EUT complies with the essential requirements in the standard.

### 4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	± 4.34dB	(1)
Radiated Emission	30MHz ~ 1000MHz	± 4.24dB	(1)
Radiated Emission	1GHz ~ 26.5GHz	± 4.68dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.45dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

## 5 General Information

### 5.1 General Description of EUT

Product Name:	Tyre Pressure Sensors ( TPMS Sensors)
Model No.:	WBE-A
Test sample(s) ID:	GTS201805000112-1
Sample(s) Status	Engineer sample
Serial No.	N/A
Hardware version	N/A
Software version	N/A
Operation Frequency:	433.93MHz
Modulation technology:	FSK or ASK
Antenna Type:	Integral Antenna
Antenna gain:	0dBi (declare by applicant)
Power supply:	DC 3V by Button battery

*Remark: Though the pre built-in firmware, this TPMS sensor transmit per 30s*

## 5.2 Test mode

Transmitting mode	Keep the EUT in transmitting mode. (New battery is used during all test)
-------------------	--

### Per-test mode.

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which only the worst case was shown in this test report and defined as follows:

Axis	X	Y	Z
Field Strength(dBuV/m)	68.11	69.71	67.38

## 5.3 Description of Support Units

Manufacturer	Description	Model	Serial Number
N/A	Adapter	CW1201500	N/A
Hamaton	TPMS Reset Tool	HTT0110A	N/A

## 5.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383, January 08, 2018.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016

## 5.5 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China Tel: 0755-27798480 Fax: 0755-27798960

## 5.6 Other Information Requested by the Customer

None.
-------

## 5.7 Additional instructions

Software (Used for test) from client

Mode	Special test SW was built-in by manufacturer.
Power set	Default

## 6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July 03 2015	July 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June 28 2017	June 27 2018
4	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June 28 2017	June 27 2018
5	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June 28 2017	June 27 2018
6	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June 28 2017	June 27 2018
7	Horn Antenna	ETS-LINDGREN	3160	GTS217	June 28 2017	June 27 2018
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial Cable	GTS	N/A	GTS213	June 28 2017	June 27 2018
10	Coaxial Cable	GTS	N/A	GTS211	June 28 2017	June 27 2018
11	Coaxial cable	GTS	N/A	GTS210	June 28 2017	June 27 2018
12	Coaxial Cable	GTS	N/A	GTS212	June 28 2017	June 27 2018
13	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June 28 2017	June 27 2018
14	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	June 28 2017	June 27 2018
15	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 28 2017	June 27 2018
16	Band filter	Amindeon	82346	GTS219	June 28 2017	June 27 2018
17	Power Meter	Anritsu	ML2495A	GTS540	June 28 2017	June 27 2018
18	Power Sensor	Anritsu	MA2411B	GTS541	June 28 2017	June 27 2018

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.16 2014	May.15 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June 28 2017	June 27 2018
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June 28 2017	June 27 2018
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June 28 2017	June 27 2018
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June 28 2017	June 27 2018


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	ChangChun	DYM3	GTS257	June 28 2017	June 27 2018

## 7 Test results and Measurement Data


### 7.1 Antenna requirement


Standard requirement:	FCC Part15 C Section 15.203
<b>15.203 requirement:</b>	
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
<b>EUT Antenna:</b>	

The antenna is integral antenna, the best case gain of the antenna is 0dBi.




## 7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209						
Test Method:	ANSI C63.10:2013						
Test Frequency Range:	9kHz to 6000MHz						
Test site:	Measurement Distance: 3m						
Receiver setup:	Frequency	Detector	RBW	VBW	Value		
	9KHz-150KHz	PK/AV	200Hz	600Hz	PK/AV		
	150KHz-30MHz	PK/AV/QP	9KHz	30KHz	PK/AV/QP		
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak		
	Above 1GHz	Peak	1MHz	3MHz	Peak		
	Above 1GHz	Peak	1MHz	10Hz	Average		
Limit: (Field strength of the fundamental signal)	Frequency	Limit (dBuV/m @3m)		Remark			
	433.93MHz	72.87		Average Value			
		92.87		Peak Value			
Limit: (Spurious Emissions)	Frequency	Limit (uV/m)	Value	Measurement Distance 3m			
	0.009MHz-0.490MHz	2400/F(KHz)	PK/AV				
	0.490MHz-1.705MHz	24000/F(KHz)	QP				
	1.705MHz-30MHz	30	QP				
	30MHz-88MHz	100	QP				
	88MHz-216MHz	150	QP				
	216MHz-960MHz	200	QP				
	960MHz-1GHz	500	QP				
	Above 1GHz	500	Average				
		5000	Peak				
Or The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level whichever limit permits a higher field strength.							
Test setup:	Below 30MHz  Below 1GHz						



Above 1GHz



#### Test Procedure:

1. The EUT was placed on the top of a rotating table (0.8 meters for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or

# GTS

Report No.: GTS201805000112F01

	average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement data:

## 7.2.1 Field Strength of The Fundamental Signal

### ASK

#### Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	PK Level (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	polarization
433.93	78.05	16.17	3.02	29.56	67.68	72.87	-5.19	Horizontal
433.93	76.30	16.17	3.02	29.56	65.93	72.87	-6.94	Vertical

### FSK

#### Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	PK Level (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	polarization
433.93	77.22	16.17	3.02	29.56	66.85	72.87	-6.02	Horizontal
433.93	80.08	16.17	3.02	29.56	69.71	72.87	-3.16	Vertical

## 7.2.2 Spurious emissions


### Below 30MHz

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.


### Below 1GHz:

#### Vertical:

#### ASK:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
51.301	46.53	12.20	0.78	30.08	29.43	40.00	-10.57	QP
125.886	49.17	8.75	1.41	29.69	29.64	43.50	-13.86	QP
362.985	45.37	14.74	2.68	29.82	32.97	46.00	-13.03	QP
701.761	44.22	19.80	4.09	29.20	38.91	46.00	-7.09	QP
848.056	40.66	21.72	4.65	29.19	37.84	46.00	-8.16	QP
945.440	40.23	22.46	5.03	29.25	38.47	46.00	-7.53	QP

**FSK:**


Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
53.131	48.41	11.93	0.80	30.08	31.06	40.00	-8.94	QP
362.985	48.96	14.74	2.68	29.82	36.56	46.00	-9.44	QP
726.805	44.34	20.21	4.19	29.17	39.57	46.00	-6.43	QP
750.108	43.78	20.53	4.28	29.15	39.44	46.00	-6.56	QP
848.056	43.62	21.72	4.65	29.19	40.80	46.00	-5.20	QP
945.440	43.08	22.46	5.03	29.25	41.32	46.00	-4.68	QP


**Horizontal:**

**ASK:**



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
338.400	52.17	14.26	2.57	29.96	39.04	46.00	-6.96	QP
362.985	50.51	14.74	2.68	29.82	38.11	46.00	-7.89	QP
483.910	49.42	17.20	3.23	29.52	40.33	46.00	-5.67	QP
798.980	42.89	21.30	4.45	29.10	39.54	46.00	-6.46	QP
848.056	44.31	21.72	4.65	29.19	41.49	46.00	-4.51	QP
942.131	43.08	22.45	5.01	29.26	41.28	46.00	-4.72	QP

FSK :



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Preamp level dBuV	Limit level dBuV/m	Over limit dB	Remark
265.676	51.13	12.34	2.20	29.93	35.74	46.00	-10.26	QP
338.400	52.09	14.26	2.57	29.96	38.96	46.00	-7.04	QP
701.761	44.57	19.80	4.09	29.20	39.26	46.00	-6.74	QP
798.980	42.73	21.30	4.45	29.10	39.38	46.00	-6.62	QP
942.131	40.16	22.45	5.01	29.26	38.36	46.00	-7.64	QP
993.011	42.08	22.75	5.19	29.21	40.81	54.00	-13.19	QP

**Above 1G:**
**Peak value:**
**ASK:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	PK Level (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Polarization
1230	40.86	25.47	4.49	35.94	34.88	54	-19.12	Vertical
2145	37.25	27.52	5.12	36.51	33.38	54	-20.62	Vertical
2985	36.7	28.46	5.91	37.19	33.88	54	-20.12	Vertical
3880	35.57	29.49	7.66	37.46	35.26	54	-18.74	Vertical
4670	37.63	31.61	8.48	37.64	40.08	54	-13.92	Vertical
5750	34.5	32.56	9.86	36.66	40.26	54	-13.74	Vertical
1215	41.24	25.42	4.48	35.93	35.21	54	-18.79	Horizontal
2105	36.97	27.03	5.08	36.48	32.6	54	-21.4	Horizontal
2965	37.6	28.44	5.89	37.17	34.76	54	-19.24	Horizontal
3835	35.59	29.42	7.58	37.45	35.14	54	-18.86	Horizontal
4705	34.87	31.66	8.52	37.64	37.41	54	-16.59	Horizontal
5765	35.31	32.59	9.88	36.63	41.15	54	-12.85	Horizontal


**FSK:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	PK Level (dBuV/m)	AV Limit (dBuV/m)	Over Limit (dB)	Polarization
1145	41.08	24.96	4.42	35.89	34.57	54	-19.43	Vertical
2050	37.53	26.45	5.01	36.44	32.55	54	-21.45	Vertical
2910	38.28	28.44	5.85	37.12	35.45	54	-18.55	Vertical
3875	35.63	29.47	7.66	37.46	35.3	54	-18.7	Vertical
4695	35.39	31.65	8.51	37.64	37.91	54	-16.09	Vertical
5725	34.75	32.53	9.83	36.68	40.43	54	-13.57	Vertical
1180	39.44	25.25	4.45	35.91	33.23	54	-20.77	Horizontal
2125	37.03	27.24	5.1	36.49	32.88	54	-21.12	Horizontal
2915	36.74	28.44	5.85	37.13	33.9	54	-20.1	Horizontal
3865	34.84	29.45	7.64	37.46	34.47	54	-19.53	Horizontal
4680	34.54	31.63	8.49	37.64	37.02	54	-16.98	Horizontal
5740	35.9	32.56	9.86	36.66	41.66	54	-12.34	Horizontal

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. Average value=Peak value + Duty cycle factor

## 7.3 20dB Occupy Bandwidth

Test Requirement:	FCC Part15 C Section 15.231 (c)
Test Method:	ANSI C63.10:2013
Limit:	The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.
Test setup:	<p style="text-align: center;"><b>Spectrum Analyzer</b></p>  <p style="text-align: center;">Non-Conducted Table</p> <p style="text-align: center;">Ground Reference Plane</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


### Measurement Data

Modulation	Test Frequency (MHz)	20dB bandwidth (MHz)	Limit (MHz)	Result
ASK	433.93	0.052	1.084	Pass
FSK	433.93	0.148	1.084	Pass


Note: Limit= Fundamental frequency $\times$ 0.25% = 433.93 $\times$ 0.25% = 1.084MHz

Test plot as follows:


ASK



FSK



## 7.4 Dwell time

Test Requirement:	FCC Part15 C Section 15.231 (e)
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=100KHz, VBW=300KHz, span=0Hz, detector: Peak
Limit:	Duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.
Test setup:	<p style="text-align: center;"><b>Spectrum Analyzer</b></p>  <p style="text-align: center;">Non-Conducted Table</p> <p style="text-align: center;">Ground Reference Plane</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

### Measurement data:

Modulation	Duration of each TX(second):	Limit (second)	Result
ASK	0.2377	<1.0	Pass
FSK	0.2462	<1.0	Pass

Silent Period Limit: 10s

Silent Period of ASK=0.2377X30=7.131s<10s


Silent Period of FSK=0.2462X30=7.386s<10s

Result:




Silent Period of ASK=31.2s>10s

Silent Period of FSK=30.6s>10s

## ASK





## FSK





## 8 Test Setup Photo

Radiated Emission



## 9 EUT Constructional Details





----- End -----