

# Analysis Report

The Equipment Under Test (EUT) is a Bluetooth headphone with Bluetooth 2.1 only function. The Bluetooth module in the EUT is operating in the frequency range from 2402MHz to 2480MHz (79 channels with 1MHz channel spacing). The EUT can be connected with a Bluetooth Device for music playing.

The EUT is powered by 3.7V DC rechargeable Li – Ion Battery.

**Antenna Type: Internal antenna**

**Antenna Gain: 0dBi**

**Nominal rated field strength is 96.8 dB $\mu$ V/m at 3m**

**Maximum allowed production tolerance: +/- 5dB**

According to the KDB 447498:

Based on the Maximum allowed field strength of production tolerance was 101.8dB $\mu$ V/m at 3m in frequency 2.480GHz, thus;

The EIRP =  $[(FS \cdot D)^2 \cdot 1000 / 30] = 4.54 \text{ mW}$

Conducted power = Radiated Power (EIRP) – Antenna Gain  
So;

Conducted Power = 4.54mW.

The SAR Exclusion Threshold Level:

=  $3.0 \cdot (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$   
=  $3.0 \cdot 5 / \sqrt{2.480} \text{ mW}$   
= 9.53 mW

Since the above conducted output power is well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.