



TEST REPORT

Report Reference No. : **TRE1805021502** **R/C.....:** 92778

FCC ID : **2APZHSC93100MDBVG3**

Applicant's name : **Nexus ID Solutions AB**

Address : Telefonvägen 26,126 26 Hägersten Sweden

Manufacturer : CiVinTec Global Co., Limited

Address : F17,1703,Headquarters Economic Center Buliding, Zhonghaixin Science&Technology Park, Bulan Rd, Shenzhen, China

Test item description : **Access Control Door Reader**

Trade Mark : -

Model/Type reference : SC93100-MDB-VG3

Listed Model(s) : -

Standard : **FCC CFR Title 47 Part 15 Subpart C Section 15.225**

Date of receipt of test sample : May 24, 2018

Date of testing : May 25, 2018 – June 06, 2018

Date of issue : June 06, 2018

Result : **PASS**

Compiled by
(position+printedname+signature)....: File administrators Shayne Zhu

Supervised by
(position+printedname+signature)....: Project Engineer Jerry Wang

Approved by
(position+printedname+signature)....: RF Manager Hans Hu

Testing Laboratory Name : **Shenzhen Huatongwei International Inspection Co., Ltd.**

Address : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

<u>1. TEST STANDARDS AND REPORT VERSION</u>	<u>3</u>
1.1. Test Standards	3
1.2. Report version information	3
<u>2. TEST DESCRIPTION</u>	<u>4</u>
<u>3. SUMMARY</u>	<u>5</u>
3.1. Client Information	5
3.2. Product Description	5
3.3. EUT operation mode	6
3.4. EUT configuration	6
<u>4. TEST ENVIRONMENT</u>	<u>7</u>
4.1. Address of the test laboratory	7
4.2. Test Facility	7
4.3. Environmental conditions	8
4.4. Statement of the measurement uncertainty	8
4.5. Equipments Used during the Test	9
<u>5. TEST CONDITIONS AND RESULTS</u>	<u>10</u>
5.1. Antenna requirement	10
5.2. Restricted Bands of Operation	11
5.3. AC Power Conducted Emissions	12
5.4. Radiated Emission	13
5.5. 20 dB Occupied Bandwidth	16
5.6. Radiated field strength of the fundamental signal	17
5.7. Out of Band Emission	19
5.8. Frequency Stability	21
<u>6. TEST SETUP PHOTOS OF THE EUT</u>	<u>22</u>
<u>7. EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	<u>23</u>

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

[FCC Rules Part 15.225](#): Operation within the band 13.110-14.010 MHz.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices.

1.2. Report version information

Revision No.	Date of issue	Description
N/A	2018-06-05	Original

2. TEST DESCRIPTION

Test Item	Section in CFR 47	Result	Test Engineer
Antenna requirement	15.203	PASS	Baozhu hu
Restricted Band of operation	15.205	PASS	Baozhu hu
AC Power Line Conducted Emissions	15.207	N/A	N/A
Radiated Emissions	15.209	PASS	Michael Jie
20dB Occupied Bandwidth	15.215	PASS	Baozhu hu
Field Strength of the Fundamental Signal	15.225(a)	PASS	Andrew Li
Out of Band Emission	15.225(b)(c)	PASS	Andrew Li
Frequency Stability	15.225(e)	PASS	Baozhu hu

Remark: N/A: not applicable

3. **SUMMARY**

3.1. Client Information

Applicant:	Nexus ID Solutions AB
Address:	Telefonvägen 26,126 26 Hägersten Sweden
Manufacturer:	CiVinTec Global Co., Limited
Address:	F17,1703,Headquarters Economic Center Buliding, Zhonghaixin Science&Technology Park, Bulan Rd, Shenzhen, China.

3.2. Product Description

Name of EUT:	Access Control Door Reader
Trade Mark:	-
Model No.:	SC93100-MDB-VG3
Listed Model(s):	-
Power supply:	DC 9V-30V
Adapter information:	-
RF Specification	
Operation frequency:	13.56MHz
Channel number:	1
Modulation Type:	ASK
Antenna type:	PCB antenna
Antenna gain:	0dBi

*: prescan all test voltage, found worst case at DC 12V, so only show the test data of DC 12V.

3.3. EUT operation mode

TEST MODE

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit.
For AC power line conducted emissions:
The EUT was set to connect with large package sizes transmission.

3.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

	Manufacturer :	/
	Model No. :	/
	Manufacturer :	/
	Model No. :	/

4. TEST ENVIRONMENT

4.1. Address of the test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Phone: 86-755-26748019 Fax: 86-755-26748089

4.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No. 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 762235

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 762235.

IC-Registration No.: 5377B-1

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377B-1.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

4.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors in calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report according to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics;Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics;Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system according to ISO/IEC 17025. Further more, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Here after the best measurement capability for Shenzhen Huatongwei is reported:

Test Items	Measurement Uncertainty	Notes
Conducted spurious emissions 9KHz-30MHz	3.39 dB	(1)
Radiated Emissions 30~1000MHz	4.24 dB	(1)
Radiated Emissions 1~18GHz	5.16 dB	(1)
Radiated Emissions 18-40GHz	5.54 dB	(1)
Occupied Bandwidth	-----	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

4.5. Equipments Used during the Test

Conducted Emissions						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. (mm-dd-yy)	Next Cal. (mm-dd-yy)
1	EMI Test Receiver	R&S	ESCI	101247	11/11/2017	11/10/2018
2	Artificial Mains	SCHWARZBECK	NNLK 8121	573	11/11/2017	11/10/2018
3	2-Line V-Network	R&S	ESH3-Z5	100049	11/11/2017	11/10/2018
4	Pulse Limiter	R&S	ESH3-Z2	101488	11/11/2017	11/10/2018
5	RF Connection Cable	HUBER+SUHNER	EF400	N/A	11/21/2017	11/20/2018
6	Test Software	R&S	ES-K1	N/A	N/A	N/A
Radiated Emissions						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. (mm-dd-yy)	Next Cal. (mm-dd-yy)
1	Semi-Anechoic Chamber	Albatross projects	SAC-3m-01	C11121	10/16/2016	10/15/2019
2	EMI Test Receiver	R&S	ESCI	100900	11/11/2017	11/10/2018
3	Loop Antenna	R&S	HFH2-Z2	100020	11/20/2017	11/19/2020
4	Ultra-Broadband Antenna	SCHWARZBECK	VULB9163	538	4/5/2017	4/4/2020
5	Horn Antenna	SCHWARZBECK	9120D	1011	3/27/2017	3/26/2020
6	Broadband Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170472	3/27/2017	3/26/2020
7	Pre-amplifier	SCHWARZBECK	BBV 9743	9743-0022	10/18/2017	10/17/2018
8	Broadband Pre-amplifier	SCHWARZBECK	BBV 9718	9718-248	10/18/2017	10/17/2018
9	Spectrum Analyzer	R&S	FSP40	100597	11/11/2017	11/10/2018
10	RF Connection Cable	HUBER+SUHNER	RE-7-FL	N/A	11/21/2017	11/20/2018
12	Test Software	Audix	E3	N/A	N/A	N/A
13	Test Software	R&S	ES-K1	N/A	N/A	N/A
14	Turntable	Maturo Germany	TT2.0-1T	N/A	N/A	N/A
15	Antenna Mast	Maturo Germany	CAM-4.0-P-12	N/A	N/A	N/A
RF Conducted Test						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. (mm-dd-yy)	Next Cal. (mm-dd-yy)
1	Spectrum Analyzer	R&S	FSV40	100048	11/11/2017	11/10/2018

5. **TEST CONDITIONS AND RESULTS**

5.1. Antenna requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Refer to statement below for compliance.

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

TEST RESULTS

Passed Not Applicable



5.2. Restricted Bands of Operation

Requirement


Only spurious emissions are permitted in any of the frequency bands listed below :

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

TEST RESULTS

Passed Not Applicable



5.3. AC Power Conducted Emissions


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10:2013
2. The EUT was placed on a plat form of nominal size, 1 m by 1.5 m, raised 10 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 10 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50ohm / 50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

Passed Not Applicable

5.4. Radiated Emission


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30MHz~88MHz	40.00	Quasi-peak
88MHz~216MHz	43.50	Quasi-peak
216MHz~960MHz	46.00	Quasi-peak
960MHz~1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


- 9 kHz ~ 30 MHz



- 30 MHz ~ 1 GHz



- Above 1 GHz



TEST PROCEDURE





1. The EUT was setup and tested according to ANSI C63.10:2013 requirements.
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Below 1 GHz:
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - (3) From 1 GHz to 10th harmonic:
RBW=1MHz, VBW=3MHz Peak detector for Peak value.
RBW=1MHz, VBW=3MHz RMS detector for Average value.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

Passed Not Applicable


Polarization:		Vertical																																																																						
Level [dB μ V/m]																																																																								
																																																																								
<table border="1"> <thead> <tr> <th>Frequency MHz</th><th>Level dBμV/m</th><th>Transd dB</th><th>Limit dBμV/m</th><th>Margin dB</th><th>Det.</th><th>Height cm</th><th>Azimuth deg</th><th>Polarization</th></tr> </thead> <tbody> <tr><td>39.700000</td><td>23.10</td><td>-10.1</td><td>40.0</td><td>16.9</td><td>QP</td><td>100.0</td><td>159.00</td><td>VERTICAL</td></tr> <tr><td>55.220000</td><td>17.90</td><td>-9.2</td><td>40.0</td><td>22.1</td><td>QP</td><td>100.0</td><td>107.00</td><td>VERTICAL</td></tr> <tr><td>105.660000</td><td>17.90</td><td>-10.5</td><td>43.5</td><td>25.6</td><td>QP</td><td>100.0</td><td>213.00</td><td>VERTICAL</td></tr> <tr><td>284.140000</td><td>21.80</td><td>-7.6</td><td>46.0</td><td>24.2</td><td>QP</td><td>100.0</td><td>53.00</td><td>VERTICAL</td></tr> <tr><td>542.160000</td><td>26.90</td><td>-0.9</td><td>46.0</td><td>19.1</td><td>QP</td><td>100.0</td><td>119.00</td><td>VERTICAL</td></tr> <tr><td>945.680000</td><td>34.70</td><td>7.2</td><td>46.0</td><td>11.3</td><td>QP</td><td>100.0</td><td>27.00</td><td>VERTICAL</td></tr> </tbody> </table>										Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization	39.700000	23.10	-10.1	40.0	16.9	QP	100.0	159.00	VERTICAL	55.220000	17.90	-9.2	40.0	22.1	QP	100.0	107.00	VERTICAL	105.660000	17.90	-10.5	43.5	25.6	QP	100.0	213.00	VERTICAL	284.140000	21.80	-7.6	46.0	24.2	QP	100.0	53.00	VERTICAL	542.160000	26.90	-0.9	46.0	19.1	QP	100.0	119.00	VERTICAL	945.680000	34.70	7.2	46.0	11.3	QP	100.0	27.00	VERTICAL
Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization																																																																
39.700000	23.10	-10.1	40.0	16.9	QP	100.0	159.00	VERTICAL																																																																
55.220000	17.90	-9.2	40.0	22.1	QP	100.0	107.00	VERTICAL																																																																
105.660000	17.90	-10.5	43.5	25.6	QP	100.0	213.00	VERTICAL																																																																
284.140000	21.80	-7.6	46.0	24.2	QP	100.0	53.00	VERTICAL																																																																
542.160000	26.90	-0.9	46.0	19.1	QP	100.0	119.00	VERTICAL																																																																
945.680000	34.70	7.2	46.0	11.3	QP	100.0	27.00	VERTICAL																																																																
Polarization:		Horizontal																																																																						
Level [dB μ V/m]																																																																								
																																																																								
<table border="1"> <thead> <tr> <th>Frequency MHz</th><th>Level dBμV/m</th><th>Transd dB</th><th>Limit dBμV/m</th><th>Margin dB</th><th>Det.</th><th>Height cm</th><th>Azimuth deg</th><th>Polarization</th></tr> </thead> <tbody> <tr><td>49.400000</td><td>20.50</td><td>-8.7</td><td>40.0</td><td>19.5</td><td>QP</td><td>100.0</td><td>308.00</td><td>HORIZONTAL</td></tr> <tr><td>55.220000</td><td>18.10</td><td>-9.2</td><td>40.0</td><td>21.9</td><td>QP</td><td>300.0</td><td>36.00</td><td>HORIZONTAL</td></tr> <tr><td>284.140000</td><td>28.50</td><td>-7.6</td><td>46.0</td><td>17.5</td><td>QP</td><td>100.0</td><td>213.00</td><td>HORIZONTAL</td></tr> <tr><td>297.720000</td><td>28.20</td><td>-7.3</td><td>46.0</td><td>17.8</td><td>QP</td><td>100.0</td><td>108.00</td><td>HORIZONTAL</td></tr> <tr><td>534.400000</td><td>27.00</td><td>-1.1</td><td>46.0</td><td>19.0</td><td>QP</td><td>300.0</td><td>284.00</td><td>HORIZONTAL</td></tr> <tr><td>893.300000</td><td>36.40</td><td>6.6</td><td>46.0</td><td>9.6</td><td>QP</td><td>300.0</td><td>353.00</td><td>HORIZONTAL</td></tr> </tbody> </table>										Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization	49.400000	20.50	-8.7	40.0	19.5	QP	100.0	308.00	HORIZONTAL	55.220000	18.10	-9.2	40.0	21.9	QP	300.0	36.00	HORIZONTAL	284.140000	28.50	-7.6	46.0	17.5	QP	100.0	213.00	HORIZONTAL	297.720000	28.20	-7.3	46.0	17.8	QP	100.0	108.00	HORIZONTAL	534.400000	27.00	-1.1	46.0	19.0	QP	300.0	284.00	HORIZONTAL	893.300000	36.40	6.6	46.0	9.6	QP	300.0	353.00	HORIZONTAL
Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization																																																																
49.400000	20.50	-8.7	40.0	19.5	QP	100.0	308.00	HORIZONTAL																																																																
55.220000	18.10	-9.2	40.0	21.9	QP	300.0	36.00	HORIZONTAL																																																																
284.140000	28.50	-7.6	46.0	17.5	QP	100.0	213.00	HORIZONTAL																																																																
297.720000	28.20	-7.3	46.0	17.8	QP	100.0	108.00	HORIZONTAL																																																																
534.400000	27.00	-1.1	46.0	19.0	QP	300.0	284.00	HORIZONTAL																																																																
893.300000	36.40	6.6	46.0	9.6	QP	300.0	353.00	HORIZONTAL																																																																

5.5. 20 dB Occupied Bandwidth

Limit

Intentional radiators must be designed to ensure that the 20dB emission bandwidth in the specific band 13.553~13.567MHz.

TEST CONFIGURATION



TEST PROCEDURE


1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
RBW \geq 1% of the 20 dB bandwidth, VBW \geq RBW
Sweep = auto, Detector function = peak, Trace = max hold
4. Measure and record the results in the test report.

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

Passed Not Applicable




5.6. Radiated field strength of the fundamental signal

LIMIT

Fundamental frequency(MHz)	Field strength of fundamental (uV/m @30m)	Field strength of fundamental (dBuV/m @3m)
13.553-13.567	15.848	124.0
13.410-13.553&13.567-13.710	334	90.5
13.110-13.410&13.710-14.010	106	80.5

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10:2013 requirements.
2. The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT waspositioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. The receiver set as follow:


Frequency	Detector	RBW	VBW	Remark
9kHz-150kHz	Quasi-peak	200Hz	600Hz	Quasi-peak Value
50kHz-30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
30MHz-1GHz	Quasi-peak	120kHz	300KHz	Quasi-peak Value

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

Passed Not Applicable



5.7. Out of Band Emission


LIMIT

Frequency(MHz)	Field strength (dBuV/m)
0.009-0.490	2400/F(kHz) at 300m
0.490-1.705	24000/F(kHz) at 30m
1.705-30	29.54 at 30m

Note:For measurements in the band 0.009MHz to 0.490MHz the specified measurement distance is 300m. The distance correction will be: Correction = $40 * \log (300/3) = 80$ dB

For measurements in the band 0.490MHz to 30MHz the specified measurement distance is 30m. The distance correction will be: Correction = $20 * \log (30/3) = 20$ Db

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10:2013 requirements.
2. The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. The receiver set as follow:


Frequency	Detector	RBW	VBW	Remark
9kHz-150kHz	Quasi-peak	200Hz	600Hz	Quasi-peak Value
50kHz-30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value

TEST MODE:

Please refer to the clause 3.3

TEST RESULTS

Passed Not Applicable




5.8. Frequency Stability

LIMIT

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+ 50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

TEST CONFIGURATION



TEST PROCEDURE

1. The equipment under test was connected to an external power supply.
2. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators.
3. The EUT was placed inside the temperature chamber.
4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 25°C operating frequency as reference frequency.
5. Turn EUT off and set the chamber temperature to -20°C . After the temperature stabilized for approximately 30 minutes recorded the frequency.
6. Repeat step measure with 10°C increased per stage until the highest temperature of $+50^\circ\text{C}$ reached.

TEST MODE:

Please refer to the clause 3.3



TEST RESULTS

Passed Not Applicable

Test Environment		Frequency Reading(MHz)	Frequency Error(%)	Limit	Result
Voltage	Temperature(°C)				
DC12V	-20	13.56008	0.0006%	$\pm 0.01\%$	Pass
	-10	13.56007	0.0005%	$\pm 0.01\%$	Pass
	0	13.56007	0.0005%	$\pm 0.01\%$	Pass
	10	13.56009	0.0007%	$\pm 0.01\%$	Pass
	20	13.56008	0.0006%	$\pm 0.01\%$	Pass
	30	13.56009	0.0007%	$\pm 0.01\%$	Pass
	40	13.56012	0.0009%	$\pm 0.01\%$	Pass
	50	13.56015	0.0011%	$\pm 0.01\%$	Pass
DC13.8V	20	13.56007	0.0005%	$\pm 0.01\%$	Pass
DC10.2V	20	13.56009	0.0007%	$\pm 0.01\%$	Pass

6. TEST SETUP PHOTOS OF THE EUT

Radiated Emissions



7. EXTERNAL AND INTERNAL PHOTOS OF THE EUT

Reference to the test report No.: TRE1805021501.

-----End of Report-----