



FCC PART 15.247

## TEST REPORT

For

**Shenzhen VanTop Technology & Innovation Co., Ltd.**

502, 5th Flr. BLDG 4, MinQi Technology Park, No. 65 Lishan Road, Taoyuan Street,  
Nanshan District, Shenzhen, China

**FCC ID: 2AQ3A-P31**

|                                                                                                                                                                                                                                                                                                                             |                                                                                      |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| <b>Report Type:</b><br>Original Report                                                                                                                                                                                                                                                                                      | <b>Product Type:</b><br>Tablet PC                                                    |
| <b>Report Number:</b> RSZ200721007-00B                                                                                                                                                                                                                                                                                      |                                                                                      |
| <b>Report Date:</b> 2020-12-30                                                                                                                                                                                                                                                                                              |                                                                                      |
| Nancy Wang                                                                                                                                                                                                                                                                                                                  |                                                                                      |
| <b>Reviewed By:</b> RF Engineer                                                                                                                                                                                                                                                                                             |  |
| <b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Shenzhen)<br>6/F., West Wing, Third Phase of Wanli Industrial<br>Building, Shihua Road, Futian Free Trade Zone,<br>Shenzhen, Guangdong, China<br>Tel: +86-755-33320018<br>Fax: +86-755-33320008<br><a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a> |                                                                                      |

**Note:** This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '\*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## **TABLE OF CONTENTS**

|                                                                          |           |
|--------------------------------------------------------------------------|-----------|
| <b>GENERAL INFORMATION.....</b>                                          | <b>4</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....                 | 4         |
| OBJECTIVE .....                                                          | 4         |
| TEST METHODOLOGY .....                                                   | 4         |
| MEASUREMENT UNCERTAINTY .....                                            | 5         |
| <b>SYSTEM TEST CONFIGURATION .....</b>                                   | <b>6</b>  |
| DESCRIPTION OF TEST CONFIGURATION .....                                  | 6         |
| EQUIPMENT MODIFICATIONS .....                                            | 7         |
| EUT EXERCISE SOFTWARE .....                                              | 7         |
| DUTY CYCLE .....                                                         | 7         |
| SUPPORT EQUIPMENT LIST AND DETAILS .....                                 | 7         |
| EXTERNAL I/O CABLE .....                                                 | 7         |
| BLOCK DIAGRAM OF TEST SETUP .....                                        | 8         |
| <b>SUMMARY OF TEST RESULTS .....</b>                                     | <b>9</b>  |
| <b>TEST EQUIPMENT LIST .....</b>                                         | <b>10</b> |
| <b>FCC§15.247 (i), §1.1307 (b) (1) &amp; §2.1093 – RF EXPOSURE .....</b> | <b>11</b> |
| APPLICABLE STANDARD .....                                                | 11        |
| <b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>                            | <b>12</b> |
| APPLICABLE STANDARD .....                                                | 12        |
| ANTENNA CONNECTOR CONSTRUCTION .....                                     | 12        |
| <b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS .....</b>               | <b>13</b> |
| APPLICABLE STANDARD .....                                                | 13        |
| EUT SETUP .....                                                          | 13        |
| EMI TEST RECEIVER SETUP.....                                             | 13        |
| TEST PROCEDURE .....                                                     | 13        |
| CORRECTED FACTOR & MARGIN CALCULATION .....                              | 14        |
| TEST DATA .....                                                          | 14        |
| <b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS.....</b>   | <b>17</b> |
| APPLICABLE STANDARD .....                                                | 17        |
| EUT SETUP .....                                                          | 17        |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....                        | 18        |
| TEST PROCEDURE .....                                                     | 18        |
| CORRECTED AMPLITUDE & MARGIN CALCULATION .....                           | 18        |
| TEST DATA .....                                                          | 18        |
| <b>FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....</b>                 | <b>28</b> |
| APPLICABLE STANDARD .....                                                | 28        |
| TEST PROCEDURE .....                                                     | 28        |
| TEST DATA .....                                                          | 28        |
| <b>FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....</b>          | <b>29</b> |
| APPLICABLE STANDARD .....                                                | 29        |
| TEST PROCEDURE .....                                                     | 29        |
| TEST DATA .....                                                          | 29        |

|                                                                       |           |
|-----------------------------------------------------------------------|-----------|
| <b>FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....</b> | <b>30</b> |
| APPLICABLE STANDARD .....                                             | 30        |
| TEST PROCEDURE .....                                                  | 30        |
| TEST DATA .....                                                       | 30        |
| <b>FCC §15.247(e) - POWER SPECTRAL DENSITY .....</b>                  | <b>31</b> |
| APPLICABLE STANDARD .....                                             | 31        |
| TEST PROCEDURE .....                                                  | 31        |
| TEST DATA .....                                                       | 31        |
| <b>APPENDIX BLE.....</b>                                              | <b>32</b> |
| APPENDIX A: DTS BANDWIDTH .....                                       | 32        |
| APPENDIX B: MAXIMUM CONDUCTED PEAK OUTPUT POWER .....                 | 35        |
| APPENDIX C: MAXIMUM POWER SPECTRAL DENSITY .....                      | 36        |
| APPENDIX D: BAND EDGE MEASUREMENTS .....                              | 39        |
| APPENDIX E: DUTY CYCLE .....                                          | 41        |
| <b>APPENDIX Wi-Fi.....</b>                                            | <b>42</b> |
| APPENDIX A: DTS BANDWIDTH .....                                       | 42        |
| APPENDIX B: MAXIMUM CONDUCTED OUTPUT POWER (AV) .....                 | 46        |
| APPENDIX C: MAXIMUM POWER SPECTRAL DENSITY .....                      | 47        |
| APPENDIX D: BAND EDGE MEASUREMENTS .....                              | 51        |
| APPENDIX E: DUTY CYCLE .....                                          | 53        |

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

|                              |                                                                                           |
|------------------------------|-------------------------------------------------------------------------------------------|
| Product                      | Tablet PC                                                                                 |
| Tested Model                 | P31                                                                                       |
| Multiple Model               | S20, S21, S30, X10, E7, E8, E10, E11, S9, P10, P40, P50, A03003, A03005, A03006           |
| Model Differences            | Refer to the DoS letter                                                                   |
| Frequency Range              | Bluetooth LE: 2402~2480MHz<br>Wi-Fi: 2412~2462MHz                                         |
| Maximum Conducted Peak Power | Bluetooth LE: 3.89dBm<br>Wi-Fi: 9.37dBm(802.11b), 9.44dBm(802.11g), 9.13dBm(802.11n-HT20) |
| Modulation Technique         | Bluetooth LE: GFSK<br>Wi-Fi: DSSS, OFDM                                                   |
| Antenna Specification*       | Internal Antenna: 2dBi(provided by the applicant)                                         |
| Voltage Range                | DC 3.8V from battery or DC 5V from adapter                                                |
| Date of Test                 | 2020-07-28 to 2020-09-24                                                                  |
| Sample number                | RSZ200721007-RF-S1 (Assigned by BACL, Shenzhen)                                           |
| Received date                | 2020-07-21                                                                                |
| Sample/EUT Status            | Good condition                                                                            |
| Adapter information          | Model: FX2U-050200U<br>Input: 100-240V~50/60Hz 0.4A max<br>Output: 5V, 2A                 |

### Objective

This report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

**Measurement Uncertainty**

| Parameter                          |            | Uncertainty |
|------------------------------------|------------|-------------|
| Occupied Channel Bandwidth         |            | ±5%         |
| RF Output Power with Power meter   |            | ±0.73dB     |
| RF conducted test with spectrum    |            | ±1.6dB      |
| AC Power Lines Conducted Emissions |            | ±1.95dB     |
| Emissions,<br>Radiated             | Below 1GHz | ±4.75dB     |
|                                    | Above 1GHz | ±4.88dB     |
| Temperature                        |            | ±1 °C       |
| Humidity                           |            | ±6%         |
| Supply voltages                    |            | ±0.4%       |

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

**Test Facility**

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

For 802.11b, 802.11g and 802.11n-HT20 mode, 11 channels are provided to testing:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 1       | 2412            | 8       | 2447            |
| 2       | 2417            | 9       | 2452            |
| 3       | 2422            | 10      | 2457            |
| 4       | 2427            | 11      | 2462            |
| 5       | 2432            | /       | /               |
| 6       | 2437            | /       | /               |
| 7       | 2442            | /       | /               |

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11.

For BLE mode, 40 channels are provided to testing:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 0       | 2402            | 20      | 2442            |
| 1       | 2404            | 21      | 2444            |
| 2       | 2406            | 22      | 2446            |
| 3       | 2408            | 23      | 2448            |
| 4       | 2410            | 24      | 2450            |
| 5       | 2412            | 25      | 2452            |
| 6       | 2414            | 26      | 2454            |
| 7       | 2416            | 27      | 2456            |
| 8       | 2418            | 28      | 2458            |
| 9       | 2420            | 29      | 2460            |
| 10      | 2422            | 30      | 2462            |
| 11      | 2424            | 31      | 2464            |
| 12      | 2426            | 32      | 2466            |
| 13      | 2428            | 33      | 2468            |
| 14      | 2430            | 34      | 2470            |
| 15      | 2432            | 35      | 2472            |
| 16      | 2434            | 36      | 2474            |
| 17      | 2436            | 37      | 2476            |
| 18      | 2438            | 38      | 2478            |
| 19      | 2440            | 39      | 2480            |

EUT was tested with Channel 0, 19 and 39.

**Equipment Modifications**

No modification was made to the EUT tested.

**EUT Exercise Software**

Wi-Fi & BLE test in the engineer mode.

The device was tested with the worst case was performed as below:

| Mode         | Data rate | Power level* |                |              |
|--------------|-----------|--------------|----------------|--------------|
|              |           | Low channel  | Middle channel | High channel |
| 802.11b      | 1 Mbps    | 10           | 10             | 10           |
| 802.11g      | 6 Mbps    | 11           | 11             | 11           |
| 802.11n-HT20 | 6.5 Mbps  | 10           | 10             | 10           |
| BLE          | /         | Default      | Default        | Default      |

The power level was provided by the applicant.

Pre-scan with all the data rates, the above data rate is the worst case for Wi-Fi test.

**Duty cycle**

Test Result Compliant. Please refer to the Appendix BLE & Appendix Wi-Fi.


**Support Equipment List and Details**

| Manufacturer | Description | Model    | Serial Number |
|--------------|-------------|----------|---------------|
| Earphone     | Ipx8        | 200909-1 | 200909-1      |

**External I/O Cable**

| Cable Description                   | Length (m) | From Port | To       |
|-------------------------------------|------------|-----------|----------|
| Un-shielding Detachable USB Cable   | 1.0        | EUT       | Adapter  |
| Un-shielding Detachable Audio Cable | 1.2        | EUT       | Earphone |

## Block Diagram of Test Setup



**SUMMARY OF TEST RESULTS**

| FCC Rules                                | Description of Test                      | Result     |
|------------------------------------------|------------------------------------------|------------|
| §15.247 (i), §1.1307 (b) (1)&<br>§2.1093 | RF Exposure                              | Compliance |
| §15.203                                  | Antenna Requirement                      | Compliance |
| §15.207 (a)                              | AC Line Conducted Emissions              | Compliance |
| §15.205, §15.209,<br>§15.247(d)          | Spurious Emissions                       | Compliance |
| §15.247 (a)(2)                           | 6 dB Emission Bandwidth                  | Compliance |
| §15.247(b)(3)                            | Maximum Conducted Output Power           | Compliance |
| §15.247(d)                               | 100 kHz Bandwidth of Frequency Band Edge | Compliance |
| §15.247(e)                               | Power Spectral Density                   | Compliance |

**TEST EQUIPMENT LIST**

| Manufacturer                               | Description                  | Model                   | Serial Number          | Calibration Date | Calibration Due Date |
|--------------------------------------------|------------------------------|-------------------------|------------------------|------------------|----------------------|
| <b>Conducted Emissions Test</b>            |                              |                         |                        |                  |                      |
| Rohde & Schwarz                            | EMI Test Receiver            | ESCI                    | 101120                 | 2020/07/09       | 2021/07/08           |
| Rohde & Schwarz                            | LISN                         | ENV216                  | 101613                 | 2020/01/22       | 2021/01/21           |
| Rohde & Schwarz                            | Transient Limitor            | ESH3Z2                  | DE25985                | 2019/11/29       | 2020/11/28           |
| Unknown                                    | CE Cable                     | CE Cable                | UF A210B-1-0720-504504 | 2019/11/29       | 2020/11/28           |
| Rohde & Schwarz                            | CE Test software             | EMC 32                  | V8.53.0                | NCR              | NCR                  |
| <b>Radiated Emission Test (30MHz-1GHz)</b> |                              |                         |                        |                  |                      |
| R&S                                        | EMI Test Receiver            | ESR3                    | 102455                 | 2020/07/09       | 2021/07/08           |
| Sonoma instrument                          | Pre-amplifier                | 310 N                   | 186238                 | 2020/04/20       | 2021/04/20           |
| Sunol Sciences                             | Broadband Antenna            | JB1                     | A040904-1              | 2017/12/22       | 2020/12/21           |
| Unknown                                    | Cable 2                      | RF Cable 2              | F-03-EM197             | 2019/11/29       | 2020/11/28           |
| Unknown                                    | Cable                        | Chamber Cable 1         | F-03-EM236             | 2019/11/29       | 2020/11/28           |
| Rohde & Schwarz                            | Auto test software           | EMC 32                  | V9.10                  | NCR              | NCR                  |
| <b>Radiated Emission Test (1GHz-25GHz)</b> |                              |                         |                        |                  |                      |
| Rohde & Schwarz                            | Spectrum Analyzer            | FSV40-N                 | 102259                 | 2020/08/04       | 2021/08/03           |
| COM-POWER                                  | Pre-amplifier                | PA-122                  | 181919                 | 2019/11/29       | 2020/11/28           |
| Quinstar                                   | Amplifier                    | QLW-18405536-J0         | 15964001002            | 2019/11/29       | 2020/11/28           |
| Sunol Sciences                             | Horn Antenna                 | DRH-118                 | A052604                | 2017/12/22       | 2020/12/21           |
| Insulted Wire Inc.                         | RF Cable                     | SPS-2503-3150           | 02222010               | 2019/11/29       | 2020/11/28           |
| Unknown                                    | RF Cable                     | W1101-EQ1 OUT           | F-19-EM005             | 2019/11/29       | 2020/11/28           |
| SNSD                                       | Band Reject filter           | BSF2402-2480MN-0898-001 | 2.4G filter            | 2020/04/20       | 2021/04/20           |
| Ducommun Technologies                      | Horn antenna                 | ARH-4223-02             | 1007726-02 1304        | 2017/12/06       | 2020/12/05           |
| <b>RF Conducted Test</b>                   |                              |                         |                        |                  |                      |
| Tonscend Corporation                       | RF control Unit              | JS0806-2                | 19D8060154             | 2020/08/04       | 2021/08/03           |
| Rohde & Schwarz                            | Signal and Spectrum Analyzer | FSV40                   | 101473                 | 2020/08/04       | 2021/08/03           |
| Unknown                                    | RF Cable                     | Unknown                 | 2301 276               | 2019/11/29       | 2020/11/28           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## **FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE**

### **Applicable Standard**

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

1.  $f(\text{GHz})$  is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test Exclusion.

### **Measurement Result**

**For worst case:**

| Mode  | Frequency (MHz) | Max Tune-up Conducted Power (dBm) | Max Tune-up Conducted Power (mW) | Calculated Distance (mm) | Calculated value | Threshold (1-g SAR) | SAR Test Exclusion |
|-------|-----------------|-----------------------------------|----------------------------------|--------------------------|------------------|---------------------|--------------------|
| BLE   | 2480            | 4.0                               | 2.51                             | 5                        | 0.79             | 3.0                 | Yes                |
| Wi-Fi | 2462            | 9.5                               | 8.91                             | 5                        | 2.8              | 3.0                 | Yes                |

**Result: No Standalone SAR test is required**

## **FCC §15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **Antenna Connector Construction**

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 2 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


**Result:** Compliance.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC§15.207

### EUT Setup



Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz  |

### Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

## Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$


## Test Data

### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25 °C     |
| Relative Humidity: | 65 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Haiguo Li on 2020-07-29.*


*EUT operation mode: Transmitting (worst case at 802.11g high channel)*

**AC 120V/60 Hz, Line****Final Result 1**

| Frequency (MHz) | QuasiPeak (dB μ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dB μ V) |
|-----------------|--------------------|-----------------|------|------------|-------------|----------------|
| 0.339010        | 35.7               | 9.000           | L1   | 19.9       | 23.5        | 59.2           |
| 0.660190        | 39.9               | 9.000           | L1   | 19.8       | 16.1        | 56.0           |
| 0.904590        | 32.2               | 9.000           | L1   | 19.8       | 23.8        | 56.0           |
| 0.923650        | 31.6               | 9.000           | L1   | 19.8       | 24.4        | 56.0           |
| 1.081890        | 31.3               | 9.000           | L1   | 19.9       | 24.7        | 56.0           |
| 1.148930        | 30.5               | 9.000           | L1   | 19.8       | 25.5        | 56.0           |

**Final Result 2**

| Frequency (MHz) | Average (dB μ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dB μ V) |
|-----------------|------------------|-----------------|------|------------|-------------|----------------|
| 0.339010        | 29.7             | 9.000           | L1   | 19.9       | 19.5        | 49.2           |
| 0.660190        | 38.8             | 9.000           | L1   | 19.8       | 7.2         | 46.0           |
| 0.904590        | 24.8             | 9.000           | L1   | 19.8       | 21.2        | 46.0           |
| 0.923650        | 24.2             | 9.000           | L1   | 19.8       | 21.8        | 46.0           |
| 1.081890        | 25.4             | 9.000           | L1   | 19.9       | 20.6        | 46.0           |
| 1.148930        | 24.2             | 9.000           | L1   | 19.8       | 21.8        | 46.0           |

**AC 120V/60 Hz, Neutral:****Final Result 1**



| Frequency (MHz) | QuasiPeak (dB μ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dB μ V) |
|-----------------|--------------------|-----------------|------|------------|-------------|----------------|
| 0.348750        | 34.3               | 9.000           | N    | 19.9       | 24.7        | 59.0           |
| 0.651630        | 35.8               | 9.000           | N    | 19.8       | 20.2        | 56.0           |
| 0.707530        | 30.1               | 9.000           | N    | 19.8       | 25.9        | 56.0           |
| 0.896590        | 33.4               | 9.000           | N    | 19.7       | 22.6        | 56.0           |
| 0.904350        | 33.0               | 9.000           | N    | 19.7       | 23.0        | 56.0           |
| 1.065830        | 30.8               | 9.000           | N    | 19.8       | 25.2        | 56.0           |

**Final Result 2**

| Frequency (MHz) | Average (dB μ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dB μ V) |
|-----------------|------------------|-----------------|------|------------|-------------|----------------|
| 0.222000        | 33.9             | 9.000           | N    | 19.8       | 18.8        | 52.7           |
| 0.270000        | 32.0             | 9.000           | N    | 19.7       | 19.1        | 51.1           |
| 0.642000        | 28.8             | 9.000           | N    | 19.8       | 17.2        | 46.0           |
| 0.886000        | 25.3             | 9.000           | N    | 19.7       | 20.7        | 46.0           |
| 0.910000        | 25.6             | 9.000           | N    | 19.7       | 20.4        | 46.0           |
| 1.034000        | 25.0             | 9.000           | N    | 19.8       | 21.0        | 46.0           |

**FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS****Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

**EUT Setup****Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

## EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range   | RBW     | Video B/W               | IF B/W  | Measurement |
|-------------------|---------|-------------------------|---------|-------------|
| 30 MHz – 1000 MHz | 100 kHz | 300 kHz                 | 120 kHz | QP          |
| Above 1 GHz       | 1MHz    | 3 MHz                   | /       | PK          |
|                   | 1MHz    | 10 Hz <sup>Note 1</sup> | /       | Average     |
|                   | 1MHz    | > 1/T <sup>Note 2</sup> | /       | Average     |

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Data


### Environmental Conditions

|                           |                 |
|---------------------------|-----------------|
| <b>Temperature:</b>       | 29~32.2 °C      |
| <b>Relative Humidity:</b> | 55~56 %         |
| <b>ATM Pressure:</b>      | 101.0~101.1 kPa |

*The testing was performed by Holland Yang on 2020-07-28 for below 1GHz and Leven Gan on 2020-09-24 for above 1GHz.*

*EUT operation mode: Transmitting*

30 MHz~1 GHz: (worst case at 802.11g high channel)



## Final Result

| Frequency (MHz) | QuasiPeak (dB µ V/m) | Limit (dB µ V/m) | Margin (dB) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB) |
|-----------------|----------------------|------------------|-------------|-------------|-----|---------------|------------|
| 30.430040       | 19.60                | 40.00            | 20.40       | 145.0       | V   | 13.0          | -7.9       |
| 35.456750       | 18.57                | 40.00            | 21.43       | 101.0       | V   | 79.0          | -11.4      |
| 581.346500      | 18.70                | 46.00            | 27.30       | 207.0       | V   | 308.0         | -2.5       |
| 681.797875      | 20.26                | 46.00            | 25.74       | 152.0       | V   | 265.0         | -1.4       |
| 835.145125      | 24.69                | 46.00            | 21.31       | 192.0       | V   | 108.0         | 2.7        |
| 936.102000      | 25.62                | 46.00            | 20.38       | 363.0       | V   | 175.0         | 4.8        |

**1 GHz-25 GHz (BLE Mode):****BLE 1M:**

| Frequency<br>(MHz)        | Receiver          |            | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB/m) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|---------------------------|-------------------|------------|---------------------|---------------|----------------|-------------------------------|------------------------------------|-------------------|----------------|
|                           | Reading<br>(dBμV) | PK/QP/Ave. |                     | Height<br>(m) | Polar<br>(H/V) |                               |                                    |                   |                |
| Low Channel (2402 MHz)    |                   |            |                     |               |                |                               |                                    |                   |                |
| 2338.34                   | 28.79             | PK         | 63                  | 1.9           | H              | 31.64                         | 60.43                              | 74                | 13.57          |
| 2338.34                   | 13.63             | Ave.       | 63                  | 1.9           | H              | 31.64                         | 45.27                              | 54                | 8.73           |
| 2486.57                   | 28.77             | PK         | 245                 | 1.6           | H              | 32.13                         | 60.90                              | 74                | 13.10          |
| 2486.57                   | 13.61             | Ave.       | 245                 | 1.6           | H              | 32.13                         | 45.74                              | 54                | 8.26           |
| 4804.00                   | 43.89             | PK         | 355                 | 2.2           | H              | 6.28                          | 50.17                              | 74                | 23.83          |
| 4804.00                   | 28.68             | Ave.       | 355                 | 2.2           | H              | 6.28                          | 34.96                              | 54                | 19.04          |
| Middle Channel (2440 MHz) |                   |            |                     |               |                |                               |                                    |                   |                |
| 4880.00                   | 43.93             | PK         | 143                 | 1.4           | H              | 6.76                          | 50.69                              | 74                | 23.31          |
| 4880.00                   | 28.72             | Ave.       | 143                 | 1.4           | H              | 6.76                          | 35.48                              | 54                | 18.52          |
| High Channel (2480 MHz)   |                   |            |                     |               |                |                               |                                    |                   |                |
| 2354.84                   | 28.79             | PK         | 129                 | 2.2           | H              | 31.77                         | 60.56                              | 74                | 13.44          |
| 2354.84                   | 13.65             | Ave.       | 129                 | 2.2           | H              | 31.77                         | 45.42                              | 54                | 8.58           |
| 2489.17                   | 28.83             | PK         | 291                 | 2.1           | H              | 32.13                         | 60.96                              | 74                | 13.04          |
| 2489.17                   | 13.67             | Ave.       | 291                 | 2.1           | H              | 32.13                         | 45.80                              | 54                | 8.20           |
| 4960.00                   | 43.91             | PK         | 67                  | 1.4           | H              | 6.80                          | 50.71                              | 74                | 23.29          |
| 4960.00                   | 28.74             | Ave.       | 67                  | 1.4           | H              | 6.80                          | 35.54                              | 54                | 18.46          |

**BLE 2M:**

| Frequency<br>(MHz)        | Receiver          |            | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB/m) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|---------------------------|-------------------|------------|---------------------|---------------|----------------|-------------------------------|------------------------------------|-------------------|----------------|
|                           | Reading<br>(dBμV) | PK/QP/Ave. |                     | Height<br>(m) | Polar<br>(H/V) |                               |                                    |                   |                |
| Low Channel (2402 MHz)    |                   |            |                     |               |                |                               |                                    |                   |                |
| 2362.64                   | 28.71             | PK         | 316                 | 2.2           | H              | 31.87                         | 60.58                              | 74                | 13.42          |
| 2362.64                   | 13.69             | Ave.       | 316                 | 2.2           | H              | 31.87                         | 45.56                              | 54                | 8.44           |
| 2486.37                   | 28.79             | PK         | 136                 | 2.0           | H              | 32.13                         | 60.92                              | 74                | 13.08          |
| 2486.37                   | 13.73             | Ave.       | 136                 | 2.0           | H              | 32.13                         | 45.86                              | 54                | 8.14           |
| 4804.00                   | 43.88             | PK         | 114                 | 2.5           | H              | 6.28                          | 50.16                              | 74                | 23.84          |
| 4804.00                   | 28.72             | Ave.       | 114                 | 2.5           | H              | 6.28                          | 35.00                              | 54                | 19.00          |
| Middle Channel (2440 MHz) |                   |            |                     |               |                |                               |                                    |                   |                |
| 4880.00                   | 43.92             | PK         | 325                 | 1.3           | H              | 6.76                          | 50.68                              | 74                | 23.32          |
| 4880.00                   | 28.75             | Ave.       | 325                 | 1.3           | H              | 6.76                          | 35.51                              | 54                | 18.49          |
| High Channel (2480 MHz)   |                   |            |                     |               |                |                               |                                    |                   |                |
| 2342.24                   | 28.74             | PK         | 202                 | 1.1           | H              | 31.64                         | 60.38                              | 74                | 13.62          |
| 2342.24                   | 13.71             | Ave.       | 202                 | 1.1           | H              | 31.64                         | 45.35                              | 54                | 8.65           |
| 2488.34                   | 28.76             | PK         | 195                 | 2.3           | H              | 32.13                         | 60.89                              | 74                | 13.11          |
| 2488.34                   | 13.72             | Ave.       | 195                 | 2.3           | H              | 32.13                         | 45.85                              | 54                | 8.15           |
| 4960.00                   | 43.94             | PK         | 223                 | 1.3           | H              | 6.80                          | 50.74                              | 74                | 23.26          |
| 4960.00                   | 28.78             | Ave.       | 223                 | 1.3           | H              | 6.80                          | 35.58                              | 54                | 18.42          |

**1 GHz-25 GHz (Wi-Fi):****802.11b Mode:**

| Frequency<br>(MHz)        | Receiver          |            | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB/m) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|---------------------------|-------------------|------------|---------------------|---------------|----------------|-------------------------------|------------------------------------|-------------------|----------------|
|                           | Reading<br>(dBμV) | PK/QP/Ave. |                     | Height<br>(m) | Polar<br>(H/V) |                               |                                    |                   |                |
| Low Channel (2412 MHz)    |                   |            |                     |               |                |                               |                                    |                   |                |
| 2346.72                   | 28.78             | PK         | 39                  | 2.3           | H              | 31.64                         | 60.42                              | 74                | 13.58          |
| 2346.72                   | 13.72             | Ave.       | 39                  | 2.3           | H              | 31.64                         | 45.36                              | 54                | 8.64           |
| 2485.94                   | 28.76             | PK         | 320                 | 1.4           | H              | 32.13                         | 60.89                              | 74                | 13.11          |
| 2485.94                   | 13.71             | Ave.       | 320                 | 1.4           | H              | 32.13                         | 45.84                              | 54                | 8.16           |
| 4824.00                   | 45.21             | PK         | 261                 | 2.5           | H              | 6.28                          | 51.49                              | 74                | 22.51          |
| 4824.00                   | 32.59             | Ave.       | 261                 | 2.5           | H              | 6.28                          | 38.87                              | 54                | 15.13          |
| Middle Channel (2437 MHz) |                   |            |                     |               |                |                               |                                    |                   |                |
| 4874.00                   | 45.19             | PK         | 25                  | 1.7           | H              | 6.76                          | 51.95                              | 74                | 22.05          |
| 4874.00                   | 32.23             | Ave.       | 25                  | 1.7           | H              | 6.76                          | 38.99                              | 54                | 15.01          |
| High Channel (2462 MHz)   |                   |            |                     |               |                |                               |                                    |                   |                |
| 2338.64                   | 28.78             | PK         | 43                  | 2.0           | H              | 31.64                         | 60.42                              | 74                | 13.58          |
| 2338.64                   | 13.72             | Ave.       | 43                  | 2.0           | H              | 31.64                         | 45.36                              | 54                | 8.64           |
| 2484.34                   | 29.15             | PK         | 300                 | 1.0           | H              | 32.13                         | 61.28                              | 74                | 12.72          |
| 2484.34                   | 13.78             | Ave.       | 300                 | 1.0           | H              | 32.13                         | 45.91                              | 54                | 8.09           |
| 4924.00                   | 45.15             | PK         | 159                 | 2.1           | H              | 6.76                          | 51.91                              | 74                | 22.09          |
| 4924.00                   | 32.39             | Ave.       | 159                 | 2.1           | H              | 6.76                          | 39.15                              | 54                | 14.85          |

**802.11g Mode:**

| Frequency<br>(MHz)        | Receiver          |            | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB/m) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|---------------------------|-------------------|------------|---------------------|---------------|----------------|-------------------------------|------------------------------------|-------------------|----------------|
|                           | Reading<br>(dBμV) | PK/QP/Ave. |                     | Height<br>(m) | Polar<br>(H/V) |                               |                                    |                   |                |
| Low Channel (2412 MHz)    |                   |            |                     |               |                |                               |                                    |                   |                |
| 2348.35                   | 28.81             | PK         | 346                 | 2.2           | H              | 31.64                         | 60.45                              | 74                | 13.55          |
| 2348.35                   | 13.75             | Ave.       | 346                 | 2.2           | H              | 31.64                         | 45.39                              | 54                | 8.61           |
| 2489.22                   | 28.78             | PK         | 118                 | 2.2           | H              | 32.13                         | 60.91                              | 74                | 13.09          |
| 2489.22                   | 13.73             | Ave.       | 118                 | 2.2           | H              | 32.13                         | 45.86                              | 54                | 8.14           |
| 4824.00                   | 45.34             | PK         | 48                  | 1.9           | H              | 6.28                          | 51.62                              | 74                | 22.38          |
| 4824.00                   | 32.26             | Ave.       | 48                  | 1.9           | H              | 6.28                          | 38.54                              | 54                | 15.46          |
| Middle Channel (2437 MHz) |                   |            |                     |               |                |                               |                                    |                   |                |
| 4874.00                   | 45.27             | PK         | 271                 | 1.9           | H              | 6.76                          | 52.03                              | 74                | 21.97          |
| 4874.00                   | 32.22             | Ave.       | 271                 | 1.9           | H              | 6.76                          | 38.98                              | 54                | 15.02          |
| High Channel (2462 MHz)   |                   |            |                     |               |                |                               |                                    |                   |                |
| 2378.54                   | 28.83             | PK         | 358                 | 2.3           | H              | 31.87                         | 60.70                              | 74                | 13.30          |
| 2378.54                   | 13.74             | Ave.       | 358                 | 2.3           | H              | 31.87                         | 45.61                              | 54                | 8.39           |
| 2485.12                   | 29.22             | PK         | 251                 | 1.4           | H              | 32.13                         | 61.35                              | 74                | 12.65          |
| 2485.12                   | 13.79             | Ave.       | 251                 | 1.4           | H              | 32.13                         | 45.92                              | 54                | 8.08           |
| 4924.00                   | 45.23             | PK         | 177                 | 2.3           | H              | 6.76                          | 51.99                              | 74                | 22.01          |
| 4924.00                   | 32.21             | Ave.       | 177                 | 2.3           | H              | 6.76                          | 38.97                              | 54                | 15.03          |

**802.11n-HT20 Mode:**

| Frequency<br>(MHz)        | Receiver          |            | Turntable<br>Degree | Rx Antenna    |                | Corrected<br>Factor<br>(dB/m) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|---------------------------|-------------------|------------|---------------------|---------------|----------------|-------------------------------|------------------------------------|-------------------|----------------|
|                           | Reading<br>(dBμV) | PK/QP/Ave. |                     | Height<br>(m) | Polar<br>(H/V) |                               |                                    |                   |                |
| Low Channel (2412 MHz)    |                   |            |                     |               |                |                               |                                    |                   |                |
| 2362.76                   | 28.82             | PK         | 22                  | 2.0           | H              | 31.87                         | 60.69                              | 74                | 13.31          |
| 2362.76                   | 13.74             | Ave.       | 22                  | 2.0           | H              | 31.87                         | 45.61                              | 54                | 8.39           |
| 2493.63                   | 28.79             | PK         | 323                 | 2.0           | H              | 32.13                         | 60.92                              | 74                | 13.08          |
| 2493.63                   | 13.72             | Ave.       | 323                 | 2.0           | H              | 32.13                         | 45.85                              | 54                | 8.15           |
| 4824.00                   | 45.23             | PK         | 322                 | 1.7           | H              | 6.28                          | 51.51                              | 74                | 22.49          |
| 4824.00                   | 32.16             | Ave.       | 322                 | 1.7           | H              | 6.28                          | 38.44                              | 54                | 15.56          |
| Middle Channel (2437 MHz) |                   |            |                     |               |                |                               |                                    |                   |                |
| 4874.00                   | 45.18             | PK         | 91                  | 2.0           | H              | 6.76                          | 51.94                              | 74                | 22.06          |
| 4874.00                   | 32.12             | Ave.       | 91                  | 2.0           | H              | 6.76                          | 38.88                              | 54                | 15.12          |
| High Channel (2462 MHz)   |                   |            |                     |               |                |                               |                                    |                   |                |
| 2355.36                   | 28.78             | PK         | 346                 | 2.4           | H              | 31.77                         | 60.55                              | 74                | 13.45          |
| 2355.36                   | 13.75             | Ave.       | 346                 | 2.4           | H              | 31.77                         | 45.52                              | 54                | 8.48           |
| 2485.23                   | 28.94             | PK         | 58                  | 1.8           | H              | 32.13                         | 61.07                              | 74                | 12.93          |
| 2485.23                   | 13.79             | Ave.       | 58                  | 1.8           | H              | 32.13                         | 45.92                              | 54                | 8.08           |
| 4924.00                   | 45.11             | PK         | 133                 | 2.3           | H              | 6.76                          | 51.87                              | 74                | 22.13          |
| 4924.00                   | 31.92             | Ave.       | 133                 | 2.3           | H              | 6.76                          | 38.68                              | 54                | 15.32          |



**Note:**

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor



Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude



The other spurious emission which is 20dB to the limit was not recorded.

**Pre-scan with 802.11b Mode, High channel  
Horizontal**



# Vertical



# Pre-scan for Average Horizontal



# Vertical




## FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

### Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 27.9 °C   |
| Relative Humidity: | 59 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Thea Xiao from 2020-09-21 to 2020-09-23.*

*EUT operation mode: Transmitting*

Test Result Compliant. Please refer to the Appendix BLE & Appendix Wi-Fi.


## FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

### Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 27.9 °C   |
| Relative Humidity: | 59 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Thea Xiao from 2020-09-21 to 2020-09-23.*

*EUT operation mode: Transmitting*


Test Result Compliant. Please refer to the Appendix BLE & Appendix Wi-Fi.

**FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE****Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

**Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

**Test Data****Environmental Conditions**

|                    |           |
|--------------------|-----------|
| Temperature:       | 27.9 °C   |
| Relative Humidity: | 59 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Thea Xiao from 2020-09-21 to 2020-09-23.*

*EUT operation mode: Transmitting*

Test Result Compliant. Please refer to the Appendix BLE & Appendix Wi-Fi.


## FCC §15.247(e) - POWER SPECTRAL DENSITY

### Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to:  $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
3. Set the VBW  $\geq 3 \times \text{RBW}$ .
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 27.9 °C   |
| Relative Humidity: | 59 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Thea Xiao from 2020-09-21 to 2020-09-23.*

*EUT operation mode: Transmitting*


Test Result Compliant. Please refer to the Appendix BLE & Appendix Wi-Fi.


## APPENDIX BLE

### Appendix A: DTS Bandwidth Test Result

| Test Mode | Antenna | Channel | DTS BW [MHz] | Limit[MHz] | Verdict |
|-----------|---------|---------|--------------|------------|---------|
| BLE_1M    | Ant1    | 2402    | 0.516        | 0.5        | PASS    |
|           |         | 2440    | 0.512        | 0.5        | PASS    |
|           |         | 2480    | 0.516        | 0.5        | PASS    |
| BLE_2M    | Ant1    | 2402    | 0.876        | 0.5        | PASS    |
|           |         | 2440    | 0.872        | 0.5        | PASS    |
|           |         | 2480    | 0.872        | 0.5        | PASS    |

## Test Graphs






**Appendix B: Maximum conducted Peak output power****Test Result**


| Test Mode | Antenna | Channel | Result[dBm] | Limit[dBm] | Verdict |
|-----------|---------|---------|-------------|------------|---------|
| BLE_1M    | Ant1    | 2402    | 3.51        | <=30       | PASS    |
|           |         | 2440    | 3.82        | <=30       | PASS    |
|           |         | 2480    | 3.13        | <=30       | PASS    |
| BLE_2M    | Ant1    | 2402    | 3.56        | <=30       | PASS    |
|           |         | 2440    | 3.89        | <=30       | PASS    |
|           |         | 2480    | 3.75        | <=30       | PASS    |

**Appendix C: Maximum power spectral density  
Test Result**


| Test Mode | Antenna | Channel | Result[dBm/3kHz] | Limit[dBm/3kHz] | Verdict |
|-----------|---------|---------|------------------|-----------------|---------|
| BLE_1M    | Ant1    | 2402    | -14.77           | <=8             | PASS    |
|           |         | 2440    | -13.74           | <=8             | PASS    |
|           |         | 2480    | -14.74           | <=8             | PASS    |
| BLE_2M    | Ant1    | 2402    | -20.1            | <=8             | PASS    |
|           |         | 2440    | -19.08           | <=8             | PASS    |
|           |         | 2480    | -19.79           | <=8             | PASS    |


## Test Graphs





## Appendix D: Band edge measurements Test Graphs






# Appendix E: Duty Cycle Test Result

| Test Mode | Antenna | Channel | Transmission Duration [ms] | Transmission Period [ms] | Duty Cycle [%] |
|-----------|---------|---------|----------------------------|--------------------------|----------------|
| BLE_1M    | Ant1    | 2440    | 0.09                       | 0.63                     | 15.20          |
| BLE_2M    | Ant1    | 2440    | 0.05                       | 0.63                     | 8.80           |

## Test Graphs




## APPENDIX Wi-Fi


### Appendix A: DTS Bandwidth Test Result

| Test Mode | Antenna | Channel | DTS BW [MHz] | Limit[MHz] | Verdict |
|-----------|---------|---------|--------------|------------|---------|
| 11B       | Ant1    | 2412    | 8.160        | 0.5        | PASS    |
|           |         | 2437    | 9.120        | 0.5        | PASS    |
|           |         | 2462    | 8.080        | 0.5        | PASS    |
| 11G       | Ant1    | 2412    | 16.480       | 0.5        | PASS    |
|           |         | 2437    | 16.480       | 0.5        | PASS    |
|           |         | 2462    | 16.440       | 0.5        | PASS    |
| 11N20SISO | Ant1    | 2412    | 17.400       | 0.5        | PASS    |
|           |         | 2437    | 17.680       | 0.5        | PASS    |
|           |         | 2462    | 17.680       | 0.5        | PASS    |

## Test Graphs




## 11G\_Ant1\_2412




Date: 21.SEP.2020 21:54:40

## 11G\_Ant1\_2437




Date: 23.SEP.2020 01:36:32

## 11G\_Ant1\_2462




Date: 23.SEP.2020 01:14:47


## 11N20SISO Ant1 2412



## 11N20SISO Ant1 2437



## 11N20SISO Ant1 2462




**Appendix B: Maximum conducted output power (AV)  
Test Result**

| Test Mode | Antenna | Channel | Result[dBm] | Limit[dBm] | Verdict |
|-----------|---------|---------|-------------|------------|---------|
| 11B       | Ant1    | 2412    | 9.37        | <=30       | PASS    |
|           |         | 2437    | 8.17        | <=30       | PASS    |
|           |         | 2462    | 9.14        | <=30       | PASS    |
| 11G       | Ant1    | 2412    | 9.17        | <=30       | PASS    |
|           |         | 2437    | 8.81        | <=30       | PASS    |
|           |         | 2462    | 9.44        | <=30       | PASS    |
| 11N20SISO | Ant1    | 2412    | 9.13        | <=30       | PASS    |
|           |         | 2437    | 8.93        | <=30       | PASS    |
|           |         | 2462    | 8.60        | <=30       | PASS    |


**Appendix C: Maximum power spectral density  
Test Result**

| Test Mode | Antenna | Channel | Result[dBm/3kHz] | Limit[dBm/3kHz] | Verdict |
|-----------|---------|---------|------------------|-----------------|---------|
| 11B       | Ant1    | 2412    | -9.25            | <=8             | PASS    |
|           |         | 2437    | -10.71           | <=8             | PASS    |
|           |         | 2462    | -9.79            | <=8             | PASS    |
| 11G       | Ant1    | 2412    | -14.95           | <=8             | PASS    |
|           |         | 2437    | -18.67           | <=8             | PASS    |
|           |         | 2462    | -18.21           | <=8             | PASS    |
| 11N20SISO | Ant1    | 2412    | -15.61           | <=8             | PASS    |
|           |         | 2437    | -17.82           | <=8             | PASS    |
|           |         | 2462    | -18.35           | <=8             | PASS    |


## Test Graphs




11G\_Ant1\_2412




11G\_Ant1\_2437




11G\_Ant1\_2462




## 11N20SISO Ant1 2412



## 11N20SISO Ant1 2437




## 11N20SISO Ant1 2462




## Appendix D: Band edge measurements Test Graphs

11B\_Ant1\_Low\_2412




Date: 21.SEP.2020 21:42:59

11B\_Ant1\_High\_2462



Date: 21.SEP.2020 21:48:24

11G\_Ant1\_Low\_2412




Date: 21.SEP.2020 21:55:29

## 11G Ant1\_High\_2462



Date: 23.SEP.2020 01:15:33

## 11N20SISO\_Ant1\_Low\_2412



Date: 21.SEP.2020 22:03:20

## 11N20SISO\_Ant1\_High\_2462





Date: 23.SEP.2020 02:09:58

## Appendix E: Duty Cycle Test Result

| Test Mode | Antenna | Channel | Transmission Duration [ms] | Transmission Period [ms] | Duty Cycle [%] |
|-----------|---------|---------|----------------------------|--------------------------|----------------|
| 11B       | Ant1    | 2437    | 4.28                       | 4.42                     | 96.83          |
| 11G       | Ant1    | 2437    | 1.38                       | 1.52                     | 90.79          |
| 11N20SISO | Ant1    | 2437    | 1.29                       | 1.43                     | 90.21          |

## Test Graphs





\*\*\*\*\* END OF REPORT \*\*\*\*\*