

# TEST REPORT

Applicant Name: Shenzhen VanTop Technology & Innovation Co., Ltd.  
Address: 506, BLDG 4, Pingshan minQi Technology Park, No. 65 Lishan Road, Pingshan Community, Taoyuan Street, Nanshan District, Shenzhen, China  
Report Number: 2501R26990E-RF-00D  
FCC ID: 2AQ3A-VT15

**Test Standard (s)**


FCC PART 15.407

**Sample Description**


Product Type: Projector  
Model No.: V702P  
Multiple Model(s) No.: M/A  
Trade Mark: N/A  
Date Received: 2025-03-07  
Issue Date: 2025-05-30

Test Result:	Pass▲
--------------	-------

▲ In the configuration tested, the EUT complied with the standards above.

**Prepared and Checked By:**

Allen Bai  
RF Engineer

**Approved By:**

Nancy Wang  
RF Supervisor

Note: The information marked\* is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

**Bay Area Compliance Laboratories Corp. (Shenzhen)**

5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China  
Tel: +86-755-33320018 Fax: +86-755-33320008 [www.baclcorp.com.cn](http://www.baclcorp.com.cn)

## **TABLE OF CONTENTS**

<b>DOCUMENT REVISION HISTORY .....</b>	<b>3</b>
<b>GENERAL INFORMATION .....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE .....	4
TEST METHODOLOGY.....	4
MEASUREMENT UNCERTAINTY .....	5
TEST FACILITY .....	5
<b>SYSTEM TEST CONFIGURATION .....</b>	<b>6</b>
<b>SUMMARY OF TEST RESULTS .....</b>	<b>10</b>
<b>TEST EQUIPMENT LIST .....</b>	<b>11</b>
<b>REQUIREMENTS AND TEST PROCEDURES .....</b>	<b>12</b>
CONDUCTED EMISSIONS.....	12
UNDESIRABLE EMISSION.....	14
26 dB & 6dB EMISSION BANDWIDTH .....	18
CONDUCTED TRANSMITTER OUTPUT POWER.....	20
POWER SPECTRAL DENSITY .....	21
DUTY CYCLE.....	22
<b>ANTENNA REQUIREMENT .....</b>	<b>23</b>
<b>TEST DATA AND RESULTS .....</b>	<b>24</b>
CONDUCTED EMISSIONS.....	24
UNDESIRABLE EMISSION.....	27
RF CONDUCTED DATA .....	161
EMISSION BANDWIDTH .....	161
99% OCCUPIED BANDWIDTH .....	170
MAXIMUM CONDUCTED OUTPUT POWER .....	179
POWER SPECTRAL DENSITY .....	182
DUTY CYCLE.....	191
<b>RF EXPOSURE EVALUATION .....</b>	<b>193</b>
<b>EUT PHOTOGRAPHS .....</b>	<b>195</b>
<b>TEST SETUP PHOTOGRAPHS .....</b>	<b>196</b>

**DOCUMENT REVISION HISTORY**

Revision Number	Report Number	Description of Revision	Date of Revision
0	2501R26990E-RF-00D	Original Report	2025-05-30

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

<b>Frequency Range</b>	5150-5250MHz; 5725-5850MHz
<b>Mode</b>	802.11a/n20/n40/ac20/ac40/ac80
<b>Device Type</b>	Client
<b>Maximum Conducted Average Output Power</b>	5150-5250MHz: 16.80dBm; 5725-5850MHz: 17.60dBm
<b>Modulation Technique</b>	OFDM
<b>Antenna Specification<sup>#</sup></b>	5150-5250MHz:ANT0=1.07dBi,ANT1=1.07dBi 5725-5850MHz:ANT0=1.13dBi,ANT1=0.87dBi (provided by the applicant)
<b>Voltage Range</b>	DC 35V from adapter
<b>Sample serial number</b>	2ZEA-5 for Conducted and Radiated Emissions Test 2ZEA-9 for RF Conducted Test (Assigned by BACL, Shenzhen)
<b>Sample/EUT Status</b>	Good condition
<b>Adapter Information</b>	Model:SOY-3500428-454 Input:100-240V~50/60Hz 2.5A Max Output:35.0V=4.28A 149.8W

### Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and E of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

## Measurement Uncertainty

Parameter	Uncertainty	
Occupied Channel Bandwidth	109.2kHz(k=2, 95% level of confidence)	
RF Frequency	56.6Hz(k=2, 95% level of confidence)	
RF output power, conducted	0.86dB(k=2, 95% level of confidence)	
Unwanted Emission, conducted	1.60dB(k=2, 95% level of confidence)	
Power Spectral Density	0.90dB(k=2, 95% level of confidence)	
AC Power Lines Conducted Emissions	9kHz-150kHz	3.63dB(k=2, 95% level of confidence)
	150kHz-30MHz	3.66dB(k=2, 95% level of confidence)
Radiated Emissions	9kHz - 30MHz	3.60dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)	5.32dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)	5.43dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Horizontal)	5.77dB(k=2, 95% level of confidence)
	200MHz~1000MHz (Vertical)	5.73dB(k=2, 95% level of confidence)
	1GHz - 6GHz	5.34dB(k=2, 95% level of confidence)
	6GHz - 18GHz	5.40dB(k=2, 95% level of confidence)
	18GHz - 40GHz	5.64dB(k=2, 95% level of confidence)
Temperature	±1°C	
Humidity	±1%	
Supply voltages	±0.4%	

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer.

For 5150-5250MHz Band, 7 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220
38	5190	46	5230
40	5200	48	5240
42	5210	/	/

For 802.11a/ac20 mode: channel 36, 40, 48 were tested;

For 802.11ac40 mode: channel 38, 46 were tested;

For 802.11ac80 mode, channel 42 was tested.

For 5725-5850MHz Band, 8 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	157	5785
151	5755	159	5795
153	5765	161	5805
155	5775	165	5825

For 802.11a/ac20 mode: channel 149, 157, 165 were tested;

For 802.11ac40 mode: channel 151, 159 were tested;

For 802.11ac80 mode, channel 155 was tested.

### EUT Exercise Software

Exercise Software <sup>#</sup>	cmd.exe			
5150-5250 MHz Band				
Mode	Test Channels	Data rate	Power Level <sup>#</sup>	
			ANT 0	ANT 1
802.11a	Low	6Mbps	14	14
	Middle	6Mbps	14	14
	High	6Mbps	14	14
802.11ac-VHT20	Low	MCS0	13	13
	Middle	MCS0	13	13
	High	MCS0	13	13
802.11ac-VHT40	Low	MCS0	14	14
	High	MCS0	14	14
802.11ac-VHT80	Middle	MCS0	11	11

5725-5850 MHz Band				
Mode	Test Channels	Data rate	Power Level <sup>#</sup>	
			ANT 0	ANT 1
802.11a	Low	6Mbps	14	14
	Middle	6Mbps	14	14
	High	6Mbps	14	14
802.11ac-VHT20	Low	MCS0	13	13
	Middle	MCS0	13	13
	High	MCS0	13	13
802.11ac-VHT40	Low	MCS0	14	14
	High	MCS0	14	14
802.11ac-VHT80	Middle	MCS0	14	14

Note:

1. The worst-case data rates are determined to be as follows for each mode based upon investigation by measuring the power and PSD across all data rates bandwidths, and modulations.
2. The device supports SISO in all modes, and MIMO 2T2R in 802.11n/ac modes, per pretest, 2T2R mode was the worst mode and reported for 802.11n/ac modes.
3. The n20/n40 mode was reduced test as identical parameter with ac20/ac40 mode.

### Special Accessories

No special accessory.

### Equipment Modifications

No modification was made to the EUT tested.

### Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
OUPU	Receptacle	PDU-OP1606K	6971041358020
Sandisk	USB disk	CZ73-64G	Unknown
Vivo	Earphone1	XE160	Unknown
CRDC	Earphone 2	YXEJ-01Z	Unknown
DELL	Notebook	Latitude 7280	B0CB5M2

### External I/O Cable


Cable Description	Length (m)	From Port	To
Unshielded Un-detachable AC Cable	1.5	Receptacle	AC Mains
Unshielded Detachable AC Cable	1.5	Adapter	Receptacle/AC Mains/LISN
Shielded Un-detachable DC Cable	1.2	EUT	Adapter
Unshielded un-detachable Audio Cable	1.0	EUT	Earphone1
Unshielded un-detachable Audio Cable	1.2	EUT	Earphone2
Unshielded detachable HDMI Cable	1.8	EUT	Notebook

## Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions below 1GHz:



For Radiated Emissions above 1GHz:



## SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307 (b) & §2.1091	MPE-Based Exemption	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	Conducted Emissions	Compliant
§15.205& §15.209 &§15.407(b)	Undesirable Emission& Restricted Bands	Compliant
§15.407(a) (e)	26 dB Emission Bandwidth & 6dB Bandwidth	Compliant
§15.407(a)	Conducted Transmitter Output Power	Compliant
§15.407 (a)	Power Spectral Density	Compliant
§15.407 (h)	Transmit Power Control (TPC)	Not Applicable
§15.407 (h)	Dynamic Frequency Selection (DFS)	Not Applicable
C63.10 §11.6	Duty Cycle	/

Not Applicable: The EUT is support 5150-5250MHz/5725-5850MHz only.

## TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
<b>Conducted Emission Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2024/12/04	2025/12/03
Rohde & Schwarz	LISN	ENV216	101613	2024/12/04	2025/12/03
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2024/05/21	2025/05/20
Unknown	CE Cable	Unknown	UF A210B-1-0720-504504	2024/05/21	2025/05/20
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
<b>Radiated Emission Test</b>					
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2024/12/04	2025/12/03
Sonoma instrument	Pre-amplifier	310N	186238	2024/05/21	2025/05/20
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
Unknown	Cable	XH500C	J-10M-A	2024/06/18	2025/06/17
BACL	Active Loop Antenna	1313-1A	4031911	2024/05/14	2027/05/13
Unknown	Cable	2Y194	0735	2024/12/04	2025/12/03
Unknown	Cable	PNG214	1354	2024/12/04	2025/12/03
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
Rohde&Schwarz	Spectrum Analyzer	FSV40	101605	2025/03/26	2026/03/25
A.H.System	Preamplifier	PAM-0118P	489	2024/11/15	2025/11/14
Schwarzbeck	Horn Antenna	BBHA9120D (1201)	1143	2023/07/26	2026/07/25
Unknown	RF Cable	KMSE	0735	2024/12/06	2025/12/05
Unknown	RF Cable	UFA147	219661	2024/12/06	2025/12/05
Unknown	RF Cable	XH750A-N	J-10M	2024/12/06	2025/12/05
JD	Filter Switch Unit	DT7220FSU	DS79906	2024/09/09	2025/09/08
JD	Multiplex Switch Test Control Set	DT7220SCU	DS79903	2024/09/09	2025/09/08
A.H.System	Pre-amplifier	PAM-1840VH	190	2024/06/18	2025/06/17
Electro-Mechanics Co	Horn Antenna	3116	9510-2270	2023/09/18	2026/09/17
UTIFLEX	RF Cable	NO. 13	232308-001	2024/12/18	2025/12/17
Audix	EMI Test software	E3	191218(V9)	NCR	NCR
<b>RF Conducted Test</b>					
Rohde&Schwarz	Spectrum Analyzer	FSV40-N	102259	2024/12/04	2025/12/03
ANRITSU	Microwave peak	MA24418A	12622	2024/05/21	2025/05/20
Unknown	10dB Attenuator	Unknown	F-03-EM190	2024/06/27	2025/06/26

**\* Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).


## REQUIREMENTS AND TEST PROCEDURES

### Conducted Emissions

#### Applicable Standard

FCC §15.207

#### EUT Setup



**Note:** 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

#### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW
150 kHz – 30 MHz	9 kHz

#### Test Procedure

During the conducted emission test, the adapter was connected to the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and Average detection mode.

## Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\text{Over Limit} = \text{Level} - \text{Limit}$$

$$\text{Level} = \text{Read Level} + \text{Factor}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).

## Undesirable Emission

### Applicable Standard

FCC §15.407 (b); §15.209; §15.205;


(b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:



- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band:
  - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209.

### EUT Setup

#### 9 kHz-30MHz:



**30MHz-1GHz:****Above 1 GHz:**

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC 15.209 and FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

## EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9 kHz-1GHz:

Frequency Range	RBW	Video B/W	IF B/W	Measurement	Detector
9 kHz – 150 kHz	/	/	200 Hz	QP	QP
	300 Hz	1 kHz	/	PK	Peak
150 kHz – 30 MHz	/	/	9 kHz	QP	QP
	10 kHz	30 kHz	/	PK	Peak
30 MHz – 1000 MHz	/	/	120 kHz	QP	QP
	100 kHz	300 kHz	/	PK	Peak

1-40GHz:

Pre-scan

Measurement	Duty cycle	RBW	Video B/W	Detector
PK	Any	1MHz	3 MHz	Peak
AV	>98%	1MHz	1 kHz	Peak
	<98%	1MHz	≥1/Ton	Peak

Final measurement for emission identified during pre-scan

Measurement	Duty cycle	RBW	Video B/W	Detector
PK	Any	1MHz	3 MHz	Peak
AV	>98%	1MHz	10 Hz	Peak
	<98%	1MHz	≥1/Ton	Peak

Note: Ton is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

## Test Procedure

### Radiated Spurious Emission

During the radiated emission test, the adapter was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all the installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

According to ANSI C63.10-2020,9.2.1: For field strength measurements made at other than the distance specified by the limit, extrapolate the measured field strength to the field strength at the distance specified by the limit using an inverse distance correction factor (20 dB/decade of distance)

$$E_{\text{SpecLimit}} = E_{\text{Meas}} + 20 \log \left( \frac{d_{\text{Meas}}}{d_{\text{SpecLimit}}} \right)$$

where

$E_{\text{SpecLimit}}$  is the field strength of the emission at the distance specified by the limit, in dB $\mu$ V/m

$E_{\text{Meas}}$  is the field strength of the emission at the measurement distance, in dB $\mu$ V/m

$d_{\text{Meas}}$  is the measurement distance, in m

$d_{\text{SpecLimit}}$  is the distance specified by the limit, in m

So the extrapolation factor of 1m is  $20 * \log(1.5/3) = -6.0$  dB, for 18-40GHz range, the limit of 1.5m distance was added by 6.0dB from limit of 3m to compared with the result measurement at 1.5m distance.

## Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Over Limit/Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit} &= \text{Level} - \text{Limit}; \text{Margin} = \text{Limit} - \text{Corrected Amplitude} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

## 26 dB & 6dB Emission Bandwidth

### Applicable Standard

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

### Test Procedure

According to ANSI C63.10-2020 Section 12.5.1 & 12.5.2 & 12.5.3

#### 12.5.1 Emission bandwidth for the band 5.725 GHz to 5.85 GHz

The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max-hold.
- e) Sweep = No faster than coupled (auto) time.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### 12.5.2 Emission bandwidth for all other bands

The procedure for this method is as follows:


- a) Set RBW = shall be in the range of 1% to 5% of the emission bandwidth.
- b) Set the VBW  $>$  RBW.
- c) Detector = peak.
- d) Trace mode = max-hold.
- e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the instrument. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is in the range of 1% to 5%.

### 12.5.3 Occupied bandwidth

See 6.9.3 for the measurement procedure for OBW.

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:

- a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be at least three times the RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than  $[10 \log (\text{OBW}/\text{RBW})]$  below the reference level. Specific guidance is given in 4.1.6.2.
- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max-hold mode (until the trace stabilizes) shall be used.
- f) Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- g) If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- h) The occupied bandwidth shall be reported by providing spectral plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).



## Conducted Transmitter Output Power

### Applicable Standard

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

### Test Procedure

According to ANSI C63.10-2020 Section 12.4.3.2 Method PM-G

- a. Place the EUT on a bench and set it in transmitting mode.
- b. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.



Note: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was add with offset into test equipment, the total offset consists of attenuator and/or RF cable and/or power splitter loss

## Power Spectral Density


For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

## Test Procedure

According to ANSI C63.10-2020 Clause 12.6 Method SA-2 should be applied



Note: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was add with offset into test equipment, the total offset consists of attenuator and/or RF cable and/or power splitter loss


## Duty Cycle

### Test Procedure

According to ANSI C63.10-2020 Section 12.2

Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

- a) A diode detector and an oscilloscope that together have a sufficiently short response time to permit accurate measurements of the ON and OFF times of the transmitted signal.
- b) The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:
  - 1) Set the center frequency of the instrument to the center frequency of the transmission.
  - 2) Set  $RBW \geq OBW$  if possible; otherwise, set  $RBW$  to the largest available value.
  - 3) Set  $VBW \geq RBW$ . Set detector = peak or average.
  - 4) The zero-span measurement method shall not be used unless both  $RBW$  and  $VBW$  are  $> 50/T$  and the number of sweep points across duration  $T$  exceeds 100. (For example, if  $VBW$  and/or  $RBW$  are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if  $T \leq 16.7 \mu s$ .)



## **ANTENNA REQUIREMENT**

### **Applicable Standard**

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

### **Antenna Connector Construction**

The EUT has two internal antennas arrangement, which were permanently attached, , fulfill the requirement of this section. Please refer to the EUT photos.

<b>Antenna</b>	<b>Antenna Type</b>	<b>Antenna Gain<sup>#</sup></b>	<b>Impedance</b>	<b>Frequency Range</b>
ANT0	FPC	1.07dBi	50Ω	5150-5250MHz
ANT1	FPC	1.07dBi	50Ω	
ANT0	FPC	1.13dBi	50Ω	5725-5850MHz
ANT1	FPC	0.87dBi	50Ω	


**Result: Compliant**

## TEST DATA AND RESULTS

### Conducted Emissions

Temperature (°C)	24.7	Relative Humidity (%)	62
ATM Pressure (kPa)	100.7	Test engineer	Macy.shi
Test date	2025.4.9		
EUT operation mode	Transmitting(Maximum output power mode, 802.11ac-VHT20 5825MHz)		

AC 120V 60 Hz, Line



Condition: Line


Project : 2501R26990E-RF

tester : Macy.shi Note:Transmitting

Setting : RBW:9kHz

Freq	Read		LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV					
1	0.160	-0.78	19.47	10.13	10.12	55.47	-36.00 Average
2	0.160	16.23	36.48	10.13	10.12	65.47	-28.99 QP
3	0.237	13.49	33.58	10.01	10.08	52.22	-18.64 Average
4	0.237	24.04	44.13	10.01	10.08	62.22	-18.09 QP
5	0.358	10.23	30.63	10.28	10.12	48.78	-18.15 Average
6	0.358	21.84	42.24	10.28	10.12	58.78	-16.54 QP
7	0.582	2.19	22.90	10.59	10.12	46.00	-23.10 Average
8	0.582	17.11	37.82	10.59	10.12	56.00	-18.18 QP
9	2.594	6.30	26.66	10.19	10.17	46.00	-19.34 Average
10	2.594	17.40	37.76	10.19	10.17	56.00	-18.24 QP
11	3.207	4.76	25.05	10.10	10.19	46.00	-20.95 Average
12	3.207	14.87	35.16	10.10	10.19	56.00	-20.84 QP

AC 120V 60 Hz, Neutral




Freq	Read	LISN	Cable	Limit	Over	Remark
	MHz	dBuV	dBuV	dB	dB	
1	0.152	0.72	21.14	10.29	10.13	55.91 -34.77 Average
2	0.152	17.81	38.23	10.29	10.13	65.91 -27.68 QP
3	0.215	7.86	28.09	10.14	10.09	53.01 -24.92 Average
4	0.215	20.24	40.47	10.14	10.09	63.01 -22.54 QP
5	0.433	4.45	25.08	10.52	10.11	47.20 -22.12 Average
6	0.433	19.96	40.59	10.52	10.11	57.20 -16.61 QP
7	0.546	3.02	23.72	10.57	10.13	46.00 -22.28 Average
8	0.546	15.68	36.38	10.57	10.13	56.00 -19.62 QP
9	3.922	6.29	26.61	10.11	10.21	46.00 -19.39 Average
10	3.922	16.14	36.46	10.11	10.21	56.00 -19.54 QP
11	5.805	3.46	24.07	10.43	10.18	50.00 -25.93 Average
12	5.805	15.11	35.72	10.43	10.18	60.00 -24.28 QP

## Undesirable Emission

<b>Temperature (°C)</b>	23.2~24.5	<b>Relative Humidity (%)</b>	45.1~50.1
<b>ATM Pressure (kPa):</b>	101.2	<b>Test engineer:</b>	Anson Su& Zenos Qiao
<b>Test date:</b>	2025/04/10~2025/04/15		
<b>EUT operation mode:</b>	Below 1GHz:Transmitting(Maximum output power mode, 802.11ac20 5825MHz) Above 1GHz: Transmitting		
<b>Note:</b>	1. For the radiated spurious emission below 30MHz, only the worst case (parallel) was recorded. 2. When the test result of peak was less than the limit of QP/Average more than 6dB, just peak value were recorded.		

**Below 1GHz:**


9kHz-150kHz\_ANT0



Site : Chamber A  
 Condition : 3m  
 Project Number : 2501R26990E-RF  
 Test Mode : 5G WIFI Transmitting  
 Detector: Peak RBW/VBW: 0.3/1kHz  
 Tester : Anson Su

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB
1	0.01	32.26	23.90	56.16	127.44	-71.28	Peak
2	0.02	30.68	22.01	52.69	122.26	-69.57	Peak
3	0.03	28.30	20.82	49.12	117.52	-68.40	Peak
4	0.06	25.63	26.08	51.71	112.39	-60.68	Peak
5	0.10	21.76	28.92	50.68	107.26	-56.58	Peak
6	0.11	21.23	36.38	57.61	106.54	-48.93	Peak


## 150kHz-30MHz\_ANT0



Site : Chamber A  
Condition : 3m  
Project Number : 2501R26990E-RF  
Test Mode : 5G WIFI Transmitting  
Detector: Peak RBW/VBW: 10/30kHz  
Tester : Anson Su

Freq	Factor	Read	Limit	Over	Remark
		Level	Level	Line	
1	0.62	4.89	36.35	41.24	71.68 -30.44 Peak
2	0.74	3.49	35.52	39.01	70.19 -31.18 Peak
3	0.94	1.66	35.92	37.58	68.04 -30.46 Peak
4	1.07	0.99	37.35	38.34	66.84 -28.50 Peak
5	1.15	0.78	43.53	44.31	66.24 -21.93 Peak
6	1.36	0.20	39.09	39.29	64.77 -25.48 Peak


## 30MHz-1GHz\_Horizontal\_ANT0



Site : Chamber A  
Condition : 3m Horizontal  
Project Number : 2501R26990E-RF  
Test Mode : 5G WIFI Transmitting  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Anson Su

Freq	Factor	Read	Limit	Over	Remark	
		Level	Level	Line		
		MHz	dB/m	dBuV	dBuV/m	dB
1	130.15	-11.23	50.21	38.98	43.50	-4.52 QP
2	131.99	-11.30	47.89	36.59	43.50	-6.91 QP
3	327.74	-10.67	51.03	40.36	46.00	-5.64 QP
4	335.74	-10.52	52.95	42.43	46.00	-3.57 QP
5	342.13	-10.36	51.30	40.94	46.00	-5.06 QP
6	378.58	-9.19	47.10	37.91	46.00	-8.09 QP


## 30MHz-1GHz\_Vertical\_ANT0



Site : Chamber A  
Condition : 3m Vertical  
Project Number : 2501R26990E-RF  
Test Mode : 5G WIFI Transmitting  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Anson Su

Freq	Factor	Read	Limit	Over	Remark	
		Level	Level	Line		
		MHz	dB/m	dBuV	dBuV/m	dB
1	31.07	-6.51	33.52	27.01	40.00	-12.99 Peak
2	61.83	-18.11	45.13	27.02	40.00	-12.98 Peak
3	130.61	-11.27	47.96	36.69	43.50	-6.81 Peak
4	335.45	-10.52	46.83	36.31	46.00	-9.69 Peak
5	458.51	-7.16	44.09	36.93	46.00	-9.07 Peak
6	500.96	-5.76	43.99	38.23	46.00	-7.77 Peak


## 9kHz-150kHz\_ANT1



Site : Chamber A  
Condition : 3m  
Project Number : 2501R26990E-RF  
Test Mode : 5G WIFI Transmitting  
Detector: Peak RBW/VBW: 0.3/1kHz  
Tester : Anson Su

Freq	Factor	Read		Limit		Over	Remark
		Level	Level	Line	Line		
1	0.01	32.08	24.38	56.46	126.67	-70.21	Peak
2	0.02	29.89	21.28	51.17	120.50	-69.33	Peak
3	0.06	25.63	25.30	50.93	112.38	-61.45	Peak
4	0.10	21.73	29.37	51.10	107.22	-56.12	Peak
5	0.11	21.23	37.72	58.95	106.54	-47.59	Peak
6	0.14	19.43	17.09	36.52	104.46	-67.94	Peak


## 150kHz-30MHz\_ANT1



Site : Chamber A  
Condition : 3m  
Project Number : 2501R26990E-RF  
Test Mode : 5G WIFI Transmitting  
Detector: Peak RBW/VBW: 10/30kHz  
Tester : Anson Su

Freq	Factor	Read	Limit	Over	Remark
		Level	Level	Line	
1	0.23	14.22	40.30	54.52	100.30 -45.78 Peak
2	0.57	5.51	36.55	42.06	72.43 -30.37 Peak
3	0.68	4.18	35.30	39.48	70.89 -31.41 Peak
4	0.83	2.44	36.20	38.64	69.08 -30.44 Peak
5	1.15	0.77	43.64	44.41	66.22 -21.81 Peak
6	1.36	0.20	38.74	38.94	64.77 -25.83 Peak


## 30MHz-1GHz\_Horizontal\_ANT1



Site : Chamber A  
Condition : 3m Horizontal  
Project Number : 2501R26990E-RF  
Test Mode : 5G WIFI Transmitting  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Anson Su

Freq	Factor	Read	Limit	Over	Remark	
		Level	Level	Line		
		MHz	dB/m	dBuV	dBuV/m	dB
1	130.09	-11.22	50.12	38.90	43.50	-4.60 QP
2	132.80	-11.38	47.81	36.43	43.50	-7.07 QP
3	327.60	-10.67	51.02	40.35	46.00	-5.65 QP
4	333.39	-10.57	53.01	42.44	46.00	-3.56 QP
5	343.93	-10.31	50.00	39.69	46.00	-6.31 QP
6	380.25	-9.15	47.11	37.96	46.00	-8.04 QP

## 30MHz-1GHz\_Verical\_AN1



Site : Chamber A  
Condition : 3m Vertical  
Project Number : 2501R26990E-RF  
Test Mode : 5G WIFI Transmitting  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Anson Su

Freq	Factor	Read		Limit		Over	Remark
		Level	Level	Line	Line		
1	31.11	-6.54	34.02	27.48	40.00	-12.52	Peak
2	61.83	-18.11	45.30	27.19	40.00	-12.81	Peak
3	130.09	-11.22	48.02	36.80	43.50	-6.70	Peak
4	336.48	-10.49	47.24	36.75	46.00	-9.25	Peak
5	456.71	-7.22	43.94	36.72	46.00	-9.28	Peak
6	503.16	-5.76	44.27	38.51	46.00	-7.49	Peak

**Above 1GHz:****5150-5250 MHz**

Frequency (MHz)	Reading (dB $\mu$ V)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
<b>802.11a_ANT0</b>							
Low Channel							
10360	55.29	PK	H	2.53	57.82	68.2	-10.38
10360	55.56	PK	V	2.53	58.09	68.2	-10.11
Middle Channel							
10400	54.90	PK	H	2.55	57.45	68.2	-10.75
10400	55.18	PK	V	2.55	57.73	68.2	-10.47
High Channel							
10480	54.57	PK	H	2.25	56.82	68.2	-11.38
10480	54.85	PK	V	2.25	57.10	68.2	-11.10
<b>802.11a_ANT1</b>							
Low Channel							
10360	53.24	PK	H	2.53	55.77	68.2	-12.43
10360	53.51	PK	V	2.53	56.04	68.2	-12.16
Middle Channel							
10400	52.89	PK	H	2.55	55.44	68.2	-12.76
10400	53.15	PK	V	2.55	55.70	68.2	-12.50
High Channel							
10480	52.56	PK	H	2.25	54.81	68.2	-13.39
10480	52.83	PK	V	2.25	55.08	68.2	-13.12
<b>802.11ac20</b>							
Low Channel							
10360	54.87	PK	H	2.53	57.40	68.2	-10.80
10360	55.15	PK	V	2.53	57.68	68.2	-10.52
Middle Channel							
10400	54.55	PK	H	2.55	57.10	68.2	-11.10
10400	54.82	PK	V	2.55	57.37	68.2	-10.83
High Channel							
10480	54.23	PK	H	2.25	56.48	68.2	-11.72
10480	54.51	PK	V	2.25	56.76	68.2	-11.44
<b>802.11ac40</b>							
Low Channel							
10380	53.61	PK	H	2.54	56.15	68.2	-12.05
10380	53.87	PK	V	2.54	56.41	68.2	-11.79
High Channel							
10460	52.85	PK	H	2.32	55.17	68.2	-13.03
10460	53.09	PK	V	2.32	55.41	68.2	-12.79
<b>802.11ac80</b>							
Middle Channel							
10420	51.92	PK	H	2.48	54.40	68.2	-13.80
10420	52.25	PK	V	2.48	54.73	68.2	-13.47

**5725-5850MHz**

Frequency (MHz)	Reading (dB $\mu$ V)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
<b>802.11a_ANT0</b>							
Low Channel							
11490	51.83	PK	H	3.54	55.37	74	-18.63
11490	37.54	AV	H	3.54	41.08	54	-12.92
11490	51.29	PK	V	3.54	54.83	74	-19.17
11490	37.32	AV	V	3.54	40.86	54	-13.14
Middle Channel							
11570	52.44	PK	H	3.3	55.74	74	-18.26
11570	38.17	AV	H	3.3	41.47	54	-12.53
11570	51.89	PK	V	3.3	55.19	74	-18.81
11570	37.96	AV	V	3.3	41.26	54	-12.74
High Channel							
11650	53.05	PK	H	3.42	56.47	74	-17.53
11650	38.73	AV	H	3.42	42.15	54	-11.85
11650	52.52	PK	V	3.42	55.94	74	-18.06
11650	38.49	AV	V	3.42	41.91	54	-12.09
<b>802.11a_ANT1</b>							
Low Channel							
11490	51.74	PK	H	3.54	55.28	74	-18.72
11490	37.37	AV	H	3.54	40.91	54	-13.09
11490	51.20	PK	V	3.54	54.74	74	-19.26
11490	37.15	AV	V	3.54	40.69	54	-13.31
Middle Channel							
11570	52.35	PK	H	3.3	55.65	74	-18.35
11570	37.98	AV	H	3.3	41.28	54	-12.72
11570	51.82	PK	V	3.3	55.12	74	-18.88
11570	37.74	AV	V	3.3	41.04	54	-12.96
High Channel							
11650	52.96	PK	H	3.42	56.38	74	-17.62
11650	38.59	AV	H	3.42	42.01	54	-11.99
11650	52.43	PK	V	3.42	55.85	74	-18.15
11650	38.38	AV	V	3.42	41.80	54	-12.20

Frequency (MHz)	Reading (dB $\mu$ V)	PK/Ave	Polar (H/V)	Factor (dB/m)	Corrected Amplitude (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
<b>802.11ac20</b>							
Low Channel							
11490	51.54	PK	H	3.54	55.08	74	-18.92
11490	37.21	AV	H	3.54	40.75	54	-13.25
11490	51.02	PK	V	3.54	54.56	74	-19.44
11490	36.96	AV	V	3.54	40.50	54	-13.50
Middle Channel							
11570	52.19	PK	H	3.3	55.49	74	-18.51
11570	37.93	AV	H	3.3	41.23	54	-12.77
11570	51.65	PK	V	3.3	54.95	74	-19.05
11570	37.72	AV	V	3.3	41.02	54	-12.98
High Channel							
11650	52.82	PK	H	3.42	56.24	74	-17.76
11650	38.54	AV	H	3.42	41.96	54	-12.04
11650	52.27	PK	V	3.42	55.69	74	-18.31
11650	38.35	AV	V	3.42	41.77	54	-12.23
<b>802.11ac40</b>							
Low Channel							
11510	52.12	PK	H	3.53	55.65	74	-18.35
11510	38.41	AV	H	3.53	41.94	54	-12.06
11510	51.58	PK	V	3.53	55.11	74	-18.89
11510	38.19	AV	V	3.53	41.72	54	-12.28
High Channel							
11590	52.95	PK	H	3.21	56.16	74	-17.84
11590	39.02	AV	H	3.21	42.23	54	-11.77
11590	52.44	PK	V	3.21	55.65	74	-18.35
11590	38.78	AV	V	3.21	41.99	54	-12.01
<b>802.11ac80</b>							
Middle Channel							
11550	52.63	PK	H	3.37	56.00	74	-18.00
11550	39.55	AV	H	3.37	42.92	54	-11.08
11550	52.07	PK	V	3.37	55.44	74	-18.56
11550	39.32	AV	V	3.37	42.69	54	-11.31

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor


Corrected Amplitude = Factor + Reading

Margin = Corrected. Amplitude - Limit

The other spurious emission which is in the noise floor level was not recorded.

**Test plots:**

Left Band edge\_Horizontal\_Peak\_802.11a\_ANT0



Condition : Horizontal

Project No. : 2501R26990E-RF


Tester : Zenos Qiao

Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak

Note : 5GWiFi-Band1-A\_ANT0-5180

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5137.127	-7.46	66.66	59.20	74.00	-14.80	Peak
2	5150.000	-7.46	64.45	56.99	74.00	-17.01	Peak


## Left Band edge\_Horizontal\_Average\_802.11a\_ANT0



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT0-5180

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5147.951	-7.46	54.01	46.55	54.00	-7.45	Average
2	5150.000	-7.46	53.93	46.47	54.00	-7.53	Average


## Left Band edge\_Vertical\_Peak\_802.11a\_ANT0



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT0-5180

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5021.673	-7.33	65.23	57.90	74.00	-16.10	Peak
2	5150.000	-7.46	62.85	55.39	74.00	-18.61	Peak


## Left Band edge\_Vertical\_Average\_802.11a\_ANT0



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT0-5180

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5148.691	-7.46	52.69	45.23	54.00	-8.77	Average
2	5150.000	-7.46	52.37	44.91	54.00	-9.09	Average


## Right Band edge\_Horizontal\_Peak\_802.11a\_ANT0



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT0-5240

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5350.000	-6.74	62.80	56.06	74.00	-17.94	Peak
2	5443.878	-6.35	65.82	59.47	74.00	-14.53	Peak

## Right Band edge\_Horizontal\_Average\_802.11a\_ANT0



Condition : Horizontal

Project No. : 2501R26990E-RF


Tester : Zenos Qiao

Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak

Note : 5GWiFi-Band1-A\_ANT0-5240

Freq	Factor	Read		Limit		Over	Limit	Remark
		MHz	dB/m	dBuV	dBuV/m			
1	5350.000	-6.74	51.70	44.96	54.00	-9.04	Average	
2	5368.176	-6.68	53.08	46.40	54.00	-7.60	Average	


## Right Band edge\_Vertical\_Peak\_802.11a\_ANT0



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT0-5240

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5350.000	-6.74	62.31	55.57	74.00	-18.43	Peak
2	5444.723	-6.35	65.96	59.61	74.00	-14.39	Peak


## Right Band edge\_Vertical\_Average\_802.11a\_ANT0



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT0-5240

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5350.000	-6.74	51.49	44.75	54.00	-9.25	Average
2	5452.394	-6.32	52.52	46.20	54.00	-7.80	Average


## Left Band edge\_Horizontal\_Peak\_802.11a\_ANT1



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT1-5180

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5147.951	-7.46	66.31	58.85	74.00	-15.15	Peak
2	5150.000	-7.46	65.45	57.99	74.00	-16.01	Peak


## Left Band edge\_Horizontal\_Average\_802.11a\_ANT1



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT1-5180

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5148.414	-7.46	53.85	46.39	54.00	-7.61	Average
2	5150.000	-7.46	53.55	46.09	54.00	-7.91	Average


## Left Band edge\_Vertical\_Peak\_802.11a\_ANT1



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT1-5180

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5135.185	-7.46	65.76	58.30	74.00	-15.70	Peak
2	5150.000	-7.46	63.14	55.68	74.00	-18.32	Peak

## Left Band edge\_Vertical\_Average\_802.11a\_ANT1



Condition : Vertical

Project No. : 2501R26990E-RF


Tester : Zenos Qiao

Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak

Note : 5GWiFi-Band1-A\_ANT1-5180

Freq	Factor	Read		Limit		Over	Limit	Remark
		MHz	dB/m	dBuV	dBuV/m			
1	5144.806	-7.46	52.48	45.02	54.00	-8.98	Average	
2	5150.000	-7.46	52.28	44.82	54.00	-9.18	Average	


## Right Band edge\_Horizontal\_Peak\_802.11a\_ANT1



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT1-5240

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5350.000	-6.74	63.45	56.71	74.00	-17.29	Peak
2	5427.463	-6.45	66.11	59.66	74.00	-14.34	Peak

## Right Band edge\_Horizontal\_Average\_802.11a\_ANT1



Condition : Horizontal

Project No. : 2501R26990E-RF


Tester : Zenos Qiao

Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak


Note : 5GWiFi-Band1-A\_ANT1-5240

Freq	Factor	Read		Limit		Over	Limit	Remark
		MHz	dB/m	dBuV	dBuV/m			
1	5350.000	-6.74	51.60	44.86	54.00	-9.14	Average	
2	5455.937	-6.31	52.67	46.36	54.00	-7.64	Average	

## Right Band edge\_Vertical\_Peak\_802.11a\_ANT1




## Right Band edge\_Vertical\_Average\_802.11a\_ANT1



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT1-5240

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5350.000	-6.74	51.43	44.69	54.00	-9.31	Average
2	5458.050	-6.29	52.51	46.22	54.00	-7.78	Average


## Left Band edge\_Horizontal\_Peak\_802.11ac-VHT20



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC20-5180

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5149.708	-7.46	66.92	59.46	74.00	-14.54	Peak
2	5150.000	-7.46	66.25	58.79	74.00	-15.21	Peak


## Left Band edge\_Horizontal\_Average\_802.11ac-VHT20



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak  
Note : 5GWiFi-Band1-AC20-5180

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5148.136	-7.46	53.63	46.17	54.00	-7.83	Average
2	5150.000	-7.46	53.42	45.96	54.00	-8.04	Average


## Left Band edge\_Vertical\_Peak\_802.11ac-VHT20



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC20-5180

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5009.924	-7.34	65.76	58.42	74.00	-15.58	Peak
2	5150.000	-7.46	63.10	55.64	74.00	-18.36	Peak


## Left Band edge\_Vertical\_Average\_802.11ac-VHT20



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak  
Note : 5GWiFi-Band1-AC20-5180

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5147.951	-7.46	52.72	45.26	54.00	-8.74	Average
2	5150.000	-7.46	52.54	45.08	54.00	-8.92	Average


## Right Band edge\_Horizontal\_Peak\_802.11ac-VHT20



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC20-5240

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5350.000	-6.74	62.54	55.80	74.00	-18.20	Peak
2	5455.125	-6.31	65.71	59.40	74.00	-14.60	Peak


## Right Band edge\_Horizontal\_Average\_802.11ac-VHT20



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak  
Note : 5GWiFi-Band1-AC20-5240

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5350.000	-6.74	51.77	45.03	54.00	-8.97	Average
2	5368.079	-6.68	53.15	46.47	54.00	-7.53	Average


## Right Band edge\_Vertical\_Peak\_802.11ac-VHT20



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC20-5240

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5350.000	-6.74	63.12	56.38	74.00	-17.62	Peak
2	5432.469	-6.43	66.16	59.73	74.00	-14.27	Peak


## Right Band edge\_Vertical\_Average\_802.11ac-VHT20



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak  
Note : 5GWiFi-Band1-AC20-5240

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5350.000	-6.74	51.59	44.85	54.00	-9.15	Average
2	5458.895	-6.29	52.48	46.19	54.00	-7.81	Average


## Left Band edge\_Horizontal\_Peak\_802.11ac-VHT40



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC40-5190

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5146.408	-7.46	71.64	64.18	74.00	-9.82	Peak
2	5150.000	-7.46	68.01	60.55	74.00	-13.45	Peak


## Left Band edge\_Horizontal\_Average\_802.11ac-VHT40



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 5GWiFi-Band1-AC40-5190

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5149.724	-7.46	57.63	50.17	54.00	-3.83	Average
2	5150.000	-7.46	57.21	49.75	54.00	-4.25	Average


## Left Band edge\_Vertical\_Peak\_802.11ac-VHT40



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC40-5190

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5149.821	-7.46	65.63	58.17	74.00	-15.83	Peak
2	5150.000	-7.46	63.97	56.51	74.00	-17.49	Peak


## Left Band edge\_Vertical\_Average\_802.11ac-VHT40



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 5GWiFi-Band1-AC40-5190

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5149.724	-7.46	54.02	46.56	54.00	-7.44	Average
2	5150.000	-7.46	53.71	46.25	54.00	-7.75	Average


## Right Band edge\_Horizontal\_Peak\_802.11ac-VHT40



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC40-5230

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5350.000	-6.74	63.52	56.78	74.00	-17.22	Peak
2	5450.361	-6.32	65.54	59.22	74.00	-14.78	Peak

## Right Band edge\_Horizontal\_Average\_802.11ac-VHT40



Condition : Horizontal

Project No. : 2501R26990E-RF


Tester : Zenos Qiao

Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak

Note : 5GWiFi-Band1-AC40-5230

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5350.000	-6.74	52.11	45.37	54.00	-8.63	Average
2	5453.249	-6.31	52.87	46.56	54.00	-7.44	Average


## Right Band edge\_Vertical\_Peak\_802.11ac-VHT40



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC40-5230

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5350.000	-6.74	62.90	56.16	74.00	-17.84	Peak
2	5459.700	-6.29	65.95	59.66	74.00	-14.34	Peak


## Right Band edge\_Vertical\_Average\_802.11ac-VHT40



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 5GWiFi-Band1-AC40-5230

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5350.000	-6.74	51.77	45.03	54.00	-8.97	Average
2	5458.837	-6.29	52.98	46.69	54.00	-7.31	Average


## Left Band edge\_Horizontal\_Peak\_802.11ac-VHT80



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC80-5210

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5149.781	-7.46	69.23	61.77	74.00	-12.23	Peak
2	5150.000	-7.46	67.50	60.04	74.00	-13.96	Peak

## Left Band edge\_Horizontal\_Average\_802.11ac-VHT80



Condition : Horizontal

Project No. : 2501R26990E-RF


Tester : Zenos Qiao

Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak

Note : 5GWiFi-Band1-AC80-5210

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5149.981	-7.46	58.21	50.75	54.00	-3.25	Average
2	5150.000	-7.46	57.99	50.53	54.00	-3.47	Average


## Left Band edge\_Vertical\_Peak\_802.11ac-VHT80



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC80-5210

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5149.181	-7.46	65.53	58.07	74.00	-15.93	Peak
2	5150.000	-7.46	64.51	57.05	74.00	-16.95	Peak


## Left Band edge\_Vertical\_Average\_802.11ac-VHT80



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak  
Note : 5GWiFi-Band1-AC80-5210

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5148.881	-7.46	54.87	47.41	54.00	-6.59	Average
2	5150.000	-7.46	54.64	47.18	54.00	-6.82	Average


## Right Band edge\_Horizontal\_Peak\_802.11ac-VHT80



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC80-5210

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	5350.000	-6.74	62.60	55.86	74.00	-18.14	Peak
2	5443.398	-6.35	65.76	59.41	74.00	-14.59	Peak


## Right Band edge\_Horizontal\_Average\_802.11ac-VHT80



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak  
Note : 5GWiFi-Band1-AC80-5210

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>		
1	5350.000	-6.74	52.78	46.04	54.00	-7.96	Average
2	5452.839	-6.31	53.78	47.47	54.00	-6.53	Average


## Right Band edge\_Vertical\_Peak\_802.11ac-VHT80



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC80-5210

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>		
1	5350.000	-6.74	62.99	56.25	74.00	-17.75	Peak
2	5381.110	-6.64	65.65	59.01	74.00	-14.99	Peak


## Right Band edge\_Vertical\_Average\_802.11ac-VHT80



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak  
Note : 5GWiFi-Band1-AC80-5210

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>		
1	5350.000	-6.74	52.75	46.01	54.00	-7.99	Average
2	5442.838	-6.35	53.84	47.49	54.00	-6.51	Average


## Left Band edge\_Horizontal\_802.11a\_ANT0



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-A\_ANT0-5745

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	Line	Limit
1	5613.021	-6.12	66.29	60.17	68.20	-8.03	Peak
2	5685.458	-5.76	65.97	60.21	94.47	-34.26	Peak
3	5719.664	-5.54	71.86	66.32	110.71	-44.39	Peak
4	5724.996	-5.48	80.13	74.65	155.20	-80.55	Peak


## Left Band edge\_Vertical\_802.11a\_ANT0



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-A\_ANT0-5745

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	Line	Limit
1	5647.505	-5.88	65.88	60.00	68.20	-8.20	Peak
2	5696.096	-5.73	65.90	60.17	102.32	-42.15	Peak
3	5719.895	-5.53	67.85	62.32	110.77	-48.45	Peak
4	5724.891	-5.49	75.69	70.20	121.95	-51.75	Peak


## Right Band edge\_Horizontal\_802.11a\_ANT0



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-A\_ANT0-5825

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		dB/m	dBuV	dBuV/m	dBuV/m		
1 5850.946	-4.68	67.26	62.58	120.04	-57.46	Peak	
2 5858.187	-4.65	66.72	62.07	109.91	-47.84	Peak	
3 5914.355	-4.46	66.46	62.00	76.05	-14.05	Peak	
4 5928.135	-4.45	66.56	62.11	68.20	-6.09	Peak	


## Right Band edge\_Vertical\_802.11a\_ANT0



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-A\_ANT0-5825

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level dB/m	Level dBuV	Line dBuV/m	Line dBuV/m		
1 5853.566	-4.66	66.12	61.46	114.07	-52.61	Peak	
2 5855.299	-4.66	65.91	61.25	110.72	-49.47	Peak	
3 5913.365	-4.46	66.73	62.27	76.78	-14.51	Peak	
4 5940.264	-4.44	66.99	62.55	68.20	-5.65	Peak	


## Left Band edge\_Horizontal\_802.11a\_ANT1



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-A\_ANT1-5745

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	Line	Limit
1	5614.571	-6.10	66.78	60.68	68.20	-7.52	Peak
2	5684.694	-5.76	66.53	60.77	93.91	-33.14	Peak
3	5719.918	-5.53	69.41	63.88	110.78	-46.90	Peak
4	5724.220	-5.49	76.82	71.33	120.42	-49.09	Peak


## Left Band edge\_Vertical\_802.11a\_ANT1



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-A\_ANT1-5745

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	Line	Limit
1	5601.734	-6.20	66.73	60.53	68.20	-7.67	Peak
2	5674.911	-5.79	66.20	60.41	86.67	-26.26	Peak
3	5718.692	-5.54	65.84	60.30	110.43	-50.13	Peak
4	5724.937	-5.49	73.34	67.85	122.06	-54.21	Peak


## Right Band edge\_Horizontal\_802.11a\_ANT1



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-A\_ANT1-5825

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	Line	Limit
1	5850.225	-4.68	69.81	65.13	121.69	-56.56	Peak
2	5855.154	-4.66	68.24	63.58	110.76	-47.18	Peak
3	5910.540	-4.45	67.12	62.67	78.87	-16.20	Peak
4	5929.476	-4.45	67.06	62.61	68.20	-5.59	Peak


## Right Band edge\_Vertical\_802.11a\_ANT1



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-A\_ANT1-5825

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level dB/m	Level dBuV	Line dBuV/m	Line dBuV/m		
1 5850.761	-4.68	66.01	61.33	120.46	-59.13	Peak	
2 5855.835	-4.66	66.21	61.55	110.57	-49.02	Peak	
3 5924.690	-4.45	67.10	62.65	68.43	-5.78	Peak	
4 5935.685	-4.45	66.25	61.80	68.20	-6.40	Peak	


## Left Band edge\_Horizontal\_802.11ac-VHT20



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC20-5745

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	Line	
1	5633.536	-5.98	66.51	60.53	68.20	-7.67	Peak
2	5656.802	-5.84	66.97	61.13	73.25	-12.12	Peak
3	5719.849	-5.53	72.56	67.03	110.76	-43.73	Peak
4	5724.150	-5.49	82.13	76.64	120.26	-43.62	Peak


## Left Band edge\_Vertical\_802.11ac-VHT20



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC20-5745

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	Line	Limit
1	5609.598	-6.14	66.17	60.03	68.20	-8.17	Peak
2	5691.494	-5.74	66.24	60.50	98.93	-38.43	Peak
3	5719.964	-5.53	68.31	62.78	110.79	-48.01	Peak
4	5724.266	-5.49	78.17	72.68	120.53	-47.85	Peak


## Right Band edge\_Horizontal\_802.11ac-VHT20



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC20-5825

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level dB/m	Level dBuV	Line dBuV/m	Line dBuV/m		
1 5850.028	-4.68	71.44	66.76	155.20	-88.44	Peak	
2 5856.640	-4.65	68.39	63.74	110.34	-46.60	Peak	
3 5915.758	-4.46	67.82	63.36	75.02	-11.66	Peak	
4 5934.488	-4.45	67.09	62.64	68.20	-5.56	Peak	


## Right Band edge\_Vertical\_Peak\_802.11ac-VHT20



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC20-5825

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	Level	dBuV	Line	dBuV/m
1	5850.018	-4.68	66.99	62.31	122.16	-59.85	Peak
2	5860.456	-4.63	65.97	61.34	109.27	-47.93	Peak
3	5923.308	-4.46	66.36	61.90	69.45	-7.55	Peak
4	5930.857	-4.45	66.70	62.25	68.20	-5.95	Peak


## Left Band edge\_Horizontal\_802.11ac-VHT40



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC40-5755

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	Line	Limit
1	5622.015	-6.05	66.42	60.37	68.20	-7.83	Peak
2	5699.156	-5.72	67.40	61.68	104.58	-42.90	Peak
3	5719.889	-5.53	83.74	78.21	110.77	-32.56	Peak
4	5724.681	-5.49	85.09	79.60	121.47	-41.87	Peak


## Left Band edge\_Vertical\_802.11ac-VHT40



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC40-5755

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level dB/m	Level dBuV	Line dBuV/m	Line dBuV/m		
1 5618.375	-6.08	66.41	60.33	68.20	-7.87	Peak	
2 5699.027	-5.72	66.66	60.94	104.48	-43.54	Peak	
3 5719.632	-5.54	79.60	74.06	110.70	-36.64	Peak	
4 5724.041	-5.49	80.17	74.68	120.01	-45.33	Peak	


## Right Band edge\_Horizontal\_802.11ac-VHT40



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC40-5795

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	Line	dB
1	5850.844	-4.68	67.17	62.49	120.27	-57.78	Peak
2	5857.303	-4.65	66.77	62.12	110.15	-48.03	Peak
3	5923.911	-4.46	66.83	62.37	69.00	-6.63	Peak
4	5940.261	-4.44	66.78	62.34	68.20	-5.86	Peak


## Right Band edge\_Vertical\_Peak\_802.11ac-VHT40



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC40-5795

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	Level	dBuV	Line	dBuV/m
1	5850.998	-4.68	66.05	61.37	119.92	-58.55	Peak
2	5855.406	-4.66	66.16	61.50	110.69	-49.19	Peak
3	5918.554	-4.45	65.95	61.50	72.95	-11.45	Peak
4	5942.517	-4.45	66.80	62.35	68.20	-5.85	Peak


## Left Band edge\_Horizontal\_802.11ac-VHT80



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC80-5775

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	Line	
1	5627.003	-6.01	66.53	60.52	68.20	-7.68	Peak
2	5688.886	-5.74	77.64	71.90	97.00	-25.10	Peak
3	5718.702	-5.54	81.78	76.24	110.44	-34.20	Peak
4	5720.734	-5.53	83.12	77.59	112.47	-34.88	Peak


## Left Band edge\_Vertical\_802.11ac-VHT80



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC80-5775

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	Line	
1	5609.845	-6.14	65.98	59.84	68.20	-8.36	Peak
2	5688.949	-5.74	74.66	68.92	97.05	-28.13	Peak
3	5719.578	-5.54	76.96	71.42	110.68	-39.26	Peak
4	5720.578	-5.53	78.88	73.35	112.12	-38.77	Peak


## Right Band edge\_Horizontal\_802.11ac-VHT80



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC80-5775

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	Line	Limit
1	5850.931	-4.68	76.93	72.25	120.08	-47.83	Peak
2	5855.404	-4.66	75.86	71.20	110.69	-39.49	Peak
3	5875.516	-4.57	69.51	64.94	104.82	-39.88	Peak
4	5945.049	-4.45	66.45	62.00	68.20	-6.20	Peak

## Right Band edge\_Vertical\_Peak\_802.11ac-VHT80




Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC80-5775

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		dB/m	dBuV	dBuV/m	dBuV/m		
1 5850.453	-4.68	72.29	67.61	121.17	-53.56	Peak	
2 5861.086	-4.63	71.58	66.95	109.09	-42.14	Peak	
3 5922.406	-4.45	67.02	62.57	70.11	-7.54	Peak	
4 5935.036	-4.45	67.06	62.61	68.20	-5.59	Peak	

**1-18GHz (Listed with the worst harmonic margin test plot)**

1-7GHz\_Horizontal\_802.11a\_ANT0



Condition : Horizontal

Project No. : 2501R26990E-RF


Tester : Zenos Qiao

Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak

Note : 5GWiFi-Band1-A\_ANT0-5180

Freq	Factor	Read	Limit	Over	Remark
		Level	Level	Line	
1	6638.455	-2.99	56.36	53.37	68.20 -14.83 Peak


## 1-7GHz\_Vertical\_802.11a\_ANT0



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT0-5180

Freq Factor	MHz	Read Level		Limit Level		Over Limit	Remark
		dB/m	dBuV	dBuV/m	dBuV/m		
1	6778.722	-3.29	55.02	51.73	68.20	-16.47	Peak


## 7-18GHz\_Horizontal\_Peak\_802.11a\_ANT0



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT0-5180

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>		
1	10360.000	2.53	55.29	57.82	68.20	-10.38	Peak
2	17960.120	13.00	49.31	62.31	74.00	-11.69	Peak

## 7-18GHz\_Horizontal\_Average\_802.11a\_ANT0



Condition : Horizontal

Project No. : 2501R26990E-RF


Tester : Zenos Qiao

Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak

Note : 5GWiFi-Band1-A\_ANT0-5180

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>		
1	17995.880	13.18	33.15	46.33	54.00	-7.67	Average


## 7-18GHz\_Vertical\_Peak\_802.11a\_ANT0



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT0-5180

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level dB/m	Level dBuV	Line dBuV/m	Line dBuV/m		
1 10360.000	2.53	55.56	58.09	68.20	-10.11	Peak	
2 17982.120	13.10	48.24	61.34	74.00	-12.66	Peak	


## 7-18GHz\_Vertical\_Average\_802.11a\_ANT0



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT0-5180

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level dB/m	Level dBuV	Line dBuV/m	Line dBuV/m		
1 17998.630	13.20	32.95	46.15	54.00	-7.85	Average	


## 1-7GHz\_Horizontal\_802.11a\_ANT1



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT1-5180

Freq Factor	MHz	Read Level		Limit Level		Over Line Limit	Remark
		dB/m	dBuV	dBuV/m	dBuV/m		
1	6442.680	-2.88	55.40	52.52	68.20	-15.68	Peak


## 1-7GHz\_Vertical\_802.11a\_ANT1



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT1-5180

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	6465.933	-2.89	55.35	52.46	68.20	-15.74	Peak


## 7-18GHz\_Horizontal\_Peak\_802.11a\_ANT1



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT1-5180

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level	Level	Line	dBuV/m		
1 10360.000	2.53	53.24	55.77	68.20	-12.43	Peak	
2 17935.370	12.88	48.01	60.89	74.00	-13.11	Peak	


## 7-18GHz\_Horizontal\_Average\_802.11a\_ANT1



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT1-5180

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level dB/m	Level dB <sub>uV</sub>	Line dB <sub>uV/m</sub>	Line dB <sub>uV/m</sub>		
1 17995.880	13.18	32.95	46.13	54.00	-7.87	Average	


## 7-18GHz\_Vertical\_Peak\_802.11a\_ANT1



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT1-5180

Freq MHz	Factor	Read		Limit		Over dB	Remark
		Level dB/m	Level dBuV	Line dBuV/m	Line dBuV/m		
1 10360.000	2.53	53.51	56.04	68.20	-12.16	Peak	
2 17982.120	13.10	47.61	60.71	74.00	-13.29	Peak	


## 7-18GHz\_Vertical\_Average\_802.11a\_ANT1



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT1-5180

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level dB/m	Level dBuV	Line dBuV/m	Line dBuV/m		
1 17991.750	13.16	33.01	46.17	54.00	54.00	-7.83	Average


## 1-7GHz\_Horizontal\_802.11ac-VHT20



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC20-5180

Freq Factor	MHz	Read Level		Limit Level		Over Limit	Remark
		dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>	dB <sub>uV/m</sub>		
1	6795.225	-3.35	56.12	52.77	68.20	-15.43	Peak


## 1-7GHz\_Vertical\_802.11ac-VHT20



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC20-5180

Freq Factor	MHz	Read Level		Limit Level		Over Line Limit	Remark
		dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>	dB <sub>uV/m</sub>		
1	6773.472	-3.29	55.56	52.27	68.20	-15.93	Peak


## 7-18GHz\_Horizontal\_Peak\_802.11ac-VHT20



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC20-5180

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level dB/m	Level dBuV	Line dBuV/m	Line dBuV/m		
1 10360.000	2.53	54.87	57.40	68.20	-10.80	Peak	
2 17973.870	13.08	48.06	61.14	74.00	-12.86	Peak	


## 7-18GHz\_Horizontal\_Average\_802.11ac-VHT20



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak  
Note : 5GWiFi-Band1-AC20-5180

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level dB/m	Level dB <sub>uV</sub>	Line dB <sub>uV/m</sub>	Line dB <sub>uV/m</sub>		
1 17995.880	13.18	33.08	46.26	54.00	-7.74	Average	


## 7-18GHz\_Vertical\_Peak\_802.11ac-VHT20



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC20-5180

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	10360.000	2.53	55.15	57.68	68.20	-10.52	Peak
2	17950.490	12.95	48.15	61.10	74.00	-12.90	Peak


## 7-18GHz\_Vertical\_Average\_802.11ac-VHT20



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak  
Note : 5GWiFi-Band1-AC20-5180

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>	dB <sub>uV/m</sub>		
17995.880	13.18	32.92	46.10	54.00	-7.90	Average	


## 1-7GHz\_Horizontal\_802.11ac-VHT40



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC40-5190

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	Level	dBuV	Line	dBuV/m
1	6409.676	-2.89	55.22	52.33	68.20	-15.87	Peak


## 1-7GHz\_Vertical\_802.11ac-VHT40



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC40-5190

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	6781.723	-3.30	55.71	52.41	68.20	-15.79	Peak


## 7-18GHz\_Horizontal\_Peak\_802.11ac-VHT40



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC40-5190

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level	dBuV	Line	dBuV/m		
1 10380.000	2.54	53.61	56.15	68.20	-12.05	Peak	
2 17983.500	13.11	47.85	60.96	74.00	-13.04	Peak	

## 7-18GHz\_Horizontal\_Average\_802.11ac-VHT40



Condition : Horizontal

Project No. : 2501R26990E-RF


Tester : Zenos Qiao

Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak

Note : 5GWiFi-Band1-AC40-5190

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	17989.000	13.14	34.03	47.17	54.00	-6.83	Average


## 7-18GHz\_Vertical\_Peak\_802.11ac-VHT40



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC40-5190

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	10380.000	2.54	53.87	56.41	68.20	-11.79	Peak
2	17980.750	13.11	48.00	61.11	74.00	-12.89	Peak


## 7-18GHz\_Vertical\_Average\_802.11ac-VHT40



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 5GWiFi-Band1-AC40-5190

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level dB/m	Level dB <sub>uV</sub>	Line dB <sub>uV/m</sub>	Line dB <sub>uV/m</sub>		
1 17998.630	13.19	34.09	47.28	54.00	-6.72	Average	


## 1-7GHz\_Horizontal\_802.11ac-VHT80



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC80-5210

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	Level	dBuV	Line	dBuV/m
1	6632.454	-3.01	55.20	52.19	68.20	-16.01	Peak


## 1-7GHz\_Vertical\_802.11ac-VHT80



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC80-5210

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	6441.930	-2.87	55.74	52.87	68.20	-15.33	Peak


## 7-18GHz\_Horizontal\_Peak\_802.11ac-VHT80



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC80-5210

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level	dBuV	Line	dBuV/m		
1 10420.000	2.48	51.92	54.40	68.20	-13.80	Peak	
2 17989.000	13.14	47.74	60.88	74.00	-13.12	Peak	

## 7-18GHz\_Horizontal\_Average\_802.11ac-VHT80



Condition : Horizontal

Project No. : 2501R26990E-RF


Tester : Zenos Qiao

Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak

Note : 5GWiFi-Band1-AC80-5210

Freq Factor	Read Level		Limit Level		Over Line Limit		Remark
	MHz	dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>	dB <sub>uV/m</sub>	dB	
1	17997.250	13.19	34.62	47.81	54.00	-6.19	Average


## 7-18GHz\_Vertical\_Peak\_802.11ac-VHT80



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-AC80-5210

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level	Level	Line	dBuV/m		
1 10420.000	2.48	52.25	54.73	68.20	-13.47	Peak	
2 17939.490	12.90	47.60	60.50	74.00	-13.50	Peak	


## 7-18GHz\_Vertical\_Average\_802.11ac-VHT80



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak  
Note : 5GWiFi-Band1-AC80-5210

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>	dB <sub>uV/m</sub>		
17991.750	13.16	34.77	47.93	54.00	-6.07	Average	


## 1-7GHz\_Horizontal\_802.11a\_ANT0



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-A\_ANT0-5825


Freq Factor	MHz	Read Level		Limit Level		Over Limit	Remark
		dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>	dB <sub>uV/m</sub>		
1	6994.750	-2.92	55.27	52.35	68.20	-15.85	Peak

## 1-7GHz\_Vertical\_802.11a\_ANT0



Freq Factor	MHz	Read Level		Limit Level		Over Limit	Remark
		dB/m	dBuV	dBuV/m	dBuV/m		
1	6442.680	-2.88	56.29	53.41	68.20	-14.79	Peak


## 7-18GHz\_Horizontal\_Peak\_802.11a\_ANT0



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-A\_ANT0-5825

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	11650.000	3.42	53.05	56.47	74.00	-17.53	Peak
2	17940.870	12.91	47.83	60.74	74.00	-13.26	Peak

## 7-18GHz\_Horizontal\_Average\_802.11a\_ANT0



Condition : Horizontal

Project No. : 2501R26990E-RF


Tester : Zenos Qiao

Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak

Note : 5GWiFi-Band4-A\_ANT0-5825

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>		
1	11650.000	3.42	38.73	42.15	54.00	-11.85	Average
2	17989.000	13.14	33.09	46.23	54.00	-7.77	Average


## 7-18GHz\_Vertical\_Peak\_802.11a\_ANT0



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-A\_ANT0-5825

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level dB/m	Level dBuV	Line dBuV/m	Line dBuV/m		
1 11650.000	3.42	52.52	55.94	74.00	-18.06	Peak	
2 17967.000	13.03	48.30	61.33	74.00	-12.67	Peak	


## 7-18GHz\_Vertical\_Average\_802.11a\_ANT0



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak  
Note : 5GWiFi-Band4-A\_ANT0-5825

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level	Level	Line	dBuV/m		
1 11650.000		3.42	38.49	41.91	54.00	-12.09	Average
2 17998.630		13.19	32.87	46.06	54.00	-7.94	Average


## 1-7GHz\_Horizontal\_802.11a\_ANT1



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-A\_ANT1-5825

Freq Factor	MHz	Read Level		Limit Level		Over Limit	Remark
		dB/m	dBuV	dBuV/m	dBuV/m		
1	6405.176	-2.89	55.12	52.23	68.20	-15.97	Peak


## 1-7GHz\_Vertical\_802.11a\_ANT1



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-A\_ANT1-5825

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	6386.423	-3.02	55.45	52.43	68.20	-15.77	Peak


## 7-18GHz\_Horizontal\_Peak\_802.11a\_ANT1



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-A\_ANT1-5825

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level	Level	Line	dBuV/m		
1 11650.000	3.42	52.96	56.38	74.00	-17.62	Peak	
2 17899.610	12.69	48.22	60.91	74.00	-13.09	Peak	


## 7-18GHz\_Horizontal\_Average\_802.11a\_ANT1



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak  
Note : 5GWiFi-Band4-A\_ANT1-5825

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level	Level	Line	Line		
		dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>	dB <sub>uV/m</sub>		
1	11650.000	3.42	38.59	42.01	54.00	-11.99	Average
2	17998.630	13.19	32.97	46.16	54.00	-7.84	Average


## 7-18GHz\_Vertical\_Peak\_802.11a\_ANT1



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-A\_ANT1-5825

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level dB/m	Level dBuV	Line dBuV/m	Line dBuV/m		
1 11650.000	3.42	52.43	55.85	74.00	-18.15	Peak	
2 17993.130	13.17	47.83	61.00	74.00	-13.00	Peak	


## 7-18GHz\_Vertical\_Average\_802.11a\_ANT1



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak  
Note : 5GWiFi-Band4-A\_ANT1-5825

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level	Level	Line	dBuV/m		
1 11650.000		3.42	38.38	41.80	54.00	-12.20	Average
2 17995.880		13.18	32.83	46.01	54.00	-7.99	Average


## 1-7GHz\_Horizontal\_802.11ac-VHT20



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC20-5825

Freq Factor	MHz	Read Level		Limit Level		Over Limit	Remark
		dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>	dB <sub>uV/m</sub>		
1	6987.249	-2.88	54.97	52.09	68.20	-16.11	Peak


## 1-7GHz\_Vertical\_802.11ac-VHT20



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC20-5825

Freq Factor	MHz	Read Level		Limit Level		Over Limit	Remark
		dB/m	dBuV	dBuV/m	dBuV/m		
1	6794.474	-3.34	55.69	52.35	68.20	-15.85	Peak


## 7-18GHz\_Horizontal\_Peak\_802.11ac-VHT20



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC20-5825

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level	dBuV	Line	dBuV/m		
1 11650.000	3.42	52.82	56.24	74.00	-17.76	Peak	
2 17969.750	13.06	47.91	60.97	74.00	-13.03	Peak	


## 7-18GHz\_Horizontal\_Average\_802.11ac-VHT20



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak  
Note : 5GWiFi-Band4-AC20-5825

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level	dB <sub>UV</sub>	Line	dB <sub>UV</sub> /m		
1 11650.000	3.42	38.54	41.96	54.00	-12.04	Average	
2 17998.630	13.19	32.93	46.12	54.00	-7.88	Average	


## 7-18GHz\_Vertical\_Peak\_802.11ac-VHT20



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC20-5825

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level	dBuV	Line	dBuV/m		
1 11650.000	3.42	52.27	55.69	74.00	-18.31	Peak	
2 17976.620	13.09	47.66	60.75	74.00	-13.25	Peak	


## 7-18GHz\_Vertical\_Average\_802.11ac-VHT20



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:1kHz Detector:Peak  
Note : 5GWiFi-Band4-AC20-5825

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level	dB <sub>UV</sub>	Line	dB <sub>UV</sub> /m		
1 11650.000	3.42	38.35	41.77	54.00	-12.23	Average	
2 17998.630	13.19	32.83	46.02	54.00	-7.98	Average	


## 1-7GHz\_Horizontal\_802.11ac-VHT40



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC40-5795

Freq Factor	MHz	Read Level		Limit Level		Over Limit	Remark
		dB/m	dB <sub>uV</sub>	dB <sub>uV/m</sub>	dB <sub>uV/m</sub>		
1	6453.932	-2.88	54.70	51.82	68.20	-16.38	Peak


## 1-7GHz\_Vertical\_802.11ac-VHT40



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC40-5795

Freq Factor	MHz	Read Level		Limit Level		Over Line Limit	Remark
		dB/m	dBuV	dBuV/m	dBuV/m		
1	6463.683	-2.89	55.91	53.02	68.20	-15.18	Peak


## 7-18GHz\_Horizontal\_Peak\_802.11ac-VHT40



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC40-5795

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	11590.000	3.21	52.95	56.16	74.00	-17.84	Peak
2	17993.130	13.17	47.75	60.92	74.00	-13.08	Peak

## 7-18GHz\_Horizontal\_Average\_802.11ac-VHT40



Condition : Horizontal

Project No. : 2501R26990E-RF


Tester : Zenos Qiao

Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak

Note : 5GWiFi-Band4-AC40-5795

Freq Factor	Read		Limit		Over	Remark
	MHz	dB/m	dBuV	dBuV/m		
1	11590.000	3.21	39.02	42.23	54.00	-11.77 Average
2	17995.880	13.18	33.88	47.06	54.00	-6.94 Average

## 7-18GHz\_Vertical\_Peak\_802.11ac-VHT40



Condition : Vertical

Project No. : 2501R26990E-RF


Tester : Zenos Qiao

Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak

Note : 5GWiFi-Band4-AC40-5795

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	11590.000	3.21	52.44	55.65	74.00	-18.35	Peak
2	17954.620	12.97	47.52	60.49	74.00	-13.51	Peak


## 7-18GHz\_Vertical\_Average\_802.11ac-VHT40



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:2kHz Detector:Peak  
Note : 5GWiFi-Band4-AC40-5795

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		dB/m	dB <sub>UV</sub>	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m		
1 11590.000	3.21	38.78	41.99	54.00	-12.01	Average	
2 17998.630	13.19	33.74	46.93	54.00	-7.07	Average	


## 1-7GHz\_Horizontal\_802.11ac-VHT80



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC80-5775

Freq Factor	MHz	Read Level		Limit Level		Over Line Limit	Remark
		dB/m	dBuV	dBuV/m	dBuV/m		
1	6954.994	-2.72	56.85	54.13	68.20	-14.07	Peak


## 1-7GHz\_Vertical\_802.11ac-VHT80



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC80-5775

Freq Factor	MHz	Read Level		Limit Level		Over Limit	Remark
		dB/m	dBuV	dBuV/m	dBuV/m		
1	6972.997	-2.81	55.92	53.11	68.20	-15.09	Peak


## 7-18GHz\_Horizontal\_Peak\_802.11ac-VHT80



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC80-5775

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level	Level	Line	Line		
1 11550.000	3.37	52.63	56.00	74.00	-18.00	Peak	
2 17964.250	13.02	48.70	61.72	74.00	-12.28	Peak	


## 7-18GHz\_Horizontal\_Average\_802.11ac-VHT80



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak  
Note : 5GWiFi-Band4-AC80-5775

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level dB/m	Level dB <sub>UV</sub>	Line dB <sub>UV</sub> /m	Line dB <sub>UV</sub> /m		
1 11550.000	3.37	39.55	42.92	54.00	-11.08	Average	
2 17989.000	13.14	34.68	47.82	54.00	-6.18	Average	


## 7-18GHz\_Vertical\_Peak\_802.11ac-VHT80



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band4-AC80-5775

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level	dBuV	Line	dBuV/m		
1 11550.000	3.37	52.07	55.44	74.00	-18.56	Peak	
2 17998.630	13.20	47.27	60.47	74.00	-13.53	Peak	

## 7-18GHz\_Vertical\_Average\_802.11ac-VHT80




Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Average reading:RBW:1MHz VBW:5kHz Detector:Peak  
Note : 5GWiFi-Band4-AC80-5775

Freq MHz	Factor	Read		Limit		Over Limit	Remark
		Level dB/m	Level dBuV	Line dBuV/m	Line dBuV/m		
1 11550.000	3.37	39.32	42.69	54.00	-11.31	Average	
2 17972.500	13.07	34.55	47.62	54.00	-6.38	Average	

18-40GHz (Only with worst case margin mode plot):


18-40GHz\_Horizontal\_802.11a\_ANT0



Condition : Horizontal  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT0-5180

	Freq	Factor	Read Level	Limit Level	Over Line	Limit	Remark
	MHz		dB/m	dBuV	dBuV/m	dBuV/m	dB
1	39680.960		22.67	35.76	58.43	80.00	-21.57 Peak

## 18-40GHz\_Vertical\_802.11a\_ANT0



Condition : Vertical  
Project No. : 2501R26990E-RF  
Tester : Zenos Qiao  
Spectrum setting: Peak reading:RBW:1MHz VBW:3MHz Detector:Peak  
Note : 5GWiFi-Band1-A\_ANT0-5180

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m		
1	39854.230	22.52	37.06	59.58	80.00	-20.42	Peak

**RF Conducted data****Emission Bandwidth****Test Information:**

<b>Sample No.:</b>	2ZEA-9	<b>Test Date:</b>	2025/03/29~2025/04/11
<b>Test Site:</b>	RF	<b>Test Mode:</b>	Transmitting
<b>Tester:</b>	Cheeb Huang	<b>Test Result:</b>	Pass

**Environmental Conditions:**

<b>Temperature:</b> (°C)	25.3-25.7	<b>Relative Humidity:</b> (%)	35-39	<b>ATM Pressure:</b> (kPa)	101.3-101.5
-----------------------------	-----------	----------------------------------	-------	-------------------------------	-------------

**Test Data:****26dB Emission Bandwidth****5150-5250MHz**


Mode	Antenna	Test Frequency (MHz)	Result (MHz)
802.11a	Chain 0	5180	20.291
		5200	20.342
		5240	20.391
	Chain 1	5180	19.870
		5200	20.392
		5240	20.493
802.11ac20	Chain 0	5180	20.594
		5200	20.595
		5240	20.696
	Chain 1	5180	20.138
		5200	20.342
		5240	20.442
802.11ac40	Chain 0	5190	40.941
		5230	41.341
	Chain 1	5190	40.240
		5230	40.240
802.11ac80	Chain 0	5210	<b>82.082</b>
	Chain 1	5210	80.881

**6dB Emission Bandwidth****5725-5850MHz**


Mode	Antenna	Test Frequency (MHz)	Result (MHz)	Limit (MHz)	Verdict
802.11a	Chain 0	5745	15.215	0.5	Pass
		5785	15.215	0.5	Pass
		5825	15.215	0.5	Pass
	Chain 1	5745	15.265	0.5	Pass
		5785	15.215	0.5	Pass
		5825	15.265	0.5	Pass
802.11ac20	Chain 0	5745	15.265	0.5	Pass
		5785	15.165	0.5	Pass
		5825	15.265	0.5	Pass
	Chain 1	5745	15.215	0.5	Pass
		5785	15.766	0.5	Pass
		5825	15.816	0.5	Pass
802.11ac40	Chain 0	5755	35.335	0.5	Pass
		5795	35.335	0.5	Pass
	Chain 1	5755	35.235	0.5	Pass
		5795	35.335	0.5	Pass
802.11ac80	Chain 0	5775	<b>75.475</b>	0.5	Pass
	Chain 1	5775	<b>75.475</b>	0.5	Pass

## 5150-5250MHz


## 802.11a\_5180MHz\_Chain 0




## 802.11a\_5200MHz\_Chain 0




## 802.11a\_5240MHz\_Chain 0




## 802.11a\_5180MHz\_Chain 1




## 802.11a\_5200MHz\_Chain 1




## 802.11a\_5240MHz\_Chain 1




## 802.11ac20\_5180MHz\_Chain 0




## 802.11ac20\_5200MHz\_Chain 0




## 802.11ac20\_5240MHz\_Chain 0




## 802.11ac20\_5180MHz\_Chain 1




## 802.11ac20\_5200MHz\_Chain 1



## 802.11ac20\_5240MHz\_Chain 1




## 802.11ac40\_5190MHz\_Chain 0




ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 16:08:24

## 802.11ac40\_5230MHz\_Chain 0




ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 16:09:46

## 802.11ac40\_5190MHz\_Chain 1




ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 16:35:29

## 802.11ac40\_5230MHz\_Chain 1




ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 16:37:25

## 802.11ac80\_5210MHz\_Chain 0



ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 11.APR.2025 09:25:34


## 802.11ac80\_5210MHz\_Chain 1



ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 11.APR.2025 09:27:20


## 5725-5850MHz

## 802.11a\_5745MHz\_Chain 0




ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 16:51:57

## 802.11a\_5785MHz\_Chain 0




ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 16:54:13

## 802.11a\_5825MHz\_Chain 0




ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 16:56:21

## 802.11a\_5785MHz\_Chain 1




ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 17:13:23

## 802.11a\_5745MHz\_Chain 1




ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 17:10:59

## 802.11a\_5825MHz\_Chain 1




ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 17:16:44

## 802.11ac20\_5745MHz\_Chain 0




ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 16:58:36

## 802.11ac20\_5785MHz\_Chain 0




ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 17:01:19

## 802.11ac20\_5825MHz\_Chain 0




ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 17:03:36

## 802.11ac20\_5745MHz\_Chain 1




ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 17:18:59

## 802.11ac20\_5785MHz\_Chain 1




ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 17:21:28

## 802.11ac20\_5825MHz\_Chain 1




ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 17:23:47

## 802.11ac40\_5755MHz\_Chain 0




ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 17:05:26

## 802.11ac40\_5795MHz\_Chain 0




ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 17:06:43

## 802.11ac40\_5755MHz\_Chain 1




ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 17:31:05

## 802.11ac40\_5795MHz\_Chain 1




ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 17:32:22

## 802.11ac80\_5775MHz\_Chain 0



ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 17:08:17

## 802.11ac80\_5775MHz\_Chain 1



ProjectNo.:2501R26990E-RF Tester:Cheeb Huang  
Date: 2.APR.2025 17:33:44

**99% Occupied Bandwidth****Test Information:**

<b>Sample No.:</b>	2ZEA-9	<b>Test Date:</b>	2025/03/29~2025/04/11
<b>Test Site:</b>	RF	<b>Test Mode:</b>	Transmitting
<b>Tester:</b>	Cheeb Huang	<b>Test Result:</b>	N/A

**Environmental Conditions:**

<b>Temperature:</b> (°C)	25.3-25.7	<b>Relative Humidity:</b> (%)	35-39	<b>ATM Pressure:</b> (kPa)	101.3-101.5
-----------------------------	-----------	----------------------------------	-------	-------------------------------	-------------

**Test Data:****5150-5250MHz**

Mode	Antenna	Test Frequency (MHz)	99% OBW (MHz)
802.11a	Chain 0	5180	16.550
		5200	16.550
		5240	16.550
	Chain 1	5180	16.500
		5200	16.550
		5240	16.550
802.11ac20	Chain 0	5180	17.600
		5200	17.600
		5240	17.600
	Chain 1	5180	17.550
		5200	17.550
		5240	17.550
802.11ac40	Chain 0	5190	36.100
		5230	36.200
	Chain 1	5190	36.200
		5230	36.200
802.11ac80	Chain 0	5210	<b>75.400</b>
	Chain 1	5210	75.200

**Note:**

The 99% Occupied Bandwidth have not fall into the band 5250-5350MHz, please refer to the test plots of 99% Occupied Bandwidth.

**5725-5850MHz**


Mode	Antenna	Test Frequency (MHz)	99% OBW (MHz)
802.11a	Chain 0	5745	16.600
		5785	16.550
		5825	16.550
	Chain 1	5745	16.600
		5785	16.550
		5825	16.550
802.11ac20	Chain 0	5745	17.600
		5785	17.550
		5825	17.600
	Chain 1	5745	17.600
		5785	17.600
		5825	17.550
802.11ac40	Chain 0	5755	36.200
		5795	36.200
	Chain 1	5755	36.200
		5795	36.200
802.11ac80	Chain 0	5775	<b>75.600</b>
	Chain 1	5775	75.200

**Note:**


The 99% Occupied Bandwidth have not fall into the band 5470-5725MHz, please refer to the test plots of 99% Occupied Bandwidth.

## 5150-5250MHz


## 802.11a\_5180MHz\_Chain 0




## 802.11a\_5200MHz\_Chain 0




## 802.11a\_5240MHz\_Chain 0



## 802.11a\_5180MHz\_Chain 1



## 802.11a\_5200MHz\_Chain 1



## 802.11a\_5240MHz\_Chain 1

