

RF exposure evaluation

§ 2.1093 Radiofrequency radiation exposure evaluation: Portable Devices.

According to § 15.247(i) and § 1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the commission's guidance.

The 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR, where}$$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm according is applied to determine SAR test exclusion.
- The result is rounded to one decimal place for comparison

For BDR+EDR:

Channel	Frequency (GHz)	Tune up Power (dBm)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)
CH 00	2.402	7.5±1.5	9.0	7.94
CH 39	2.441	6.5±1.8	8.3	6.76
CH 78	2.480	7.5±1.6	9.1	8.13

Channel	Frequency (GHz)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)	Test distance (mm)	Result	Exclusion thresholds for 1-g SAR
CH 78	2.480	9.1	8.13	5	2.56	3.0

For BLE(1M):

Channel	Frequency (GHz)	Tune up Power (dBm)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)
CH 00	2.402	5±1	6	3.98
CH 19	2.440	5±1	6	3.98
CH 39	2.480	5±1	6	3.98

Channel	Frequency (GHz)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)	Test distance (mm)	Result	Exclusion thresholds for 1-g SAR
CH 19	2.440	6	3.98	5	1.24	3.0

For BLE (2M):

Channel	Frequency (GHz)	Tune up Power (dBm)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)
CH 00	2.402	5±1	6	3.98
CH 19	2.440	5±1	6	3.98
CH 39	2.480	5±1	6	3.98

Channel	Frequency (GHz)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)	Test distance (mm)	Result	Exclusion thresholds for 1-g SAR
CH 19	2.440	6	3.98	5	1.24	3.0