

FCC and ISED Canada Testing of the

Frymaster, LLC
WG7833-B0

In accordance with FCC 47 CFR part 15.247 and
ISED Canada's Radio Standards Specifications
RSS-247

Prepared for: Frymaster, LLC
8700 Line Avenue
Shreveport, LA 71106

FCC ID: 2AQ4D-5066500
IC: 24291-5066500

COMMERCIAL-IN-CONFIDENCE

Document Number: TP72160507.500 | Version Number: 01

RESPONSIBLE FOR	NAME	DATE	SIGNATURE
Authorized Signatory	Peter Walsh	2020 -December-21	
Testing	Thierry Jean Charles	2020-December-21	

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD Product Service document control rules.

FCC Accreditation Designation Number US1063 Tampa, FL Test Laboratory	Innovation, Science, and Economic Development Canada Accreditation Site Number 2087A-2 Tampa, FL Test Laboratory
--	--

EXECUTIVE SUMMARY

Samples of this product were tested and found to be in compliance with 15.247 and ISED Canada's RSS-247.

 A2LA Cert. No. 2955.15	DISCLAIMER AND COPYRIGHT This non-binding report has been prepared by TÜV SÜD America with all reasonable skill and care. The document is confidential to the potential Client and TÜV SÜD America. No part of this document may be reproduced without the prior written approval of TÜV SÜD America. © TÜV SÜD.
	DISCLAIMER AND COPYRIGHT Our A2LA Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our A2LA Accreditation. Results of test not covered by our A2LA Accreditation Schedule are marked NUA (Not A2LA Accredited).

TÜV SÜD America
5610 West Sligh Ave., Suite 100
Tampa, FL 33634

Phone: 813-284-2715
www.tuv-sud-america.com



America

Add value.
Inspire trust.



Contents

1	Report Summary	3
1.1	Report Modification Record.....	3
1.2	Introduction.....	3
1.3	Brief Summary of Results	5
1.4	Product Information	6
1.5	Deviations from the Standard.....	8
1.6	EUT Modification Record	9
1.7	Test Location	9
2	Test Details	10
2.1	Antenna Requirements.....	10
2.2	99% Bandwidth	11
2.3	Peak Output Power	21
2.4	Radiated Spurious Emissions into Restricted Frequency Bands.....	31
2.5	Duty Cycle	42
3	Test Equipment Information	46
3.1	General Test Equipment Used	46
4	Diagram of Test Set-ups.....	47
5	Measurement Uncertainty	51
6	Accreditation, Disclaimers and Copyright.....	52



1 Report Summary

1.1 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Issue	Description of Change	Date of Issue
1	First Issue	2020-December-21

1.2 Introduction

The purpose of this report is to demonstrate compliance with Part 15 Subpart C of the FCC's Code of Federal Regulations Section 15.247 and Innovation Science and Economic Development Canada's Radio Standards Specification RSS-247 for the tests documented herein.

The evaluation is investigating compliance of the Frymaster, LLC wireless module model WG7833-B0, (FCC ID: 2AQ4D-5066500, IC: 24291-5066500), when integrated within the Convotherm Elektrogeräte GmbH model 5066500 host product. The Maximum TX Output Power of the 2.4 GHz Wi-Fi radio was reduced as documented herein to meet the requirements.



Applicant	Frymaster, LLC
Manufacturer	Jorgin
Applicant's Email Address	ralph.macy@welbilt.com
Model Number(s)	WG7833-B0
Host Serial Number(s)	ACVT1902000023, ACTV1902000016
FCC ID	2AQ4D-5066500
ISED Certification Number	24291-5066500
Hardware Version(s)	Rev. 0.7
Software Version(s)	N/A
Number of Samples Tested	2
Test Specification/Issue/Date	US Code of Federal Regulations (CFR): Title 47, Part 15, Subpart C: Radio Frequency Devices, Intentional Radiators, 2019 Innovation, Science and Economic Development Canada Radio Standards Specification: RSS-247 — Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices, Issue 2, February 2017
Test Plan/Issue/Date	2020-May-12
Order Number	72160507
Date	2020-June-04
Date of Receipt of EUT	2020-July-27
Start of Test	2020-July-30
Finish of Test	2020-September-09
Name of Engineer(s)	Thierry Jean-Charles
Related Document(s)	ANSI C63.10-2013: American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices US Code of Federal Regulations (CFR): Title 47, Part 2, Subpart J: Equipment Authorization Procedures, 2019. FCC OET KDB Publication 558074 D01 15.247 Meas Guidance v05r02: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of the FCC Rules. Innovation, Science and Economic Development Canada Radio Standards Specification: RSS-GEN - General Requirements for Compliance of Radio Apparatus, Issue 5, Amendment 1, March 2019.

1.3 Brief Summary of Results

A brief summary of the tests carried out in accordance with FCC Part 15.247 and ISED Canada's RSS-247 is shown below.

Table 1.3-1: Test Result Summary

Test Parameter	Test Plan (Yes/No)	Test Result	FCC 47 CFR Rule Part	ISED Canada's RSS	Test Report Page No
Antenna Requirement	Yes	Pass	15.203, 15.204	-----	10
6 dB Bandwidth	No	Not Tested	15.247(a)(2)	RSS-247 5.2(a)	
99% Bandwidth	Yes	Pass	-----	RSS-GEN 6.6	11
Peak Output Power	Yes	Pass	15.247(b)(3)	RSS-247 5.4(d)	21
Band-Edge Compliance of RF Conducted Emissions	No	Not Tested	15.247(d)	RSS-247 5.5	
RF Conducted Spurious Emissions	No	Not Tested	15.247(d)	RSS-247 5.5	
Radiated Spurious Emissions into Restricted Frequency Bands	Yes	Pass	15.205, 15.209	RSS-GEN 8.9, 8.10	31
Power Spectral Density	No	Not Tested	15.247(e)	RSS-247 5.2(b)	
Power Line Conducted Emissions	No	Not Tested	15.207	RSS-GEN 8.8	
Duty Cycle	Yes	-----	N/A	N/A	42

1.4 Product Information

1.4.1 Technical Description

The EUT consists of an 802.11a/b/g/n / BLE module. The information provided below applies to the 2.4 GHz Wi-Fi radio.

Technical Details

Mode of Operation:	IEEE 802.11b/g/n
Frequency Range:	802.11b/g/n 20 MHz: 2412 MHz - 2462 MHz 802.11n 40 MHz: 2422 MHz - 2452 MHz
Number of Channels:	802.11b/b/n 20 MHz: 11 802.11 n 40 MHz: 7
Channel Separation:	802.11b/g/n: 5 MHz
Data Rate:	802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n 20 MHz: 6.5, 13, 19.5, 26, 39, 52, 58.5, 65 Mbps 802.11n 40 MHz: 13.5, 27, 40.5, 54, 81, 108, 121.5, 135 Mbps
Modulations:	802.11b: CCK, DSSS 802.11g/n: OFDM
Antenna Type/Gain:	PCB Antenna / 4.13 dBi
Input Power:	120V/60Hz (Host Device)

A full description and detailed product specification details are available from the manufacturer.

Table 1.4.1-1 – Cable Descriptions

Cable/Port	Description
Ethernet	10 m cable from EUT, not shielded, connected to router
USB	30 cm cable from EUT, not shielded, flash drive installed
RS485	65 cm cable from EUT, not shielded, connected to loopback board
AC switch	1.3 m, not shielded
DC wiring	75 cm cable from EUT, not shielded, connected to power supply

Table 1.4.1-2 – Support Equipment Descriptions

Make/Model	Description
Dell / Latitude E7250	Laptop
Welbilt / UI Function Test Adapter Board Ver. A	Adaptor Board
NetGear / N600 Wireless Dual Band Router WNDR3400	Ethernet router
Meanwell/GST36B12-P1J	Power supply
Generic	USB flash drives (2)

Declaration of Build Status

EQUIPMENT DESCRIPTION	
Model Name/Number	WG7833-B0
Part Number	
Hardware Version	Rev. 0.7
Software Version	
FCC ID (if applicable)	2AQ4D-5066500
ISED ID (if applicable)	24291-5066500
Technical Description (Please provide a brief description of the intended use of the equipment)	RF Module, IEEE 802.11a/b/g/n with BT/BLE

UN-INTENTIONAL RADIATOR	
Highest frequency generated or used in the device or on which the device operates or tunes	
Lowest frequency generated or used in the device or on which the device operates or tunes	
Class A Digital Device (Use in commercial, industrial or business environment) ☐	
Class B Digital Device (Use in residential environment only) ☒	

Power Source			
AC	Single Phase	Three Phase	Nominal Voltage
	☒	☐	230 50/60Hz
External DC	Nominal Voltage		Maximum Current
	12 to 24 Vdc		1A
Battery	Nominal Voltage		Battery Operating End Point Voltage

EXTREME CONDITIONS			
Maximum temperature	0	°C	Minimum temperature
			60 °C

Ancillaries
Please list all ancillaries which will be used with the device.

I hereby declare that the information supplied is correct and complete.

Name: Ralph Macy

Position held: Engineering Manager Date: 12/03/2020

1.4.2 Modes of Operation

The EUT was evaluated for the 2.4 GHz Wi-Fi radio while integrated within the 5066500 display host product. The host device was set in typical orientation of installation.

1.4.3 Monitoring of Performance

The EUT was evaluated for TX output power and radiated spurious emissions. The EUT power settings and data rate configurations are provided below:

Table 1.4.3-1: EUT Test Configurations

Mode	Test Command. Power Setting	Data rate	Tested Channels
802.11b	11000	1 Mbps	2412, 2437, 2462 MHz
802.11g	10000	6 Mbps	2412, 2437, 2462 MHz
802.11n 20 MHz	9000	6.5 Mbps	2412, 2437, 2462 MHz
802.11n 40 MHz	7000	13 Mbps	2422, 2437, 2452 MHz

1.4.4 Performance Criteria

The EUT was evaluated for the maximum TX Output Power and and Radiated Spurious Emissions as described below.

Table 1.4.4 -1: Performance Criteria

Parameter	Requirement
Antenna Requirement	FCC: Section 15.203. 15.204
99% Bandwidth	ISED Canada: RSS-GEN 6.6
Peak Output Power	FCC: Section 15.247(b)(3); ISED Canada: RSS-247 5.4(d)
Radiated Spurious Emissions into Restricted Frequency Bands	FCC: Sections 15.205, 15.209; ISED Canada: RSS-GEN 8.9, 8.10

1.5 Deviations from the Standard

The EUT was evaluated without any deviations from the test standards.

1.6 EUT Modification Record

The table below details modifications made to the EUT during the test program. The modifications incorporated during each test are recorded on the appropriate test pages.

Modification State	Description of Modification still fitted to EUT	Modification Fitted By	Date Modification Fitted

The equipment was tested as provided without any modifications.

1.7 Test Location

TÜV SÜD Product Service conducted the following tests at our Tampa FL Test Laboratory.

Test Name	Name of Engineer(s)	Accreditation
AC Powered Operating		
Antenna Requirement	Thierry Jean-Charles	A2LA
99% Bandwidth	Thierry Jean-Charles	A2LA
Peak Output Power	Thierry Jean-Charles	A2LA
Radiated Spurious Emissions into Restricted Frequency Bands	Thierry Jean-Charles	A2LA
Duty Cycle	Thierry Jean-Charles	A2LA

Office Address:

TÜV SÜD America, Inc.
5610 W. Sligh Ave, Suite 100
Tampa, FL 33634
USA

2 Test Details

2.1 Antenna Requirements

2.1.1 Specification Reference

FCC: Section 15.203, 15.204

2.1.2 Equipment Under Test and Modification State

S/N: ACTV1902000016

2.1.3 Date of Test

8/5/2020

2.1.4 Test Method

N/A

2.1.5 Environmental Conditions

Ambient Temperature	N/A
Relative Humidity	N/A
Atmospheric Pressure	N/A

2.1.6 Test Results

Limit Clause FCC Sections: 15.203, 15.204

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

The EUT uses U.FL. connectors at the antenna ports. The antenna connectors are considered unique and therefore meet the requirements of FCC Section 15.203.

2.1.7 Test Location and Test Equipment Used

This test was carried out in TÜV SÜD America, Inc., 5610 W. Sligh Ave, Suite 100, Tampa, FL 33634, USA.

As this is a visual inspection, no test equipment was used.

2.2 99% Bandwidth

2.2.1 Specification Reference

ISED Canada: RSS-GEN 6.7

2.2.2 Equipment Under Test and Modification State

S/N: ACTV1902000016

2.2.3 Date of Test

8/31/2020 to 9/1/2020

2.2.4 Test Method

The 99% occupied bandwidth was measured with the spectrum analyzer span set to fully display the emission. The RBW was set to 1% to 5% of the approximated bandwidth. The occupied 99% bandwidth was measured by using 99% bandwidth equipment function of the spectrum analyzer using a peak detector.

2.2.5 Environmental Conditions

Ambient Temperature 25°C
Relative Humidity 47.7 %
Atmospheric Pressure 1015.6 mbar


2.2.6 Test Results

AC Powered Operating

Limit Clause ISED RSS-GEN 6.7


Table 2.2.6-1: 99% Bandwidth Test Results – 802.11b

Frequency (MHz)	99% Bandwidth (MHz)
2412	14.6111
2437	14.6493
2462	14.6678




Date: 31.AUG.2020 22:09:06

Figure 2.2.6-1: 99% Bandwidth Test Results – 802.11b – Low Channel



Date: 31.AUG.2020 22:21:47

Figure 2.2.6-2: 99% Bandwidth Test Results – 802.11b – Middle Channel




Date: 31.AUG.2020 22:31:00

Figure 2.2.6-3: 99% Bandwidth Test Results – 802.11b – High Channel


Table 2.2.6-2: 99% Bandwidth Test Results – 802.11g

Frequency (MHz)	99% Bandwidth (MHz)
2412	17.0545
2437	17.0218
2462	16.9688




Date: 31.AUG.2020 22:55:00

Figure 2.2.6-4: 99% Bandwidth Test Results – 802.11g – Low Channel



Date: 31.AUG.2020 23:05:48

Figure 2.2.6-5: 99% Bandwidth Test Results – 802.11g – Middle Channel




Date: 31.AUG.2020 23:14:47

Figure 2.2.6-6: 99% Bandwidth Test Results – 802.11g – High Channel

Table 2.2.6-3: 99% Bandwidth Test Results – 802.11n 20 MHz

Frequency (MHz)	99% Bandwidth (MHz)
2412	18.1027
2437	17.9912
2462	17.9739




Date: 31.AUG.2020 23:24:20

Figure 2.2.6-7: 99% Bandwidth Test Results – 802.11n 20 MHz – Low Channel


Table 2.2.6-4: 99% Bandwidth Test Results – 802.11n 40 MHz

Frequency (MHz)	99% Bandwidth (MHz)
2422	36.6000
2437	36.5875
2452	36.5625




Date: 1.SEP.2020 00:03:45

Figure 2.2.6-10: 99% Bandwidth Test Results – 802.11n 40 MHz – Low Channel



Date: 1.SEP.2020 00:12:06

Figure 2.2.6-11: 99% Bandwidth Test Results – 802.11n 40 MHz – Middle Channel



Date: 1.SEP.2020 00:16:48

Figure 2.2.6-12: 99% Bandwidth Test Results – 802.11n 40 MHz – High Channel

2.2.7 Test Location and Test Equipment Used

This test was carried out in TÜV SÜD America, Inc., 5610 W. Sligh Ave, Suite 100, Tampa, FL 33634, USA.

Instrument	Manufacturer	Type No	TE No	Software / Firmware Revision	Calibration Period (months)	Calibration Due
Spectrum Analyzer	Rohde & Schwarz	FSP40	BEMC00283	4.50 SP5	24	04-Oct-2021
Attenuator 20dB, 2.9 mm-M/F, DC-40GHz 2 W	Aeroflex Inmet	40AH2W-20	BEMC02111	N/A	12	24-Jul-2021
Duratest High Frequency Cable 26.5GHz	Teledyne Storm Products	921-0101-036	BEMC02112	N/A	12	12-Oct-2020

TU - Traceability Unscheduled

O/P MON - Traceability Unscheduled

N/A - Not Applicable

2.3 Peak Output Power

2.3.1 Specification Reference

FCC Section 15.247(b)(3)
ISED Canada: RSS-247 5.4(d)

2.3.2 Equipment Under Test and Modification State

S/N: ACTV1902000016

2.3.3 Date of Test

8/31/2020 to 9/1/2020

2.3.4 Test Method

The fundamental emission output power was measured in accordance with ANSI C63.10 Subclause 11.9.2.2.4 Method AVGSA-2. The RF output of the equipment under test was directly connected to the input of the spectrum analyzer through suitable attenuation.

The duty cycle correction factor test results are provided in Section 2.5 of this document.

2.3.5 Environmental Conditions

Ambient Temperature 25°C
Relative Humidity 47.7 %
Atmospheric Pressure 1015.6 mbar

2.3.6 Test Results


AC Powered Operating

Limit Clause FCC Part 15.247(b)(3), ISED RSS-247 5.4(d)

The Maximum Output Power allowed for systems using digital modulation is 1 Watt (30 dBm)


Table 2.4.6-1: Maximum Output Power Results – 802.11 b

Frequency (MHz)	Measured Output Power (dBm)	Duty Cycle Correction (dB)	Corrected Output Power (dBm)
2412	9.40	0.24	9.64
2437	9.75	0.24	9.99
2462	9.97	0.24	10.21




Date: 31.AUG.2020 22:11:34

Figure 2.4.6-1: Maximum Output Power Results – 802.11b Low Channel



Date: 31.AUG.2020 22:24:04

Figure 2.4.6-2: Maximum Output Power Results – 802.11b Middle Channel




Date: 31.AUG.2020 22:33:11

Figure 2.4.6-3: Maximum Output Power Results – 802.11b High Channel


Table 2.4.6-2: Maximum Output Power Results – 802.11g

Frequency (MHz)	Measured Output Power (dBm)	Duty Cycle Correction (dB)	Corrected Output Power (dBm)
2412	7.36	1.31	8.67
2437	7.53	1.31	8.84
2462	7.72	1.31	9.03




Date: 31.AUG.2020 22:57:17

Figure 2.4.6-4: Maximum Output Power Results – 802.11g Low Channel



Date: 31.AUG.2020 23:07:59

Figure 2.4.6-5: Maximum Output Power Results – 802.11g Middle Channel




Date: 31.AUG.2020 23:16:54

Figure 2.4.6-6: Maximum Output Power Results – 802.11g High Channel


Table 2.4.6-3: Maximum Output Power Results – 802.11n 20 MHz

Frequency (MHz)	Measured Output Power (dBm)	Duty Cycle Correction (dB)	Corrected Output Power (dBm)
2412	6.79	1.39	8.18
2437	6.72	1.39	8.11
2462	6.78	1.39	8.17




Date: 31.AUG.2020 23:26:29

Figure 2.4.6-7: Maximum Output Power Results – 802.11n 20 MHz Low Channel



Date: 31.AUG.2020 23:35:45

Figure 2.4.6-8: Maximum Output Power Results – 802.11n 20 MHz Middle Channel




Date: 31.AUG.2020 23:45:35

Figure 2.4.6-9: Maximum Output Power Results – 802.11n 20 MHz High Channel


Table 2.4.6-4: Maximum Output Power Results – 802.11n 40 MHz

Frequency (MHz)	Measured Output Power (dBm)	Duty Cycle Correction (dB)	Corrected Output Power (dBm)
2422	3.67	2.46	6.13
2437	3.31	2.46	5.77
2452	3.33	2.46	5.79




Date: 1.SEP.2020 00:08:50

Figure 2.4.6-10: Maximum Output Power Results – 802.11n 40 MHz Low Channel



Date: 1.SEP.2020 00:14:14

Figure 2.4.6-11: Maximum Output Power Results – 802.11n 40 MHz Middle Channel



Date: 1.SEP.2020 00:18:56

Figure 2.4.6-12: Maximum Output Power Results – 802.11n 40 MHz High Channel

2.3.7 Test Location and Test Equipment Used

This test was carried out in TÜV SÜD America, Inc., 5610 W. Sligh Ave, Suite 100, Tampa, FL 33634, USA.

Instrument	Manufacturer	Type No	TE No	Software / Firmware Revision	Calibration Period (months)	Calibration Due
Spectrum Analyzer	Rohde & Schwarz	FSP40	BEMC00283	4.50 SP5	24	04-Oct-2021
Attenuator 20dB, 2.9 mm- M/F, DC-40GHz 2 W	Aeroflex Inmet	40AH2W-20	BEMC02111	N/A	12	24-Jul-2021
Duratest High Frequency Cable 26.5GHz	Teledyne Storm Products	921-0101-036	BEMC02112	N/A	12	12-Oct-2020

TU - Traceability Unscheduled

O/P MON - Traceability Unscheduled

N/A - Not Applicable

2.4 Radiated Spurious Emissions into Restricted Frequency Bands

2.4.1 Specification Reference

FCC Sections: 15.205, 15.209;
ISED Canada: RSS-GEN 8.9, 8.10

2.4.2 Equipment Under Test and Modification State

S/N: ACVT1902000023

2.4.3 Date of Test

7/30/2020 to 9/9/2020

2.4.4 Test Method

Radiated emissions tests were made over the frequency range of 9 kHz to 26 GHz, 10 times the highest fundamental frequency. Each emission found to be in a restricted band as defined by section 15.205, including any emission at the operational band-edge, was compared to the radiated emission limits as defined in Section 15.209.

For measurements below 30 MHz, the receive antenna height was set to 1 m and the EUT was rotated through 360 degrees. The resolution bandwidth was set to 200 Hz below 150 kHz and to 9 kHz above 150 kHz.

The EUT was rotated through 360° and the receive antenna height was varied from 1m to 4m so that the maximum radiated emissions level would be detected. For frequencies below 1000 MHz, quasi-peak measurements were made using a resolution bandwidth RBW of 120 kHz and a video bandwidth VBW of 300 kHz. For frequencies above 1000 MHz, peak measurements are made with RBW of 1 MHz and VBW of 3 MHz. Average measurements are performed in the linear scale using VBW of 1 kHz.

2.4.5 Duty Cycle Correction

No duty cycle correction factor was used during the evaluation for radiated emissions.

2.4.6 Environmental Conditions

Ambient Temperature	24.3 °C
Relative Humidity	49.2 %
Atmospheric Pressure	1013.6 mbar

2.4.7 Test Results

AC Powered Operating

Limit Clause FCC Sections 15.205, 15.209, ISED Canada: RSS-GEN 8.9, 8.10

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009-0.490	2400/F(kHz)	300
0.4090-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

Table 2.4.7-1: Radiated Emissions Test Results - 802.11b

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
Low Channel										
2390	56.00	45.69	H	-5.22	50.78	40.47	74.0	54.0	23.2	13.5
2390	63.40	57.51	V	-5.22	58.18	52.29	74.0	54.0	15.8	1.7
4824	50.01	45.89	H	-0.18	49.83	45.71	74.0	54.0	24.2	8.3
4824	55.07	52.90	V	-0.18	54.89	52.72	74.0	54.0	19.1	1.3
14472	43.03	35.14	H	11.55	54.58	46.69	74.0	54.0	19.4	7.3
14472	41.71	30.70	V	11.55	53.26	42.25	74.0	54.0	20.7	11.8
19296	40.85	34.29	H	11.72	52.57	46.01	83.5	63.5	30.9	17.5
19296	39.84	29.65	V	11.72	51.56	41.37	83.5	63.5	31.9	22.1
Middle Channel										
4874	48.87	44.41	H	-0.10	48.77	44.31	74.0	54.0	25.2	9.7
4874	55.64	53.48	V	-0.10	55.54	53.38	74.0	54.0	18.5	0.6
7311	42.75	31.72	H	3.71	46.46	35.43	74.0	54.0	27.5	18.6
7311	42.76	31.64	V	3.71	46.47	35.35	74.0	54.0	27.5	18.7
19496	40.36	32.26	H	11.64	52.00	43.90	83.5	63.5	31.5	19.6
19496	39.18	29.63	V	11.64	50.82	41.27	83.5	63.5	32.7	22.2
High Channel										
2483.5	55.37	44.07	H	-5.05	50.32	39.02	74.0	54.0	23.7	15.0
2483.5	59.76	49.77	V	-5.05	54.71	44.72	74.0	54.0	19.3	9.3
4924	48.12	43.13	H	-0.01	48.11	43.12	74.0	54.0	25.9	10.9
4924	55.52	53.32	V	-0.01	55.51	53.31	74.0	54.0	18.5	0.7
7386	43.91	32.56	H	3.76	47.67	36.32	74.0	54.0	26.3	17.7
7386	43.69	32.00	V	3.76	47.45	35.76	74.0	54.0	26.5	18.2
19696	39.96	32.90	H	11.66	51.62	44.56	83.5	63.5	31.9	18.9
19696	38.64	29.06	V	11.66	50.30	40.72	83.5	63.5	33.2	22.8

Notes:

- All emissions above 19.7 GHz were attenuated below the limits and the noise floor of the measurement equipment.
- The emissions above 18 GHz were measured at a test distance of 1 m. The limits are adjusted accordingly using the distance factor of $20 \cdot \log(3/1) = 9.5$ dB.

Table 2.4.7-2: Radiated Emissions Test Results - 802.11g

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
Low Channel										
2390	60.42	45.46	H	-5.22	55.20	40.24	74.0	54.0	18.8	13.8
2390	75.94	58.08	V	-5.22	70.72	52.86	74.0	54.0	3.3	1.1
4824	45.35	35.45	H	-0.18	45.17	35.27	74.0	54.0	28.8	18.7
4824	55.28	46.32	V	-0.18	55.10	46.14	74.0	54.0	18.9	7.9
14472	41.56	34.99	H	11.55	53.11	46.54	74.0	54.0	20.9	7.5
14472	39.77	29.22	V	11.55	51.32	40.77	74.0	54.0	22.7	13.2
19296	41.06	33.73	H	11.72	52.78	45.45	83.5	63.5	30.7	18.1
19296	39.22	28.53	V	11.72	50.94	40.25	83.5	63.5	32.6	23.3
Middle Channel										
4874	44.81	35.87	H	-0.10	44.71	35.77	74.0	54.0	29.3	18.2
4874	54.83	46.03	V	-0.10	54.73	45.93	74.0	54.0	19.3	8.1
7311	41.06	29.65	H	3.71	44.77	33.36	74.0	54.0	29.2	20.6
7311	40.36	29.58	V	3.71	44.07	33.29	74.0	54.0	29.9	20.7
19496	40.35	33.21	H	11.64	51.99	44.85	83.5	63.5	31.5	18.6
19496	39.99	29.03	V	11.64	51.63	40.67	83.5	63.5	31.9	22.8
High Channel										
2483.5	62.28	46.01	H	-5.05	57.23	40.96	74.0	54.0	16.8	13.0
2483.5	75.97	55.75	V	-5.05	70.92	50.70	74.0	54.0	3.1	3.3
4924	46.42	37.70	H	-0.01	46.41	37.69	74.0	54.0	27.6	16.3
4924	53.50	45.86	V	-0.01	53.49	45.85	74.0	54.0	20.5	8.2
7386	40.37	29.89	H	3.76	44.13	33.65	74.0	54.0	29.9	20.3
7386	41.45	29.77	V	3.76	45.21	33.53	74.0	54.0	28.8	20.5
19696	40.90	33.39	H	11.66	52.56	45.05	83.5	63.5	30.9	18.4
19696	39.39	30.44	V	11.66	51.05	42.10	83.5	63.5	32.4	21.4

Notes:

- All emissions above 19.7 GHz were attenuated below the limits and the noise floor of the measurement equipment.
- The emissions above 18 GHz were measured at a test distance of 1 m. The limits are adjusted accordingly using the distance factor of $20 \cdot \log(3/1) = 9.5$ dB.

Table 2.4.7-3: Radiated Emissions Test Results - 802.11n 20 MHz

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
Low Channel										
2390	63.05	45.98	H	-5.22	57.83	40.76	74.0	54.0	16.2	13.2
2390	77.21	58.29	V	-5.22	71.99	53.07	74.0	54.0	2.0	0.9
4824	44.08	35.15	H	-0.18	43.90	34.97	74.0	54.0	30.1	19.0
4824	53.52	45.03	V	-0.18	53.34	44.85	74.0	54.0	20.7	9.2
14472	41.51	35.09	H	11.55	53.06	46.64	74.0	54.0	20.9	7.4
14472	39.48	29.16	V	11.55	51.03	40.71	74.0	54.0	23.0	13.3
19296	40.89	34.02	H	11.72	52.61	45.74	83.5	63.5	30.9	17.8
19296	39.31	29.70	V	11.72	51.03	41.42	83.5	63.5	32.5	22.1
Middle Channel										
4874	43.91	35.32	H	-0.10	43.81	35.22	74.0	54.0	30.2	18.8
4874	53.73	45.27	V	-0.10	53.63	45.17	74.0	54.0	20.4	8.8
19496	40.72	33.20	H	11.64	52.36	44.84	83.5	63.5	31.1	18.7
19496	39.62	28.48	V	11.64	51.26	40.12	83.5	63.5	32.2	23.4
High Channel										
2483.5	61.58	44.85	H	-5.05	56.53	39.80	74.0	54.0	17.5	14.2
2483.5	73.77	55.01	V	-5.05	68.72	49.96	74.0	54.0	5.3	4.0
4924	44.12	35.57	H	-0.01	44.11	35.56	74.0	54.0	29.9	18.4
4924	52.34	45.32	V	-0.01	52.33	45.31	74.0	54.0	21.7	8.7
19696	40.03	31.34	H	11.66	51.69	43.00	83.5	63.5	31.8	20.5
19696	38.95	29.23	V	11.66	50.61	40.89	83.5	63.5	32.9	22.6

Notes:

- All emissions above 19.7 GHz were attenuated below the limits and the noise floor of the measurement equipment.
- The emissions above 18 GHz were measured at a test distance of 1 m. The limits are adjusted accordingly using the distance factor of $20 \cdot \log(3/1) = 9.5$ dB.

Table 2.4.7-4: Radiated Emissions Test Results - 802.11n 40 MHz

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
Low Channel										
2390	58.59	45.19	H	-5.22	53.37	39.97	74.0	54.0	20.6	14.0
2390	76.41	58.68	V	-5.22	71.19	53.46	74.0	54.0	2.8	0.5
4844	42.59	34.53	H	-0.15	42.44	34.38	74.0	54.0	31.6	19.6
4844	49.73	43.44	V	-0.15	49.58	43.29	74.0	54.0	24.4	10.7
19376	40.63	33.19	H	11.69	52.32	44.88	83.5	63.5	31.2	18.6
19376	39.87	29.71	V	11.69	51.56	41.40	83.5	63.5	31.9	22.1
Middle Channel										
4874	43.23	35.25	H	-0.10	43.13	35.15	74.0	54.0	30.9	18.8
4874	48.35	43.23	V	-0.10	48.25	43.13	74.0	54.0	25.7	10.9
19496	40.92	33.34	H	11.64	52.56	44.98	83.5	63.5	30.9	18.5
19496	39.85	29.19	V	11.64	51.49	40.83	83.5	63.5	32.0	22.7
High Channel										
2483.5	55.24	43.92	H	-5.05	50.19	38.87	74.0	54.0	23.8	15.1
2483.5	72.37	55.85	V	-5.05	67.32	50.80	74.0	54.0	6.7	3.2
4904	43.14	35.63	H	-0.04	43.10	35.59	74.0	54.0	30.9	18.4
4904	48.52	43.40	V	-0.04	48.48	43.36	74.0	54.0	25.5	10.6
19616	40.75	33.73	H	11.65	52.40	45.38	83.5	63.5	31.1	18.1
19616	39.25	29.56	V	11.65	50.90	41.21	83.5	63.5	32.6	22.3

Notes:

- All emissions above 19.7 GHz were attenuated below the limits and the noise floor of the measurement equipment.
- The emissions above 18 GHz were measured at a test distance of 1 m. The limits are adjusted accordingly using the distance factor of $20 \cdot \log(3/1) = 9.5$ dB.




Figure 2.4.7-1: Radiated Emissions Representative Scan – below 30 MHz




Figure 2.4.7-2: Radiated Emissions Representative Scan – 30 MHz – 1 GHz – Horizontal Polarization




Figure 2.4.7-3: Radiated Emissions Representative Scan – 30 MHz – 1 GHz – Vertical Polarization




Figure 2.4.7-4: Radiated Emissions Representative Scan – 1 GHz – 18 GHz – Horizontal Polarization




Figure 2.4.7-5: Radiated Emissions Representative Scan – 1 GHz – 18 GHz – Vertical Polarization




Figure 2.4.7-6: Radiated Emissions Representative Scan – 18 GHz – 26.5 GHz – Horizontal Polarization




Figure 2.4.7-7: Radiated Emissions Representative Scan – 18 GHz – 26.5 GHz – Vertical Polarization

2.4.8 Sample Calculations

$$R_C = R_U + CF_T$$

Where:

CF_T	=	Total Correction Factor (AF+CA+AG)-DC (Average Measurements Only)
R_U	=	Uncorrected Reading
R_C	=	Corrected Level
AF	=	Antenna Factor
CA	=	Cable Attenuation
AG	=	Amplifier Gain
DC	=	Duty Cycle Correction Factor

Example Calculation: Peak

Corrected Level: $56 + (-5.22) = 50.78 \text{ dB}\mu\text{V/m}$

Margin: $74 \text{ dB}\mu\text{V/m} - 50.78 \text{ dB}\mu\text{V/m} = 23.22 \text{ dB}$

Example Calculation: Average

Corrected Level: $45.69 + (-5.22) - 0 = 40.47 \text{ dB}\mu\text{V/m}$

Margin: $54 \text{ dB}\mu\text{V/m} - 40.47 \text{ dB}\mu\text{V/m} = 13.53 \text{ dB}$

2.4.9 Test Location and Test Equipment Used

This test was carried out in TÜV SÜD America, Inc., 5610 W. Sligh Ave, Suite 100, Tampa, FL 33634, USA.

Instrument	Manufacturer	Type No	TE No	Software / Firmware Revision	Calibration Period (months)	Calibration Due
9kHz-26.5GHz EMC analyzer/HYZ	Agilent	E7405A	BEMC00523	A.14.06	24	27-Nov-2020
10dB Attenuator	Merrimac	FAN-6-10K	BEMC02086	N/A	12	12-Oct-2020
Tile Automation Software	ETS Lindgren	TILE4! - Version 4.2.A	BEMC02095	4.2A	N/A	NCR
BI LOG PERIODIC, ANTENNA	Schaffner	CBL6112B	TEMC00005	N/A	24	31-Oct-2021
Loop Antenna	Com Power	AL-130	TEMC00025	N/A	24	26-Sep-2021
Horn Antenna	Schwarzbeck	BBHA-9170	TEMC00029	N/A	60	23-Aug-2021
EMC Chamber	Panashield	N/A	TEMC00031	N/A	36	28-Jan-2021
Double Ridge Guide Horn	ETS Lindgren	3117	TEMC00061	N/A	24	07-Feb-2022
18 GHz-40 GHz Microwave Preamplifier	COM-power	PAM-840A	TEMC00147	N/A	12	16-Mar-2021
PAM-118A	Com-Power Corporation	PAM-118A	TEMC00160	N/A	12	16-Mar-2021
2.4 GHz Notch Filter	Micro-Tronics	BRM50702-01	TEMC00176	N/A	12	12-Mar-2021
A81-0303 18 GHz Cable Set	Teledyne Storm Products	A81-0303-360/96	TEMC00201	N/A	12	22-Apr-2021
1571AN 40 GHz Cable	IW Microwave	KPS-1571AN	TEMC00218	N/A	12	06-Jul-2021

TU - Traceability Unscheduled
O/P MON - Traceability Unscheduled
N/A - Not Applicable
NCR – No Calibration Required

2.5 Duty Cycle

2.5.1 Specification Reference

None

2.5.2 Equipment Under Test and Modification State

S/N: ACTV1902000016

2.5.3 Date of Test

9/9/2020

2.5.4 Test Method

The duty cycle was measured in accordance with ANSI C63.10 Section 11.6 Duty cycle (D), transmission duration (T), and maximum power control level. The unit was connected directly to the input of the spectrum analyzer via suitable attenuation. The RBW and VBW were set to 10 MHz and the number of sweep points across duration T was set to exceed 100.

2.5.5 Environmental Conditions

Ambient Temperature 26.6 °C
Relative Humidity 43.4 %
Atmospheric Pressure 1016.2 mbar


2.5.6 Test Results

AC Powered Operating

Table 2.5.6-5: Duty Cycle Correction


Mode	Time On (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction (dB)
802.11b	8.44	8.9225	0.95	0.24
802.11g	1.4	1.8945	0.74	1.31
802.11n 20 MHz	1.308	1.803	0.73	1.39
802.11n 40 MHz	0.647625	1.141375	0.57	2.46

Note: duty Cycle Correction = $10 * \log(1/(\text{Time On} / \text{Period}))$




Date: 9.SEP.2020 23:40:42

Figure 2.5.6-1: Duty Cycle – 802.11b




Date: 9.SEP.2020 23:46:36

Figure 2.5.6-2: Duty Cycle – 802.11g



Date: 9.SEP.2020 23:49:47

Figure 2.5.6-3: Duty Cycle – 802.11n 20 MHz



Date: 9.SEP.2020 23:53:39

Figure 2.5.6-4: Duty Cycle – 802.11n 40 MHz

2.5.7 Test Location and Test Equipment Used

This test was carried out in TÜV SÜD America, Inc., 5610 W. Sligh Ave, Suite 100, Tampa, FL 33634, USA.

Instrument	Manufacturer	Type No	TE No	Software / Firmware Revision	Calibration Period (months)	Calibration Due
Spectrum Analyzer	Rohde & Schwarz	FSP40	BEMC00283	4.50 SP5	24	04-Oct-2021
Attenuator 20dB, 2.9 mm- M/F, DC-40GHz 2 W	Aeroflex Inmet	40AH2W-20	BEMC02111	N/A	12	24-Jul-2021
Duratest High Frequency Cable 26.5GHz	Teledyne Storm Products	921-0101-036	BEMC02112	N/A	12	12-Oct-2020

TU - Traceability Unscheduled

O/P MON - Traceability Unscheduled

N/A - Not Applicable

3 Test Equipment Information

3.1 General Test Equipment Used

Instrument	Manufacturer	Type No	TE No	Software / Firmware Revision	Calibration Period (months)	Calibration Due
9kHz-26.5GHz EMC analyzer/HYZ	Agilent	E7405A	BEMC00523	A.14.06	24	27-Nov-2020
10dB Attenuator	Merrimac	FAN-6-10K	BEMC02086	N/A	12	12-Oct-2020
Tile Automation Software	ETS Lindgren	TILE4! - Version 4.2.A	BEMC02095	4.2A	N/A	NCR
BI LOG PERIODIC, ANTENNA	Schaffner	CBL6112B	TEMC00005	N/A	24	31-Oct-2021
Loop Antenna	Com Power	AL-130	TEMC00025	N/A	24	26-Sep-2021
Horn Antenna	Schwarzbeck	BBHA-9170	TEMC00029	N/A	60	23-Aug-2021
EMC Chamber	Panashield	N/A	TEMC00031	N/A	36	28-Jan-2021
Double Ridge Guide Horn	ETS Lindgren	3117	TEMC00061	N/A	24	07-Feb-2022
18 GHz-40 GHz Microwave Preamplifier	COM-power	PAM-840A	TEMC00147	N/A	12	16-Mar-2021
PAM-118A	Com-Power Corporation	PAM-118A	TEMC00160	N/A	12	16-Mar-2021
2.4 GHz Notch Filter	Micro-Tronics	BRM50702-01	TEMC00176	N/A	12	12-Mar-2021
A81-0303 18 GHz Cable Set	Teledyne Storm Products	A81-0303-360/96	TEMC00201	N/A	12	22-Apr-2021
1571AN 40 GHz Cable	IW Microwave	KPS-1571AN	TEMC00218	N/A	12	06-Jul-2021
Spectrum Analyzer	Rohde & Schwarz	FSP40	BEMC00283	4.50 SP5	24	04-Oct-2021
Attenuator 20dB, 2.9 mm-M/F, DC-40GHz 2 W	Aeroflex Inmet	40AH2W-20	BEMC02111	N/A	12	24-Jul-2021
Duratest High Frequency Cable 26.5GHz	Teledyne Storm Products	921-0101-036	BEMC02112	N/A	12	12-Oct-2020

TU - Traceability Unscheduled
O/P MON - Traceability Unscheduled
N/A - Not Applicable
NCR – No Calibration Required

4 Diagram of Test Set-ups




Figure 4-1 - Radiated Emissions Test Setup up to 1 GHz




Figure 4-2 - Radiated Emissions Test Setup above 1 GHz




Figure 4-3 - Radiated Emissions Test Setup below 30 MHz




Figure 4-4 – Conducted Emissions Test Setup

5 Measurement Uncertainty

For a 95% confidence level, the measurement uncertainties for defined systems are:

Table 5-1 - Values of U_{CISPR} and U_{Lab}

Measurement	U_{CISPR}	U_{Lab}
Conducted disturbance (mains port) (9 kHz – 150 kHz) (150 kHz – 30 MHz)	3.8 dB 3.4 dB	3.71 dB 3.31 dB
Conducted disturbance (telecom port) (150 kHz – 30 MHz 55 dB LCL) (150 kHz – 30 MHz 65 dB LCL) (150 kHz – 30 MHz 75 dB LCL)	5.0 dB 5.0 dB 5.0 dB	4.11 dB 4.50 dB 4.94 dB
Radiated disturbance (electric field strength on an open area test site or alternative test site) (30 MHz – 1 000 MHz) (1 – 6 GHz) (6-18 GHz)	6.3 dB 5.2 dB 5.5 dB	5.85 dB 4.48 dB 4.48 dB

Notes:

U_{CISPR} resembles a value of measurement uncertainty for a specific test, which was determined by considering uncertainties associated with the quantities listed in CISPR 16-4-2:2011.

6 Accreditation, Disclaimers and Copyright

TÜV SÜD America Inc.'s reports apply only to the specific sample tested under stated test conditions. It is the manufacturer's responsibility to assure the continued compliance of production units of this model. TÜV SÜD America, Inc. shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD America, Inc.'s issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and TÜV SÜD America, Inc., extracts from the test report shall not be reproduced, except in full without TÜV SÜD America, Inc.'s written approval.

This report must not be used to claim product certification, approval, or endorsement by A2LA, NIST, or any agency of the federal government.