

SPECIFICATIONS

PengBanXingYe ShenZhen Technology Co. , Ltd
Address: Room 608, Building 4, 1970 Science and
Technology Town, Minzhi Street, Longhua
District, Shenzhen.

客户:

CUSTOMER: _____

产品名称:

DESCRIPTION: PBX2012MA04

客户型号:

CUSTOMER PART NO: _____

产品型号:

OUR MODEL NO: PBX2012MA04

日期:

DATE: _____

确认签字, 盖章后请返回承认书一份

PLEASE RETURN TO US ONE COPY OF "SPECIFICATION FOR
APPROVAL" WITH YOUR APPROVED SIGNATURES

核准	王海	审核	刘飞	制作	刘小美
----	----	----	----	----	-----

客户确认签章(APPROVED SIGNATURE)

--	--	--	--

PBX2012MA04 Specification


Operating Temp. : -40°C~+85°C

1. FEATURES:


- Light weight, compact
- Wide bandwidth, low cost
- Built-in antenna with high gain

2. APPLICATIONS:

- Bluetooth, Wireless LAN, Mobile TV
- Home RF System, etc



3. PRODUCT IDENTIFICATION

(1) Product type: Multilayer chip Antenna
 (2) External Dimensions (L×W) (mm): 2.0*1.2

4. SHAPE AND DIMENSIONS:**SHAPE AND DIMENSIONS**

L	W	H	A
2.0±0.2	1.2±0.2	0.55±0.1	0.4±0.1

UNLESS OTHER SPECIFIED TOLERANCES ON: X=± X.X=± X.XX=± ANGLES =± HOLEDIA =±		 深圳市朋伴兴业科技有限公司 <small>PENGBANXING</small>	
SCALE: N/A UNIT: mm		THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF PBXY TECHNOLOGY Limited AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
DRAWN BY : Sera CHECKED BY: XD			
DESIGNED BY: Sera APPROVED BY: XD			
TITLE: CHIP2450-21 Specification		DOCUMENT NO.	2012
			SPEC REV.
			P1

TERMINAL-CONFIGURATION**EVALUATION BOARD****APPLICATION GUIDE**

UNLESS OTHER SPECIFIED TOLERANCES ON:
 $X = \pm$ $X.X = \pm$ $X.XX = \pm$
 $\text{ANGLES} = \pm$ $\text{HOLE DIA} = \pm$



深圳市朋伴兴业科技有限公司

SCALE: N/A UNIT: mm
 DRAWN BY: Sera CHECKED BY: XD
 DESIGNED BY: Sera APPROVED BY: XD

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF PBXY TECHNOLOGY Limited AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE: CHIP2450-21 Specification

DOCUMENT NO.

2012

SPEC REV.
P1

5. SPECIFICATIONS:


ITEM	SPECIFICATION
Frequency Band	2400MHz~2483MHz
VSWR	Less than 3
Polarization	Linear
*Peak Gain	-1.0dBi
*Peak Efficiency	72. 6% Typ.
Impedance	50 Ω Typ.

* Test condition: Test board size 98*65 mm

Matching circuit: Pi matching circuit will be required

6. Electrical Characteristics :

VSWR




Mark	Frequency	VSWR
1	2400 MHz	3.04
2	2450 MHz	1.15
3	2500 MHz	2.57


UNLESS OTHER SPECIFIED TOLERANCES ON: X=± X.X=± X.XX=± ANGLES =± HOLEDIA =±		 深圳市朋伴兴业科技有限公司
SCALE: N/A UNIT: mm		THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF PBXY TECHNOLOGY Limited AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION
DRAWN BY : Sera CHECKED BY: XD		
DESIGNED BY: Sera APPROVED BY: XD		
TITLE: CHIP2450-21 Specification		DOCUMENT NO. 2012
		SPEC REV. P1

Radiation Pattern


The Gain pattern is measured in INPAQ's FAR-field chamber. DUT is placed on the table of rotator, a standard horn antenna and Vector Network Analyzer is used to collect data.



◎ 3D Gain Pattern (2400 MHz_Max gain)



◎ 2D Gain Pattern (2400 MHz_Max gain)



UNLESS OTHER SPECIFIED TOLERANCES ON:

$X = \pm$ $X.X = \pm$ $X.XX =$
ANGLES $= \pm$ **HOLE DIA** $= \pm$

SCALE: N/A **UNIT:** mm

DRAWN BY: Sera **CHECKED BY:** XD

DESIGNED BY: Sera **APPROVED BY:** XD



深圳市朋伴兴业科技有限公司

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF PBXY TECHNOLOGY Limited AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE: CHIP2450-21 Specification

DOCUMENT NO.

2012

SPEC REV.
P1