

FCC TEST REPORT

For

FUJIAN NANPING NANFU BATTERY CO.,LTD

Wireless Charger

Model No.: EAC012

Prepared For : FUJIAN NANPING NANFU BATTERY CO.,LTD

Address : 109 Industry Road, Nanping, Fujian, China

Prepared By : Shenzhen Anbotek Compliance Laboratory Limited

Address : 1/F, Building D, Sogood Science and Technology Park, Sanwei
community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong,
China.518102

Tel: (86) 755-26066440 Fax: (86) 755-26014772

Report Number : SZAWW180820004-01

Date of Receipt : Aug. 20, 2018

Date of Test : Aug. 20~Sept. 04, 2018

Date of Report : Sept. 04, 2018

Contents

1. General Information.....	4
1.1. Client Information.....	4
1.2. Description of Device (EUT).....	4
1.3. Auxiliary Equipment Used During Test.....	4
1.4. Description of Test Modes.....	5
1.5. List of channels.....	5
1.6. Description Of Test Setup.....	6
1.7. Test Equipment List.....	7
1.8. Description of Test Facility.....	8
2. Summary of Test Results.....	9
3. Conducted Emission Test.....	10
3.1. Test Standard and Limit.....	10
3.2. Test Setup.....	10
3.3. Test Procedure.....	10
3.4. Test Data.....	10
4. Radiation Spurious Emission and Band Edge.....	15
4.1. Test Standard and Limit.....	15
4.2. Test Setup.....	15
4.3. Test Procedure.....	16
4.4. Test Data.....	17
5. Antenna Requirement.....	23
5.1. Test Standard and Requirement.....	23
5.2. Antenna Connected Construction.....	23
APPENDIX I -- TEST SETUP PHOTOGRAPH.....	24
APPENDIX II -- EXTERNAL PHOTOGRAPH.....	26
APPENDIX III -- INTERNAL PHOTOGRAPH.....	29

TEST REPORT

Applicant : FUJIAN NANPING NANFU BATTERY CO.,LTD
Manufacturer : FUJIAN NANPING NANFU BATTERY CO.,LTD
Product Name : Wireless Charger
Model No. : EAC012
Trade Mark : NANFU
Rating(s) : Input: DC 5V, 2A/ DC 9V, 1.8A
Output: 5W/ 7.5W/ 10W

Test Standard(s) : FCC Part15 Subpart C 2017, Paragraph 15.209

Test Method(s) : ANSI C63.10: 2013


The device described above is tested by Shenzhen Anbotech Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotech Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotech Compliance Laboratory Limited.

Date of Test

Aug. 20~Sept. 04, 2018

Prepared by



(Engineer / Oliay Yang)

Reviewer

(Supervisor / Calvin Liu)

Approved & Authorized Signer

(Manager / Tom Chen)

1. General Information

1.1. Client Information

Applicant	:	FUJIAN NANPING NANFU BATTERY CO.,LTD
Address	:	109 Industry Road, Nanping, Fujian, China
Manufacturer	:	FUJIAN NANPING NANFU BATTERY CO.,LTD
Address	:	109 Industry Road, Nanping, Fujian, China

1.2. Description of Device (EUT)

Product Name	:	Wireless Charger
Model No.	:	EAC012
Trade Mark	:	NANFU
Test Power Supply	:	AC 120V, 60Hz for adapter / AC 240V, 60Hz for adapter
Test Sample No.	:	S1, S2
Product Description	Operation Frequency:	111-200KHz
	Number of Channel:	19 Channels
	Modulation Type:	ASK
	Antenna Type:	Loop Antenna
	Antenna Gain(Peak):	0 dBi
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		

1.3. Auxiliary Equipment Used During Test

Adapter	:	Model: A2013 Input: 100-240V 50-60Hz 0.7A Output: 3.6-6.5V--- 3A/ 6.5-9V--- 2A/ 9-12V--- 1.5A
Mobile Phone	:	Samsung

1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH01
Mode 2	CH10
Mode 3	CH20
Mode 4	Keeping TX+Charging mode



For Conducted Emission	
Final Test Mode	Description
Mode 4	Keeping TX+Charging mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH01
Mode 2	CH10
Mode 3	CH20
Mode 4	Keeping TX+Charging mode

1.5. List of channels

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
1	0.111	6	0.135	11	0.160	16	0.185
2	0.115	7	0.140	12	0.165	17	0.190
3	0.120	8	0.145	13	0.170	18	0.195
4	0.125	9	0.150	14	0.175	19	0.200
5	0.130	10	0.155	15	0.180	20	0.205

1.6. Description Of Test Setup



1.7. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Nov. 17, 2017	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Nov. 17, 2017	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Nov. 17, 2017	1 Year
4.	Spectrum Analysis	Agilent	E4407B	US39390582	Nov. 17, 2017	1 Year
5.	Spectrum Analysis	Agilent	N9038A	MY53227295	Nov. 17, 2017	1 Year
6.	Preamplifier	SKET Electronic	BK1G18G30D	KD17503	Nov. 17, 2017	1 Year
7.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Nov. 17, 2017	1 Year
8.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Nov. 20, 2017	1 Year
9.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Nov. 20, 2017	1 Year
10.	Loop Antenna	Schwarzbeck	HFH2-Z2	100047	Nov. 17, 2017	1 Year
11.	Horn Antenna	Schwarzbeck	BBHA9170	9170-375	Nov. 17, 2017	1 Year
12.	Pre-amplifier	SONOMA	310N	186860	Nov. 17, 2017	1 Year
13.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
14.	RF Test Control System	YIHENG	YH3000	2017430	Nov. 18, 2017	1 Year
15.	Power Sensor	DAER	RPR3006W	15I00041SN045	Nov. 17, 2017	1 Year
16.	Power Sensor	DAER	RPR3006W	15I00041SN046	Nov. 17, 2017	1 Year
17.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 18, 2017	1 Year
18.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Nov. 18, 2017	1 Year
19.	Signal Generator	Agilent	E4421B	MY41000743	Nov. 18, 2017	1 Year
20.	DC Power Supply	LW	TPR-6410D	349315	Nov. 01, 2017	1 Year
21.	Constant Temperature Humidity Chamber	Sertep	ZJ-HWHS80B	ZJ-17042804	Nov. 01, 2017	1 Year

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, July 31, 2017.

ISED-Registration No.: 8058A-1

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A-1, June 13, 2016.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102

2. Summary of Test Results


Standard Section	Test Item	Result
FCC Part 15, Paragraph 15.207	Conducted Emission Test	PASS
FCC Part 15, Paragraph 15.209(a)(f)	Spurious Emission	PASS

3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50
Remark: (1) *Decreasing linearly with logarithm of the frequency. (2) The lower limit shall apply at the transition frequency.			

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.


The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

Please to see the following pages

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: Keeping TX+Charging mode
Test Specification: AC 240V, 60Hz for adapter
Comment: Live Line
Tem.: 22.2°C Hum.: 59%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.4780	14.64	19.97	34.61	56.37	-21.76	QP	
2	0.6900	7.14	20.04	27.18	46.00	-18.82	AVG	
3	1.1500	14.12	20.12	34.24	56.00	-21.76	QP	
4	2.4100	6.20	20.15	26.35	46.00	-19.65	AVG	
5	4.2619	15.19	20.19	35.38	56.00	-20.62	QP	
6	6.9260	12.18	20.26	32.44	50.00	-17.56	AVG	
7	9.0580	16.77	20.31	37.08	60.00	-22.92	QP	
8	11.8540	14.64	20.31	34.95	50.00	-15.05	AVG	
9	15.5820	17.56	20.27	37.83	50.00	-12.17	AVG	
10	18.5140	20.45	20.32	40.77	60.00	-19.23	QP	
11	21.1780	18.94	20.33	39.27	50.00	-10.73	AVG	
12	23.8420	19.92	20.29	40.21	60.00	-19.79	QP	

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: Keeping TX+Charging mode
Test Specification: AC 240V, 60Hz for adapter
Comment: Neutral Line
Tem.: 22.2°C Hum.: 59%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	1.1260	16.42	20.12	36.54	56.00	-19.46	QP	
2	1.7300	8.65	20.13	28.78	46.00	-17.22	AVG	
3	2.1340	16.23	20.14	36.37	56.00	-19.63	QP	
4	3.4620	8.29	20.17	28.46	46.00	-17.54	AVG	
5	3.9940	16.55	20.18	36.73	56.00	-19.27	QP	
6	6.1260	12.13	20.24	32.37	50.00	-17.63	AVG	
7	7.7260	17.22	20.28	37.50	60.00	-22.50	QP	
8	8.5219	17.85	20.30	38.15	60.00	-21.85	QP	
9	9.3220	13.95	20.32	34.27	50.00	-15.73	AVG	
10	13.4500	15.88	20.28	36.16	50.00	-13.84	AVG	
11	17.9820	18.87	20.31	39.18	50.00	-10.82	AVG	
12	21.9740	21.75	20.32	42.07	60.00	-17.93	QP	

Conducted Emission Test Data


Test Site: 1# Shielded Room
Operating Condition: Keeping TX+Charging mode
Test Specification: AC 120V, 60Hz for adapter
Comment: Live Line
Tem.: 22.2°C Hum.: 59%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.5660	17.47	20.00	37.47	56.00	-18.53	QP	
2	0.7740	4.39	20.06	24.45	46.00	-21.55	AVG	
3	1.7180	7.40	20.13	27.53	46.00	-18.47	AVG	
4	3.4340	7.27	20.17	27.44	46.00	-18.56	AVG	
5	6.8700	12.77	20.26	33.03	50.00	-16.97	AVG	
6	11.3580	16.32	20.32	36.64	50.00	-13.36	AVG	
7	15.0580	20.07	20.26	40.33	60.00	-19.67	QP	
8	15.5860	20.30	20.27	40.57	60.00	-19.43	QP	
9	17.4340	20.41	20.30	40.71	60.00	-19.29	QP	
10	17.4340	18.77	20.30	39.07	50.00	-10.93	AVG	
11	19.0220	20.11	20.32	40.43	60.00	-19.57	QP	
12	22.1900	21.03	20.31	41.34	60.00	-18.66	QP	

Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: Keeping TX+Charging mode
Test Specification: AC 120V, 60Hz for adapter
Comment: Neutral Line
Tem.: 22.2°C Hum.: 59%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.5180	12.98	19.99	32.97	46.00	-13.03	AVG	
2	0.5260	20.76	19.99	40.75	56.00	-15.25	QP	
3	0.9180	18.14	20.10	38.24	56.00	-17.76	QP	
4	1.1900	7.98	20.12	28.10	46.00	-17.90	AVG	
5	1.3260	17.39	20.13	37.52	56.00	-18.48	QP	
6	1.7660	17.04	20.14	37.18	56.00	-18.82	QP	
7	3.6980	8.03	20.17	28.20	46.00	-17.80	AVG	
8	12.1500	16.95	20.31	37.26	50.00	-12.74	AVG	
9	15.8500	18.82	20.27	39.09	50.00	-10.91	AVG	
10	18.2300	20.52	20.31	40.83	60.00	-19.17	QP	
11	20.3420	18.49	20.34	38.83	50.00	-11.17	AVG	
12	21.6620	20.88	20.32	41.20	60.00	-18.80	QP	

4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector = Quasi-Peak, Trace mode = Max hold, Sweep = auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW = 30kHz, Detector = Quasi-Peak, Trace mode = Max hold, Sweep = auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector = Quasi-Peak, Trace mode = Max hold, Sweep = auto couple.

4.4. Test Data

PASS

Test Results

(Between 9KHz – 30MHz)

Job No.: SZAWW180820004-01

Standard: FCC PART15 C_3m


Power Source: AC 120V, 60Hz for adapter

Test item: Radiation Test

Temp.(C)/Hum.(%RH): 24.3(C)/55%RH

Test Mode: Mode 4

Distance: 3m




Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	degree (dgc)
0.0352	47.93	19.61	2.57	0	70.11	136.55	-66.44	Peak	67
0.0352	41.16	19.61	2.57	0	63.34	116.55	-53.21	AV	67
0.1373	62.55	19.63	2.59	0	84.77	124.79	-40.02	Peak	128
0.1373	52.89	19.63	2.59	0	75.11	104.79	-29.68	AV	128
0.2716	48.46	19.63	2.59	0	70.68	118.90	-48.22	Peak	241
0.2716	39.69	19.63	2.59	0	61.91	98.90	-36.99	AV	241
0.5260	46.47	19.65	2.61	0	68.73	93.18	-24.45	Peak	352
0.5260	37.54	19.65	2.61	0	59.80	73.18	-13.38	AV	352
1.0500	32.98	19.71	2.67	0	55.36	87.18	-31.82	Peak	119
1.0500	25.09	19.71	2.67	0	47.47	67.18	-19.71	AV	119
9.3900	26.36	19.83	2.73	0	48.92	89.54	-40.62	Peak	88
9.3900	16.46	19.83	2.73	0	39.02	69.54	-30.52	AV	88

Remark: According to FCC PART 15.209 (d), the emission limits for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, Radiated emission limits in these three bands are based on measurements employing an average detector.

(Between 30MHz -1000 MHz)

Job No.:	SZAWW180820004-01	Polarization:	Horizontal
Standard:	FCC PART15 C _3m	Power Source:	AC 120V, 60Hz for adapter
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Test Mode:	Mode 4	Distance:	3m



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	39.7146	38.84	-14.52	24.32	40.00	-15.68	QP	300	0	
2	55.0274	38.70	-16.73	21.97	40.00	-18.03	QP	300	75	
3	170.7926	45.60	-19.58	26.02	43.50	-17.48	QP	300	148	
4	192.4186	47.45	-19.67	27.78	43.50	-15.72	QP	300	196	
5	220.6171	49.05	-19.26	29.79	46.00	-16.21	QP	300	264	
6	340.7817	44.09	-14.27	29.82	46.00	-16.18	QP	300	360	

Job No.: SZAWW180820004-01
Standard: FCC PART15 C_3m
Test item: Radiation Test
Test Mode: Mode 4
Polarization: Vertical
Power Source: AC 120V, 60Hz for adapter
Temp.(C)/Hum.(%RH): 24.3(C)/55%RH
Distance: 3m



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	36.2541	48.51	-15.41	33.10	40.00	-6.90	QP	300	0	
2	39.7947	50.03	-13.48	36.55	40.00	-3.45	QP	300	65	
3	50.9420	45.47	-15.59	29.88	40.00	-10.12	QP	300	116	
4	97.4560	41.53	-14.99	26.54	43.50	-16.96	QP	300	196	
5	169.0054	49.09	-16.60	32.49	43.50	-11.01	QP	300	244	
6	219.0753	49.07	-14.33	34.74	46.00	-11.26	QP	300	360	

Job No.:	SZAWW180820004-01	Polarization:	Horizontal
Standard:	FCC PART15 C_3m	Power Source:	AC 240V, 60Hz for adapter
Test item:	Radiation Test	Temp.(C)/Hum.(%RH):	24.3(C)/55%RH
Test Mode:	Mode 4	Distance:	3m



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	33.4449	43.89	-17.55	26.34	40.00	-13.66	QP	300	0	
2	39.2991	40.78	-14.76	26.02	40.00	-13.98	QP	300	69	
3	119.4361	55.11	-21.29	33.82	43.50	-9.68	QP	300	114	
4	162.0414	52.16	-20.60	31.56	43.50	-11.94	QP	300	196	
5	216.0240	52.26	-19.23	33.03	46.00	-12.97	QP	300	241	
6	332.5187	47.01	-14.66	32.35	46.00	-13.65	QP	300	360	

Job No.: SZAWW180820004-01
Standard: FCC PART15 C_3m
Test item: Radiation Test
Test Mode: Mode 4
Polarization: Vertical
Power Source: AC 240V, 60Hz for adapter
Temp.(C)/Hum.(%RH): 24.3(C)/55%RH
Distance: 3m



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	33.9174	50.99	-16.40	34.59	40.00	-5.41	QP	300	0	
2	41.1320	47.72	-13.59	34.13	40.00	-5.87	QP	300	69	
3	89.2764	47.50	-17.38	30.12	43.50	-13.38	QP	300	114	
4	154.2786	51.24	-17.14	34.10	43.50	-9.40	QP	300	169	
5	215.2678	47.97	-14.44	33.53	43.50	-9.97	QP	300	214	
6	337.2155	39.60	-13.44	26.16	46.00	-19.84	QP	300	360	


5. Antenna Requirement

5.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203
Requirement	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard

5.2. Antenna Connected Construction

The antenna is a Loop Antenna which permanently attached, and the best case gain of the antenna is 0 dBi. It complies with the standard requirement.



APPENDIX I-- TEST SETUP PHOTOGRAPH

Photo of Conducted Emission Measurement








Photo of Radiation Emission Test






APPENDIX II -- EXTERNAL PHOTOGRAPH








APPENDIX III -- INTERNAL PHOTOGRAPH





----- End of Report -----