



RF TEST REPORT

Applicant Beijing Chusudu Technology Co., Ltd.
FCC ID 2AQ5PAUTORINGA2
Product Vehicular wireless terminal(with 4G function)
Brand AutoRing
Model A2
Report No. R1807A0315-R4V1
Issue Date October 24, 2018

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2017)/ FCC CFR 47 Part 90S (2017)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Performed by: Jiangpeng Lan

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



TABLE OF CONTENT

1. Test Laboratory	4
1.1. Notes of the Test Report	4
1.2. Test facility	4
1.3. Testing Location	5
2. General Description of Equipment under Test.....	6
3. Applied Standards	7
4. Test Configuration	8
5. Test Case Results	9
5.1. RF Power Output	9
5.2. Effective Radiated Power	12
5.3. Occupied Bandwidth	15
5.4. Emission Mask	21
5.5. Peak-to-Average Power Ratio (PAPR).....	27
5.6. Frequency Stability.....	29
5.7. Spurious Emissions at Antenna Terminals.....	32
5.8. Radiates Spurious Emission	37
6. Main Test Instruments.....	44
ANNEX A: EUT Appearance and Test Setup	45
A.1 EUT Appearance.....	45
A.2 Test Setup.....	48

Summary of measurement results

No.	Test Type	Clause in FCC rules	Verdict
1	RF power output	2.1046/90.635(b)	PASS
2	Effective Radiated Power	90.635(b)	PASS
3	Occupied Bandwidth	2.1049/ 90.209	PASS
4	Emission Masks	2.1051 / 90.691	PASS
5	Peak-to-Average Power Ratio	KDB 971168 D01(5.7)	PASS
6	Frequency Stability	2.1055 / 90.213	PASS
7	Spurious Emissions at Antenna Terminals	2.1051 / 90.691	PASS
8	Radiates Spurious Emission	2.1053 /90.691	PASS
Date of Testing: July 8 ,2018 ~ August 1 ,2018			
Note: PASS: The EUT complies with the essential requirements in the standard. FAIL: The EUT does not comply with the essential requirements in the standard.			

1. Test Laboratory

1.1. Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2. Test facility

CNAS (accreditation number:L2264)

TA Technology (Shanghai) Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

IC (recognition number is 8510A)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Canada to perform electromagnetic emission measurement.

VCCI (recognition number is C-4595, T-2154, R-4113, G-10766)

TA Technology (Shanghai) Co., Ltd. has been listed by industry Japan to perform electromagnetic emission measurement.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.



1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com

2. General Description of Equipment under Test

Client Information

Applicant	Beijing Chusudu Technology Co., Ltd.
Applicant address	Dongsheng Plaza A,5th Floor,8 Zhongguancun East Rd, Haidian District, Beijing, China
Manufacturer	Beijing Chusudu Technology Co., Ltd.
Manufacturer address	Dongsheng Plaza A,5th Floor,8 Zhongguancun East Rd, Haidian District, Beijing, China

General Information

EUT Description			
Model	A2		
Product IMEI	863346039069490		
Hardware Version	V3.1		
Software Version	RC108_D2_MT2_C1_BOM_V3.1_S20180622		
Power Supply	External Power Supply		
Antenna Type	Internal Antenna		
Antenna Gain	1.0dBi		
Test Mode(s)	LTE Band 26;		
Test Modulation	QPSK 16QAM;		
Maximum E.R.P.	LTE Band 26:	13.19dBm	
Rated Power Supply Voltage	3.7V		
Extreme Voltage	Minimum: 3.2V Maximum: 4.2V		
Extreme Temperature	Lowest:- 20°C Highest: +70°C		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	LTE Band 26	814 ~ 824	859 ~ 869
EUT Accessory			
AutoRing A2 Power Cable	Manufacturer: Shenzhen GuanLiJie Technology Co.,Ltd Model: AutoRing A2 Power cord		
Camera	Manufacturer: Beijing Chusudu Technology Co., Ltd. Model: MMT-AHD-H65		
Note: The information of the EUT is declared by the manufacturer.			



3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC CFR47 Part 2 (2017)

FCC CFR 47 Part 90S (2017)

ANSI/TIA-603-E (2016)

KDB 971168 D01 Power Meas License Digital Systems v03r01

4. Test Configuration

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (X axis, vertical polarization) and the worst case was recorded.

All mode and data rates and positions were investigated.

The following testing in LTE is set based on the maximum RF Output Power.

Test modes are chosen as the worst case configuration below for LTE Band 26

Test items	Bandwidth (MHz)				Modulation		RB			Test Channel		
	1.4	3	5	10	QPSK	16QAM	1	50%	100%	L	M	H
RF power output	O	O	O	O	O	O	O	O	O	O	O	O
Effective Isotropic Radiated power	O	O	O	O	O	O	O	O	O	O	O	O
Occupied Bandwidth	O	O	O	O	O	O	-	-	O	O	O	O
Emission Mask	O	O	O	O	O	O	O	-	O	O	O	O
Peak-to-Average Power Ratio	O	O	O	O	O	O	-	-	O	O	O	O
Frequency Stability	O	O	O	O	O	O	O	O	O	O	O	O
Spurious Emissions at Antenna Terminals	O	O	O	O	O	O	O	-	-	O	O	O
Radiates Spurious Emission	O	-	O	O	O	-	O	-	-	O	O	O
Note	1. The mark "O" means that this configuration is chosen for testing. 2. The mark "-" means that this configuration is not testing.											

5. Test Case Results

5.1. RF Power Output


Ambient condition

Temperature	Relative humidity
21°C ~25°C	40%~60%

Methods of Measurement

During the process of the testing, The EUT is controlled by the Base Station Simulator to ensure max power transmission and proper modulation.

Test Setup



The loss between RF output port of the EUT and the input port of the tester has been taken into consideration.

Limits

Part 90.635 (b) the maximum output power of the transmitter for mobile stations is 100 watts.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.

Test Results

LTE Band 26				Conducted Power(dBm)		
BW	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26697/814.7	26740/819	26783/823.3
1.4MHz	QPSK	1	0	23.61	23.58	23.57
		1	2	23.53	23.50	23.50
		1	5	23.53	23.47	23.52
		3	0	23.49	23.52	23.45
		3	2	23.48	23.41	23.57
		3	3	23.46	23.43	23.48
		6	0	22.44	22.51	22.50
	16QAM	1	0	22.84	22.46	22.60
		1	2	22.80	22.37	22.58
		1	5	22.77	22.38	22.56
		3	0	22.53	22.47	22.45
		3	2	22.58	22.48	22.54
		3	3	22.51	22.48	22.45
		6	0	21.51	21.58	21.55
BW	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26705/815.5	26740/819	26775/822.5
3MHz	QPSK	1	0	23.61	23.57	23.57
		1	13	23.55	23.55	23.52
		1	24	23.52	23.46	23.51
		12	0	22.57	22.60	22.55
		12	6	22.58	22.47	22.64
		12	13	22.53	22.53	22.55
		25	0	22.51	22.52	22.50
	16QAM	1	0	22.81	22.45	22.60
		1	13	22.81	22.41	22.60
		1	24	22.76	22.38	22.55
		12	0	21.62	21.59	21.55
		12	6	21.65	21.55	21.61
		12	13	21.59	21.56	21.55
		25	0	21.52	21.58	21.53
BW	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				26715/816.5	26740/819	26765/822.5
5MHz	QPSK	1	0	23.58	23.53	23.54
		1	13	23.54	23.51	23.50



		1	24	23.50	23.45	23.48
		12	0	22.54	22.55	22.51
		12	6	22.56	22.43	22.61
		12	13	22.50	22.48	22.51
		25	0	22.48	22.47	22.46
	16QAM	1	0	22.79	22.41	22.55
		1	13	22.77	22.39	22.56
		1	24	22.74	22.35	22.53
		12	0	21.59	21.55	21.52
		12	6	21.62	21.53	21.58
		12	13	21.56	21.51	21.51
		25	0	21.50	21.54	21.50
BW	Modulation	RB size	RB offset	Channel/Frequency(MHz)		
				/	26740/819	/
10MHz	QPSK	1	0	/	23.56	/
		1	25	/	23.52	/
		1	49	/	22.99	/
		25	0	/	22.50	/
		25	13	/	22.61	/
		25	25	/	22.49	/
		50	0	/	22.52	/
	16QAM	1	0	/	23.00	/
		1	25	/	23.01	/
		1	49	/	22.76	/
		25	0	/	21.58	/
		25	13	/	21.54	/
		25	25	/	21.56	/
		50	0	/	21.54	/

5.2. Effective Radiated Power

Ambient condition

Temperature	Relative humidity
21°C ~25°C	40%~60%

Methods of Measurement


1. The testing follows FCC KDB 971168 v03r01 Section 5.8 and ANSI/TIA-603-E (2016).
2. EUT was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna between 1.0m and 4.0m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
3. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz for above 1GHz and RBW=100kHz, VBW=300kHz for 30MHz to 1GHz, And the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl), the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:
$$\text{Power(EIRP)} = \text{PMea} - \text{PAg} - \text{Pcl} + \text{Ga}$$

The measurement results are amend as described below:
$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole,
$$\text{ERP} = \text{EIRP} - 2.15\text{dBi}.$$

The RB allocation refers to section 5.1, using the maximum output power configuration.

Test configuration

Below 1GHz:



Limits

Rule Part 90.635(b) specifies that “The maximum output power of the transmitter for mobile stations is 100 watts”.

Limit	$\leq 100 \text{ W}$ (50 dBm)
-------	-------------------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 1.19 \text{ dB}$

Test Results:

The measurement is performed for both of horizontal and vertical antenna Polarization, and only the data of worst mode is recorded in this report.

LTE Band 26						
bandwidth	Channel	Frequency (MHz)	Polarization	ERP (dBm)	Limit (dBm)	Conclusion
1.4 MHz (QPSK)	Low	814.7	Horizontal	12.93	50	Pass
	Mid	819	Horizontal	12.71	50	Pass
	High	823.3	Horizontal	12.82	50	Pass
3 MHz (QPSK)	Low	814.7	Horizontal	13.02	50	Pass
	Mid	819	Horizontal	13.19	50	Pass
	High	823.3	Horizontal	13.08	50	Pass
5 MHz (QPSK)	Low	815.5	Horizontal	12.67	50	Pass
	Mid	819	Horizontal	12.77	50	Pass
	High	822.5	Horizontal	13.00	50	Pass
10 MHz (QPSK)	Mid	819	Horizontal	13.05	50	Pass
1.4 MHz (16QAM)	Low	814.7	Horizontal	12.42	50	Pass
	Mid	819	Horizontal	12.21	50	Pass
	High	823.3	Horizontal	12.34	50	Pass
3 MHz (16QAM)	Low	814.7	Horizontal	12.53	50	Pass
	Mid	819	Horizontal	12.60	50	Pass
	High	823.3	Horizontal	12.84	50	Pass
5 MHz (16QAM)	Low	815.5	Horizontal	12.39	50	Pass
	Mid	819	Horizontal	12.48	50	Pass
	High	822.5	Horizontal	12.73	50	Pass
10 MHz (16QAM)	Mid	819	Horizontal	12.80	50	Pass

5.3. Occupied Bandwidth

Ambient condition

Temperature	Relative humidity
21°C ~25°C	40%~60%

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.


RBW is set to 51 kHz, VBW is set to 160 kHz for LTE Band 26 (1.4MHz),

RBW is set to 100 kHz, VBW is set to 300 kHz for LTE Band 26 (3MHz/5MHz).

RBW is set to 300 kHz, VBW is set to 1MHz for LTE Band 26 (10MHz).

99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

No specific occupied bandwidth requirements in part 2.1049.

Part 90.209 (a) Each authorization issued to a station licensed under this part will show an emission designator representing the class of emission authorized. The designator will be prefixed by a specified necessary bandwidth. This number does not necessarily indicate the bandwidth occupied by the emission at any instant. In those cases where part 2.202 of this chapter does not provide a formula for the computation of necessary bandwidth, the occupied bandwidth, as defined in part 2 of this chapter, may be used in lieu of the necessary bandwidth.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 624\text{Hz}$.



Test Result

LTE Band 26						
RB	Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	99% Power Bandwidth(MHz)	-26dBc Bandwidth(MHz)
100%	QPSK	1.4	26697	814.7	1.1264	1.316
			26740	819	1.1213	1.311
			26783	823.3	1.1326	1.310
		3	26705	815.5	2.7449	3.038
			26740	819	2.7404	3.053
			26775	822.5	2.7386	3.044
		5	26715	816.5	4.5254	5.106
			26740	819	4.5404	5.089
			26765	821.5	4.5237	5.084
		10	26740	819	9.0633	10.200
	16QAM	1.4	26697	814.7	1.1188	1.295
			26740	819	1.1295	1.312
			26783	823.3	1.1229	1.318
		3	26705	815.5	2.7340	3.043
			26740	819	2.7536	3.058
			26775	822.5	2.7330	3.055
		5	26715	816.5	4.5478	5.084
			26740	819	4.5263	5.071
			26765	821.5	4.5547	5.112
		10	26740	819	9.0580	10.090




LTE Band 26 QPSK 1.4MHz CH26697



LTE Band 26 QPSK 3MHz CH26705




LTE Band 26 QPSK 1.4MHz CH26740



LTE Band 26 QPSK 3MHz CH26740



LTE Band 26 QPSK 1.4MHz CH26783



LTE Band 26 QPSK 3MHz CH26775







LTE Band 26 QPSK 5MHz CH26715



LTE Band 26 QPSK 5MHz CH26740



LTE Band 26 QPSK 5MHz CH26765



LTE Band 26 QPSK 10MHz CH26740







LTE Band 26 16QAM 1.4MHz CH26697




LTE Band 26 16QAM 3MHz CH26705




LTE Band 26 16QAM 1.4MHz CH26740




LTE Band 26 16QAM 3MHz CH26740



LTE Band 26 16QAM 1.4MHz CH26783




LTE Band 26 16QAM 3MHz CH26775







LTE Band 26 16QAM 5MHz CH26715




LTE Band 26 16QAM 5MHz CH26740



LTE Band 26 16QAM 5MHz CH26765



LTE Band 26 16QAM 10MHz CH26740



5.4. Emission Mask

Ambient condition

Temperature	Relative humidity
21°C ~25°C	40%~60%

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The average detector is used.

RBW is set to 15 kHz, VBW is set to 51 kHz for LTE Band 26 (1.4MHz),


RBW is set to 30 kHz, VBW is set to 100 kHz for LTE Band 26 (3MHz),

RBW is set to 51 kHz, VBW is set to 160 kHz for LTE Band 26 (5MHz),

RBW is set to 100 kHz, VBW is set to 300 kHz for LTE Band 26 (10MHz),

Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

Rule Part 90.691(a) specifies that “ For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.”

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U=0.684\text{dB}$.



Test Result:


LTE Band 26 QPSK 1.4MHz CH-Low 1RB




LTE Band 26 QPSK 1.4MHz CH-High 1RB



LTE Band 26 QPSK 1.4MHz CH-Low 100%RB



LTE Band 26 QPSK 1.4MHz CH-High 100%RB



LTE Band 26 QPSK 3MHz CH-Low 1RB




LTE Band 26 QPSK 3MHz CH-High 1RB






LTE Band 26 QPSK 3MHz CH-Low 100%RB



LTE Band 26 QPSK 3MHz CH-High 100%RB




LTE Band 26 QPSK 5MHz CH-Low 1RB




LTE Band 26 QPSK 5MHz CH-High 1RB



LTE Band 26 QPSK 5MHz CH-Low 100%RB




LTE Band 26 QPSK 5MHz CH-High 100%RB



LTE Band 26 QPSK 10MHz CH-Low 1RB



LTE Band 26 QPSK 10MHz CH-Low 100%RB



LTE Band 26 16QAM 1.4MHz CH-Low 1RB



LTE Band 26 16QAM 1.4MHz CH-High 1RB



LTE Band 26 16QAM 1.4MHz CH-Low 100%RB



LTE Band 26 16QAM 1.4MHz CH-High 100%RB






LTE Band 26 16QAM 3MHz CH-Low 1RB




LTE Band 26 16QAM 3MHz CH-High 1RB



LTE Band 26 16QAM 3MHz CH-Low 100%RB



LTE Band 26 16QAM 3MHz CH-High 100%RB



LTE Band 26 16QAM 5MHz CH-Low 1RB




LTE Band 26 16QAM 5MHz CH-High 1RB







LTE Band 26 16QAM 5MHz CH-Low 100%RB




LTE Band 26 16QAM 5MHz CH-High 100%RB



LTE Band 26 16QAM 10MHz CH-Low 1RB



LTE Band 26 16QAM 10MHz CH-High 100%RB



5.5. Peak-to-Average Power Ratio (PAPR)

Ambient condition


Temperature	Relative humidity
21°C ~25°C	40%~60%

Methods of Measurement

Measure the total peak power and record as PPk. And measure the total average power and record as PAvg. Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$\text{PAPR (dB)} = \text{PPk (dBm)} - \text{PAvg (dBm)}.$$

Test Setup



Limits

In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB in 24.232(d).

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.

**Test Results**

Mode	Channel	Frequency (MHz)	Peak(dBm)	Avg(dBm)	PAPR(dB)	Limit(dB)	Conclusion
1.4 MHz (QPSK)	26697	814.7	27.43	22.44	4.99	13	PASS
	26740	819	27.69	22.51	5.18	13	PASS
	26783	823.3	27.48	22.50	4.98	13	PASS
3 MHz (QPSK)	26697	814.7	27.64	22.51	5.13	13	PASS
	26740	819	27.83	22.52	5.31	13	PASS
	26783	823.3	27.82	22.50	5.32	13	PASS
5 MHz (QPSK)	26697	814.7	27.71	22.48	5.23	13	PASS
	26740	819	27.79	22.47	5.32	13	PASS
	26783	823.3	27.80	22.46	5.34	13	PASS
10 MHz (QPSK)	26740	819	27.75	22.52	5.23	13	PASS
1.4 MHz (16QAM)	26697	814.7	27.32	21.51	5.81	13	PASS
	26740	819	27.49	21.58	5.91	13	PASS
	26783	823.3	27.26	21.55	5.71	13	PASS
3 MHz (16QAM)	26697	814.7	27.46	21.52	5.94	13	PASS
	26740	819	27.67	21.58	6.09	13	PASS
	26783	823.3	27.63	21.53	6.10	13	PASS
5 MHz (16QAM)	26697	814.7	27.44	21.50	5.94	13	PASS
	26740	819	27.55	21.54	6.01	13	PASS
	26783	823.3	27.56	21.50	6.06	13	PASS
10 MHz (16QAM)	26740	819	27.51	21.54	5.97	13	PASS

5.6. Frequency Stability

Ambient condition

Temperature	Relative humidity
21°C ~25°C	40%~60%

Method of Measurement

1. Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -30°C to +70°C in 10°C step size,

(1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -30°C to +70°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements.

2. Frequency Stability (Voltage Variation)


The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery-operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.2 V and 4.2 V, with a nominal voltage of 3.7V.

Test setup



Limits

According to the Sec. 90.213.(a) Unless noted elsewhere, transmitters used in the services governed by this part must have a minimum frequency stability as specified in the following table.

Minimum Frequency Stability

[Parts per million (ppm)]

Frequency range (MHz)	Fixed and base stations	Mobile stations	
		Over 2 watts output power	2 watts or less output power
809-824	1.5	2.5	2.5

Note: The EUT should meet Mobile stations limit.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 3$, $U = 0.01\text{ppm}$.



Test Result

LTE Band 26					
(QPSK, 10MHz BANDWIDTH)					
Condition		814	824	Delta (Hz)	Frequency Stability(ppm)
Temperature	Voltage	F low@-13dBm(MHz)	F high@-13dBm(MHz)		
Normal (25°C)	Normal	814.4402	823.6078	-3.94	-0.00481
Extreme (70°C)		814.4414	823.6066	-4.48	-0.00547
Extreme (60°C)		814.4395	823.6085	-3.65	-0.00446
Extreme (50°C)		814.4392	823.6088	2.12	0.00259
Extreme (40°C)		814.4407	823.6076	4.88	0.00596
Extreme (30°C)		814.4398	823.6084	1.14	0.00139
Extreme (20°C)		814.4393	823.6087	3.62	0.00442
Extreme (10C)		814.4409	823.6071	-3.45	-0.00421
Extreme (0°C)		814.4458	823.6087	-3.23	-0.00394
Extreme (-10°C)		814.4395	823.6085	-10.37	-0.01266
Extreme (-20°C)		814.4401	823.6079	-3.26	-0.00398
Extreme (-30°C)		814.4400	823.6096	-6.61	-0.00807
25°C	LV	814.4399	823.6085	-8.16	-0.00996
	HV	814.4396	823.6090	-3.62	-0.00442
(16QAM,10MHz BANDWIDTH)					
Condition		814	824	Delta (Hz)	Frequency Stability(ppm)
Temperature	Voltage	F low@-13dBm(MHz)	F high@-13dBm(MHz)		
Normal (25°C)	Normal	814.4941	823.5271	-2.31	-0.00282
Extreme (70°C)		814.4929	823.5285	5.97	0.00729
Extreme (60°C)		814.4948	823.5264	-0.19	-0.00023
Extreme (50°C)		814.4951	823.5261	-9.25	-0.01129
Extreme (40°C)		814.4938	823.5276	-1.10	-0.00134
Extreme (30°C)		814.4947	823.5265	6.60	0.00806
Extreme (20°C)		814.4954	823.5262	-0.73	-0.00089
Extreme (10C)		814.4934	823.5278	5.45	0.00665
Extreme (0°C)		814.4943	823.5269	4.90	0.00598
Extreme (-10°C)		814.4948	823.5264	10.73	0.01310
Extreme (-20°C)		814.4942	823.5278	14.85	0.01813
Extreme (-30°C)		814.4942	823.5286	4.92	0.00601
25°C	LV	814.4949	823.5265	6.69	0.00817
	HV	814.4945	823.5281	1.10	0.00134

5.7. Spurious Emissions at Antenna Terminals


Ambient condition

Temperature	Relative humidity
21°C ~25°C	40%~60%

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 30MHz to the 10th harmonic of the carrier. The peak detector is used. RBW is set to 100 kHz and VBW is set to 300 kHz, Sweep is set to ATUO.

Test setup



Limits

Rule Part 90.691 specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty


The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
100kHz-1GHz	0.684 dB
1GHz-12.75GHz	1.407 dB


Test Result

If disturbances were found more than 20dB below limit line, the mark is not required for the EUT.
The signal beyond the limit is carrier.


LTE Band 26 1.4MHz CH Low 30MHz~1GHz




LTE Band 26 1.4MHz CH Low 1GHz~9GHz




LTE Band 26 1.4MHz CH Middle 30MHz~1GHz




LTE Band 26 1.4MHz CH Middle 1GHz~9GHz



LTE Band 26 1.4MHz CH High 30MHz~1GHz




LTE Band 26 1.4MHz CH High 1GHz~9GHz







LTE Band 26 3MHz CH Low 30MHz~1GHz




LTE Band 26 3MHz CH Low 1GHz~9GHz




LTE Band 26 3MHz CH Middle 30MHz~1GHz




LTE Band 26 3MHz CH Middle 1GHz~9GHz



LTE Band 26 3MHz CH High 30MHz~1GHz




LTE Band 26 3MHz CH High 1GHz~9GHz







LTE Band 26 5MHz CH Low 30MHz~1GHz




LTE Band 26 5MHz CH Low 1GHz~9GHz




LTE Band 26 5MHz CH Middle 30MHz~1GHz




LTE Band 26 5MHz CH Middle 1GHz~9GHz



LTE Band 26 5MHz CH High 30MHz~1GHz




LTE Band 26 5MHz CH High 1GHz~9GHz






LTE Band 26 10MHz CH Middle 30MHz~1GHz



LTE Band 26 10MHz CH Middle 1GHz~9GHz



5.8. Radiates Spurious Emission

Ambient condition

Temperature	Relative humidity
21°C ~25°C	40%~60%

Method of Measurement


1. The testing follows FCC KDB 971168 v03r01 Section 5.8 and ANSI/TIA-603-E (2016).
2. The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz for above 1GHz and RBW=100kHz, VBW=300kHz for 30MHz to 1GHz,, And the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAG) should be recorded after test.
7. The measurement results are obtained as described below:

$$\text{Power(EIRP)} = \text{PMea} - \text{PAG} - \text{Pcl} + \text{Ga}$$
The measurement results are amend as described below:


$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, $\text{ERP} = \text{EIRP} - 2.15\text{dBi}$.
The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup

30MHz~~~ 1GHz



Above 1GHz



Limits

Rule Part 90.691 specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 3.55$ dB.

**Test Result**

Sweep the whole frequency band through the range from 30MHz to the 10th harmonic of the carrier, the emissions below the noise floor will not be recorded in the report.

LTE Band 26 1.4MHz CH Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1629.4	-50.21	2.00	10.75	vertical	-43.61	-13.00	30.61	45
3	2444.1	-59.88	2.51	11.05	vertical	-53.49	-13.00	40.49	0
4	3258.8	-62.17	4.20	11.15	vertical	-57.37	-13.00	44.37	135
5	4073.5	-58.57	5.20	11.15	vertical	-54.77	-13.00	41.77	270
6	4888.2	-57.54	5.50	11.95	vertical	-53.24	-13.00	40.24	180
7	5702.9	-57.50	5.70	13.55	vertical	-51.80	-13.00	38.80	90
8	6517.6	-56.04	6.30	13.75	vertical	-50.74	-13.00	37.74	45
9	7332.3	-51.49	6.80	13.85	vertical	-46.59	-13.00	33.59	45
10	8147.0	-45.46	6.90	14.25	vertical	-40.26	-13.00	27.26	0
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2.The worst emission was found in the antenna is Horizontal position.									

LTE Band 26 1.4MHz CH Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1638.0	-51.78	2.00	10.75	vertical	-45.18	-13.00	32.18	315
3	2457.0	-58.52	2.51	11.05	vertical	-52.13	-13.00	39.13	225
4	3346.0	-62.84	4.20	11.15	vertical	-58.04	-13.00	45.04	315
5	4182.5	-54.74	5.20	11.15	vertical	-50.94	-13.00	37.94	135
6	5019.0	-55.93	5.50	11.95	vertical	-51.63	-13.00	38.63	270
7	5855.5	-57.11	5.70	13.55	vertical	-51.41	-13.00	38.41	315
8	6692.0	-53.52	6.30	13.75	vertical	-48.22	-13.00	35.22	135
9	7528.5	-51.96	6.80	13.85	vertical	-47.06	-13.00	34.06	270
10	8365.0	-47.82	6.90	14.25	vertical	-42.62	-13.00	29.62	45
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2.The worst emission was found in the antenna is Horizontal position.									

LTE Band 26 1.4MHz CH High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1646.6	-57.57	2.00	10.75	vertical	-50.97	-13.00	37.97	135
3	2469.9	-55.62	2.51	11.05	vertical	-49.23	-13.00	36.23	270
4	3294.0	-61.83	4.20	11.15	vertical	-57.03	-13.00	44.03	0
5	4117.5	-58.31	5.20	11.15	vertical	-54.51	-13.00	41.51	315
6	4941.0	-51.66	5.50	11.95	vertical	-47.36	-13.00	34.36	225
7	5764.5	-58.27	5.70	13.55	vertical	-52.57	-13.00	39.57	135
8	6588.0	-53.56	6.30	13.75	vertical	-48.26	-13.00	35.26	270
9	7411.5	-48.59	6.80	13.85	vertical	-43.69	-13.00	30.69	180
10	8235.0	-46.72	6.90	14.25	vertical	-41.52	-13.00	28.52	45

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

LTE Band 26 5MHz CH Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1633.0	-50.78	2.00	10.75	vertical	-44.18	-13.00	31.18	180
3	2449.5	-59.62	2.51	11.05	vertical	-53.23	-13.00	40.23	90
4	3266.0	-61.73	4.20	11.15	vertical	-56.93	-13.00	43.93	0
5	4082.5	-59.03	5.20	11.15	vertical	-55.23	-13.00	42.23	315
6	4899.0	-58.06	5.50	11.95	vertical	-53.76	-13.00	40.76	225
7	5715.5	-58.13	5.70	13.55	vertical	-52.43	-13.00	39.43	135
8	6532.0	-56.66	6.30	13.75	vertical	-51.36	-13.00	38.36	270
9	7348.5	-51.32	6.80	13.85	vertical	-46.42	-13.00	33.42	180
10	8165.0	-49.83	6.90	14.25	vertical	-44.63	-13.00	31.63	90

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



LTE Band 26 5MHz CH Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1638.0	-51.78	2.00	10.75	vertical	-45.18	-13.00	32.18	45
3	2457.0	-60.41	2.51	11.05	vertical	-54.02	-13.00	41.02	45
4	3276.0	-61.84	4.20	11.15	vertical	-57.04	-13.00	44.04	45
5	4095.0	-58.92	5.20	11.15	vertical	-55.12	-13.00	42.12	45
6	4914.0	-57.90	5.50	11.95	vertical	-53.60	-13.00	40.60	0
7	5733.0	-55.72	5.70	13.55	vertical	-50.02	-13.00	37.02	315
8	6552.0	-55.75	6.30	13.75	vertical	-50.45	-13.00	37.45	135
9	7371.0	-51.32	6.80	13.85	vertical	-46.42	-13.00	33.42	270
10	8190.0	-48.24	6.90	14.25	vertical	-43.04	-13.00	30.04	45

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

LTE Band 26 5MHz CH High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1643.0	-52.37	2.00	10.75	vertical	-45.77	-13.00	32.77	0
3	2464.5	-58.57	2.51	11.05	vertical	-52.18	-13.00	39.18	315
4	3386.0	-62.34	4.20	11.15	vertical	-57.54	-13.00	44.54	0
5	4232.5	-58.81	5.20	11.15	vertical	-55.01	-13.00	42.01	315
6	5079.0	-54.11	5.50	11.95	vertical	-49.81	-13.00	36.81	225
7	5925.0	-58.46	5.70	13.55	vertical	-52.76	-13.00	39.76	135
8	6772.0	-54.18	6.30	13.75	vertical	-48.88	-13.00	35.88	270
9	7618.5	-49.13	6.80	13.85	vertical	-44.23	-13.00	31.23	180
10	8465.0	-46.22	6.90	14.25	vertical	-41.02	-13.00	28.02	90

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



LTE Band 26 10MHz CH Low

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1638.0	-51.35	2.00	10.75	vertical	-44.75	-13.00	31.75	135
3	2457.0	-61.15	2.51	11.05	vertical	-54.76	-13.00	41.76	270
4	3276.0	-61.45	4.20	11.15	vertical	-56.65	-13.00	43.65	45
5	4095.0	-58.66	5.20	11.15	vertical	-54.86	-13.00	41.86	45
6	4914.0	-56.94	5.50	11.95	vertical	-52.64	-13.00	39.64	0
7	5733.0	-57.81	5.70	13.55	vertical	-52.11	-13.00	39.11	315
8	6552.0	-55.83	6.30	13.75	vertical	-50.53	-13.00	37.53	135
9	7371.0	-50.99	6.80	13.85	vertical	-46.09	-13.00	33.09	270
10	8190.0	-49.36	6.90	14.25	vertical	-44.16	-13.00	31.16	315

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

LTE Band 26 10MHz CH Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1638.0	-51.68	2.00	10.75	vertical	-45.08	-13.00	32.08	45
3	2457.0	-59.80	2.51	11.05	vertical	-53.41	-13.00	40.41	0
4	3276.0	-61.45	4.20	11.15	vertical	-56.65	-13.00	43.65	270
5	4095.0	-59.20	5.20	11.15	vertical	-55.40	-13.00	42.40	180
6	4914.0	-56.90	5.50	11.95	vertical	-52.60	-13.00	39.60	90
7	5733.0	-59.10	5.70	13.55	vertical	-53.40	-13.00	40.40	45
8	6552.0	-55.83	6.30	13.75	vertical	-50.53	-13.00	37.53	45
9	7371.0	-50.99	6.80	13.85	vertical	-46.09	-13.00	33.09	0
10	8190.0	-50.50	6.90	14.25	vertical	-45.30	-13.00	32.30	315

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



LTE Band 26 10MHz CH High

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1638.0	-50.76	2.00	10.75	vertical	-44.16	-13.00	31.16	315
3	2457.0	-60.89	2.51	11.05	vertical	-54.50	-13.00	41.50	225
4	3276.0	-61.45	4.20	11.15	vertical	-56.65	-13.00	43.65	270
5	4095.0	-59.20	5.20	11.15	vertical	-55.40	-13.00	42.40	45
6	4914.0	-56.90	5.50	11.95	vertical	-52.60	-13.00	39.60	0
7	5733.0	-61.10	5.70	13.55	vertical	-55.40	-13.00	42.40	315
8	6552.0	-55.10	6.30	13.75	vertical	-49.80	-13.00	36.80	225
9	7371.0	-51.90	6.80	13.85	vertical	-47.00	-13.00	34.00	135
10	8190.0	-49.80	6.90	14.25	vertical	-44.60	-13.00	31.60	270

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

6. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Base Station Simulator	R&S	CMW500	113824	2018-05-20	2019-05-19
Power Splitter	Hua Xiang	SHX-GF2-2-13	10120101	/	/
Spectrum Analyzer	Agilent	N9010A	MY47191109	2018-05-20	2019-05-19
Signal Analyzer	R&S	FSV30	100815	2017-12-17	2018-12-16
EMI Test Receiver	R&S	ESCI	100948	2018-05-20	2019-05-19
Signal generator	R&S	SMB 100A	102594	2018-05-13	2019-05-12
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2014-12-06	2019-12-05
Trilog Antenna	SCHWARZBECK	VUBL 9163	9163-201	2017-11-18	2020-11-17
Horn Antenna	R&S	HF907	100126	2014-12-06	2019-12-05
Horn Antenna	ETS-Lindgren	3160-09	00102644	2015-01-30	2020-01-29
Climatic Chamber	ESPEC	SU-242	93000506	2017-12-17	2020-12-16
RF Cable	Agilent	SMA 15cm	0001	/	/
Preamplifier	R&S	SCU18	102327	2018-05-20	2019-05-19
Software	R&S	EMC32	V9.26.0	/	/
MOB COMMS DC SUPPLY	Keysight	66319D	MY43004105	2018-05-07	2019-05-06

*****END OF REPORT *****

ANNEX A: EUT Appearance and Test Setup

A.1 EUT Appearance




Front Side



Back Side

a: EUT



b: AutoRing A2 Power Cable






c:Camera

Picture 1 EUT and Accessory

A.2 Test Setup



Below 1GHz



Above 1GHz

Picture 2: Radiated Spurious Emissions Test setup