

RF Test Report

Applicant : Hon Lin Technology Co., Ltd.
Product Type : UWB Anchor-D6
Trade Name : Cloud Network Technology Singapore Pte. Ltd.
Model Number : UWB Anchor-D6
Applicable Standard : FCC 47 CFR PART 15 SUBPART F
ANSI C63.10:2013
Received Date : Aug. 05, 2025
Test Period : Aug. 14, 2025 ~ Aug. 22, 2025
Issued Date : Sep. 15, 2025

Issued by

Eurofins E&E Wireless Taiwan Co., Ltd.
No. 140-1, Changan Street, Bade District,
Taoyuan City, Taiwan (R.O.C.)
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330
Frequency Range: 9 kHz to 325 GHz
Bade test site :
Test Firm Registration Number: 226252
Test Firm Designation Number: TW0010
Wugu test site :
Test Firm Registration Number: 191812
Test Firm Designation Number: TW0034

Note:

1. The test results are valid only for samples provided by customers and under the test conditions described in this report.
2. This report shall not be reproduced except in full, without the written approval of Eurofins E&E Wireless Taiwan Co., Ltd.
3. The relevant information is provided by customers in this test report. According to the correctness, appropriateness or completeness of the information provided by the customer, if there is any doubt or error in the information which affects the validity of the test results, the laboratory does not take the responsibility.

Revision History

Rev.	Issued Date	Description	Revised by
00	Sep. 15, 2025	Initial Issue	Emma Chao

Verification of Compliance

Applicant : Hon Lin Technology Co., Ltd.

Product Type : UWB Anchor-D6

Trade Name : Cloud Network Technology Singapore Pte. Ltd.

Model Number : UWB Anchor-D6

FCC ID : 2AQ68-DKCUWBD6

Applicable Standard : FCC 47 CFR PART 15 SUBPART F
ANSI C63.10:2013

Test Result : Complied

Issued By : Eurofins E&E Wireless Taiwan Co., Ltd.
No. 140-1, Changan Street, Bade District,
Taoyuan City, Taiwan (R.O.C.)
Tel : +886-3-2710188 / Fax : +886-3-2710190
Taiwan Accreditation Foundation accreditation number: 1330



Eurofins E&E Wireless Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Eurofins E&E Wireless Taiwan Co., Ltd. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Approved By : _____

TABLE OF CONTENTS

1	General Information	5
1.1.	Summary of Test Result.....	5
1.2.	Testing Location.....	6
1.3.	Measurement Uncertainty.....	6
1.4.	Test Site Environment.....	6
2	EUT Description.....	7
3	Test Methodology.....	8
3.1.	Mode of Operation	8
3.2.	EUT Test Step.....	9
3.3.	Configuration of Test System Details	9
3.4.	Test Instruments	10
4	Measurement Procedure.....	11
4.1.	AC Power Line Conducted Emission Measurement	11
4.2.	Radiated Emission Measurement.....	13
4.3.	Peak Power Measurement.....	16
4.4.	UWB Bandwidth Measurement.....	17
4.5.	Technical requirements for indoor UWB systems	18
4.6.	Antenna Measurement	18
5	Test Results	19
5.1.	Transmitter Radiated Emissions Test Results.....	19

Appendix A. Test Setup Photographs

1 General Information

1.1. Summary of Test Result

Standard	Item	Result	Remark
15.207	AC Power Conducted Emission	N/A	Note 1
15.209, 15.517(c), 15.517(d)	Transmitter Radiated Emissions	PASS	-----
15.517(e)	Peak Power Measurement	PASS	-----
15.503	UWB Bandwidth	PASS	-----
15.517(a)(5)	Technical requirements for indoor UWB systems	PASS	-----
15.203	Antenna Requirement	PASS	-----

Note 1: The car will not be connected to the AC Power.

Note 2: The above test items refer to the test standards.

Decision Rule

- ☒ Uncertainty is not included.
- ☐ Uncertainty is included.

Standard	Description
CFR47, Part 15, Subpart F	Intentional Radiators
ANSI C63. 10: 2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

1.2. Testing Location

Lab Name: Eurofins E&E Wireless Taiwan Co., Ltd.
Site Address: ☐ No. 140-1, Changan Street, Bade District, Taoyuan City, Taiwan (R.O.C.)
Site Address: ☒ No. 2, Wuquan 5th Rd. Wugu Dist., New Taipei City, Taiwan (R.O.C.)

1.3. Measurement Uncertainty

Test Item	Frequency	Uncertainty				
		BD		WG		
Conducted Emission	150 kHz ~ 30 MHz	2.7 dB		2.6 dB		
Test Item	Frequency	Uncertainty				
		96601-BD	96603-BD	96602-WG	96603-WG	96604-WG
Radiated Emission	9 kHz ~ 30 MHz	1.8 dB	1.8 dB	1.9 dB	1.9 dB	1.9 dB
	30 MHz ~ 1000 MHz	4.7 dB	4.7 dB	4.7 dB	4.7 dB	4.5 dB
	1000 MHz ~ 18000 MHz	4.7 dB	4.8 dB	4.6 dB	4.7 dB	5.1 dB
	18000 MHz ~ 26500 MHz	4.0 dB	4.1 dB	3.9 dB	4.1 dB	4.3 dB
	26500 MHz ~ 40000 MHz	4.2 dB	4.2 dB	4.2 dB	4.2 dB	4.6 dB
RF Bandwidth		4.5 %	4.5 %	4.5 %	4.5 %	3.3 %

1.4. Test Site Environment

Items	Required (IEC 60068-1)	Interval(*)
Temperature (°C)	15-35	20-30
Humidity (%RH)	25-75	45-75

(*)The measurement ambient temperature is within this range.

2 EUT Description

The product specifications of the EUT presented in the report are declared by the manufacturer who shall take full responsibility for the authenticity(except EIRP, Field Strength).

Applicant	Hon Lin Technology Co., Ltd. 11F, No.32, Jihu Rd., Neihu Dist., Taipei City 114, Taiwan		
Product Type	UWB Anchor-D6		
Trade Name	Cloud Network Technology Singapore Pte. Ltd.		
Model Number	UWB Anchor-D6		
FCC ID	2AQ68-DKCUWBD6		
Frequency Range	6489 MHz (CH5) and 7987 MHz (CH9)		
Modulation Type	BPRF		
UWB Channel	CH 5 / CH 9		
Antenna Information	Type	Gain	
	PCB Antenna	ANT-1	3.75 dBi (CH9) / 4.52 dBi (CH5)
		ANT-2	5.72 dBi (CH9) / 4.83 dBi (CH5)
Operate Temp. Range	-40 ~ +85 °C		
EUT Power Rating	12 Vdc, 0.16 A		
EIRP	CH5: ANT-1 : -1.35 dBm/50 MHz		
	CH5: ANT-2 : -1.15 dBm/50 MHz		
Field Strength	CH5: ANT-1 : 77.96 dBuV/m, @1m		
	CH5: ANT-2 : 78.16 dBuV/m, @1m		

Testing Sample No.	
Test Item	Sample Number
Radiation	C259064_A001

EUT Modify Description :

Modify Description :

CIIPC

For marketing purposes, the software enabled 6489.6 MHz (CH5), there is no difference in the hardware, and nothing else has changed.

After the evaluation is completed, all test items within the newly added frequency range must be retested.

Original Report : USRC255085001

3 Test Methodology

3.1. Mode of Operation

Decision of Test Eurofins has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Pre-Test Mode	Final-Test Mode
Transmit Mode	V

Test Mode	Power Setting		Test Software Version
	ANT-1	ANT-2	
Transmit Mode	51	51	Engineering Mode


By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "Z axis" position was the worst, then the final test was executed the worst condition and test data were recorded in this report.

3.2. EUT Test Step

1	Setup the EUT shown on "Configuration of Test System Details".
2	Turn on the power of EUT.

3.3. Configuration of Test System Details

Radiated Emissions



Devices Description					
	Product	Manufacturer	Model Number	Serial Number	Power Cord
(1)	Notebook	DELL	Latitude 5420	---	---
(2)	Power Adapter	DVE	DSA-24PFM-12L FEU 120200	---	---
(3)	PCAN	TSMASER	TC1012	---	---
(4)	Power + CAN cable	Cloud Network Technology Singapore Pet. Ltd.	PowerCAN cable	---	---

3.4. Test Instruments

For Radiated Emissions

Test Period: Aug. 14, 2025 ~ Aug. 22, 2025

Testing Engineer: Marin Lee

Radiation test sites		Semi Anechoic Room 96602-WG				
Use	Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Cal. Period
☒	LOOP Antenna (9 kHz~30 MHz)	Schwarzbeck Mess-Elektronik	FMZB 1513-60	1513-60-031	Mar. 6, 2025	1 year
☒	Trilog Broadband Antenna (30 MHz~1 GHz)	Schwarzbeck Mess-Elektronik	VULB9168	01276	Jan. 20, 2025	1 year
☒	Broadband Horn Antenna (1 GHz~18 GHz)	RF SPIN	DRH18-E	210305A18ES	Feb. 19, 2025	1 year
☒	Broadband Horn Antenna (15 GHz~40 GHz)	Schwarzbeck Mess-Elektronik	BBHA9170	01133	Jan. 14, 2025	1 year
☒	Spectrum Analyzer (10 Hz~44 GHz)	KEYSIGHT	N9020B	MY60112362	Jan. 16, 2025	1 year
☒	Spectrum Analyzer (10 Hz~44 GHz)	R&S	FSV3044	101255	Dec.18,2024	1 year
☒	Pre-Amplifier	Agilent	8447D	2944A10961	Jul. 10, 2025	1 year
☒	Pre-Amplifier	EMCI	EMC118A45SE	980822	Nov. 26, 2024	1 year
☒	Pre-Amplifier	EMCI	EMC184045SE	980861	Dec. 18, 2024	1 year
☒	Coaxial Cable (9 kHz~1000 MHz)	EMCI	EMCCFD400-NM- NM-2000	211006	Oct. 24, 2024	1 year
☒	Coaxial Cable (9 kHz~1000 MHz)	EMCI	EMCCFD400-NM- NM-2000	211007	Oct. 24, 2024	1 year
☒	Coaxial Cable (9 kHz~1000 MHz)	EMCI	EMCCFD400-NM- NM-6000	211015	Oct. 24, 2024	1 year
☒	Coaxial Cable (1 GHz~18 GHz)	EMCI	EMC104-SM-SM- 1000	211026	Oct. 24, 2024	1 year
☒	Coaxial Cable (1 GHz~18 GHz)	EMCI	EMC104-SM-SM- 2000	211035	Oct. 24, 2024	1 year
☒	Coaxial Cable (1 GHz~18 GHz)	EMCI	EMC104-SM-SM- 8000	211036	Oct. 24, 2024	1 year
☒	Coaxial Cable (18 GHz~40 GHz)	EMCI	EMC101G-KM- KM-600	211211	Jan. 15, 2025	1 year
☒	Coaxial Cable (18 GHz~40 GHz)	EMCI	EMC101G-KM- KM-2000	211210	Jan. 15, 2025	1 year
☒	Coaxial Cable (18 GHz~40 GHz)	EMCI	EMC101G-KM- KM-6000	211209	Jan. 15, 2025	1 year
☒	Highpass Filter	Warison	WFIL-H6000- 26500F	WR4BBFWC4B1	Oct. 24, 2024	1 year
☒	Highpass Filter	Warison	WFIL-H8000- 26000F	001	Oct. 24, 2024	1 year
☒	Software	R_RAM	V1.3	N/A	N.C.R.	---

Note: N.C.R. = No Calibration Request


4 Measurement Procedure

4.1. AC Power Line Conducted Emission Measurement

■ Limit

Frequency (MHz)	Quasi-peak	Average
0.15 - 0.5	66 to 56	56 to 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

■ Test Setup



■ Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a $50\ \Omega // 50\ \mu\text{H}$ coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a $50\ \Omega // 50\ \mu\text{H}$ coupling impedance with 50 ohm termination.

Tabletop device shall be placed on a non-conducting platform, of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The wall of screened room shall be located 40 cm to the rear of the EUT. Other surfaces of tabletop or floor standing EUT shall be at least 80 cm from any other ground conducting surface including one or more LISNs. For floor-standing device shall be placed under the EUT with a 12 mm insulating material.

Conducted emissions were investigated over the frequency range from 0.15 MHz to 30 MHz using a resolution bandwidth of 9 kHz. The equipment under test (EUT) shall be meet the limits in section 4.1, as applicable, including the average limit and the quasi-peak limit when using respectively, an average detector and quasi-peak detector measured in accordance with the methods described of related standard. When all of peak value were complied with quasi-peak and average limit from 150 kHz to 30 MHz then quasi-peak and average measurement was unnecessary.

The AMN shall be placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for AMNs mounted on top of the ground reference plane. This distance is between the closest points of the AMN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8 m from the AMN. If the mains power cable is longer than 1 m then the cable shall be folded back and forth at the centre of the lead to form a bundle no longer than 0.4 m. All of interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long. All of EUT and AE shall be separate place more than 0.1 m. All 50 Ω ports of the LISN shall be resistively terminated into 50 Ω loads when not connected to the measuring instrument.

If the reading of the measuring receiver shows fluctuations close to the limit, the reading shall be observed for at least 15 s at each measurement frequency; the higher reading shall be recorded with the exception of any brief isolated high reading which shall be ignored.

4.2. Radiated Emission Measurement

■ Limit of Radiated Emission below 960 MHz Measurement (FCC 15.209)

Frequency (MHz)	Field Strength (μV/m at meter)	Measurement Distance (meter)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 - 88	100	3
88-216	150	3
216-960	200	3

Notes: (1) Emission level (dBuV/m)=20 log Emission level (uV/m).

Limits of Radiated Emission above 960 MHz Measurement (FCC 15.517(c))

Frequency (MHz)	EIRP (dBm), RBW = 1 MHz	Emission level (dBuV/m) (at 3 m)
960 – 1610	-75.3	19.9
1610 – 1990	-53.3	41.9
1990 – 3100	-51.3	43.9
3100 – 10600	-41.3	53.9
Above 10600	-51.3	43.9

Notes: (1) The limit for radiated test was performed according to FCC PART 15F.

(2) Emission level (dBuV/m) = EIRP (dBm) + 95.2, example, Emission level (dBuV/m) = -75.3 + 95.2 = 19.9

Limits of Radiated Emission in GPS band Measurement (FCC 15.517(d))


Frequency (MHz)	EIRP (dBm), RBW ≥ 1 kHz	Emission level (dBuV/m) (at 3 m)
1164 – 1240	-85.3	9.9
1559 – 1610	-85.3	9.9

Notes: (1) The limit for radiated test was performed according to FCC PART 15F.


(2) Emission level (dBuV/m) = EIRP (dBm) + 95.2, example, Emission level (dBuV/m) = -85.3 + 95.2 = 9.9

■ Setup

Below 1 GHz



Above 1 GHz



■ Test Procedure

Final radiation measurements were made on a three-meter, Semi Anechoic Chamber. The EUT system was placed on a nonconductive turntable which is 0.8 meters height, top surface 1.0 x 1.5 meter. The spectrum was examined from 9 kHz to 40 GHz in order to cover the whole spectrum below 10th harmonic which could generate from the EUT. During the test, EUT was set to transmit continuously & Measurements spectrum range from 9 kHz to 40 GHz is investigated. For measurements below 960 MHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak. For measurements below 30 MHz, all amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

For measurements above 960 MHz the resolution bandwidth is set to 1 MHz (GPS Band for 1 kHz), and then the video bandwidth is set to 3 MHz (GPS Band for 3 kHz) for average measurements.

A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

SCHWARZBECK MESS-ELEKTRONIK Biconilog Antenna (mode VULB9168) at 3 Meter and the SCHWARZBECK Double Ridged Guide Antenna (model BBHA9120D&9170) was used in frequencies 1 – 40 GHz at a distance of 1 meter. All test results were extrapolated to equivalent signal at 3 meters utilizing an inverse linear distance extrapolation Factor (20 dB/decade).

For the transmitter unwanted emission shall be measured using following options below:

Refer as ANSI C63.10, clause 4.1.4 and 4.1.4.2.2.

For radiated measurement:

Refer as ANSI C63.10, clause 6.4, 6.5 and 6.6.

The actual field is intensity in referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB/m), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

$$(1) \text{ Emission level (dBuV/m) = FI (dBuV) + AF (dBuV/m) + CL (dB) - PA (dB)}$$

FI= Reading of the field intensity.

AF= Antenna factor.

CL= Cable loss.

PA = Preamplifier Gain.


P.S Amplitude is auto calculate in spectrum analyzer.

4.3. Peak Power Measurement

■ Limit

There is a limit on the peak level of the emissions contained within a 50 MHz bandwidth centered on the frequency at which the highest radiated emission occurs, f_M . That limit is 0 dBm EIRP

■ Test Setup



■ Test Procedure

For the peak power shall be measured using following options below:

Refer as ANSI C63.10, clause 10.3.1, 10.3.2, 10.3.4, and 10.3.6.

4.4. UWB Bandwidth Measurement

■ Limit


UWB bandwidth. For the purpose of this subpart, the UWB bandwidth is the frequency band bounded by the points that are 10 dB below the highest radiated emission, as based on the complete transmission system including the antenna. The upper boundary is designated f_H and the lower boundary is designated f_L . The frequency at which the highest radiated emission occurs is designated f_M .

Center frequency. The center frequency, f_c , equals $(f_H + f_L)/2$.

Fractional bandwidth. The fractional bandwidth equals $2(f_H - f_L)/(f_H + f_L)$.

Ultra-wideband (UWB) transmitter. An intentional radiator that, at any point in time, has a fractional bandwidth equal to or greater than 0.20 or has a UWB bandwidth equal to or greater than 500 MHz, regardless of the fractional bandwidth.

■ Test Setup



■ Test Procedure

For the UWB Bandwidth shall be measured using following options below:


Refer as ANSI C63.10, clause 6.9.3 and 10.1.

4.5. Technical requirements for indoor UWB systems

■ Limit

A communications system shall transmit only when the intentional radiator is sending information to an associated receiver.

■ Test Setup



■ Test Procedure

Follow the test step as below:

1. Turn on EUT and companion receiver.
2. Check no transmitting signal from the EUT, when the EUT does not associate with the companion receiver.
4. Set the companion receiver to receiving mode.
5. Set the EUT to associate the companion receiver and then start to transmit.
6. Suspend the receiving function of the associated companion receiver.
7. Check if there is no transmission after stop sending information to receiver.

4.6. Antenna Measurement

■ Limit

For intentional device, according to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

■ Antenna Connector Construction

See section 2 – antenna information.


5 Test Results

5.1. Transmitter Radiated Emissions Test Results

ANT-1


Below 1 GHz

Test Site:	96602 - WG	Standard:	Part 15.517
Test Mode:	Transmit mode		
Polarization:	Horizontal		
Remark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	40.67	44.40	-8.25	36.15	40.00	-3.85	QP
2	165.80	46.07	-7.63	38.44	43.50	-5.06	QP
3	278.32	50.40	-7.00	43.40	46.00	-2.61	QP
4	397.63	48.59	-4.89	43.70	46.00	-2.30	QP
5	741.98	40.60	1.53	42.13	46.00	-3.87	QP
6	969.93	32.28	4.90	37.18	54.00	-16.82	QP


Test Site:	96602 - WG	Standard:	Part 15.517
Test Mode:	Transmit mode		
Polarization:	Vertical		
Remark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	41.64	45.94	-8.05	37.89	40.00	-2.11	QP
2	159.98	48.22	-7.37	40.85	43.50	-2.65	QP
3	398.60	41.46	-4.90	36.56	46.00	-9.44	QP
4	628.49	38.04	-0.46	37.58	46.00	-8.42	QP
5	743.92	35.17	1.62	36.79	46.00	-9.21	QP
6	995.15	31.94	5.26	37.20	54.00	-16.80	QP

Above 1 GHz

Test Site:	96602 - WG	Standard:	Part 15.517
Test Mode:	UWB 6489.6 MHz		
Polarization:	Horizontal		
Remark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	1938.00	33.60	-5.16	28.44	41.93	-13.49	RMS
2	3002.00	34.28	-2.25	32.03	43.93	-11.90	RMS
3	5900.00	33.29	3.18	36.47	53.93	-17.46	RMS
4	9030.00	33.12	5.94	39.07	53.93	-14.87	RMS
5	12790.00	33.68	7.80	41.48	43.93	-2.45	RMS

Note: EIRP (dBm) = dBuV/m + 20*LOG(Test Distance) - 104.77

Test Distance = 3m

-75.3 (dBm) - 20*LOG(3) + 104.77 = 19.93 (dBuV/m)


-53.3 (dBm) - 20*LOG(3) + 104.77 = 41.93 (dBuV/m)

-51.3 (dBm) - 20*LOG(3) + 104.77 = 43.93 (dBuV/m)

-41.3 (dBm) - 20*LOG(3) + 104.77 = 53.93 (dBuV/m)

-51.3 (dBm) - 20*LOG(3) + 104.77 = 43.93 (dBuV/m)

Test Site:	96602 - WG	Standard:	Part 15.17
Test Mode:	UWB 6489.6 MHz		
Polarization:	Vertical		
Remark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	1868.00	33.86	-5.46	28.40	41.93	-13.53	RMS
2	2127.00	41.40	-4.25	37.15	43.93	-6.78	RMS
3	5907.00	33.46	3.16	36.62	53.93	-17.31	RMS
4	10240.00	33.89	5.31	39.20	53.93	-14.73	RMS
5	13030.00	33.79	7.68	41.47	43.93	-2.46	RMS

Note: EIRP (dBm) = dBuV/m + 20*LOG(Test Distance) - 104.77

Test Distance = 3m

-75.3 (dBm) - 20*LOG(3) + 104.77 = 19.93 (dBuV/m)

-53.3 (dBm) - 20*LOG(3) + 104.77 = 41.93 (dBuV/m)


-51.3 (dBm) - 20*LOG(3) + 104.77 = 43.93 (dBuV/m)

-41.3 (dBm) - 20*LOG(3) + 104.77 = 53.93 (dBuV/m)

-51.3 (dBm) - 20*LOG(3) + 104.77 = 43.93 (dBuV/m)

GPS Band

Test Site:	96602 - WG	Standard:	Part 15.517
Test Mode:	UWB 6489.6 MHz		
Polarization:	Horizontal		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	1232.63	9.01	-6.96	2.05	19.47	-17.42	RMS

Note: EIRP (dBm) = dBuV/m + 20*LOG(Test Distance) - 104.77

Test Distance = 1m

-85.3 (dBm) - 20*LOG(1) + 104.77 = 19.47 (dBuV/m)

Test Site:	96602 - WG	Standard:	Part 15.517
Test Mode:	UWB 6489.6 MHz		
Polarization:	Vertical		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	1239.92	5.78	-6.96	-1.18	19.47	-20.65	RMS

Note: EIRP (dBm) = dBuV/m + 20*LOG(Test Distance) - 104.77

Test Distance = 1m

-85.3 (dBm) - 20*LOG(1) + 104.77 = 19.47 (dBuV/m)

Test Site:	96602 - WG	Standard:	Part 15.517
Test Mode:	UWB 6489.6 MHz		
Polarization:	Horizontal		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	1560.07	8.19	-6.60	1.59	19.47	-17.88	RMS

Note: EIRP (dBm) = dBuV/m + 20*LOG(Test Distance) - 104.77

Test Distance = 1m

-85.3 (dBm) - 20*LOG(1) + 104.77 = 19.47 (dBuV/m)

Test Site:	96602 - WG	Standard:	Part 15.17
Test Mode:	UWB 6489.6 MHz		
Polarization:	Vertical		
Remark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	1560.07	6.23	-6.60	-0.37	19.47	-19.84	RMS


Note: EIRP (dBm) = dBuV/m + 20*LOG(Test Distance) - 104.77

Test Distance = 1m

-85.3 (dBm) - 20*LOG(1) + 104.77 = 19.47 (dBuV/m)

Peak Power Test Results

Test Site:	96602 - WG	Standard:	Part 15.517
Test Mode:	UWB 6489.6 MHz		
Polarization:	Horizontal		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	6582.60	72.22	5.74	77.96	79.31	-1.35	PEAK

Note: EIRP (dBm) = E(dBuV/m) - 95.23

EIRP (dBm) = 77.96 dBuV/m - 95.23 = -17.27 dBm

EIRP 50 MHz (dBm) = EIRP 8MHz - 20 log (8 MHz / 50 MHz) = -18.07 - (-15.92) = -1.35 dBm

Test Site:	96602 - WG	Standard:	Part 15.517
Test Mode:	UWB 6489.6 MHz		
Polarization:	Vertical		
Remark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	6614.60	66.36	5.77	72.13	79.31	-7.18	PEAK

Note: EIRP (dBm) = E(dBuV/m) - 95.23


EIRP (dBm) = 72.13 dBuV/m - 95.23 = -23.1 dBm

EIRP 50 MHz (dBm) = EIRP 8MHz - 20 log (8 MHz / 50 MHz) = -23.1 - (-15.92) = -7.18 dBm

ANT-2


Below 1 GHz

Test Site:	96602 - WG	Standard:	Part 15.517
Test Mode:	Transmit mode		
Polarization:	Horizontal		
Remark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	40.65	44.39	-8.25	36.14	40.00	-3.86	QP
2	158.04	45.13	-7.28	37.85	43.50	-5.65	QP
3	299.66	49.68	-6.37	43.31	46.00	-2.69	QP
4	398.65	48.24	-4.90	43.34	46.00	-2.66	QP
5	731.31	38.50	1.23	39.73	46.00	-6.27	QP
6	993.21	31.50	5.20	36.70	54.00	-17.30	QP


Test Site:	96602 - WG	Standard:	Part 15.517
Test Mode:	Transmit mode		
Polarization:	Vertical		
Remark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	41.35	46.06	-8.14	37.92	40.00	-2.08	QP
2	161.92	48.01	-7.45	40.56	43.50	-2.94	QP
3	419.94	40.71	-4.45	36.26	46.00	-9.74	QP
4	617.82	35.49	-0.62	34.87	46.00	-11.13	QP
5	719.67	34.38	0.85	35.23	46.00	-10.77	QP
6	975.75	31.86	4.94	36.80	54.00	-17.20	QP

Above 1 GHz

Test Site:	96602 - WG	Standard:	Part 15.17
Test Mode:	UWB 6489.6 MHz		
Polarization:	Horizontal		
Remark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	1952.00	32.86	-5.07	27.79	41.93	-14.14	RMS
2	2722.00	34.59	-3.06	31.53	43.93	-12.40	RMS
3	5774.00	33.30	3.10	36.40	53.93	-17.53	RMS
4	9690.00	33.67	5.41	39.08	53.93	-14.85	RMS
5	12550.00	33.67	7.80	41.47	43.93	-2.46	RMS

Note: EIRP (dBm) = dBuV/m + 20*LOG(Test Distance) - 104.77

Test Distance = 3m

-75.3 (dBm) - 20*LOG(3) + 104.77 = 19.93 (dBuV/m)


-53.3 (dBm) - 20*LOG(3) + 104.77 = 41.93 (dBuV/m)

-51.3 (dBm) - 20*LOG(3) + 104.77 = 43.93 (dBuV/m)

-41.3 (dBm) - 20*LOG(3) + 104.77 = 53.93 (dBuV/m)

-51.3 (dBm) - 20*LOG(3) + 104.77 = 43.93 (dBuV/m)

Test Site:	96602 - WG	Standard:	Part 15.17
Test Mode:	UWB 6489.6 MHz		
Polarization:	Vertical		
Remark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	1945.00	33.70	-5.13	28.57	41.93	-13.36	RMS
2	2134.00	39.96	-4.23	35.73	43.93	-8.20	RMS
3	4794.00	37.93	1.30	39.23	53.93	-14.70	RMS
4	9000.00	32.88	5.97	38.85	53.93	-15.08	RMS
5	13590.00	33.68	7.67	41.36	43.93	-2.58	RMS

Note: EIRP (dBm) = dBuV/m + 20*LOG(Test Distance) - 104.77

Test Distance = 3m

-75.3 (dBm) - 20*LOG(3) + 104.77 = 19.93 (dBuV/m)

-53.3 (dBm) - 20*LOG(3) + 104.77 = 41.93 (dBuV/m)


-51.3 (dBm) - 20*LOG(3) + 104.77 = 43.93 (dBuV/m)

-41.3 (dBm) - 20*LOG(3) + 104.77 = 53.93 (dBuV/m)

-51.3 (dBm) - 20*LOG(3) + 104.77 = 43.93 (dBuV/m)

GPS Band

Test Site:	96602 - WG	Standard:	Part 15.517
Test Mode:	UWB 6489.6 MHz		
Polarization:	Horizontal		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	1200.02	9.06	-6.90	2.16	19.47	-17.31	RMS

Note: EIRP (dBm) = dBuV/m + 20*LOG(Test Distance) - 104.77

Test Distance = 1m

-85.3 (dBm) - 20*LOG(1) + 104.77 = 19.47 (dBuV/m)

Test Site:	96602 - WG	Standard:	Part 15.517
Test Mode:	UWB 6489.6 MHz		
Polarization:	Vertical		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	1239.16	6.31	-6.96	-0.65	19.47	-20.12	RMS

Note: EIRP (dBm) = dBuV/m + 20*LOG(Test Distance) - 104.77

Test Distance = 1m

-85.3 (dBm) - 20*LOG(1) + 104.77 = 19.47 (dBuV/m)

Test Site:	96602 - WG	Standard:	Part 15.517
Test Mode:	UWB 6489.6 MHz		
Polarization:	Horizontal		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	1560.07	8.15	-6.60	1.55	19.47	-17.92	RMS

Note: EIRP (dBm) = dBuV/m + 20*LOG(Test Distance) - 104.77

Test Distance = 1m

-85.3 (dBm) - 20*LOG(1) + 104.77 = 19.47 (dBuV/m)

Test Site:	96602 - WG	Standard:	Part 15.17
Test Mode:	UWB 6489.6 MHz		
Polarization:	Vertical		
Remark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	1578.48	5.88	-6.66	-0.78	19.47	-20.25	RMS


Note: EIRP (dBm) = dBuV/m + 20*LOG(Test Distance) - 104.77

Test Distance = 1m

-85.3 (dBm) - 20*LOG(1) + 104.77 = 19.47 (dBuV/m)

Peak Power Test Results

Test Site:	96602 - WG	Standard:	Part 15.517
Test Mode:	UWB 6489.6 MHz		
Polarization:	Horizontal		
Remark:			




ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	6583.60	72.42	5.74	78.16	79.31	-1.15	PEAK

Note: EIRP (dBm) = E(dBuV/m) - 95.23

EIRP (dBm) = 78.16 dBuV/m - 95.23 = -17.07 dBm

EIRP 50 MHz (dBm) = EIRP 8MHz - 20 log (8 MHz / 50 MHz) = -17.07 - (-15.92) = -1.15 dBm

Test Site:	96602 - WG	Standard:	Part 15.517
Test Mode:	UWB 6489.6 MHz		
Polarization:	Vertical		
Remark:			



ID	Frequency MHz	Reading dBuV	Correct Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
1	6743.60	65.95	6.03	71.98	79.31	-7.33	PEAK



Note: EIRP (dBm) = E(dBuV/m) - 95.23

EIRP (dBm) = 71.98 dBuV/m - 95.23 = -23.25 dBm

EIRP 50 MHz (dBm) = EIRP 8MHz - 20 log (8 MHz / 50 MHz) = -23.25 - (-15.92) = -7.33 dBm


UWB Bandwidth Test Results

Test Mode: UWB Mode				
Antenna	Center Frequency (MHz)	Bandwidth (10 dB)		
		Bandwidth (MHz)		Limit (MHz)
ANT-1	6583	594		≥ 500
ANT-2	6660	584		≥ 500
Antenna	Center Frequency (MHz)	Bandwidth (10 dB)		
		UWB	Bandwidth (MHz)	Limit (MHz)
ANT-1	6583	FL	6200	≥ 31
		FH	6794	≤ 106
ANT-2	6660	FL	6201	≥ 31
		FH	6785	≤ 106




Technical requirements for indoor UWB systems Test Results

Plot 1



Powering up for EUT.
No Transmit. (noise floor)

Plot 2



Mkr1: EUT associates the companion receiver and start to transmit.
Mkr2: Disables the companion receiver's RX functionality.
EUT disassociates from the companion receiver and stop transmitting.

---END---