


Embedded Dual-Band Antenna for WA-P-LB-02-883

1. Explanation of part number :



- (1) Product Type : Wireless Antenna
- (2) Material : PCB
- (3) Frequency : 2400-2500 、 5150-5850 MHz
- (4) Coaxial Cable Type : Black Cable
- (5) Suffix : 883

2. Electrical Specification :

Those specifications were specially defined for **IDL755** model **Dual-Band Antenna**, and all characteristics were measured under the model's handset testing jig.

2-1. Frequency Band :

Frequency Band	MHz
WiFi	2400-2500 、 5150-5850 MHz

2-2. Impedance :

50 ohm nominal

2-3. Matching circuit :

None

UNLESS OTHER SPECIFIED TOLERANCES ON :
 X = N/A X.X = N/A X.XX = N/A
 ANGLES = N/A HOLEDIA = N/A



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY : 涂正憲

CHECKED BY : 鄭榮謀

DESIGNED BY : 黃健育

APPROVED BY : 謝立庭

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION


TITLE : Embedded Dual-Band Antenna for
WA-P-LB-02-883

DOCUMENT
NO.

ENS000156290

SPEC REV.
P1

2-4. VSWR :



2-5. Efficiency :

Frequency (MHz)	Efficiency (%)	Peak Gain (dBi)
2400	53.99	3.22
2450	55.11	3.58
2500	52.61	3.45
5150	56.23	4.38
5250	58.48	4.21
5350	54.45	4.55
5470	56.23	4.38
5600	52.72	4.42
5725	52.48	4.21
5785	52.36	4.07
5850	50.47	3.97

UNLESS OTHER SPECIFIED TOLERANCES ON :
 X = N/A X.X = N/A X.XX = N/A
 ANGLES = N/A HOLEDIA = N/A



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY : 涂正憲

CHECKED BY : 鄭榮謀

DESIGNED BY : 黃健育

APPROVED BY : 謝立庭

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF
 INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED
 OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF
 APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : Embedded Dual-Band Antenna for
 WA-P-LB-02-883

DOCUMENT
 NO.


ENS000156290

SPEC REV.

P1

3. Antenna Drawing :

The appearance of the antenna is according to drawing Figure . 3-1-1



NOTE:

- 外觀標準:需完整無破損,不可有變形、髒污、毛邊、翹曲、裂縫、褶疊等情形。
Appearance standard : They must be complete. It means those must not have the deformations, dirt, burrs, warps, cracks, folds, etc.
- 工程圖上“”號為重點尺寸標註指示
Mark “” are the key dimensions.
- 工程圖上“”號為Cpk量測尺寸標註指示
Mark “” are CPK dimensions.
- QQC&FQC只需量測重點尺寸&CPK
CPK&KEY dimensions for QQC&FQC.

Drawing Rev.P0

Figure 3-1-1.

ITEM	DESCRIPTION	MATERIAL SPECIFICATION	QUANTITY	UNIT	SUPPLIER	UL NO.
1	PCB	L45*W28.5*T0.8mm	1	PCS	N/A	N/A
2	Cable	1.13LLS,White	1	PCS	HA0008	E318898
3	Tube	Transparent	1	PCS	HA0059	N/A
4	Connector	IPEX MHF I-PEX Equivalent(compatible)	1	PCS	HA0063	E213445

UNLESS OTHER SPECIFIED TOLERANCES ON :
X=N/A X.X=N/A X.XX=N/A
ANGLES=N/A HOLEDIA=N/A



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY : 涂正甯

CHECKED BY : 鄭榮謀

DESIGNED BY : 黃健育

APPROVED BY : 謝立庭


TITLE : Embedded Dual-Band Antenna for WA-P-LB-02-883	
--	--

DOCUMENT NO.	
-----------------	--

ENS000156290


SPEC	REV.
P1	

4. Connector Specification :



1. Material

- (1) Housing : PBT , UL94V-0
- (2) Contact
phosphor bronze
gold plating $0.1\mu\text{m}$ MIN.
over nickel $1.27\mu\text{m}$ MIN.
- (3) Ground contact
phosphor bronze
gold plating $0.05\mu\text{m}$ MIN.
over nickel $1.27\mu\text{m}$ MIN.



UNLESS OTHER SPECIFIED TOLERANCES ON :
X = N/A X.X = N/A X.XX = N/A
ANGLES = N/A HOLEDIA = N/A



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY : 涂正憲

CHECKED BY : 鄭榮謀

DESIGNED BY : 黃健育

APPROVED BY : 謝立庭

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : Embedded Dual-Band Antenna for
WA-P-LB-02-883

DOCUMENT
NO.

ENS000156290

SPEC REV.
P1