



RF Exposure Analysis

FCC ID: 2AQ6NH1

Analysis for FCC portable use – Ponix Systems, Herbert product

Standalone SAR test exclusion considerations are defined in KDB 447498D01 (v06) Chapter 4.3.1 where the 1-g head or body and 10-g extremity SAR exclusion threshold is defined by the following formula:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The maximum conducted output power for the device is -16 dBm (0.025mW).

Applying the above data using the given KDB 447498 D01 formula, and minimum separation distance of 5mm, the following results:

$(0.025\text{mW} / 5 \text{ mm}) \times \sqrt{2.45 \text{ GHz}} = 0.01$ (i.e.: ≤ 3.0 for 1-g SAR)

This demonstrates the device meets the criteria for 1-g head/ body SAR test exemption.

Conclusion

The Ponix Systems, Herbert product is exempt from SAR testing and can be used for Portable applications.

A handwritten signature in black ink, appearing to read "Herbert".

Ponix Systems GmbH
Sechshauser Straße 55-57/4
1150 - Vienna
Austria
office@ponix-systems.at
www.ponix.systems

Signature: _____

Date: 11.13.2018