



## FCC RF EXPOSURE REPORT

*For*

**TaroVR**

**MODEL NUMBER: TaroVR I**

**PROJECT NUMBER: 4788148204**

**REPORT NUMBER: 478148204-3**

**FCC ID: 2AQ7D-TARO-VR001**

**ISSUE DATE: Sep. 20, 2018**

*Prepared for*

**HANGZHOU TARO INFORMATION TECHNOLOGY LLC  
A703 HUAXING SHIDAIGUANGCHANG, NO.478, WENSAN RD, HANGZHOU, CHINA**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch  
Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-  
Tech Development Zone Dongguan, 523808, People's Republic of China**  
Tel: +86 769 22038881  
Fax: +86 769 33244054  
Website: [www.ul.com](http://www.ul.com)

Revision History

Rev.	Issue Date	Revisions	Revised By
--	09/24/2018	Initial Issue	

## TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS .....	4
2. TEST METHODOLOGY .....	5
3. FACILITIES AND ACCREDITATION .....	5
4. REQUIREMENT .....	6

## 1. ATTESTATION OF TEST RESULTS

### Applicant Information

Company Name: HANGZHOU TARO INFORMATION TECHNOLOGY LLC.  
Address: A703 HUAXING SHIDAIGUANGCHANG, NO.478, WENSAN RD,  
HANGZHOU, CHINA

### Manufacturer Information

Company Name: WESTLAKE ELETRONIC.  
Address: NO.23, NUMBER 10 RD, ECONOMIC DEVELOPMENT ZONE,  
HANGZHOU

### EUT Information

EUT Name: TaroVR  
Model: TaroVR I  
Sample Received Date: Dec .7, 2017  
Date of Tested: May 10~May 20, 2018

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47CFR§2.1093	Complies
KDB-447498 D01 V06	Complies

Tested By:



Miller Ma  
Engineer Project Associate

Checked By:



Shawn Wen  
Laboratory Leader

Approved By:



Stephen Guo

Laboratory Manager

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06.

## 3. FACILITIES AND ACCREDITATION

Test Location	Dongguan Dongdian Testing Service Co., Ltd
Address	No. 17, Zongbu Road 2, Songshan Lake Sci&Tech Park, Dongguan City, Guangdong Province, 523808, China
Accreditation Certificate	<p>Dongguan Dongdian Testing Service Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing. Valid time is until January 31, 2018.</p> <p>Dongguan Dongdian Testing Service Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 270092, Renewal date March 11, 2015, valid time is until March 11, 2018.</p> <p>The 3m Alternate Test Site of Dongguan Dongdian Testing Service Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 10288A on April 23, 2015, valid time is until April 23, 2018.</p>

Note:

1. All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China
2. The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.
3. For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OATS.

## 4. REQUIREMENT

### LIMIT AND CALCULATION METHOD

#### RF EXPOSURE LIMIT

FCC 1.1310: The criteria listed in table 1 shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in

§ 1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of § 2.1093 of this chapter. Further information on evaluating compliance with these limits can be found in the FCC's OST/OET Bulletin Number 65, "Evaluating Compliance with FCC-Specified Guidelines for Human Exposure to Radiofrequency Radiation."

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

According to KDB-447498 D01 V06 Standalone SAR test exclusion considerations:

a) For 100 MHz to 6 GHz and test separation distances  $\leq$  50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR, and  $\leq 7.5$  for 10-g extremity SAR,30 where

· f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation31

· The result is rounded to one decimal place for comparison

· The values 3.0 and 7.5 are referred to as numeric thresholds in step b) below

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $<$  5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

## **CALCULATED RESULTS**

Frequency	Maximum Output Power	EIRP		Distance	Limit	Calculated Result
(MHz)	(dBm)	(dBm)	(mW)	(mm)	--	--
2402	-2	-2	0.631	5	3	0.196

Note: 1. Calculation Results = Max Tune Up Power (mW) /5\*  $\sqrt{}$  Frequency (GHz)  
2. The Power comes from report 4788148204-1.  
3. The minimum separation distance of the device = 0 mm, according to KDB-447498 D01 V06, 5 mm is applied to determine SAR test exclusion.  
4. Owing to the maximum Calculated Result is below the limit, so it deemed to comply with the basic restrictions without testing which means that no SAR is required.

## **END OF REPORT**