

# Hanson Robotics Limited

# TEST REPORT

**SCOPE OF WORK**

FCC TESTING-HR\_WIFIUSBD01

**REPORT NUMBER**

180725019SZN-003

**ISSUE DATE**

22 November 2018

**[REVISED DATE]**

[-----]

**PAGES**

57

**DOCUMENT CONTROL NUMBER**

FCC SAR\_b

© 2017 INTERTEK



## **SAR TEST REPORT**

*For*

Hanson Robotics Limited

Scratch X Dongle

Model No.: HR\_WIFIUSBD01

Report No.: 180725019SZN-003

Issue Date: 22 November 2018

*Prepared by*

Intertek Testing Services Shenzhen Ltd.  
101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community,  
GuanHu Subdistrict, LongHua District, ShenZhen, P.R. China

Telephone: 86-755-8601 6288

Fax: 86-755-8601 6751

- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- The test report only allows to be revised only within the report defined retention period unless further standard or the requirement was noticed

# Table of Contents

|   |           |
|---|-----------|
| <b>1 GENERAL INFORMATION .....</b>                              | <b>4</b>  |
| <b>2 STATEMENT OF COMPLIANCE .....</b>                          | <b>5</b>  |
| <b>3 EQUIPMENT UNDER TEST (EUT) TECHNICAL DESCRIPTION .....</b> | <b>7</b>  |
| <b>4 AUXILIARY EQUIPMENT DETAILS .....</b>                      | <b>8</b>  |
| <b>5 SUPPORT EQUIPMENT.....</b>                                 | <b>8</b>  |
| <b>6 TEST FACILITY .....</b>                                    | <b>8</b>  |
| <b>7 GUIDANCE STANDARD.....</b>                                 | <b>9</b>  |
| <b>8 EUT ANTENNA LOCATIONS .....</b>                            | <b>10</b> |
| <b>9 RF EXPOSURE .....</b>                                      | <b>11</b> |
| 9.1 LIMITS.....   | 11        |
| 9.2 EVALUATION .....  | 11        |
| <b>10 SPECIFIC ABSORPTION RATE (SAR).....</b>                   | <b>12</b> |
| 10.1 INTRODUCTION .....   | 12        |
| 10.2 SAR DEFINITION.....  | 12        |
| <b>11 SAR MEASUREMENTS SYSTEM CONFIGURATION .....</b>           | <b>13</b> |
| 11.1 SAR MEASUREMENT SET-UP .....                               | 13        |
| 11.2 DASY5 E-FIELD PROBE SYSTEM .....                           | 14        |
| 11.3 E-FIELD PROBE CALIBRATION.....                             | 15        |
| 11.4 OTHER TEST EQUIPMENT.....                                  | 16        |
| 11.5 SCANNING PROCEDURE .....                                   | 18        |
| 11.6 DATA STORAGE AND EVALUATION .....                          | 20        |
| 11.7 TISSUE-EQUIVALENT LIQUID.....                              | 22        |
| 11.8 SYSTEM CHECK .....   | 23        |

|  |           |
|--|-----------|
| <b>12 MEASUREMENT PROCEDURES.....</b>                                  | <b>25</b> |
| 12.1 GENERAL DESCRIPTION OF TEST PROCEDURES .....                      | 25        |
| 12.2 MEASUREMENT VARIABILITY .....                                     | 26        |
| <b>13 TEST RESULTS .....</b>   | <b>27</b> |
| 13.1 Conducted Power Results .....                                     | 27        |
| 13.2 SAR TEST RESULTS .....  | 29        |
| 13.3 2.4 GHz 802.11g/n-HT20 OFDM SAR Test Exclusion Requirements ..... | 29        |
| 13.4 Simultaneous Transmission Conditions.....                         | 29        |
| 13.5 MAXIMUM GRAPH RESULTS .....                                       | 29        |
| <b>14 MEASUREMENT UNCERTAINTY .....</b>                                | <b>30</b> |
| <b>15 MAIN TEST INSTRUMENT .....</b>                                   | <b>31</b> |
| <b>ANNEX A : TEST LAYOUT AND SETUP .....</b>                           | <b>32</b> |
| <b>ANNEX B : SYSTEM CHECK RESULTS.....</b>                             | <b>33</b> |
| <b>ANNEX C : MAXIMUM GRAPH RESULTS.....</b>                            | <b>34</b> |
| <b>ANNEX D : SYSTEM VALIDATION.....</b>                                | <b>35</b> |
| <b>ANNEX E : PROBE, DAE AND DIPOLE CALIBRATION CERTIFICATE .....</b>   | <b>36</b> |

## 1 GENERAL INFORMATION

|                      |   |
|----------------------|---|
| Applicant:           | Hanson Robotics Limited<br>Unit 209B, 2/F, Phonics Centre, Phase One Hong Kong Science Park, Pak Shek Kok, N.T, HONG KONG |
| Manufacturer:        | Dongguan Aifei Electronic Technology Co., Ltd.  |
| Product Description: | Scratch X Dongle  |
| Model Number:        | HR_WIFIUSBD01   |
| File Number:         | 180725019SZN-003  |
| Date of Test:        | 22 November 2018  |

The above equipment was tested by Intertek Testing Services Shenzhen Ltd. Longhua Branch. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in IEEE 1528-2013 and KDB 865664. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in ANSI/IEEE C95.1-1992.

The test results of this report relate only to the tested sample identified in this report.

Prepared and Checked by:

Damon Wang  
Engineer

Approved by:

---

Kidd Yang  
Technical Supervisor  
Date: 22 November 2018

## 2 STATEMENT OF COMPLIANCE

Max. Reported SAR (1g)

| Test Position         |                       | Mode    | Channel / Frequency(MHz) | Limit of SAR1g: 1.6 W/kg |       |
|-----------------------|-----------------------|---------|--------------------------|--------------------------|-------|
| Measured SAR1g (W/kg) | Reported SAR1g (W/kg) |         |                          |                          |       |
| Body                  | Horizontal-Up         | 802.11b | 1 / 2412                 | 0.186                    | 0.208 |

The SAR values found for the Scratch X Dongle is below the maximum recommended levels of 1.6 W/kg as averaged over any 1g tissue according to the ANSI C95.1-1992.

The maximum reported SAR value is: 0.208W/kg (1g).

**Modified Information**

| Rev.    | Summary         | Date of Rev.     | Report No.       |
|---------|-----------------|------------------|------------------|
| Ver.1.0 | Original Report | 22 November 2018 | 180725019SZN-003 |

### 3 EQUIPMENT UNDER TEST (EUT) TECHNICAL DESCRIPTION

| Characteristics            | Description  |
|----------------------------|--|
| Device type:               | Scratch X Dongle   |
| Exposure Category:         | Uncontrolled Environment / General Population                  |
| Test Mode(s):              | 802.11 b/g/n-HT20  |
| Operating Frequency Range: | 802.11 b/g/n-HT20: 2412MHz – 2462MHz                           |
| Modulation:                | BPSK, QPSK, 16QAM, 64QAM, CCK, DQPSK, DBPSK                    |
| Power Level:               | IEEE 802.11b/g: 15dBm (max.)<br>IEEE 802.11n-HT20: 12dBm(max.) |
| Antenna Type:              | internal permanent antenna                                     |
| Antenna Gain:              | 5 dBi  |
| Dimensions (cm)            | 6.0*2.5*1  |
| Power supply:              | D.C. 5V by USB Port  |
| Product Software Version:  | Firmware ver hr-usbd-rc01                                      |
| Product Hardware Version:  | USB TO UART WIFI V1.3  |

*Note:*

1. For more details, please refer to the User's manual of the EUT.
2. The sample under test was selected by the Client.

## 4 AUXILIARY EQUIPMENT DETAILS

|               |         |          |
|---------------|---------|----------|
| AE: Battery   | Battery | Earphone |
| Manufacturer: | /       | /        |
| Model:        | /       | /        |
| S/N:          | /       | /        |
| capacity:     | /       | /        |
| Voltage:      | /       | /        |

## 5 SUPPORT EQUIPMENT

| Equipment                   | Manufacturer | Model No. |
|-----------------------------|--------------|-----------|
| USB Cable (Shielded, 25cm ) | N/A          | N/A       |
| Laptop                      | ThinkPad     | T420      |
| Laptop                      | ThinkPad     | X1        |

Note: the USB cable does not influence the radiating characteristics and output power of the transmitter.

## 6 TEST FACILITY

|                  |   |
|------------------|---|
| Site Description |   |
| EMC Lab.         | The Laboratory has been assessed and proved to be in compliance with CNAS/CL01: 2006(identical to ISO/IEC17025: 2005)<br>The Certificate Registration Number is L0327 |
|                  | Accredited by FCC<br>The Certificate Registration Number is CN1188  |
| Name of Firm     | Intertek Testing Services Shenzhen Ltd.   |
| Site Location    | 101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, Shenzhen, P.R. China  |

## 7 GUIDANCE STANDARD


The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47CFR §2.1093** Radiofrequency Radiation Exposure Evaluation: Portable Devices
- ANSI C95.1, 1992**: Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.(IEEE Std C95.1-1991)
- IEEE Std 1528™-2013**: IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
- KDB 865664 D01** SAR measurement 100 MHz to 6 GHz v01r04: SAR Measurement Requirements for 100 MHz to 6 GHz
- KDB 865664 D02 RF Exposure Reporting v01r02**: RF Exposure Compliance Reporting and Documentation Considerations
- KDB 447498 D01** Mobile Portable RF Exposure v06: Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies
- KDB 447498 D02** SAR Procedures for Dongle Xmtr v02r01 provides guidance for SAR testing of USB dongle transmitters.
- KDB 248227 D01** SAR measurement for 802.11 a b g v02r02:SAR Measurement Procedures for 802.11 a/b/g Transmitters

### Remark:

This portable wireless equipment has been measured in all cases requested by the relevant standards. Test results in Chapter 11 of this test report are below limits specified in the relevant standards for the tested bands only.

## 8 EUT ANTENNA LOCATIONS



All Sides for SAR Testing Evaluation:

| Mode                                   | Horizontal-Down | Horizontal-Up | Vertical-Back | Vertical Front |
|--|-----------------|---------------|---------------|----------------|
| Distance from the antenna (mm)         | 4.5             | 4.5           | 6             | 7.5            |
| Exemption with Max. Allowed Power (mW) | 9.6             | 9.6           | 11.6          | 14.5           |
| 802.11b                                | YES             | YES           | YES           | YES            |

Note: Exemption with Max. Allowed Power Calculation according to KDB 447498 D01 Clause 4.3.1 with the following formula:

- For 100 MHz to 6 GHz and *test separation distances*  $\leq$  50 mm, the 1-g SAR test exclusion thresholds are determined by the following:  

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR,}$$
\*where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz  
\*When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.
- For 100 MHz to 6 GHz and *test separation distances*  $>$  50 mm, the 1-g SAR test exclusion thresholds are determined by the following  

$$\{[\text{Power allowed at numeric threshold for 50 mm in step a)}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot 10]\} \text{ mW, for } > 1500 \text{ MHz and } \leq 6 \text{ GHz}$$
- EUT maximum power level: 15dBm=31.62mW (Duty factor = 1)

## 9 RF EXPOSURE

### 9.1 LIMITS

#### Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Limits for General Population/Uncontrolled Exposure (W/kg)

| Whole-Body | Partial-Body | Hands, Wrists, Feet and ankles |
|------------|--------------|--------------------------------|
| 0.08       | 1.6          | 4.0                            |

Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

### 9.2 EVALUATION

According to FCC KDB447498 D01 and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. Portable transmitters with output power greater than the applicable low threshold require SAR testing to qualify for TCB approval.

## 10 SPECIFIC ABSORPTION RATE (SAR)

### 10.1 INTRODUCTION

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

### 10.2 SAR DEFINITION

The SAR definition is the time derivative (rate) of the incremental energy ( $dW$ ) absorbed by (dissipated in) an incremental mass ( $dm$ ) contained in a volume element ( $dv$ ) of a given density ( $\rho$ ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = c \left( \frac{\delta T}{\delta t} \right)$$

Where:  $C$  is the specific heat capacity,  $\delta T$  is the temperature rise and  $\delta t$  is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of tissue and  $E$  is the RMS electrical field strength.


However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

## 11 SAR MEASUREMENTS SYSTEM CONFIGURATION

### 11.1 SAR MEASUREMENT SET-UP

The DASY5 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Stäubli TX=RX family) with controller, teach pendant and software.
- An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running Win 7 professional operating system and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.



Picture 1: SAR Lab Test Measurement Set-up

## 11.2 DASY5 E-FIELD PROBE SYSTEM

The SAR measurements were conducted with the dosimetric probe designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multifiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY5 software reads the reflection turning a software approach and looks for the maximum using 2<sup>nd</sup> ord curve fitting. The approach is stopped at reaching the maximum.

### Probe Specifications:

Model: EX3DV4

Calibration: ISO/IEC 17025 calibration service available

Probe Length: 337 mm

Probe Tip Length: 9 mm

Body Diameter: 10 mm

Tip Diameter: 2.5 mm

Application: High Precision dosimetric measurements in any exposure scenario (e.g., very strong Picture 2 E-field Probe gradient fields).



Picture 2: E-FIELD PROBE

### 11.3 E-FIELD PROBE CALIBRATION

Each E-Probe/Probe Amplifier combination has unique calibration parameters. A TEM cell calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm<sup>2</sup>) using an RF Signal generator, TEM cell, and RF Power Meter.

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mw/ cm<sup>2</sup>.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C \frac{\Delta T}{\Delta t}$$

Where:

$\Delta t$  = Exposure time (30 seconds),  
C = Heat capacity of tissue (brain or muscle),  
 $\Delta T$  = Temperature increase due to RF exposure.

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

Where:

$\sigma$  = Simulated tissue conductivity,  
 $\rho$  = Tissue density (kg/m<sup>3</sup>).

## 11.4 OTHER TEST EQUIPMENT

### 11.4.1 Data Acquisition Electronics (DAE)

The data acquisition electronics consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of the DAE is 200 MΩ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Picture 3: DAE

### 11.4.2 Robot

The SPEAG DASY system uses the high precision robots (DASY5: TX90XL) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchron motors; no stepper motors)
- Low ELF interference (motor control fields shielded via the closed metallic construction shields)



Picture 4: DASY 5

### 11.4.3 Measurement Server

The Measurement server is based on a PC/104 CPU broad with CPU (DASY5: 400 MHz, Intel Celeron), chip disk (DASY5: 128MB), RAM (DASY5: 128MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY I/O broad, which is directly connected to the PC/104 bus of the CPU broad.



Picture 5: Server for DASY 5

The measurement server performs all real-time data evaluation of field measurements and surface detection, controls robot movements and handles safety operation. The PC operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port which is reserved for future applications. Please note that this expansion port does not have a standardized pinout, and therefore only devices provided by SPEAG can be connected. Devices from any other supplier could seriously damage the measurement server.

### 11.4.4 Device Holder for Phantom

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5mm distance, a positioning uncertainty of  $\pm 0.5\text{mm}$  would produce a SAR uncertainty of  $\pm 20\%$ . Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

The DASY device holder is designed to cope with the different positions given in the standard. It has two scales for device rotation (with respect to the body axis) and device inclination (with respect to the line between the ear reference points). The rotation centers for both scales are the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon = 3$  and loss tangent  $\delta = 0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.

<Laptop Extension Kit>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the Mounting Device in place of the phone positioner. The extension is fully compatible with the Twin-SAM and ELI phantoms.



Picture 6: Device Holder

#### 11.4.5 Phantom

The SAM Twin Phantom V5.0 is constructed of a fiberglass shell integrated in a table. The shape of the shell is based on data from an anatomical study designed to Represent the 90<sup>th</sup> percentile of the population. The phantom enables the dissymmetric evaluation of SAR for both left and right-handed handset usage, as well as body-worn usage using the flat phantom region. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. The shell phantom has a 2mm shell thickness (except the ear region where shell thickness increases to 6 mm).

Shell Thickness:  $2 \pm 0.2$  mm

Filling Volume: Approx. 25 liters

Dimensions: 810 x 1000 x 500 mm (H x L x W)

Available: Special



**Picture 7: SAM Twin Phantom**

#### 11.5 SCANNING PROCEDURE

The DASY5 installation includes predefined files with recommended procedures for measurements and validation. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.

The “reference” and “drift” measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the DUT’s output power and should vary max.  $\pm 5\%$ .

The “surface check” measurement tests the optical surface detection system of the DASY5 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above  $\pm 0.1$ mm). To prevent wrong results tests are only

executed when the liquid is free of air bubbles. The difference between the optical surface detection and the actual surface depends on the probe and is specified with each probe. (It does not depend on the surface reflectivity or the probe angle to the surface within  $\pm 30^\circ$ .)

#### Area Scan

The Area Scan is used as a fast scan in two dimensions to find the area of high field values before running a detailed measurement around the hot spot. Before starting the area scan a grid spacing is set according to FCC KDB Publication 865664. During scan the distance of the probe to the phantom remains unchanged. After finishing area scan, the field maxima within a range of 2 dB will be ascertained.

#### Zoom Scan

After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm.

#### Spatial Peak Detection

The procedure for spatial peak SAR evaluation has been implemented and can determine values of masses of 1g and 10g, as well as for user-specific masses. The DASY5 system allows evaluations that combine measured data and robot positions, such as:

- maximum search
- extrapolation
- boundary correction
- peak search for averaged SAR

During a maximum search, global and local maxima searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation. Extrapolation routines require at least 10 measurement points in 3-D space.

They are used in the Zoom Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Shepard's method for extrapolation.

A Z-axis scan measures the total SAR value at the x-and y-position of the maximum SAR value found during the cube scan. The probe is moved away in z-direction from the bottom of the SAM phantom in 5mm steps.

Table 1: Area and Zoom Scan Resolutions per FCC KDB Publication 865664 D01

| Frequency | Maximum Area Scan Resolution (mm)<br>( $\Delta x_{area}$ , $\Delta y_{area}$ ) | Maximum Zoom Scan Resolution (mm)<br>( $\Delta x_{zoom}$ , $\Delta y_{zoom}$ ) | Maximum Zoom Scan Spatial Resolution (mm)<br>( $\Delta z_{zoom}$ ) | Minimum Zoom Scan Volume (mm) (x,y,z) |
|-----------|--|--|--|---------------------------------------|
| ≤2 GHz    | ≤15  | ≤8   | ≤5   | ≥ 30                                  |
| 2-3 GHz   | ≤12  | ≤5   | ≤5   | ≥30                                   |
| 3-4 GHz   | ≤12  | ≤5   | ≤4   | ≥28                                   |
| 4-5 GHz   | ≤10  | ≤4   | ≤3   | ≥25                                   |
| 5-6 GHz   | ≤10  | ≤4   | ≤2   | ≥22                                   |

## 11.6 DATA STORAGE AND EVALUATION

### 11.6.1 Data Storage

The DASY5 software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension ".DAE4". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device set up, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the

selected probe type ([V/m], [A/m], [°C], [mW/g], [mW/cm<sup>2</sup>], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a loss less media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

### 11.6.2 Data Evaluation by SEMCAD

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:

- Sensitivity Norm<sub>i</sub>, a<sub>i0</sub>, a<sub>i1</sub>, a<sub>i2</sub>
- Conversion factor ConvF<sub>i</sub>
- Diode compression point Dcp<sub>i</sub>

Device parameters:

- Frequency f
- Crest factor cf

Media parameters:

- Conductivity
- Density

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY5 components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics.

If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot c f / dcp_i$$

With  $V_i$  = compensated signal of channel  $i$  ( $i = x, y, z$ )

$U_i$  = input signal of channel  $i$  ( $i = x, y, z$ )

$cf$  = crest factor of exciting field (DASY parameter)

$dcp_i$  = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be

evaluated:

E-field probes:  $E_i = (V_i / Norm_i \cdot ConvF)^{1/2}$

H-field probes:  $H_i = (V_i)^{1/2} \cdot (a_{i0} + a_{i1} f + a_{i2} f^2) / f$

With  $V_i$  = compensated signal of channel  $i$  ( $i = x, y, z$ )

$Norm_i$  = sensor sensitivity of channel  $i$  ( $i = x, y, z$ )

[mV/(V/m)2] for E-field Probes

$ConvF$  = sensitivity enhancement in solution

$a_{ij}$  = sensor sensitivity factors for H-field probes

$f$  = carrier frequency [GHz]

$E_i$  = electric field strength of channel  $i$  in V/m

$H_i$  = magnetic field strength of channel  $i$  in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = (E_{tot}) 2 \cdot \sigma / (\rho \cdot 1000)$$

with  $SAR$  = local specific absorption rate in mW/g

$E_{tot}$  = total field strength in V/m

= conductivity in [mho/m] or [Siemens/m]

= equivalent tissue density in g/cm<sup>3</sup>

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = E_{tot}^2 / 3770 \text{ or } P_{pwe} = H_{tot}^2 \cdot 37.7$$

with  $P_{pwe}$  = equivalent power density of a plane wave in mW/cm<sup>2</sup>

$E_{tot}$  = total electric field strength in V/m ;

$H_{tot}$  = total magnetic field strength in A/m

## 11.7 TISSUE-EQUIVALENT LIQUID

### 11.7.1 Tissue-equivalent Liquid Ingredients

The liquid is consisted of water, salt and Glycol. The liquid has previously been proven to be suited for worst-case. The Table 2 shows the detail solution, Table 3 is target tissue dielectric parameters. It's satisfying the latest tissue dielectric parameters requirements proposed by the KDB 865664 D01.

Table 2: Composition of the Head and Body Tissue Equivalent Matter

| MIXTURE%                           |  | FREQUENCY (Body) 2450MHz                |
|------------------------------------|--|---|
| Water                              |  | 73.2                                    |
| Glycol                             |  | 26.7                                    |
| Salt                               |  | 0.1                                     |
| Dielectric Parameters Target Value |  | f=2450MHz $\epsilon=52.7$ $\sigma=1.95$ |

### 11.7.2 Tissue-equivalent Liquid Properties


Table 3: Dielectric Performance of Tissue Simulating Liquid

| Test Date  | Frequency (MHz) | Tissue Type | Liquid Temp (°C) | Conductivity (σ) | Permittivity (εr) | Conductivity Target (σ) | Permittivity Target (εr) | Delta (σ) (%) | Delta (εr) (%) | Limit (%) |
|------------|-----------------|-------------|------------------|------------------|-------------------|-------------------------|--------------------------|---------------|----------------|-----------|
| 2018-11-22 | 2450            | Body        | 21.5             | 2.009            | 52.56             | 1.95                    | 52.70                    | 3.03          | -0.27          | ±5        |

## 11.8 SYSTEM CHECK

### 11.8.1 Description of System Check

The manufacturer calibrates the probes annually. Dielectric parameters of the tissue simulants were measured every day using the dielectric probe kit and the network analyzer. A system check measurement was made following the determination of the dielectric parameters of the simulant, using the dipole validation kit. A power level of 250 mW was supplied to the dipole antenna, which was placed under the flat section of the twin SAM phantom. The system check results (dielectric parameters and SAR values) are given in the table 5. System check results have to be equal or near the values determined during dipole calibration with the relevant liquids and test system ( $\pm 10\%$ ). System check is performed regularly on all frequency bands where tests are performed with the DASY5 system.



Picture 9: System Check Set-up

### 11.8.2 System Check Results

Table 6: System Check for Body Tissue Simulating Liquid

| Frequency | Test Date  | Dielectric Parameters |                | 250mW<br>Measured<br>SAR1g | 1W<br>Normalized<br>SAR1g | 1W Target<br>SAR1g | Limit( $\pm 10\%$<br>Deviation) |
|-----------|------------|-----------------------|----------------|----------------------------|---------------------------|--------------------|---------------------------------|
|           |            | $\epsilon_r$          | $\sigma$ (s/m) |                            |                           |                    |                                 |
| 2450MHz   | 2018-11-22 | 52.56                 | 2.009          | 13.5                       | 54.00                     | 50.70              | 6.51                            |

Note: 1. The graph results see ANNEX B.  
 2. Target Values used derive from the calibration certificate.

## 12 MEASUREMENT PROCEDURES

### 12.1 GENERAL DESCRIPTION OF TEST PROCEDURES

For WLAN SAR testing, WLAN engineering testing software installed on the DUT can provide continuous transmitting RF signal. This RF signal utilized in SAR measurement has almost 100% duty cycle and its crest factor is 1.

For the 802.11b/g/n SAR tests, a communication link is set up with the test mode software for WIFI mode test. During the test, at the each test frequency channel, the EUT is operated at the RF continuous emission mode. Provided higher maximum output power is not specified for the other channels, channels 1, 6 and 11 are used to configure 22 MHz DSSS and 20 MHz OFDM channels for SAR measurements; otherwise, the closest adjacent channel with the highest maximum output power specified for production units should be tested instead of channels 1, 6 or 11. When 40 MHz channels are supported, and provided higher maximum output power is not specified for other applicable 40 MHz channels, channel 6 is used to measure SAR; otherwise, the channel with highest specified maximum output power should be tested instead. In addition, SAR test reduction with respect to reported SAR and transmission band width according to 4.3.3 of KDB Publication 447498 D01 may also be applied 802.11b/g/n operating modes are tested independently according to the service requirements in each frequency band. 802.11b/g/n modes are tested on the maximum average output channel.

SAR is measured for 2.4 GHz 802.11b DSSS using either a fixed test position or, when applicable, the initial test position procedure. SAR test reduction is determined according to the following:

- a) When the reported SAR of the highest measured maximum output power channel (see 3.1) for the exposure configuration is  $\leq 0.8 \text{ W/kg}$ , no further SAR testing is required for 802.11b DSSS in that exposure configuration.
- b) When the reported SAR is  $> 0.8 \text{ W/kg}$ , SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is  $> 1.2 \text{ W/kg}$ , SAR is required for the third channel; i.e., all channels require testing.

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied (see 5.3, including subclauses). SAR is not required for the following 2.4 GHz OFDM conditions.

When KDB Publication 447498 D01 SAR test exclusion applies to the OFDM configuration.

When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2 \text{ W/kg}$ .

## 12.2 MEASUREMENT VARIABILITY

Per FCC KDB Publication 865664 D01, SAR measurement variability was assessed for each frequency band, which was determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media were required for SAR measurements in a frequency band, the variability measurement procedures were applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. These additional measurements were repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device was returned to ambient conditions (normal room temperature) with the battery fully charged before it was re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR Measurement Variability was assessed using the following procedures for each frequency band:

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$  or when the original or repeated measurement is  $\geq 1.45$  W/kg ( $\sim 10\%$  from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .

## 13 TEST RESULTS

### 13.1 Conducted Power Results

| Mode      | Channel / Frequency (MHz) | Data rate (Mbps) | AV Power (dBm) | Tune up limited (dBm) |
|-----------|---------------------------|------------------|----------------|-----------------------|
| 11b       | 1 / 2412                  | 1                | 14.5           | 13 ± 2                |
|           |                           | 2                | 14.0           | 13 ± 2                |
|           |                           | 5.5              | 14.1           | 13 ± 2                |
|           |                           | 11               | 13.8           | 13 ± 2                |
|           | 6 / 2437                  | 1                | 13.1           | 13 ± 2                |
|           |                           | 2                | 12.9           | 13 ± 2                |
|           |                           | 5.5              | 12.9           | 13 ± 2                |
|           |                           | 11               | 12.8           | 13 ± 2                |
|           | 11 / 2462                 | 1                | 11.92          | 13 ± 2                |
|           |                           | 2                | 11.88          | 13 ± 2                |
|           |                           | 5.5              | 11.86          | 13 ± 2                |
|           |                           | 11               | 11.82          | 13 ± 2                |
| 11g       | 1 / 2412                  | 6                | 14.18          | 12 ± 3                |
|           |                           | 9                | 14.11          | 12 ± 3                |
|           |                           | 12               | 13.98          | 12 ± 3                |
|           |                           | 18               | 14.08          | 12 ± 3                |
|           |                           | 24               | 14.01          | 12 ± 3                |
|           |                           | 36               | 13.97          | 12 ± 3                |
|           |                           | 48               | 13.92          | 12 ± 3                |
|           |                           | 54               | 13.92          | 12 ± 3                |
|           | 6 / 2437                  | 6                | 13.74          | 12 ± 3                |
|           |                           | 9                | 13.71          | 12 ± 3                |
|           |                           | 12               | 13.68          | 12 ± 3                |
|           |                           | 18               | 13.65          | 12 ± 3                |
|           |                           | 24               | 13.71          | 12 ± 3                |
|           |                           | 36               | 13.64          | 12 ± 3                |
|           |                           | 48               | 13.61          | 12 ± 3                |
|           |                           | 54               | 13.58          | 12 ± 3                |
| 11 / 2462 | 11 / 2462                 | 6                | 9.12           | 12 ± 3                |
|           |                           | 9                | 9.09           | 12 ± 3                |
|           |                           | 12               | 9.06           | 12 ± 3                |
|           |                           | 18               | 9.10           | 12 ± 3                |
|           |                           | 24               | 9.01           | 12 ± 3                |
|           |                           | 36               | 9.03           | 12 ± 3                |
|           |                           | 48               | 9.03           | 12 ± 3                |
|           |                           | 54               | 9.01           | 12 ± 3                |

| Mode     | Channel / Frequency (MHz) | Data rate (Mbps) | AV Power (dBm) | Tune up limited (dBm) |
|----------|---------------------------|------------------|----------------|-----------------------|
| 11n-HT20 | 1 / 2412                  | MCS0             | 11.62          | 10 ± 2                |
|          |                           | MCS1             | 11.60          | 10 ± 2                |
|          |                           | MCS2             | 11.58          | 10 ± 2                |
|          |                           | MCS3             | 11.59          | 10 ± 2                |
|          |                           | MCS4             | 11.54          | 10 ± 2                |
|          |                           | MCS5             | 11.51          | 10 ± 2                |
|          |                           | MCS6             | 11.48          | 10 ± 2                |
|          |                           | MCS7             | 11.49          | 10 ± 2                |
|          | 6 / 2437                  | MCS0             | 11.40          | 10 ± 2                |
|          |                           | MCS1             | 11.38          | 10 ± 2                |
|          |                           | MCS2             | 11.37          | 10 ± 2                |
|          |                           | MCS3             | 11.35          | 10 ± 2                |
|          |                           | MCS4             | 11.37          | 10 ± 2                |
|          |                           | MCS5             | 11.35          | 10 ± 2                |
|          |                           | MCS6             | 11.33          | 10 ± 2                |
|          |                           | MCS7             | 11.30          | 10 ± 2                |
|          | 11 / 2462                 | MCS0             | 9.90           | 10 ± 2                |
|          |                           | MCS1             | 9.87           | 10 ± 2                |
|          |                           | MCS2             | 9.85           | 10 ± 2                |
|          |                           | MCS3             | 9.81           | 10 ± 2                |
|          |                           | MCS4             | 9.84           | 10 ± 2                |
|          |                           | MCS5             | 9.86           | 10 ± 2                |
|          |                           | MCS6             | 9.82           | 10 ± 2                |
|          |                           | MCS7             | 9.80           | 10 ± 2                |

### 13.2 SAR TEST RESULTS

#### IEEE 802.11b

| Test Position   | Channel / Frequency (MHz) | Mode | Maximum Allowed Power (dBm) | Conducted Power (dBm) | Drift $\pm 0.21$ dB | Limit SAR1g 1.6 W/kg  |                |                       |
|---|---------------------------|------|-----------------------------|-----------------------|---------------------|-----------------------|----------------|-----------------------|
|   |                           |      |                             |                       | Drift (dB)          | Measured SAR1g (W/kg) | Scaling Factor | Reported SAR1g (W/kg) |
| Test Position of Body   |                           |      |                             |                       |                     |                       |                |                       |
| Horizontal-Down   | 1 / 2412                  | DSSS | 15                          | 14.5                  | 0.11                | 0.183                 | 1.12           | 0.205                 |
| Horizontal-Up   | 1 / 2412                  | DSSS | 15                          | 14.5                  | 0.12                | 0.186                 | 1.12           | 0.208                 |
| Vertical-Back   | 1 / 2412                  | DSSS | 15                          | 14.5                  | 0.08                | 0.114                 | 1.12           | 0.128                 |
| Vertical-Front  | 1 / 2412                  | DSSS | 15                          | 14.5                  | -0.10               | 0.168                 | 1.12           | 0.188                 |
| Note:<br>1 When the reported SAR of the highest measured maximum output power channel for the exposure configuration is $\leq 0.8$ W/kg, no further SAR testing is required for 802.11b DSSS in that exposure configuration.<br>2 When the reported SAR is $> 0.8$ W/kg, SAR is required for that exposure configuration using the next highest measured output power channel. When any reported SAR is $> 1.2$ W/kg, SAR is required for the third channel; i.e., all channels require testing.<br>3 The EUT exercise program (provided by client) used during SAR testing was designed to exercise the various system components in a manner similar to a typical use. During the test, Channel and test mode software provided by the applicant was used to control the operating channel as well as the test mode. The worst-case configuration is used in all specified testing. |                           |      |                             |                       |                     |                       |                |                       |

### 13.3 2.4 GHz 802.11g/n-HT20 OFDM SAR Test Exclusion Requirements

| Test Position  | Channel / Frequency (MHz) | 802.11b Max. Allowed Power (dBm) | 802.11g/n Max. Allowed Power (dBm) | Limit SAR1g :1.6W/kg         |                |                        |
|--|---------------------------|----------------------------------|------------------------------------|------------------------------|----------------|------------------------|
|  |                           |                                  |                                    | 802.11b Report SAR 1g (W/kg) | Scaling Factor | Adjusted SAR 1g (W/kg) |
| Horizontal-Up  | 1 / 2412                  | 15                               | 15                                 | 0.208                        | 1.0            | 0.208                  |
| Note: SAR is not required for the 2.4 GHz OFDM conditions if When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is $\leq 1.2$ W/kg. |                           |                                  |                                    |                              |                |                        |

### 13.4 Simultaneous Transmission Conditions

No simultaneous SAR

### 13.5 MAXIMUM GRAPH RESULTS

The graph results see ANNEX C.

## 14 MEASUREMENT UNCERTAINTY

When the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval.


## 15 MAIN TEST INSTRUMENT

| Equipment No. | Equipment                 | Manufacturer                 | Model No.                 | Serial No.      | Last Cal.  | Cal. Interval |
|---------------|---------------------------|------------------------------|---------------------------|-----------------|------------|---------------|
| SZ060-01      | SAR Test System           | SPEAG                        | DASY52 SAR TX90XL         | F14/5YJ0B1/A/01 | N/A        | N/A           |
| SZ060-01-01   | E-Field Probe             | SPEAG                        | EX3DV4                    | 7322            | 8/30/2018  | 1 year        |
| SZ060-01-10   | System Validation Dipole  | SPEAG                        | D2450V2                   | 966             | 8/31/2018  | 3 years       |
| SZ060-01-13   | Data Acquisition Unit     | SPEAG                        | DAE4                      | 1473            | 8/29/2018  | 1 year        |
| SZ060-01-14   | Dielectric Assessment Kit | SPEAG                        | DAKS 3.5                  | 1056            | N/A        | N/A           |
| SZ060-01-15   | Vector Reflectometer      | Copper Mountain Technologies | Planar R140               | 0090614         | N/A        | N/A           |
| SZ060-01-16   | Thermometer               | LKM electronics GmbH         | DTM3000                   | 3477            | 8/10/2018  | 1 year        |
| SZ060-01-17   | Power Amplifier           | Mini Circuits                | ZHL-42W+                  | QA1449003       | N/A        | N/A           |
| SZ060-01-18   | Power Amplifier           | Mini Circuits                | ZVE-8G+                   | 111701437       | N/A        | N/A           |
| SZ060-01-20   | SAM Twin Phantom          | SPEAG                        | SAM Twin Phantom V5.0     | 1891            | N/A        | N/A           |
| SZ180-15      | Signal Generator          | R&S                          | SMB100A                   | 113589          | 8/29/2018  | 1 year        |
| SZ070-04      | Directional Bridge        | Agilent                      | 86205A                    | MY31402141      | 12/28/2017 | 1 year        |
| SZ182-02      | RF Power Meter            | Anritsu                      | ML2496A                   | 1302005         | 6/5/2018   | 1 year        |
| SZ182-03      | Average power sensor      | R&S                          | NRP-Z22                   | 101689          | 6/5/2018   | 1 year        |
| N/A           | Device Holder             | SPEAG                        | N/A                       | N/A             | N/A        | N/A           |
| SZ070-01      | Attenuator                | Huber Suhner                 | 10dB                      | N/A             | N/A        | N/A           |
| SZ070-02      | Attenuator                | Huber Suhner                 | 30dB                      | N/A             | N/A        | N/A           |
| SZ060-01-22   | SAR Test System Software  | SPEAG                        | DASY5.2 SW: 52.10.1(1476) | N/A             | N/A        | N/A           |

## ANNEX A : TEST LAYOUT AND SETUP



Specific Absorption Rate Test Layout



Liquid Depth in the flat phantom (18.2cm)

**Note: Test SETUP please refer to pdf description “SAR Test setup photos”.**

## ANNEX B : SYSTEM CHECK RESULTS

Date: 11/22/2018

Test Laboratory: Intertek Service

System Check 2450

Communication System: UID 0, \_CW (0); Frequency: 2450 MHz; Duty Cycle: 1:1

 Medium: 2450 Body Medium parameters used:  $f = 2450$  MHz;  $\sigma = 2.009$  S/m;  $\epsilon_r = 52.56$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature: 22.0 °C; Liquid Temperature: 21.5 °C

DASY Configuration:

- Probe: EX3DV4 - SN7322; ConvF(7.3, 7.3, 7.3) @ 2450 MHz; Calibrated: 8/30/2018
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1473; Calibrated: 8/29/2018
- Phantom: SAM 1 V5.0 (30deg); Type: QD 000 P40 CD; Serial: 1891
- DASY52 52.10.1(1476); SEMCAD X 14.6.11(7439)

**Area Scan (21x31x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of SAR (measured) = 23.0 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 111.8 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 28.5 W/kg

**SAR(1 g) = 13.5 W/kg; SAR(10 g) = 6.3 W/kg**

Maximum value of SAR (measured) = 23.1 W/kg



## ANNEX C : MAXIMUM GRAPH RESULTS

Date: 11/22/2018

Test Laboratory: Intertek Service

### 802.11b-Horizontal-Up-CH1

Communication System: UID 0, WiFi 802.11 b (0); Frequency: 2412 MHz; Duty Cycle: 1:1  
 Medium: 2450 Body Medium parameters used:  $f = 2412$  MHz;  $\sigma = 1.961$  S/m;  $\epsilon_r = 52.69$ ;  
 $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Ambient Temperature: 22.0 °C; Liquid Temperature: 21.5 °C

DASY Configuration:

- Probe: EX3DV4 - SN7322; ConvF(7.3, 7.3, 7.3) @ 2412 MHz; Calibrated: 8/30/2018
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1473; Calibrated: 8/29/2018
- Phantom: SAM 1 V5.0 (30deg); Type: QD 000 P40 CD; Serial: 1891
- DASY52 52.10.1(1476); SEMCAD X 14.6.11(7439)

**Area Scan (19x34x1):** Measurement grid: dx=2mm, dy=2mm

Maximum value of SAR (measured) = 0.352 W/kg


**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.951 V/m; Power Drift = 0.12 dB

Peak SAR (extrapolated) = 0.490 W/kg

**SAR(1 g) = 0.186 W/kg; SAR(10 g) = 0.075 W/kg**

Maximum value of SAR (measured) = 0.338 W/kg



## ANNEX D : SYSTEM VALIDATION

The SAR system must be validated against its performance specifications before it is deployed. When SAR probes, system components or software are changed, upgraded or recalibrated, these must be validated with the SAR system(s) that operates with such components.

**Table D.1: System Validation Part 1**

| System No. | Probe SN. | Liquid name | Validation date | Frequency point | Permittivity $\epsilon$ | Conductivity $\sigma$ (S/m) |
|------------|-----------|-------------|-----------------|-----------------|-------------------------|-----------------------------|
| 1          | 7322      | Body        | 9/03/2018       | 2450MHz         | 51.50                   | 2.04                        |

**Table D.2: System Validation Part 2**

|                |                 |      |      |
|----------------|-----------------|------|------|
| CW Validation  | Sensitivity     | PASS | PASS |
|                | Probe linearity | PASS | PASS |
|                | Probe Isotropy  | PASS | PASS |
| Mod Validation | MOD.type        | QPSK | QPSK |
|                | Duty factor     | PASS | PASS |
|                | PAR             | PASS | PASS |

**ANNEX E : PROBE, DAE AND DIPOLE CALIBRATION CERTIFICATE**

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
 E-mail: ctll@chinattl.com [Http://www.chinattl.cn](http://www.chinattl.cn)



Client

Intertek

Certificate No: Z18-60296

**CALIBRATION CERTIFICATE**

Object EX3DV4 - SN:7322

Calibration Procedure(s) FF-Z11-004-01  
Calibration Procedures for Dosimetric E-field Probes

Calibration date: August 30, 2018

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature( $22\pm3$ )°C and humidity<70%.

## Calibration Equipment used (M&amp;TE critical for calibration)

| Primary Standards       | ID #        | Cal Date(Calibrated by, Certificate No.) | Scheduled Calibration |
|-------------------------|-------------|--|-----------------------|
| Power Meter NRP2        | 101919      | 20-Jun-18 (CTTL, No.J18X05032)           | Jun-19                |
| Power sensor NRP-Z91    | 101547      | 20-Jun-18 (CTTL, No.J18X05032)           | Jun-19                |
| Power sensor NRP-Z91    | 101548      | 20-Jun-18 (CTTL, No.J18X05032)           | Jun-19                |
| Reference10dBAttenuator | 18N50W-10dB | 09-Feb-18(CTTL, No.J18X01133)            | Feb-20                |
| Reference20dBAttenuator | 18N50W-20dB | 09-Feb-18(CTTL, No.J18X01132)            | Feb-20                |
| Reference Probe EX3DV4  | SN 3846     | 25-Jan-18(SPEAG, No.EX3-3846_Jan18)      | Jan-19                |
| DAE4                    | SN 777      | 15-Dec-17(SPEAG, No.DAE4-777_Dec17)      | Dec -18               |
| Secondary Standards     | ID #        | Cal Date(Calibrated by, Certificate No.) | Scheduled Calibration |
| SignalGeneratorMG3700A  | 6201052605  | 21-Jun-18 (CTTL, No.J18X05033)           | Jun-19                |
| Network Analyzer E5071C | MY46110673  | 14-Jan-18 (CTTL, No.J18X00561)           | Jan -19               |

| Calibrated by: | Name        | Function           | Signature |
|----------------|-------------|--------------------|-----------|
|                | Yu Zongying | SAR Test Engineer  |           |
| Reviewed by:   | Lin Hao     | SAR Test Engineer  |           |
| Approved by:   | Qi Dianyuan | SAR Project Leader |           |

Issued: August 31, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
 E-mail: [cttl@chinattl.com](mailto:cttl@chinattl.com) [Http://www.chinattl.cn](http://www.chinattl.cn)

#### Glossary:

|                       |   |
|-----------------------|---|
| TSL                   | tissue simulating liquid  |
| NORM $x,y,z$          | sensitivity in free space   |
| ConvF                 | sensitivity in TSL / NORM $x,y,z$   |
| DCP                   | diode compression point   |
| CF                    | crest factor (1/duty_cycle) of the RF signal  |
| A,B,C,D               | modulation dependent linearization parameters   |
| Polarization $\Phi$   | $\Phi$ rotation around probe axis   |
| Polarization $\theta$ | $\theta$ rotation around an axis that is in the plane normal to probe axis (at measurement center), i<br>$\theta=0$ is normal to probe axis |

Connector Angle information used in DASY system to align probe sensor X to the robot coordinate system

#### Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- c) IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- d) KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

#### Methods Applied and Interpretation of Parameters:

- $NORMx,y,z$ : Assessed for E-field polarization  $\theta=0$  ( $f \leq 900$ MHz in TEM-cell;  $f > 1800$ MHz: waveguide).  $NORMx,y,z$  are only intermediate values, i.e., the uncertainties of  $NORMx,y,z$  does not effect the  $E^2$ -field uncertainty inside TSL (see below ConvF).
- $NORM(f)x,y,z = NORMx,y,z * frequency\_response$  (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- $DCPx,y,z$ : DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics.
- $Ax,y,z; Bx,y,z; Cx,y,z; VRx,y,z; A,B,C$  are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- *ConvF and Boundary Effect Parameters*: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty valued are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to  $NORMx,y,z * ConvF$  whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$ MHz to  $\pm 100$ MHz.
- *Spherical Isotropy (3D deviation from isotropy)*: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- *Sensor Offset*: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- *Connector Angle*: The angle is assessed using the information gained by determining the  $NORMx$  (no uncertainty required).



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
E-mail: [ctl@chinattl.com](mailto:ctl@chinattl.com) [Http://www.chinattl.cn](http://www.chinattl.cn)

# Probe EX3DV4

SN: 7322

Calibrated: August 30, 2018

Calibrated for DASY/EASY Systems

(Note: non-compatible with DASY2 system!)



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
 E-mail: [ctl@chinattl.com](mailto:ctl@chinattl.com) [Http://www.chinattl.cn](http://www.chinattl.cn)

## DASY/EASY – Parameters of Probe: EX3DV4 – SN: 7322

### Basic Calibration Parameters

|   | Sensor X | Sensor Y | Sensor Z | Unc (k=2) |
|---|----------|----------|----------|-----------|
| Norm( $\mu$ V/(V/m) <sup>2</sup> ) <sup>A</sup> | 0.45     | 0.55     | 0.53     | ±10.0%    |
| DCP(mV) <sup>B</sup>                            | 97.7     | 98.4     | 98.9     |           |

### Modulation Calibration Parameters

| UID | Communication System Name | A<br>dB | B<br>dB/ $\mu$ V | C   | D<br>dB | VR<br>mV | Unc <sup>E</sup><br>(k=2) |
|-----|---------------------------|---------|------------------|-----|---------|----------|---------------------------|
| 0   | CW                        | X       | 0.0              | 1.0 | 0.00    | 160.7    | ±2.2%                     |
|     |                           | Y       | 0.0              | 1.0 |         | 176.7    |                           |
|     |                           | Z       | 0.0              | 1.0 |         | 172.1    |                           |

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor k=2, which for a normal distribution Corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of Norm X, Y, Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Page 5 and Page 6).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
 E-mail: [ctl@chinattl.com](mailto:ctl@chinattl.com) [Http://www.chinattl.cn](http://www.chinattl.cn)

## DASY/EASY – Parameters of Probe: EX3DV4 – SN: 7322

### Calibration Parameter Determined in Head Tissue Simulating Media

| f [MHz] <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-------------|
| 835                  | 41.5                               | 0.90                            | 9.54    | 9.54    | 9.54    | 0.17               | 1.36                    | ±12.1%      |
| 1750                 | 40.1                               | 1.37                            | 8.27    | 8.27    | 8.27    | 0.23               | 1.01                    | ±12.1%      |
| 1900                 | 40.0                               | 1.40                            | 7.89    | 7.89    | 7.89    | 0.26               | 0.95                    | ±12.1%      |
| 2300                 | 39.5                               | 1.67                            | 7.70    | 7.70    | 7.70    | 0.50               | 0.75                    | ±12.1%      |
| 2450                 | 39.2                               | 1.80                            | 7.48    | 7.48    | 7.48    | 0.54               | 0.73                    | ±12.1%      |
| 2600                 | 39.0                               | 1.96                            | 7.26    | 7.26    | 7.26    | 0.64               | 0.68                    | ±12.1%      |
| 5250                 | 35.9                               | 4.71                            | 5.28    | 5.28    | 5.28    | 0.50               | 1.25                    | ±13.3%      |
| 5750                 | 35.4                               | 5.22                            | 4.70    | 4.70    | 4.70    | 0.50               | 1.55                    | ±13.3%      |

<sup>C</sup> Frequency validity above 300 MHz of ±100MHz only applies for DASY v4.4 and higher (Page 2), else it is restricted to ±50MHz. The uncertainty is the RSS of ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

<sup>F</sup> At frequency below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ±10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ±5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for the frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
 E-mail: [cttl@chinattl.com](mailto:cttl@chinattl.com) [Http://www.chinattl.cn](http://www.chinattl.cn)

## DASY/EASY – Parameters of Probe: EX3DV4 – SN: 7322

### Calibration Parameter Determined in Body Tissue Simulating Media

| f [MHz] <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unct. (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-------------|
| 835                  | 55.2                               | 0.97                            | 9.73    | 9.73    | 9.73    | 0.18               | 1.38                    | ±12.1%      |
| 1750                 | 53.4                               | 1.49                            | 7.90    | 7.90    | 7.90    | 0.20               | 1.13                    | ±12.1%      |
| 1900                 | 53.3                               | 1.52                            | 7.70    | 7.70    | 7.70    | 0.19               | 1.21                    | ±12.1%      |
| 2450                 | 52.7                               | 1.95                            | 7.30    | 7.30    | 7.30    | 0.58               | 0.74                    | ±12.1%      |
| 2600                 | 52.5                               | 2.16                            | 7.08    | 7.08    | 7.08    | 0.65               | 0.68                    | ±12.1%      |
| 5250                 | 48.9                               | 5.36                            | 4.75    | 4.75    | 4.75    | 0.50               | 1.40                    | ±13.3%      |
| 5750                 | 48.3                               | 5.94                            | 4.11    | 4.11    | 4.11    | 0.55               | 1.65                    | ±13.3%      |

<sup>C</sup> Frequency validity above 300 MHz of ±100MHz only applies for DASY v4.4 and higher (Page 2), else it is restricted to ±50MHz. The uncertainty is the RSS of ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.


<sup>F</sup> At frequency below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ±10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ±5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for the frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
E-mail: [ctl@chinattl.com](mailto:ctl@chinattl.com) [Http://www.chinattl.cn](http://www.chinattl.cn)

## Frequency Response of E-Field (TEM-Cell: ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field:  $\pm 7.4\%$  ( $k=2$ )





Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
E-mail: [ctl@chinattl.com](mailto:ctl@chinattl.com) [Http://www.chinattl.cn](http://www.chinattl.cn)

### Receiving Pattern ( $\Phi$ ), $\theta=0^\circ$

f=600 MHz, TEM



f=1800 MHz, R22





Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
E-mail: [ctl@chinattl.com](mailto:ctl@chinattl.com) [Http://www.chinattl.cn](http://www.chinattl.cn)

**Dynamic Range  $f(\text{SAR}_{\text{head}})$   
(TEM cell,  $f = 900 \text{ MHz}$ )**







Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
 E-mail: [cttl@chinattl.com](mailto:cttl@chinattl.com) [Http://www.chinattl.cn](http://www.chinattl.cn)

## Conversion Factor Assessment

$f=835$  MHz, WGLS R9(H\_convF)       $f=1750$  MHz, WGLS R22(H\_convF)



## Deviation from Isotropy in Liquid





Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
E-mail: [cttl@chinattl.com](mailto:cttl@chinattl.com) [Http://www.chinattl.cn](http://www.chinattl.cn)

## DASY/EASY – Parameters of Probe: EX3DV4 – SN: 7322

### Other Probe Parameters

|  |            |
|--|------------|
| <b>Sensor Arrangement</b>                            | Triangular |
| <b>Connector Angle (°)</b>                           | 43.5       |
| <b>Mechanical Surface Detection Mode</b>             | enabled    |
| <b>Optical Surface Detection Mode</b>                | disable    |
| <b>Probe Overall Length</b>                          | 337mm      |
| <b>Probe Body Diameter</b>                           | 10mm       |
| <b>Tip Length</b>                                    | 9mm        |
| <b>Tip Diameter</b>                                  | 2.5mm      |
| <b>Probe Tip to Sensor X Calibration Point</b>       | 1mm        |
| <b>Probe Tip to Sensor Y Calibration Point</b>       | 1mm        |
| <b>Probe Tip to Sensor Z Calibration Point</b>       | 1mm        |
| <b>Recommended Measurement Distance from Surface</b> | 1.4mm      |



In Collaboration with  
**s p e a g**  
 CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
 E-mail: [cttl@chinattl.com](mailto:cttl@chinattl.com) <http://www.chinattl.cn>



中国认可  
 国际互认  
 校准  
**CNAS**  
 CALIBRATION  
 CNAS L0570

Client : **Intertek**

**Certificate No: Z18-60297**

## CALIBRATION CERTIFICATE

Object DAE4 - SN: 1473

Calibration Procedure(s) FF-Z11-002-01  
 Calibration Procedure for the Data Acquisition Electronics  
 (DAEx)

Calibration date: August 29, 2018

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature( $22\pm3$ )°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards      | ID #    | Cal Date(Calibrated by, Certificate No.) | Scheduled Calibration |
|------------------------|---------|--|-----------------------|
| Process Calibrator 753 | 1971018 | 20-Jun-18 (CTTL, No.J18X05034)           | June-19               |

| Calibrated by: | Name        | Function           | Signature |
|----------------|-------------|--------------------|-----------|
|                | Yu Zongying | SAR Test Engineer  |           |
| Reviewed by:   | Lin Hao     | SAR Test Engineer  |           |
| Approved by:   | Qi Dianyuan | SAR Project Leader |           |

Issued: August 31, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
E-mail: [ctl@chinattl.com](mailto:ctl@chinattl.com) [Http://www.chinattl.cn](http://www.chinattl.cn)

**Glossary:**

|                 |   |
|-----------------|---|
| DAE             | data acquisition electronics  |
| Connector angle | information used in DASY system to align probe sensor X to the robot coordinate system. |

**Methods Applied and Interpretation of Parameters:**

- *DC Voltage Measurement*: Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- *Connector angle*: The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The report provide only calibration results for DAE, it does not contain other performance test results.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
E-mail: [ctl@chinattl.com](mailto:ctl@chinattl.com) [Http://www.chinattl.cn](http://www.chinattl.cn)

**DC Voltage Measurement**

A/D - Converter Resolution nominal

High Range: 1LSB =  $6.1\mu V$ , full range = -100...+300 mV  
Low Range: 1LSB =  $61nV$ , full range = -1.....+3mV

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

| Calibration Factors | X                          | Y                          | Z                          |
|---------------------|----------------------------|----------------------------|----------------------------|
| High Range          | $404.030 \pm 0.15\% (k=2)$ | $404.626 \pm 0.15\% (k=2)$ | $404.476 \pm 0.15\% (k=2)$ |
| Low Range           | $3.96429 \pm 0.7\% (k=2)$  | $3.99515 \pm 0.7\% (k=2)$  | $3.98817 \pm 0.7\% (k=2)$  |

**Connector Angle**

|   |                           |
|---|---------------------------|
| Connector Angle to be used in DASY system | $346.5^\circ \pm 1^\circ$ |
|---|---------------------------|



In Collaboration with  
**S p e a g**  
 CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
 E-mail: cttl@chinattl.com http://www.chinattl.cn



中国认可  
 国际互认  
 校准  
**CNAS**  
 CALIBRATION  
 CNAS L0570

Client

Intertek

Certificate No: Z18-60303

## CALIBRATION CERTIFICATE

Object D2450V2 - SN: 966

Calibration Procedure(s) FF-Z11-003-01  
 Calibration Procedures for dipole validation kits

Calibration date: August 31, 2018

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature( $22\pm3$ )°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards       | ID #       | Cal Date(Calibrated by, Certificate No.) | Scheduled Calibration |
|-------------------------|------------|--|-----------------------|
| Power Meter NRV         | 102083     | 01-Nov-17 (CTTL, No.J17X08756)           | Oct-18                |
| Power sensor NRV-Z5     | 100542     | 01-Nov-17 (CTTL, No.J17X08756)           | Oct-18                |
| Reference Probe EX3DV4  | SN 7464    | 12-Sep-17(SPEAG, No.EX3-7464_Sep17)      | Sep-18                |
| DAE4                    | SN 1524    | 13-Sep-17(SPEAG, No.DAE4-1524_Sep17)     | Sep-18                |
| Secondary Standards     | ID #       | Cal Date(Calibrated by, Certificate No.) | Scheduled Calibration |
| Signal Generator E4438C | MY49071430 | 23-Jan-18 (CTTL, No.J18X00560)           | Jan-19                |
| NetworkAnalyzer E5071C  | MY46110673 | 24-Jan-18 (CTTL, No.J18X00561)           | Jan-19                |

|                |                 |                             |            |
|----------------|-----------------|-----------------------------|------------|
| Calibrated by: | Name: Zhao Jing | Function: SAR Test Engineer | Signature: |
| Reviewed by:   | Lin Hao         | SAR Test Engineer           |            |
| Approved by:   | Qi Dianyuan     | SAR Project Leader          |            |

Issued: September 3, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



In Collaboration with  
**s p e a g**  
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
E-mail: [ctl@chinattl.com](mailto:ctl@chinattl.com) <http://www.chinattl.cn>

**Glossary:**

|       |                                |
|-------|--------------------------------|
| TSL   | tissue simulating liquid       |
| ConvF | sensitivity in TSL / NORMx,y,z |
| N/A   | not applicable or not measured |

**Calibration is Performed According to the Following Standards:**

- a) IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- b) IEC 62209-1, "Measurement procedure for assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices- Part 1: Device used next to the ear (Frequency range of 300MHz to 6GHz)", July 2016
- c) IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010
- d) KDB865664, SAR Measurement Requirements for 100 MHz to 6 GHz

**Additional Documentation:**

- e) DASY4/5 System Handbook

**Methods Applied and Interpretation of Parameters:**

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution Corresponds to a coverage probability of approximately 95%.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
 E-mail: ctll@chinattl.com http://www.chinattl.cn

### Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                          |              |
|------------------------------|--------------------------|--------------|
| DASY Version                 | DASY52                   | 52.10.1.1476 |
| Extrapolation                | Advanced Extrapolation   |              |
| Phantom                      | Triple Flat Phantom 5.1C |              |
| Distance Dipole Center - TSL | 10 mm                    | with Spacer  |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm        |              |
| Frequency                    | 2450 MHz ± 1 MHz         |              |

### Head TSL parameters

The following parameters and calculations were applied.

|   | Temperature     | Permittivity | Conductivity     |
|---|-----------------|--------------|------------------|
| Nominal Head TSL parameters             | 22.0 °C         | 39.2         | 1.80 mho/m       |
| Measured Head TSL parameters            | (22.0 ± 0.2) °C | 38.8 ± 6 %   | 1.80 mho/m ± 6 % |
| Head TSL temperature change during test | <1.0 °C         | ----         | ----             |

### SAR result with Head TSL

|  |                    |                           |
|--|--------------------|---------------------------|
| SAR averaged over 1 $cm^3$ (1 g) of Head TSL   | Condition          |                           |
| SAR measured                                   | 250 mW input power | 13.3 mW / g               |
| SAR for nominal Head TSL parameters            | normalized to 1W   | 53.1 mW /g ± 18.8 % (k=2) |
| SAR averaged over 10 $cm^3$ (10 g) of Head TSL | Condition          |                           |
| SAR measured                                   | 250 mW input power | 6.20 mW / g               |
| SAR for nominal Head TSL parameters            | normalized to 1W   | 24.8 mW /g ± 18.7 % (k=2) |

### Body TSL parameters

The following parameters and calculations were applied.

|   | Temperature     | Permittivity | Conductivity     |
|---|-----------------|--------------|------------------|
| Nominal Body TSL parameters             | 22.0 °C         | 52.7         | 1.95 mho/m       |
| Measured Body TSL parameters            | (22.0 ± 0.2) °C | 52.3 ± 6 %   | 1.98 mho/m ± 6 % |
| Body TSL temperature change during test | <1.0 °C         | ----         | ----             |

### SAR result with Body TSL

|  |                    |                           |
|--|--------------------|---------------------------|
| SAR averaged over 1 $cm^3$ (1 g) of Body TSL   | Condition          |                           |
| SAR measured                                   | 250 mW input power | 12.8 mW / g               |
| SAR for nominal Body TSL parameters            | normalized to 1W   | 50.7 mW /g ± 18.8 % (k=2) |
| SAR averaged over 10 $cm^3$ (10 g) of Body TSL | Condition          |                           |
| SAR measured                                   | 250 mW input power | 6.01 mW / g               |
| SAR for nominal Body TSL parameters            | normalized to 1W   | 23.9 mW /g ± 18.7 % (k=2) |



In Collaboration with  
**S p e a g**  
 CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
 E-mail: ctll@chinattl.com http://www.chinattl.cn

#### Appendix (Additional assessments outside the scope of CNAS L0570)

##### Antenna Parameters with Head TSL

|                                      |               |
|--------------------------------------|---------------|
| Impedance, transformed to feed point | 53.0Ω+ 2.76jΩ |
| Return Loss                          | - 28.1dB      |

##### Antenna Parameters with Body TSL

|                                      |               |
|--------------------------------------|---------------|
| Impedance, transformed to feed point | 49.3Ω+ 5.09jΩ |
| Return Loss                          | - 25.7dB      |

##### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.021 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.  
 No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

##### Additional EUT Data

|                 |       |
|-----------------|-------|
| Manufactured by | SPEAG |
|-----------------|-------|



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
 E-mail: ctll@chinattl.com http://www.chinattl.cn

**DASY5 Validation Report for Head TSL**

Date: 08.31.2018

Test Laboratory: CTTL, Beijing, China

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 966**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

 Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.802$  S/m;  $\epsilon_r = 38.84$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7464; ConvF(7.89, 7.89, 7.89) @ 2450 MHz; Calibrated: 9/12/2017
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1524; Calibrated: 9/13/2017
- Phantom: MFP\_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)


**Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm**

Reference Value = 100.1 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 27.6 W/kg

**SAR(1 g) = 13.3 W/kg; SAR(10 g) = 6.2 W/kg**

Maximum value of SAR (measured) = 22.2 W/kg






In Collaboration with  
**s p e a g**  
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
E-mail: ctll@chinattl.com <http://www.chinattl.cn>

### Impedance Measurement Plot for Head TSL





In Collaboration with  
**s p e a g**  
 CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
 E-mail: ctll@chinattl.com http://www.chinattl.cn

**DASY5 Validation Report for Body TSL**

Date: 08.30.2018

Test Laboratory: CTTL, Beijing, China

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 966**

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.982$  S/m;  $\epsilon_r = 52.34$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7464; ConvF(8.09, 8.09, 8.09) @ 2450 MHz; Calibrated: 9/12/2017
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1524; Calibrated: 9/13/2017
- Phantom: MFP\_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)


**Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 93.62 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 25.8 W/kg

**SAR(1 g) = 12.8 W/kg; SAR(10 g) = 6.01 W/kg**


Maximum value of SAR (measured) = 21.0 W/kg





Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504  
E-mail: ctll@chinattl.com http://www.chinattl.cn

### Impedance Measurement Plot for Body TSL



Certificate No: Z18-60303

Page 8 of 8

\*\*\*\*\*End of Report\*\*\*\*\*