



RF exposure Estimation

China

1. Introduction

Product: GEOX CONNNECT, model: 200178005KF is a machine with music player function, which contain Bluetooth function inside.

FCC ID: 2AQ7N200178005KF

2. Limit and Guidelines on Exposure to Electromagnetic Fields

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 Mobile Portable RF Exposure v05r02, no SAR required if power is lower than the flowing threshold:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is $<$ 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

3. Calculation method

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

BDR+EDR:

Conducted Power + tune up tolerance = 0.94842mW

Distance = 5 mm

$f = 2.402 \text{ GHz}$

$[0.94842/5] * \text{SQRT}(2.402) = 0.29398$

$0.29398 \leq 3.0$

BLE:

Conducted Power + tune up tolerance = 1.1246mW

Distance = 5 mm

$f = 2.402 \text{ GHz}$

$[1.1246/5] * \text{SQRT}(2.402) = 0.34859$

$0.34859 \leq 3.0$

Therefore, excluded from SAR testing.

TUV SUD China, Guangzhou Branch

Reviewed by:



Peter Jia / Project Reviewer
Date: 2021-03-16



Prepared By:



Tim Pang / Project Handler
Date: 2021-03-16