

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a NOVELTY RC TALKING BOW TIE operating at 2.4G Band. The EUT can be powered by DC 4.5V (3 X 1.5V LR44 batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

Modulation Type: GFSK.

The normal radiated output power (e.i.r.p) is: -12.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -12.0dBm (tolerance: +/- 3dB).

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 83.6dB μ V/m at 3m in the frequency 2440MHz

The EIRP = $[(FS^*D)^2 / 30]$ mW = -11.63dBm
which is within the production variation.

The Minimum peak radiated emission for the EUT is 82.0dB μ V/m at 3m in the frequency 2405MHz

The EIRP = $[(FS^*D)^2 / 30]$ mW = -13.23dBm
which is within the production variation.

The maximum conducted output power specified is -9 dBm = 0.126 mW

The source- based time-averaging conducted output power
= 0.126 * Duty cycle mW < 0.126 mW (Duty cycle < 100%)

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)
= 3.0 * 5 / sqrt (2.475) mW
= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 18.551ms

Effective period of the cycle = 2.464ms

DC = 2.464ms / 18.551ms = 0.1328 or 13.28%