



RF TEST REPORT

Product Name: DTEN D7X 75"

Model Name: DBR1475, DBR1475-S1

FCC ID: 2AQ7Q-DBR1475

Issued For : DTEN Inc

97 E Brokaw Road suite 180 San Jose CA 95112

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Chen Hsong Industrial Park,
No.177 Renmin West Road, Jinsha Community, Kengzi
Street, Pingshan New District, Shenzhen, China

Report Number: LGT22L023RF05

Sample Received Date: Sep. 28, 2022

Date of Test: Sep. 28, 2022 – Feb. 17, 2023

Date of Issue: Feb. 17, 2023

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.

TEST REPORT CERTIFICATION

Applicant DTEN Inc
Address 97 E Brokaw Road suite 180 San Jose CA 95112
Manufacturer DTEN Inc
Address 97 E Brokaw Road suite 180 San Jose CA 95112
Product Name DTEN D7X 75"
Trademark DTEN
Model Name DBR1475, DBR1475-S1
Sample Status: Normal

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC Part 15.247, Subpart C ANSI C63.10-2013	PASS

Prepared by:

Zane Shan

Zane Shan
Engineer

Approved by:

Vita Li

Vita Li
Technical Director



Table of Contents	Page
1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF THE EUT	8
2.2 DESCRIPTION OF THE TEST MODES	10
2.3 TEST SOFTWARE AND POWER LEVEL	11
2.4 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING	11
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
3. EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.2 RADIATED EMISSION MEASUREMENT	17
4. CONDUCTED SPURIOUS & BAND EDGE EMISSION	34
4.1 LIMIT	34
4.2 TEST PROCEDURE	34
4.3 DEVIATION FROM STANDARD	34
4.4 TEST SETUP	34
4.5 EUT OPERATION CONDITIONS	34
4.6 TEST RESULTS	34
5. POWER SPECTRAL DENSITY TEST	35
5.1 LIMIT	35
5.2 TEST PROCEDURE	35
5.3 DEVIATION FROM STANDARD	35
5.4 TEST SETUP	35
5.5 EUT OPERATION CONDITIONS	35
5.6 TEST RESULTS	35
6. BANDWIDTH TEST	36
6.1 LIMIT	36
6.2 TEST PROCEDURE	36
6.3 DEVIATION FROM STANDARD	36
6.4 TEST SETUP	36
6.5 EUT OPERATION CONDITIONS	36
6.6 TEST RESULTS	36

Table of Contents	Page
7. PEAK OUTPUT POWER TEST	37
7.1 LIMIT	37
7.2 TEST PROCEDURE	37
7.3 DEVIATION FROM STANDARD	37
7.4 TEST SETUP	37
7.5 EUT OPERATION CONDITIONS	37
7.6 TEST RESULTS	37
8. ANTENNA REQUIREMENT	38
8.1 STANDARD REQUIREMENT	38
8.2 EUT ANTENNA	38
APPENDIX I:TEST RESULTS	39
DUTY CYCLE	39
MAXIMUM PEAK CONDUCTED OUTPUT POWER	56
-6DB BANDWIDTH	58
MAXIMUM POWER SPECTRAL DENSITY LEVEL	71
BAND EDGE	93
CONDUCTED RF SPURIOUS EMISSION	110

Revision History

Rev.	Issue Date	Contents
00	Feb. 17, 2023	Initial Issue

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 15.247 Meas Guidance v05r02.

FCC Part 15.247,Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	--
15.247 (a)(2)	6dB Bandwidth	PASS	--
15.247 (b)(3)	Output Power	PASS	--
15.209	Radiated Spurious Emission	PASS	--
15.247 (d)	Conducted Spurious & Band Edge Emission	PASS	--
15.247 (e)	Power Spectral Density	PASS	--
15.205	Restricted Band Edge Emission	PASS	--
Part 15.247(d)/ Part 15.209(a)	Band Edge Emission	PASS	--
15.203	Antenna Requirement	PASS	--

NOTE:

(1) 'N/A' denotes test is not applicable in this Test Report.

(2) All tests are according to ANSI C63.10-2013.

(3) For model DBR1475 and DBR1475-S1, the TP control board have two types of A and B, this do not affect RF parameters. DBR1475 with type A was selected as the typical model for all necessary tests performed. For the details of type A&B, please refer to the EUT photos.

1.1 TEST FACTORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Chen Hsong Industrial Park, No.177 Renmin West Road, Jinsha Community, Kengzi Street, Pingshan New District, Shenzhen, China
Accreditation Certificate	A2LA Certificate No.: 6727.01
	FCC Registration No.: 746540
	CAB ID: CN0136

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95** %.

Parameter	Uncertainty
Occupied Channel Bandwidth	± 3.2 %
RF Output Power, Conducted	± 0.71 dB
Power Spectral Density, Conducted	± 1.57 dB
Unwanted Emission, Conducted	± 0.63 dB
Conducted emission	± 2.80 dB
All Emissions, Radiated (0.009-30MHz)	± 2.16 dB
All Emissions, Radiated (30MHz-1GHz)	± 4.40 dB
All Emissions, Radiated (1GHz-18GHz)	± 5.49 dB
Temperature	$\pm 0.5^{\circ}\text{C}$
Humidity	± 2 %
Duty Cycle	± 2.3 %

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF THE EUT

Product Name	DTEN D7X 75"	
Trademark	DTEN	
Model Name	DBR1475	
Series Model	DBR1475-S1	
Model Difference	Only the model name and shipping packaging method are different.	
Product Description	The EUT is a DTEN D7X 75"	
	Operation Frequency:	802.11b/g/n/ax(20MHz): 2412~2462 MHz 802.11n/ax(40MHz):2422~2452MHz
	Modulation Type:	802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11ax(OFDM): BPSK,QPSK,16-QAM,64-QAM, 256-QAM
	Number of Channel:	802.11b/g/n/ac/ax(20MHz): 11CH 802.11n/ac/ax(40MHz): 7CH
	Antenna Designation:	Dipole Antenna
	Antenna Gain(dBi):	ANT 1:4.62 ANT 2:4.62 MIMO:7.63
	Duty Cycle:	>98%
Channel List	Please refer to the Note 2.	
Rating	Input: AC 100-240V~ 50/60Hz 4.0A	
Hardware Version	RK3588.6 Ver:1.3	
Software Version	0.6.4	
Connecting I/O Port(s)	Please refer to the Note 1.	

802.11 b/g : SISO mode only, 802.11n HT20 /HT40/AX40: MIMO mode only.

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User Manual.

2.

Operation Frequency of channel			
802.11b/g/n/ax(20MHz)		Channel List for 802.11n/ax(40MHz)	
Channel	Frequency	Channel	Frequency
01	2412	03	2422
02	2417	04	2427
03	2422	05	2432
04	2427	06	2437
05	2432	07	2442
06	2437	08	2447
07	2442	09	2452
08	2447		
09	2452		
10	2457		
11	2462		

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	DTEN	MAW-105-0104	Dipole Antenna	N/A	ANT 1:4.62	2.4G WIFI
2			Dipole Antenna	N/A	ANT 2:4.62 MIMO:7.63	2.4G WIFI

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Carrier Frequency Channel

2.4GHz Test Frequency:

For 802.11b/g/n/ax(20MHz)		For 802.11n/ax(40MHz)	
Channel	Freq.(MHz)	Channel	Freq.(MHz)
01	2412	03	2422
06	2437	06	2437
11	2462	09	2452

Note: The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.

2.2 DESCRIPTION OF THE TEST MODES

Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Worst Mode	Description	Data Rate
Mode 1	TX IEEE 802.11b CH1	1 Mbps
Mode 2	TX IEEE 802.11b CH6	1 Mbps
Mode 3	TX IEEE 802.11 b CH11	1 Mbps
Mode 4	TX IEEE 802.11g CH1	6 Mbps
Mode 5	TX IEEE 802.11g CH6	6 Mbps
Mode 6	TX IEEE 802.11g CH11	6 Mbps
Mode 7	TX IEEE 802.11n HT20 CH1	MCS 0
Mode 8	TX IEEE 802.11n HT20 CH6	MCS 0
Mode 9	TX IEEE 802.11n HT20 CH11	MCS 0
Mode 10	TX IEEE 802.11n HT40 CH3	MCS 0
Mode 11	TX IEEE 802.11n HT40 CH6	MCS 0
Mode 12	TX IEEE 802.11n HT40 CH9	MCS 0
Mode 13	TX IEEE 802.11ax HE20 CH1	MCS 0
Mode 14	TX IEEE 802.11ax HE20 CH6	MCS 0
Mode 15	TX IEEE 802.11ax HE20 CH11	MCS 0
Mode 16	TX IEEE 802.11ax HE40 CH3	MCS 0
Mode 17	TX IEEE 802.11ax HE40 CH6	MCS 0
Mode 18	TX IEEE 802.11ax HE40 CH9	MCS 0

Note:

- (1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.
- (2) We have be tested for all avaiable U.S. voltage and frequencies(For 120V,50/60Hz and 240V, 50/60Hz) for which the device is capable of operation, and the worst case of 120V /60Hz is shown in the report.

AC Conducted Emission

Test Case	
AC Conducted Emission	Mode13: TX Mode + WLAN Link

2.3 TEST SOFTWARE AND POWER LEVEL

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level.

Accessories Equipment

Description	Manufacturer	Model	S/N	Rating
USB C-to-C cable	DTEN	N/A	N/A	1.9m, shielded
stylus	DTEN	N/A	N/A	N/A
Power cord	XIEKANG ELECTRONIC	N/A	N/A	3m, US plug
Camera	DTEN	N/A	N/A	2pcs

Auxiliary Equipment

Description	Manufacturer	Model	S/N	Rating
Laptop	HUAWEI	HKF-16	N/A	N/A

2.4 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS.

Test software Version	Test program: 2.4G WIFI		
CMD	b	SISO	15
	g	SISO	15
	n20	SISO	15
	n20	MIMO	15
	n40	SISO	15
	n40	MIMO	15
	ax20	SISO	15
	ax20	MIMO	15
	ax40	SISO	15
	ax40	MIMO	15

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
EMI Test Receiver	R&S	ESU8	100372	2022.04.12	2023.04.11
LISN	COM-POWER	LI-115	02032	2022.04.13	2023.04.12
LISN	SCHWARZBECK	NNLK 8121	00847	2022.08.19	2023.08.18
CE Cable	N.A	C01	N.A	2022.05.05	2023.05.04
Transient Limiter	CYBERTEK	EM5010A	E2250100049	2022.08.19	2023.08.18
Temperature & Humidity	KTJ	TA218B	N.A	2022.05.05	2023.05.04
Testing Software	EMC-I_V1.4.0.3_SKET				

RF Radiated Test equipment					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
EMI Test Receiver	R&S	ESU8	100372	2022.04.12	2023.04.11
Active loop Antenna	R&S	HFH2-Z2	POS871398181	2022.06.02	2024.06.01
Spectrum Analyzer	Kesight	N9010B	MY60242508	2022.04.29	2023.04.28
Bilog Antenna	SCHAFFNER	CBL6112B	2705	2022.06.05	2024.06.04
Bilog Antenna	SCHAFFNER	VULB 9168	01447	2022.12.12	2023.12.11
Horn Antenna	Schwarzbeck	3115	10SL0060	2022.06.02	2024.06.01
Pre-amplifier(0.1M -3GHz)	HP	8447D	2727A05655	2022.04.11	2023.04.10
Pre-amplifier(1-26 .5G)	Agilent	8449B	3008A4722	2022.04.13	2023.04.12
RE Cable (9K-1G)	N.A	R01	N.A	2022.05.05	2023.05.04
RE Cable (1-26G)	N.A	R02	N.A	2022.05.05	2023.05.04
Wireless Communications Test Set	R&S	CMW 500	137737	2022.04.29	2023.04.28
Temperature & Humidity	KTJ	TA218B	N.A	2022.05.05	2023.05.04
Testing Software	EMC-I_V1.4.0.3_SKET				

RF Conducted Test equipment					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Until
Signal Analyzer	Keysight	N9010B	MY60242508	2022.04.29	2023.04.28
RF Automatic Test system	MW	MW200-RFCB	MW220322LG	2022.04.29	2023.04.28
MXG Vector Signal Generator	Keysight	N5182B	MY59100717	2022.06.02	2023.06.01
Temperature& Humidity test chamber	AISRY	LX-1000L	171200018	2022.05.10	2023.05.09
Attenuator	eastsheep	90db	N.A	2022.04.29	2023.04.28
Router	TP-LINK(FCC ID:Q87-WRT320 0ACM)	TL-WR885N	1125074010735	N.C.R	N.C.R
Temperature & Humidity	KTJ	TA218B	N.A	2022.05.05	2023.05.04
Testing Software	MTS8310_V2.0.0.0_MW				

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table.

FREQUENCY (MHz)	Conducted Emissionlimit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of “ * ” marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- a. The EUT is 0.8 m from the horizontal ground plane and 0.4 m from the vertical ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments are powered from additional LISN(s). The LISN provides 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN is at least 80 cm from the nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



Note: 1. Support units were connected to second LISN.


2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes support units.

3.1.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


3.1.5 TEST RESULT

Project: LGT22L023	Test Engineer: Dylan.shi
EUT: DTEN D7X 75"	Temperature: 17.2°C
M/N: DBR1475	Humidity: 55%RH
Test Voltage: AC 120V/60Hz	Test Data: 2023-01-03
Test Mode: TX 2.4GHz	
Note:	



No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Margin dB	Detector	Polar
1*	526.000kHz	38.71	10.51	49.22	56.00	-6.78	PK	L1
2	5.834MHz	36.30	10.80	47.10	60.00	-12.90	QP	L1
3	20.894MHz	37.38	11.10	48.48	60.00	-11.52	QP	L1
4*	170.000kHz	37.81	10.50	48.31	54.96	-6.65	AV	L1
5*	6.126MHz	29.56	10.85	40.41	50.00	-9.59	AV	L1
6*	21.034MHz	32.29	11.11	43.40	50.00	-6.60	AV	L1

Project: LGT22L023	Test Engineer: Dylan.shi
EUT: DTEN D7X 75"	Temperature: 17.2°C
M/N: DBR1475	Humidity: 55%RH
Test Voltage: AC 120V/60Hz	Test Data: 2023-01-03
Test Mode: TX 2.4GHz	
Note:	



No.	Frequency	Reading dBuV	Factor dB	Level dBuV	Limit dBuV	Margin dB	Detector	Polar
1	1.362MHz	32.69	10.60	43.29	56.00	-12.71	QP	N
2	5.850MHz	37.63	10.80	48.43	60.00	-11.57	QP	N
3	20.690MHz	36.55	11.10	47.65	60.00	-12.35	QP	N
4*	878.000kHz	28.66	10.52	39.18	46.00	-6.82	AV	N
5*	6.146MHz	29.07	10.85	39.92	50.00	-10.08	AV	N
6	20.894MHz	31.64	11.10	42.74	50.00	-7.26	CAV	N

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

In any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the Restricted band specified on Part15.205(a)&209(a) limit in the table and according to ANSI C63.10-2013 below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micровolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1000MHz-25GHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

LIMITS OF RESTRICTED FREQUENCY BANDS

FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (MHz)	FREQUENCY (GHz)
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP/AV
Start Frequency	9 KHz/150KHz(Peak/QP/AV)
Stop Frequency	150KHz/30MHz(Peak/QP/AV)
RB / VB (emission in restricted band)	200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz); 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz)

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak/QP
Start Frequency	30 MHz(Peak/QP)
Stop Frequency	1000 MHz (Peak/QP)
RB / VB (emission in restricted band)	120 KHz / 300 KHz

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

For Restricted band

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2310 to 2430 MHz Upper Band Edge: 2445 to 2500 MHz
RB / VB	1 MHz / 3 MHz(Peak) 1 MHz/1/T MHz(AVG)

Receiver Parameter	Setting
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE


- The measuring distance at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz, and above 1GHz.
- The EUT was placed on the top of a rotating table 0.8 m (above 1GHz is 1.5 m) above the ground at a 3 m anechoic chamber test site. The table was rotated 360 degree to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m (above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarization of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and QuasiPeak detector mode will be re-measured.
- If the Peak Mode measured value is compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and no additional QP Mode measurement was performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

3.2.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.4 EUT OPERATING CONDITIONS

Please refer to section 3.1.4 of this report.

3.2.5 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where

FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor


For example

Frequency	FS	RA	AF	CL	AG	Factor
(MHz)	(dB μ V/m)	(dB μ V/m)	(dB)	(dB)	(dB)	(dB)
300	40	58.1	12.2	1.6	31.9	-18.1

$$\text{Factor} = \text{AF} + \text{CL} - \text{AG}$$


3.2.6 TEST RESULT

Project: LGT22L023	Test Engineer: Dylan.shi
EUT: DTEN D7X 75"	Temperature: 21.5°C
M/N: DBR1475	Humidity: 48%RH
Test Voltage: AC 120V/60Hz	Test Data: 2023-01-03
Test Mode: TX 2.4GHz	
Note:	




No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	486.021MHz	9.89	19.05	28.94	46.00	-17.06	PK	Hor
2*	666.563MHz	12.89	23.14	36.03	46.00	-9.97	PK	Hor
3*	853.530MHz	10.91	26.15	37.06	46.00	-8.94	PK	Hor

Project: LGT22L023	Test Engineer: Dylan.shi
EUT: DTEN D7X 75"	Temperature: 21.5°C
M/N: DBR1475	Humidity: 48%RH
Test Voltage: AC 120V/60Hz	Test Data: 2023-01-03
Test Mode: TX 2.4GHz	
Note:	




No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	133.305MHz	14.43	13.07	27.50	43.50	-16.00	PK	Ver
2*	504.088MHz	14.44	19.36	33.80	46.00	-12.20	PK	Ver
3*	804.060MHz	10.88	25.69	36.57	46.00	-9.43	PK	Ver

Project: LGT22L023	Test Engineer: Dylan.shi
EUT: DTEN D7X 75"	Temperature: 15.2°C
M/N: DBR1475	Humidity: 35%RH
Test Voltage: AC 120V/60Hz	Test Data: 2023-01-30
Test Mode: 802.11ax20 2412	
Note:	




No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1.404GHz	63.90	-21.36	42.54	74.00	-31.46	PK	Hor
2*	2.959GHz	70.20	-8.56	61.64	74.00	-12.36	PK	Hor
3*	8.977GHz	55.49	-1.23	54.26	74.00	-19.74	PK	Hor
4*	1.404GHz	53.16	-21.36	31.80	54.00	-22.20	AV	Hor
5*	2.944GHz	57.14	-8.63	48.51	54.00	-5.49	AV	Hor
6*	8.977GHz	44.83	-1.23	43.60	54.00	-10.40	AV	Hor

Project: LGT22L023	Test Engineer: Dylan.shi
EUT: DTEN D7X 75"	Temperature: 15.2°C
M/N: DBR1475	Humidity: 35%RH
Test Voltage: AC 120V/60Hz	Test Data: 2023-01-30
Test Mode: 802.11ax20 2412	
Note:	




No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1.404GHz	64.65	-21.36	43.29	74.00	-30.71	PK	Ver
2*	2.940GHz	73.03	-8.66	64.37	74.00	-9.63	PK	Ver
3*	8.950GHz	54.30	-1.31	52.99	74.00	-21.01	PK	Ver
4*	1.404GHz	53.96	-21.36	32.60	54.00	-21.40	AV	Ver
5*	2.966GHz	57.88	-8.52	49.36	54.00	-4.64	AV	Ver
6*	8.950GHz	44.91	-1.31	43.60	54.00	-10.40	AV	Ver

Project: LGT22L023	Test Engineer: Dylan.shi
EUT: DTEN D7X 75"	Temperature: 15.2°C
M/N: DBR1475	Humidity: 35%RH
Test Voltage: AC 120V/60Hz	Test Data: 2023-01-30
Test Mode: 802.11ax20 2437	
Note:	




No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1.854GHz	61.20	-17.70	43.50	74.00	-30.50	PK	Hor
2*	2.940GHz	67.72	-8.66	59.06	74.00	-14.94	PK	Hor
3*	8.926GHz	54.89	-1.38	53.51	74.00	-20.49	PK	Hor
4*	1.854GHz	49.70	-17.70	32.00	54.00	-22.00	AV	Hor
5*	2.944GHz	53.54	-8.63	44.91	54.00	-9.09	AV	Hor
6*	8.926GHz	44.28	-1.38	42.90	54.00	-11.10	AV	Hor

Project: LGT22L023	Test Engineer: Dylan.shi
EUT: DTEN D7X 75"	Temperature: 15.2°C
M/N: DBR1475	Humidity: 35%RH
Test Voltage: AC 120V/60Hz	Test Data: 2023-01-30
Test Mode: 802.11ax20 2437	
Note:	




No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1.406GHz	65.70	-21.35	44.35	74.00	-29.65	PK	Ver
2*	2.940GHz	73.67	-8.66	65.01	74.00	-8.99	PK	Ver
3*	8.939GHz	54.24	-1.34	52.90	74.00	-21.10	PK	Ver
4*	1.406GHz	53.85	-21.35	32.50	54.00	-21.50	AV	Ver
5*	2.964GHz	58.28	-8.53	49.75	54.00	-4.25	AV	Ver
6*	8.939GHz	44.64	-1.34	43.30	54.00	-10.70	AV	Ver

Project: LGT22L023	Test Engineer: Dylan.shi
EUT: DTEN D7X 75"	Temperature: 15.2°C
M/N: DBR1475	Humidity: 35%RH
Test Voltage: AC 120V/60Hz	Test Data: 2023-01-30
Test Mode: 802.11ax20 2462	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1.782GHz	62.16	-18.43	43.73	74.00	-30.27	PK	Hor
2*	2.940GHz	68.08	-8.66	59.42	74.00	-14.58	PK	Hor
3*	8.971GHz	55.06	-1.25	53.81	74.00	-20.19	PK	Hor
4*	1.782GHz	51.43	-18.43	33.00	54.00	-21.00	AV	Hor
5*	2.944GHz	54.67	-8.63	46.04	54.00	-7.96	AV	Hor
6*	8.971GHz	44.75	-1.25	43.50	54.00	-10.50	AV	Hor


Project: LGT22L023	Test Engineer: Dylan.shi
EUT: DTEN D7X 75"	Temperature: 15.2°C
M/N: DBR1475	Humidity: 35%RH
Test Voltage: AC 120V/60Hz	Test Data: 2023-01-30
Test Mode: 802.11ax20 2462	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	1.404GHz	64.58	-21.36	43.22	74.00	-30.78	PK	Ver
2*	2.940GHz	72.91	-8.66	64.25	74.00	-9.75	PK	Ver
3*	8.922GHz	54.26	-1.39	52.87	74.00	-21.13	PK	Ver
4*	1.404GHz	53.96	-21.36	32.60	54.00	-21.40	AV	Ver
5*	2.944GHz	58.34	-8.63	49.71	54.00	-4.29	AV	Ver
6*	8.922GHz	44.29	-1.39	42.90	54.00	-11.10	AV	Ver


3.2.7 RADIATED BAND EDGE

Project: LGT22L023	Test Engineer: Dylan.shi
EUT: DTEN D7X 75"	Temperature: 20°C
M/N: DBR1475	Humidity: 34%RH
Test Voltage: AC 120V/60Hz	Test Data: 2023-01-30
Test Mode: 802.11ax20 2412	
Note:	




No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	2.3217GHz	17.42	34.11	51.53	74.00	-22.47	PK	Hor
2*	2.3900GHz	15.85	33.95	49.80	74.00	-24.20	PK	Hor

Project: LGT22L023	Test Engineer: Dylan.shi
EUT: DTEN D7X 75"	Temperature: 20°C
M/N: DBR1475	Humidity: 34%RH
Test Voltage: AC 120V/60Hz	Test Data: 2023-01-30
Test Mode: 802.11ax20 2412	
Note:	




No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	2.3471GHz	16.59	34.05	50.64	74.00	-23.36	PK	Ver
2*	2.3900GHz	13.95	33.95	47.90	74.00	-26.10	PK	Ver

Project: LGT22L023	Test Engineer: Dylan.shi
EUT: DTEN D7X 75"	Temperature: 20°C
M/N: DBR1475	Humidity: 34%RH
Test Voltage: AC 120V/60Hz	Test Data: 2023-01-30
Test Mode: 802.11ax20 2462	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	2.4835GHz	14.17	34.13	48.30	74.00	-25.70	PK	Hor
2*	2.4861GHz	17.50	34.13	51.63	74.00	-22.37	PK	Hor

Project: LGT22L023	Test Engineer: Dylan.shi
EUT: DTEN D7X 75"	Temperature: 20°C
M/N: DBR1475	Humidity: 34%RH
Test Voltage: AC 120V/60Hz	Test Data: 2023-01-30
Test Mode: 802.11ax20 2462	
Note:	



No.	Frequency	Reading dBuV	Factor dB/m	Level dBuV/m	Limit dBuV/m	Margin dB	Detector	Polar
1*	2.4835GHz	13.87	34.13	48.00	74.00	-26.00	PK	Ver
2*	2.4987GHz	16.68	34.16	50.84	74.00	-23.16	PK	Ver

4. CONDUCTED SPURIOUS & BAND EDGE EMISSION

4.1 LIMIT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

4.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 to 2432 MHz Upper Band Edge: 2442 to 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



The EUT which is powered by the $\{ \text{Power} \}$, is connected to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

4.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

4.6 TEST RESULTS

For the measurement records, refer to the appendix I.

5. POWER SPECTRAL DENSITY TEST

5.1 LIMIT

FCC Part15.247 , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	≤ 8 dBm (RBW ≥ 3 KHz)	2400-2483.5	PASS

5.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the $100 \text{ kHz} \geq \text{RBW} \geq 3 \text{ kHz}$.
4. Set the $\text{VBW} \geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

5.6 TEST RESULTS

For the measurement records, refer to the appendix I.

6. BANDWIDTH TEST

6.1 LIMIT

FCC Part15.247,Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

6.2 TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW $\geq$ 3RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

6.6 TEST RESULTS

For the measurement records, refer to the appendix I.

7. PEAK OUTPUT POWER TEST

7.1 LIMIT

FCC Part15.247, Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS

7.2 TEST PROCEDURE

One of the following procedures may be used to determine the maximum peak conducted output power of a DTS EUT.

RBW $\geq$ DTS bandwidth

The following procedure shall be used when an instrument with a resolution bandwidth that is greater than the DTS bandwidth is available to perform the measurement:

- Set the RBW $\geq$ DTS bandwidth.
- Set VBW $\geq$ [3 $\times$ RBW].
- Set span $\geq$ [3 $\times$ RBW].
- Sweep time = auto couple.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.

Integrated band power method:

The following procedure can be used when the maximum available RBW of the instrument is less than the

DTS bandwidth:

- Set the RBW = 1 MHz.
- Set the VBW $\geq$ [3 $\times$ RBW].
- Set the span $\geq$ [1.5 $\times$ DTS bandwidth].
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select the peak detector). If the instrument does not have a band power function, then sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS channel bandwidth.


PKPM1 Peak power meter method:

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

Please refer to section 3.1.4 of this report.

7.6 TEST RESULTS

For the measurement records, refer to the appendix I.

8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


8.2 EUT ANTENNA


The EUT antenna is Dipole Antenna. It comply with the standard requirement.


APPENDIX I:TEST RESULTS




DUTY CYCLE




Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	b	2412	Ant1	99.91	0	0.08
NVNT	b	2437	Ant1	99.92	0	0.08
NVNT	b	2462	Ant1	99.91	0	0.08
NVNT	b	2412	Ant2	99.91	0	0.08
NVNT	b	2437	Ant2	99.91	0	0.08
NVNT	b	2462	Ant2	99.91	0	0.08
NVNT	g	2412	Ant1	99.24	0	0.48
NVNT	g	2437	Ant1	99.34	0	0.48
NVNT	g	2462	Ant1	99.34	0	0.48
NVNT	g	2412	Ant2	99.24	0	0.48
NVNT	g	2437	Ant2	99.24	0	0.48
NVNT	g	2462	Ant2	99.34	0	0.48
NVNT	n20	2412	Ant1	99.74	0	0.18
NVNT	n20	2437	Ant1	99.74	0	0.18
NVNT	n20	2462	Ant1	99.71	0	0.18
NVNT	n20	2412	Ant2	99.74	0	0.18
NVNT	n20	2437	Ant2	99.74	0	0.18
NVNT	n20	2462	Ant2	99.71	0	0.18
NVNT	n20	2412	Sum	99.71	0	0.18
NVNT	n20	2437	Sum	99.74	0	0.18
NVNT	n20	2462	Sum	99.71	0	0.18
NVNT	n40	2422	Ant1	99.74	0	0.18
NVNT	n40	2437	Ant1	99.71	0	0.18
NVNT	n40	2452	Ant1	99.71	0	0.18
NVNT	n40	2422	Ant2	99.74	0	0.18
NVNT	n40	2437	Ant2	99.74	0	0.18
NVNT	n40	2452	Ant2	99.74	0	0.18
NVNT	n40	2422	Sum	99.74	0	0.18
NVNT	n40	2437	Sum	99.74	0	0.18
NVNT	n40	2452	Sum	99.71	0	0.18
NVNT	ax20	2412	Ant1	99.74	0	0.18
NVNT	ax20	2437	Ant1	99.74	0	0.18
NVNT	ax20	2462	Ant1	99.74	0	0.18
NVNT	ax20	2412	Ant2	99.74	0	0.18
NVNT	ax20	2437	Ant2	99.74	0	0.18
NVNT	ax20	2462	Ant2	99.74	0	0.18
NVNT	ax20	2412	Sum	99.71	0	0.18
NVNT	ax20	2437	Sum	99.71	0	0.18
NVNT	ax20	2462	Sum	99.71	0	0.18
NVNT	ax40	2422	Ant1	99.71	0	0.18
NVNT	ax40	2437	Ant1	99.71	0	0.18
NVNT	ax40	2452	Ant1	99.71	0	0.18
NVNT	ax40	2422	Ant2	99.71	0	0.18
NVNT	ax40	2437	Ant2	99.71	0	0.18
NVNT	ax40	2452	Ant2	99.71	0	0.18
NVNT	ax40	2422	Sum	99.74	0	0.18
NVNT	ax40	2437	Sum	99.74	0	0.18
NVNT	ax40	2452	Sum	99.74	0	0.18


































































MAXIMUM PEAK CONDUCTED OUTPUT POWER

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	b	2412	Ant1	13.15	30	Pass
NVNT	b	2437	Ant1	13.51	30	Pass
NVNT	b	2462	Ant1	13.09	30	Pass
NVNT	b	2412	Ant2	12.89	30	Pass
NVNT	b	2437	Ant2	12.91	30	Pass
NVNT	b	2462	Ant2	12.64	30	Pass
NVNT	g	2412	Ant1	16.21	30	Pass
NVNT	g	2437	Ant1	16.51	30	Pass
NVNT	g	2462	Ant1	16.24	30	Pass
NVNT	g	2412	Ant2	16.09	30	Pass
NVNT	g	2437	Ant2	16.07	30	Pass
NVNT	g	2462	Ant2	15.81	30	Pass
NVNT	n20	2412	Ant1	15.93	30	Pass
NVNT	n20	2437	Ant1	16.36	30	Pass
NVNT	n20	2462	Ant1	16.01	30	Pass
NVNT	n20	2412	Ant2	15.97	30	Pass
NVNT	n20	2437	Ant2	15.89	30	Pass
NVNT	n20	2462	Ant2	15.62	30	Pass
NVNT	n20	2412	Ant1	16.27	30	Pass
NVNT	n20	2412	Ant2	16.22	30	Pass
NVNT	n20	2412	Sum	19.26	30	Pass
NVNT	n20	2437	Ant1	16.69	30	Pass
NVNT	n20	2437	Ant2	16.23	30	Pass
NVNT	n20	2437	Sum	19.48	30	Pass
NVNT	n20	2462	Ant1	16.25	30	Pass
NVNT	n20	2462	Ant2	15.91	30	Pass
NVNT	n20	2462	Sum	19.09	30	Pass
NVNT	n40	2422	Ant1	16.25	30	Pass
NVNT	n40	2437	Ant1	16.61	30	Pass
NVNT	n40	2452	Ant1	16.54	30	Pass
NVNT	n40	2422	Ant2	16.24	30	Pass
NVNT	n40	2437	Ant2	16.2	30	Pass
NVNT	n40	2452	Ant2	16.18	30	Pass
NVNT	n40	2422	Ant1	16.56	30	Pass
NVNT	n40	2422	Ant2	16.61	30	Pass
NVNT	n40	2422	Sum	19.6	30	Pass
NVNT	n40	2437	Ant1	16.87	30	Pass
NVNT	n40	2437	Ant2	16.51	30	Pass
NVNT	n40	2437	Sum	19.7	30	Pass
NVNT	n40	2452	Ant1	16.79	30	Pass
NVNT	n40	2452	Ant2	16.55	30	Pass
NVNT	n40	2452	Sum	19.68	30	Pass
NVNT	ax20	2412	Ant1	17.35	30	Pass
NVNT	ax20	2437	Ant1	17.67	30	Pass
NVNT	ax20	2462	Ant1	17.35	30	Pass
NVNT	ax20	2412	Ant2	17.19	30	Pass
NVNT	ax20	2437	Ant2	16.28	30	Pass
NVNT	ax20	2462	Ant2	16.94	30	Pass
NVNT	ax20	2412	Ant1	17.28	30	Pass
NVNT	ax20	2412	Ant2	17.23	30	Pass
NVNT	ax20	2412	Sum	20.27	30	Pass
NVNT	ax20	2437	Ant1	17.72	30	Pass
NVNT	ax20	2437	Ant2	17.07	30	Pass
NVNT	ax20	2437	Sum	20.42	30	Pass
NVNT	ax20	2462	Ant1	17.29	30	Pass
NVNT	ax20	2462	Ant2	16.87	30	Pass
NVNT	ax20	2462	Sum	20.1	30	Pass
NVNT	ax40	2422	Ant1	16.59	30	Pass
NVNT	ax40	2437	Ant1	16.88	30	Pass

NVNT	ax40	2452	Ant1	16.86	30	Pass
NVNT	ax40	2422	Ant2	16.58	30	Pass
NVNT	ax40	2437	Ant2	16.58	30	Pass
NVNT	ax40	2452	Ant2	16.52	30	Pass
NVNT	ax40	2422	Ant1	16.77	30	Pass
NVNT	ax40	2422	Ant2	16.88	30	Pass
NVNT	ax40	2422	Sum	19.84	30	Pass
NVNT	ax40	2437	Ant1	17.27	30	Pass
NVNT	ax40	2437	Ant2	16.79	30	Pass
NVNT	ax40	2437	Sum	20.05	30	Pass
NVNT	ax40	2452	Ant1	17.14	30	Pass
NVNT	ax40	2452	Ant2	16.72	30	Pass
NVNT	ax40	2452	Sum	19.95	30	Pass

-6DB BANDWIDTH

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	b	2412	Ant1	7.588	0.5	Pass
NVNT	b	2437	Ant1	7.116	0.5	Pass
NVNT	b	2462	Ant1	7.955	0.5	Pass
NVNT	b	2412	Ant2	7.521	0.5	Pass
NVNT	b	2437	Ant2	8.088	0.5	Pass
NVNT	b	2462	Ant2	8.071	0.5	Pass
NVNT	g	2412	Ant1	16.301	0.5	Pass
NVNT	g	2437	Ant1	16.283	0.5	Pass
NVNT	g	2462	Ant1	15.952	0.5	Pass
NVNT	g	2412	Ant2	16.316	0.5	Pass
NVNT	g	2437	Ant2	16.291	0.5	Pass
NVNT	g	2462	Ant2	16.318	0.5	Pass
NVNT	n20	2412	Ant1	17.577	0.5	Pass
NVNT	n20	2437	Ant1	17.154	0.5	Pass
NVNT	n20	2462	Ant1	17.553	0.5	Pass
NVNT	n20	2412	Ant2	16.807	0.5	Pass
NVNT	n20	2437	Ant2	16.629	0.5	Pass
NVNT	n20	2462	Ant2	16.881	0.5	Pass
NVNT	n40	2422	Ant1	36.385	0.5	Pass
NVNT	n40	2437	Ant1	36.312	0.5	Pass
NVNT	n40	2452	Ant1	35.915	0.5	Pass
NVNT	n40	2422	Ant2	36.303	0.5	Pass
NVNT	n40	2437	Ant2	36.319	0.5	Pass
NVNT	n40	2452	Ant2	36.312	0.5	Pass
NVNT	ax20	2412	Ant1	18.481	0.5	Pass
NVNT	ax20	2437	Ant1	17.78	0.5	Pass
NVNT	ax20	2462	Ant1	18.652	0.5	Pass
NVNT	ax20	2412	Ant2	18.385	0.5	Pass
NVNT	ax20	2437	Ant2	18.567	0.5	Pass
NVNT	ax20	2462	Ant2	18.956	0.5	Pass
NVNT	ax40	2422	Ant1	37.800	0.5	Pass
NVNT	ax40	2437	Ant1	36.246	0.5	Pass
NVNT	ax40	2452	Ant1	37.385	0.5	Pass
NVNT	ax40	2422	Ant2	37.247	0.5	Pass
NVNT	ax40	2437	Ant2	37.406	0.5	Pass
NVNT	ax40	2452	Ant2	36.837	0.5	Pass



