

Project No.: TM-2302000083P
Report No.: TMWK2302000257KR

FCC ID: 2AQ8A-EKSLNP5C

Page: 1 / 59
Rev.: 01

RADIO TEST REPORT

FCC 47 CFR PART 15 SUBPART C


Test Standard	FCC Part 15.247
Product name	Enkore Smart Leverset
Brand Name	Pamex
Model No.	EKS-LNP5C
Test Result	Pass
Statements of Conformity	Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

The test Result was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were given in ANSI C63.10: 2013 and compliance standards.

The test results of this report relate only to the tested sample (EUT) identified in this report.

The test Report of full or partial shall not copy. Without written approval of Compliance Certification Services Inc. (Wugu Laboratory)

Approved by:



Sehni Hu
Supervisor

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	March 6, 2023	Initial Issue	ALL	Doris Chu
01	March 22, 2023	See the following Note Rev. (01)	P.16, P.22	Doris Chu

Rev. (01)

1. Modify 6dB BW from MHz to kHz in section 4.2.4.
2. Modify average power table line in section 4.3.4.

Table of contents

1.	GENERAL INFORMATION	4
1.1	EUT INFORMATION	4
1.2	EUT CHANNEL INFORMATION	5
1.3	ANTENNA INFORMATION	5
1.4	MEASUREMENT UNCERTAINTY.....	6
1.5	FACILITIES AND TEST LOCATION	7
1.6	INSTRUMENT CALIBRATION	8
1.7	SUPPORT AND EUT ACCESSORIES EQUIPMENT	9
1.8	TEST METHODOLOGY AND APPLIED STANDARDS	9
2.	TEST SUMMARY	10
3.	DESCRIPTION OF TEST MODES.....	11
3.1	THE WORST MODE OF OPERATING CONDITION	11
3.2	THE WORST MODE OF MEASUREMENT	12
3.3	EUT DUTY CYCLE	13
4.	TEST RESULT	14
4.1	AC POWER LINE CONDUCTED EMISSION	14
4.2	6DB BANDWIDTH AND OCCUPIED BANDWIDTH (99%)	15
4.3	OUTPUT POWER MEASUREMENT	21
4.4	POWER SPECTRAL DENSITY	23
4.5	CONDUCTED BAND EDGE AND SPURIOUS EMISSION	27
4.6	RADIATION BANDEDGE AND SPURIOUS EMISSION	34
APPENDIX 1 - PHOTOGRAPHS OF EUT		

1. GENERAL INFORMATION

1.1 EUT INFORMATION

Applicant	Pamex Inc. 4680 Vinita Court, Chino, CA, 91710, United States
Manufacturer	ALZK Co., Ltd. 9F., No. 36, Sec. 3, Bade Rd., Songshan Dist., Taipei City, Taiwan
Equipment	Enkore Smart Leverset
Model Name	EKS-LNP5C
Model Discrepancy	N/A
Brand Name	Pamex
Received Date	February 4, 2023
Date of Test	February 7 ~ 8, 2023
Power Supply	Power from Battery. (DC 1.5*4V)
HW Version	V0.0.3
SW Version	000002_00.03.02

Remark:

1. For more details, please refer to the User's manual of the EUT.
2. Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.

1.2 EUT CHANNEL INFORMATION

Frequency Range	2402MHz-2480MHz
Modulation Type	GFSK for BLE 1 Mbps GFSK for BLE 2 Mbps
Number of channels	40 Channels

Remark:

Refer as ANSI C63.10: 2013 clause 5.6.1 Table 4 for test channels

Number of frequencies to be tested		
Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
☐ 1 MHz or less	1	Middle
☐ 1 MHz to 10 MHz	2	1 near top and 1 near bottom
☒ More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

1.3 ANTENNA INFORMATION

Antenna Specification	☐ PIFA ☒ Chip ☐ Dipole ☐ Coils
Antenna Gain	Gain: -0.79 dBi
Antenna connector	N/A

Notes:

1.The antenna(s) of the EUT are permanently attached and there are no provisions for connection to an external antenna. So the EUT complies with the requirements of §15.203.

1.4 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	± 2.1183
Channel Bandwidth	± 2.1863
RF output power (Power Meter + Power sensor)	± 1.2688
Power Spectral density	± 2.1855
Conducted Bandedge	± 2.1866
Conducted Spurious Emission	± 2.1859
Radiated Emission_9kHz-30MHz	± 3.814
Radiated Emission_30MHz-200MHz	± 4.272
Radiated Emission_200MHz-1GHz	± 4.619
Radiated Emission_1GHz-6GHz	± 5.522
Radiated Emission_6GHz-18GHz	± 5.228
Radiated Emission_18GHz-26GHz	± 4.089
Radiated Emission_26GHz-40GHz	± 4.019

Remark:

1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$
2. ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report.

Report No.: TMWK2302000257KR

1.5 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at

☒ No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan.

☐ No. 12, Ln. 116, Wugong 3rd Rd., Wugu Dist., New Taipei City, Taiwan 24803

CAB identifier: TW1309

Test site	Test Engineer	Remark
AC Conduction Room	-	Not applicable, because EUT not connect to AC Main Source direct.
Radiation	Ray Li	-
RF Conducted	David Li	-

Remark: The lab has been recognized as the FCC accredited lab. under the KDB 974614 D01 and is listed in the FCC public Access Link (PAL) database, FCC Registration No. :444940, the FCC Designation No.:TW1309

1.6 INSTRUMENT CALIBRATION

RF Conducted Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Power Meter	Anritsu	ML2496A	2136002	2022-11-24	2023-11-23
EXA Signal Analyzer	Keysight	N9010B	MY60242460	2023-02-02	2024-02-01
Power Sensor	Anritsu	MA2411B	1911386	2022-08-08	2023-08-07
Power Sensor	Anritsu	MA2411B	1911387	2022-08-08	2023-08-07
Software	Radio Test Software Ver. 21				

3M 966 Chamber Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Loop Antenna	COM-POWER	AL-130	121051	2022-04-13	2023-04-12
Preamplifier	EMEC	EM330	060609	2022-02-23	2023-02-22
Thermo-Hygro Meter	WISEWIND	1206	D07	2022-12-19	2023-12-18
PXA Signal Analyzer	Keysight Technologies	N9030B	MY62291089	2022-10-14	2023-10-13
Preamplifier	HP	8449B	3008A00965	2022-12-23	2023-12-22
Bi-Log Antenna	Sunol Sciences	JB3	A030105	2022-08-03	2023-08-02
Cable	Huber+Suhner	104PEA	20995+11112+182330	2022-02-23	2023-02-22
Coaxial Cable	EMCI	EMC105	190914+33953	2022-06-15	2023-06-14
Horn Antenna	ETC	MCTD 1209	DRH13M02003	2023-01-12	2024-01-11
High Pass Filters	Titan Microwave	T04H30001800070S01	22011402-4	2022-06-29	2023-06-28
Horn Antenna	SCHWARZBECK	BBHA9170	1047	2022-12-30	2023-12-29
Pre-Amplifier	EMCI	EMC184045SE	980860	2022-12-27	2023-12-26
Cable	EMCI	EMC101G	211010+211011+211012	2022-12-12	2023-12-11
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Software	e3 6.11-20180419c				

AC Conducted Emissions Test Site					
Equipment	Manufacturer	Model	S/N	Cal Date	Cal Due
N/A					

Remark:

- Each piece of equipment is scheduled for calibration once a year.
- N.C.R. = No Calibration Required.

1.7 SUPPORT AND EUT ACCESSORIES EQUIPMENT

EUT Accessories Equipment						
No.	Equipment	Brand	Model	Series No.	FCC ID	IC
	N/A					

Support Equipment						
No.	Equipment	Brand	Model	Series No.	FCC ID	IC
1	NB(E)	Lenovo	IBM 7663	N/A	N/A	N/A

1.8 TEST METHODOLOGY AND APPLIED STANDARDS

The test methodology, setups and results comply with all requirements in accordance with ANSI C63.10:2013, FCC Part 2, FCC Part 15.247 and KDB 558074.

2. TEST SUMMARY

FCC Standard Section	Report Section	Test Item	Result
15.203	1.3	Antenna Requirement	Pass
15.207(a)	4.1	AC Conducted Emission	N/A
15.247(a)(2)	4.2	6 dB Bandwidth	Pass
-	4.2	Occupied Bandwidth (99%)	Pass
15.247(b)(3)	4.3	Output Power Measurement	Pass
15.247(e)	4.4	Power Spectral Density	Pass
15.247(d)	4.5	Conducted Band Edge	Pass
15.247(d)	4.5	Conducted Spurious Emission	Pass
15.247(d)	4.6	Radiation Band Edge	Pass
15.247(d)	4.6	Radiation Spurious Emission	Pass

3. DESCRIPTION OF TEST MODES

3.1 THE WORST MODE OF OPERATING CONDITION

Operation mode	BLE Mode (1Mbps) BLE Mode (2Mbps)
Test Channel Frequencies	1.Lowest Channel : 2402MHz 2.Middle Channel : 2442MHz 3.Highest Channel : 2480MHz

Remark:

1. EUT pre-scanned data rate of output power for each mode, the worst data rate were recorded in this report.

3.2 THE WORST MODE OF MEASUREMENT

Radiated Emission Measurement Above 1G	
Test Condition	Radiated Emission Above 1G
Power supply Mode	Mode 1: EUT power by Battery
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4
Worst Position	☐ Placed in fixed position. ☒ Placed in fixed position at X-Plane (E2-Plane) ☐ Placed in fixed position at Y-Plane (E1-Plane) ☐ Placed in fixed position at Z-Plane (H-Plane)

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by Battery
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Remark:

1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis ,X,Y, Z and two polarity, for radiated measurement. The worst case(Z -Plane) were recorded in this report

Report No.: TMWK2302000257KR

3.3 EUT DUTY CYCLE


Temperature: 21.8°C

Test date: February 7, 2023

Humidity: 58% RH

Tested by: David Li

Duty Cycle				
Configuration	Duty Cycle (%) = Ton / (Ton+Toff)	Duty Factor (dB) =10*log (1/Duty Cycle)	1/T (kHz)	VBW setting (kHz)
BLE 1M	100.00	0.00	0.33	0.01
BLE 2M	100.00	0.00	0.33	0.01



Report No.: TMWK2302000257KR

4. TEST RESULT

4.1 AC POWER LINE CONDUCTED EMISSION

4.1.1 Test Limit

According to §15.207(a),

Frequency Range (MHz)	Limits(dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50


* Decreases with the logarithm of the frequency.

4.1.2 Test Procedure

Test method Refer as ANSI C63.10: 2013 clause 6.2,

1. The EUT was placed above horizontal ground plane and 0.4m above vertical ground plane
2. EUT connected to the line impedance stabilization network (LISN)
3. Receiver set RBW of 9kHz and Detector Peak, and note as quasi-peak and average.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Recorded Line for Neutral and Line.

4.1.3 Test Setup



4.1.4 Test Result

Not applicable, because EUT not connect to AC Main Source direct.

Report No.: TMWK2302000257KR

4.2 6dB BANDWIDTH AND OCCUPIED BANDWIDTH (99%)

4.2.1 Test Limit

According to §15.247(a)(2)

6 dB Bandwidth :

Limit	Shall be at least 500kHz
-------	--------------------------


Occupied Bandwidth(99%) : For reporting purposes only.

4.2.2 Test Procedure

Test method Refer as ANSI C63.10: 2013,

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT.
3. SA set RBW = 100KHz, VBW = 300KHz and Detector = Peak, to measurement 6dB Bandwidth.
4. SA set RBW = 1% ~ 5% OBW, VBW = three times the RBW and Detector = Peak, to measurement 99% Bandwidth.
5. Measure and record the result of 6 dB Bandwidth and 99% Bandwidth. in the test report.

4.2.3 Test Setup



4.2.4 Test Result

Temperature: 21.8°C

Test date: February 7, 2023

Humidity: 58% RH

Tested by: David Li

Test mode: BLE-1Mbps mode / 2402-2480 MHz				
Channel	Frequency (MHz)	OBW (99%) (MHz)	6dB BW (kHz)	6dB limit (kHz)
Low	2402	1.0741	709.30	≥500
Mid	2442	1.0877	715.80	
High	2480	1.0793	716.50	


Test mode: BLE-2Mbps mode / 2402-2480 MHz				
Channel	Frequency (MHz)	OBW (99%) (MHz)	6dB BW (kHz)	6dB limit (kHz)
Low	2402	2.0758	1363.00	≥500
Mid	2442	2.0693	1369.00	
High	2480	2.0538	1351.00	

Test Data


6dB BANDWIDTH

BLE-1Mbps mode


Low CH



Mid CH




High CH




BLE-2Mbps mode

Low CH



Mid CH




High CH



Report No.: TMWK2302000257KR


Test Data

BANDWIDTH (99%)




BLE-2Mbps mode


Low CH



Mid CH



High CH



4.3 OUTPUT POWER MEASUREMENT

4.3.1 Test Limit

According to §15.247(b)(3)

Peak output power :

FCC

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement,

Limit	☒ Antenna not exceed 6 dBi : 30dBm ☐ Antenna with DG greater than 6 dBi [Limit = 30 – (DG – 6)] ☐ Point-to-point operation
-------	---


Average output power : For reporting purposes only.

4.3.2 Test Procedure

Test method Refer as ANSI C63.10:2013.

1. The EUT RF output connected to the power meter by RF cable.
2. Setting maximum power transmit of EUT.
3. The path loss was compensated to the results for each measurement.
4. Measure and record the result of Peak output power and Average output power. in the test report.

4.3.3 Test Setup



Report No.: TMWK2302000257KR

4.3.4 Test Result

Temperature: 21.8°C

Test date: February 7, 2023

Humidity: 58% RH

Tested by: David Li

Peak output power :

BLE 1M mode:

CH	Frequency (MHz)	Power set	Peak Power Output (dBm)	Required Limit (dBm)
Low	2402	5	4.06	30
Mid	2442	5	3.94	30
High	2480	5	3.64	30

BLE 2M mode:

CH	Frequency (MHz)	Power set	Peak Power Output (dBm)	Required Limit (dBm)
Low	2402	5	4.05	30
Mid	2442	5	3.87	30
High	2480	5	3.73	30

Average output power :

BLE 1M mode:

CH	Frequency (MHz)	Power set	Average Power Output (dBm)	Required Limit (dBm)
Low	2402	5	4.00	30
Mid	2442	5	3.89	30
High	2480	5	3.59	30

BLE 2M mode:

CH	Frequency (MHz)	Power set	Average Power Output (dBm)	Required Limit (dBm)
Low	2402	5	4.00	30
Mid	2442	5	3.80	30
High	2480	5	3.66	30

4.4 POWER SPECTRAL DENSITY

4.4.1 Test Limit

According to §15.247(e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Limit	☒ Antenna not exceed 6 dBi : 8dBm ☐ Antenna with DG greater than 6 dBi [Limit = 8 – (DG – 6)] ☐ Point-to-point operation :
-------	---

4.4.2 Test Procedure

Test method Refer as ANSI C63.10:2013.

1. The EUT RF output connected to the spectrum analyzer by RF cable.
2. Setting maximum power transmit of EUT
3. SA set RBW = 3kHz, VBW = 10kHz, Span = 1.5 times DTS Bandwidth (6 dB BW), Detector = Peak, Sweep Time = Auto and Trace = Max hold.
4. The path loss and Duty Factor were compensated to the results for each measurement by SA.
5. Mark the maximum level.
6. Measure and record the result of power spectral density. in the test report.

4.4.3 Test Setup



4.4.4 Test Result

Temperature: 21.8°C

Test date: February 7, 2023

Humidity: 58% RH

Tested by: David Li

BLE 1M mode

Frequency (MHz)	RF Power Density (dBm/3kHz)	Maximum Limit (dBm/3kHz)	Result
2402	-4.97	8	PASS
2442	-6.04	8	PASS
2480	-5.50	8	PASS

BLE 2M mode


Frequency (MHz)	RF Power Density (dBm/3kHz)	Maximum Limit (dBm/3kHz)	Result
2402	-9.33	8	PASS
2442	-7.58	8	PASS
2480	-9.36	8	PASS

Report No.: TMWK2302000257KR


Test Data

BLE-1Mbps mode


Low CH



Mid CH




High CH




BLE-2Mbps mode


Low CH



Mid CH



High CH



4.5 CONDUCTED BAND EDGE AND SPURIOUS EMISSION

4.5.1 Test Limit

According to §15.247(d)

FCC: In any 100 kHz bandwidth outside the authorized frequency band,


Non-restricted bands shall be attenuated at least 20 dB/30 dB relative to the maximum PSD level in 100 kHz by RF conducted or a radiated measurement which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

4.5.2 Test Procedure

Test method Refer as ANSI C63.10:2013.

1. EUT RF output port connected to the SA by RF cable, and the path loss was compensated to result.
2. SA setting, RBW=100kHz, VBW=300kHz, Detector=Peak, Trace mode = max hold, SWT = Auto.
3. In any 100 kHz bandwidth outside the authorized frequency band, shall be attenuated at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when conducted power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

4.5.3 Test Setup



Report No.: TMWK2302000257KR

4.5.4 Test Result

Test Data

Temperature: 21.8°C

Test date: February 7, 2023

Humidity: 58% RH


Tested by: David Li

BLE-1Mbps mode Low CH

Reference Level



Band Edge



Spurious Emission 30MHz-25GHz




BLE-1Mbps mode Mid CH

Reference Level



Spurious Emission 30MHz-25GHz



BLE-1Mbps mode High CH

Reference Level



Band Edge




Spurious Emission 30MHz-25GHz




Report No.: TMWK2302000257KR

BLE-2Mbps mode Low CH


Reference Level



Band Edge



Spurious Emission 30MHz-25GHz




BLE-2Mbps mode Mid CH

Reference Level



Spurious Emission 30MHz-25GHz



BLE-2Mbps mode High CH

Reference Level



Band Edge



Spurious Emission 30MHz-25GHz



4.6 RADIATION BANDEDGE AND SPURIOUS EMISSION

4.6.1 Test Limit

FCC according to §15.247(d), §15.209 and §15.205,

In any 100 kHz bandwidth outside the authorized frequency band, all harmonic and spurious must be least 20 dB below the highest emission level with the authorized frequency band. Radiation emission which fall in the restricted bands must also follow the FCC section 15.209 as below limit in table.

Below 30 MHz

Frequency	Field Strength (microvolts/m)	Magnetic H-Field (microamperes/m)	Measurement Distance (metres)
9-490 kHz	2,400/F (F in kHz)	2,400/F (F in kHz)	300
490-1,705 kHz	24,000/F (F in kHz)	24,000/F (F in kHz)	30
1.705-30 MHz	30	N/A	30

Above 30 MHz

Frequency (MHz)	Field Strength microvolts/m at 3 metres (watts, e.i.r.p.)	
	Transmitters	Receivers
30-88	100 (3 nW)	100 (3 nW)
88-216	150 (6.8 nW)	150 (6.8 nW)
216-960	200 (12 nW)	200 (12 nW)
Above 960	500 (75 nW)	500 (75 nW)

Remark:

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

4.6.2 Test Procedure

Test method Refer as ANSI C63.10:2013.

1. The EUT is placed on a turntable, Above 1 GHz is 1.5m and below 1 GHz is 0.8m above ground plane. The EUT Configured un accordance with ANSI C63.10: 2013, and the EUT set in a continuous mode.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level. And EUT is set 3m away from the receiving antenna, which is scanned from 1m to 4m above the ground plane to find out the highest emissions. Measurement are made polarized in both the vertical and the horizontal positions with antenna.
3. Span shall wide enough to full capture the emission measured. The SA from 9KHz to 26.5GHz set to the low, Mid and High channels with the EUT transmit.

Remark:

1. Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.
2. No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz).

3. The SA setting following :

- (1) Below 1G : RBW = 100kHz, VBW $\geq$ 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.
- (2) Above 1G :
 - (2.1) For Peak measurement : RBW = 1MHz, VBW $\geq$ 3 RBW, Sweep = Auto, Detector = Peak, Trace = Max hold.
 - (2.2) For Average measurement : RBW = 1MHz, VBW
 - *If Duty Cycle $\geq$ 98%, VBW=10Hz.
 - *If Duty Cycle < 98%, VBW=1/T.


4. Data result

Actual FS=Spectrum Reading Level+Factor


Margin=Actual FS- Limit

4.6.3 Test Setup


9kHz ~ 30MHz



30MHz ~ 1GHz




Above 1 GHz



4.6.4 Test Result


Band Edge Test Data

Test Mode:	BLE-1Mbps Low CH	Temp/Hum	22.8(°C) / 61%RH
Test Item	Band Edge	Test Date	February 8, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak / Average		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2362.63	Peak	39.60	7.29	46.89	74.00	-27.11
2386.82	Average	28.87	7.41	36.28	54.00	-17.72
2402.00	Peak	81.05	7.26	88.31	--	--
2402.00	Average	80.24	7.26	87.50	--	--
2483.81	Average	28.78	7.80	36.58	54.00	-17.42
2489.95	Peak	39.90	7.81	47.72	74.00	-26.28

Test Mode:	BLE-1Mbps Low CH	Temp/Hum	22.8(°C) / 61%RH
Test Item	Band Edge	Test Date	February 8, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak / Average		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBUV/m)	Limit @3m (dBUV/m)	Margin (dB)
2381.98	Peak	39.89	7.36	47.24	74.00	-26.76
2387.88	Average	28.92	7.42	36.34	54.00	-17.66
2402.00	Peak	81.71	7.26	88.97	--	--
2402.00	Average	80.93	7.26	88.19	--	--
2483.70	Peak	39.14	7.80	46.94	74.00	-27.06
2498.09	Average	28.91	7.83	36.74	54.00	-17.26

Test Mode:	BLE-1Mbps High CH	Temp/Hum	22.8(°C) / 61%RH
Test Item	Band Edge	Test Date	February 8, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak / Average		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2388.23	Average	28.87	7.42	36.29	54.00	-17.71
2389.41	Peak	39.56	7.44	47.00	74.00	-27.00
2480.00	Peak	78.58	7.79	86.37	--	--
2480.00	Average	77.77	7.79	85.57	--	--
2486.29	Average	28.80	7.81	36.61	54.00	-17.39
2496.32	Peak	39.00	7.82	46.82	74.00	-27.18

Test Mode:	BLE-1Mbps High CH	Temp/Hum	22.8(°C) / 61%RH
Test Item	Band Edge	Test Date	February 8, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak / Average		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2352.13	Peak	39.65	7.39	47.04	74.00	-26.96
2384.22	Average	29.02	7.38	36.39	54.00	-17.61
2480.00	Peak	82.97	7.79	90.77	--	--
2480.00	Average	82.21	7.79	90.00	--	--
2483.50	Average	29.26	7.80	37.06	54.00	-16.94
2483.58	Peak	39.05	7.80	46.85	74.00	-27.15

Test Mode:	BLE-2Mbps Low CH	Temp/Hum	22.8(°C) / 61%RH
Test Item	Band Edge	Test Date	February 8, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak / Average		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2350.24	Average	28.90	7.41	36.31	54.00	-17.69
2358.26	Peak	39.50	7.33	46.84	74.00	-27.16
2402.00	Peak	80.92	7.26	88.18	--	--
2402.00	Average	78.87	7.26	86.13	--	--
2492.19	Peak	39.19	7.82	47.01	74.00	-26.99
2498.33	Average	28.68	7.83	36.51	54.00	-17.49

Test Mode:	BLE-2Mbps Low CH	Temp/Hum	22.8(°C) / 61%RH
Test Item	Band Edge	Test Date	February 8, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak / Average		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBUV/m)	Limit @3m (dBUV/m)	Margin (dB)
2353.42	Peak	40.28	7.38	47.66	74.00	-26.34
2383.63	Average	28.90	7.37	36.28	54.00	-17.72
2402.00	Peak	81.47	7.26	88.73	--	--
2402.00	Average	79.44	7.26	86.70	--	--
2492.78	Average	28.89	7.82	36.70	54.00	-17.30
2495.50	Peak	38.97	7.82	46.80	74.00	-27.20

Test Mode:	BLE-2Mbps High CH	Temp/Hum	22.8(°C) / 61%RH
Test Item	Band Edge	Test Date	February 8, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak / Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
2369.00	Peak	39.42	7.24	46.65	74.00	-27.35
2383.51	Average	28.91	7.37	36.28	54.00	-17.72
2480.00	Peak	77.19	7.79	84.99	--	--
2480.00	Average	74.99	7.79	82.79	--	--
2483.50	Average	29.42	7.80	37.22	54.00	-16.78
2490.07	Peak	39.05	7.81	46.87	74.00	-27.13


Test Mode:	BLE-2Mbps High CH	Temp/Hum	22.8(°C) / 61%RH
Test Item	Band Edge	Test Date	February 8, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak / Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBUV/m)	Limit @3m (dBUV/m)	Margin (dB)
2344.22	Peak	38.94	7.34	46.28	54.00	-27.72
2384.34	Average	27.75	7.38	35.13	74.00	-18.87
2480.00	Peak	84.20	7.79	91.99	--	--
2480.00	Average	82.02	7.79	89.81	--	--
2483.50	Peak	39.10	7.80	46.90	54.00	-27.10
2483.58	Average	29.86	7.80	37.66	74.00	-16.34

Below 1G Test Data


Test Mode:	BLE-1Mbps Mode	Temp/Hum	22.8(°C) / 61%RH
Test Item	30MHz-1GHz	Test Date	February 8, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
30.61	Peak	29.23	-3.65	25.59	40.00	-14.41
74.26	Peak	37.09	-15.71	21.38	40.00	-18.62
159.98	Peak	35.91	-10.83	25.08	43.50	-18.42
425.28	Peak	29.89	-5.27	24.62	46.00	-21.38
718.09	Peak	29.93	-0.09	29.83	46.00	-16.17
933.07	Peak	29.62	3.12	32.74	46.00	-13.26

Note: No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz).

Test Mode:	BLE-1Mbps Mode	Temp/Hum	22.8(°C) / 61%RH
Test Item	30MHz-1GHz	Test Date	February 8, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBUV)	Factor (dB)	Actual FS (dBUV/m)	Limit @3m (dBUV/m)	Margin (dB)
32.06	Peak	30.54	-3.78	26.76	40.00	-13.24
122.15	Peak	29.66	-9.38	20.28	43.50	-23.22
194.42	Peak	29.48	-10.84	18.65	43.50	-24.85
471.84	Peak	29.83	-4.09	25.74	46.00	-20.26
780.17	Peak	29.46	1.09	30.54	46.00	-15.46
882.15	Peak	30.07	2.16	32.23	46.00	-13.77

Note: No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz).

Above 1G Test Data

Test Mode:	BLE-1Mbps Low CH	Temp/Hum	22.8(°C) / 61%RH
Test Item	Harmonic	Test Date	February 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak / Average		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4804.00	Peak	46.46	5.17	51.63	74.00	-22.37
4804.00	Average	44.44	5.17	49.61	54.00	-4.39
7206.00	Peak	33.26	12.79	46.05	74.00	-27.95
7206.00	Average	26.97	12.79	39.76	54.00	-14.24
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode:	BLE-1Mbps Low CH	Temp/Hum	22.8(°C) / 61%RH
Test Item	Harmonic	Test Date	February 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak / Average		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBUV)	Factor (dB)	Actual FS (dBUV/m)	Limit @3m (dBUV/m)	Margin (dB)
4804.00	Peak	47.99	5.17	53.16	74.00	-20.84
4804.00	Average	45.44	5.17	50.61	54.00	-3.39
7206.00	Peak	33.20	12.79	45.99	74.00	-28.01
7206.00	Average	27.26	12.79	40.04	54.00	-13.96
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode:	BLE-1Mbps Mid CH	Temp/Hum	22.8(°C) / 61%RH
Test Item	Harmonic	Test Date	February 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak / Average		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4884.00	Peak	47.27	5.61	52.88	74.00	-21.12
4884.00	Average	44.55	5.61	50.16	54.00	-3.84
7326.00	Peak	32.23	12.72	44.95	74.00	-29.05
7326.00	Average	26.01	12.72	38.74	54.00	-15.26
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode:	BLE-1Mbps Mid CH	Temp/Hum	22.8(°C) / 61%RH
Test Item	Harmonic	Test Date	February 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak / Average		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4884.00	Peak	48.86	5.61	54.47	74.00	-19.53
4884.00	Average	46.70	5.61	52.31	54.00	-1.69
7326.00	Peak	32.46	12.72	45.18	74.00	-28.82
7326.00	Average	26.95	12.72	39.67	54.00	-14.33
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode:	BLE-1Mbps High CH	Temp/Hum	22.8(°C) / 61%RH
Test Item	Harmonic	Test Date	February 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak / Average		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBUV/m)	Limit @3m (dBUV/m)	Margin (dB)
4960.00	Peak	47.60	6.23	53.83	74.00	-20.17
4960.00	Average	44.74	6.23	50.97	54.00	-3.03
7440.00	Peak	31.89	12.66	44.55	74.00	-29.45
7440.00	Average	25.64	12.66	38.30	54.00	-15.70
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode:	BLE-1Mbps High CH	Temp/Hum	22.8(°C) / 61%RH
Test Item	Harmonic	Test Date	February 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak / Average		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4960.00	Peak	48.84	6.23	55.06	74.00	-18.94
4960.00	Average	46.72	6.23	52.94	54.00	-1.06
7440.00	Peak	33.60	12.66	46.26	74.00	-27.74
7440.00	Average	28.74	12.66	41.39	54.00	-12.61
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode:	BLE-2Mbps Low CH	Temp/Hum	22.8(°C) / 61%RH
Test Item	Harmonic	Test Date	February 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak / Average		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4804.00	Peak	45.66	5.17	50.84	74.00	-23.16
4804.00	Average	42.23	5.17	47.40	54.00	-6.60
7206.00	Peak	32.47	12.79	45.25	74.00	-28.75
7206.00	Average	25.88	12.79	38.66	54.00	-15.34
N/A						

Remark:

- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode:	BLE-2Mbps Low CH	Temp/Hum	22.8(°C) / 61%RH
Test Item	Harmonic	Test Date	February 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak / Average		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4804.00	Peak	45.69	5.17	50.86	74.00	-23.14
4804.00	Average	42.99	5.17	48.16	54.00	-5.84
7206.00	Peak	32.75	12.79	45.54	74.00	-28.46
7206.00	Average	26.26	12.79	39.05	54.00	-14.95
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode:	BLE-2Mbps Mid CH	Temp/Hum	22.8(°C) / 61%RH
Test Item	Harmonic	Test Date	February 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak / Average		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4884.00	Peak	46.73	5.61	52.34	74.00	-21.66
4884.00	Average	42.60	5.61	48.21	54.00	-5.79
7326.00	Peak	32.43	12.72	45.15	74.00	-28.85
7326.00	Average	25.65	12.72	38.37	54.00	-15.63
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode:	BLE-2Mbps Mid CH	Temp/Hum	22.8(°C) / 61%RH
Test Item	Harmonic	Test Date	February 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak / Average		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBUV)	Factor (dB)	Actual FS (dBUV/m)	Limit @3m (dBUV/m)	Margin (dB)
4884.00	Peak	43.07	5.61	48.67	74.00	-25.33
4884.00	Average	39.45	5.61	45.06	54.00	-8.94
7326.00	Peak	33.08	12.72	45.80	74.00	-28.20
7326.00	Average	25.09	12.72	37.81	54.00	-16.19
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode:	BLE-2Mbps High CH	Temp/Hum	22.8(°C) / 61%RH
Test Item	Harmonic	Test Date	February 7, 2023
Polarize	Vertical	Test Engineer	Ray Li
Detector	Peak / Average		




Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4960.00	Peak	45.89	6.23	52.11	74.00	-21.89
4960.00	Average	42.18	6.23	48.40	54.00	-5.60
7440.00	Peak	32.84	12.66	45.49	74.00	-28.51
7440.00	Average	26.19	12.66	38.84	54.00	-15.16
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

Test Mode:	BLE-2Mbps High CH	Temp/Hum	22.8(°C) / 61%RH
Test Item	Harmonic	Test Date	February 7, 2023
Polarize	Horizontal	Test Engineer	Ray Li
Detector	Peak / Average		



Freq. (MHz)	Detector Mode (PK/QP/AV)	Spectrum Reading Level (dBμV)	Factor (dB)	Actual FS (dBμV/m)	Limit @3m (dBμV/m)	Margin (dB)
4960.00	Peak	45.01	6.23	51.24	74.00	-22.76
4960.00	Average	41.19	6.23	47.42	54.00	-6.58
7440.00	Peak	33.22	12.66	45.88	74.00	-28.12
7440.00	Average	26.75	12.66	39.41	54.00	-14.59
N/A						

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

--End of Test Report--