

RF EXPOSURE REPORT

Product: Remote Controller

Model Name: D23

FCC ID: 2AQ95-NIUD23

Applicant: Beijing Niu Technology Co., Ltd

Address: 11F, Fangheng Times Center Block A (Lianluo Building), No. 10 Wangjing street, Chaoyang, Beijing, China

Manufacturer: Jiangsu Niu Electric Technology Co., Ltd.

Address: No.5 Lingxiang Rd, WEZ, Wujin, Changzhou, Jiangsu Province

Prepared by: BV 7Layers Communications Technology (Shenzhen) Co. Ltd

Lab Location: No.B102, Dazu Chuangxin Mansion, North of Beihuan Avenue, North Area, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, China

TEL: +86 755 8869 6566

FAX: +86 755 8869 6577

E-MAIL: customerservice.dg@cn.bureauveritas.com

Report No.: SA180830W001

Received Date: Dec. 03, 2018

Test Date: Dec. 04, 2018 ~ Jan. 04, 2019

Issued Date: Jan. 07, 2019

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



Test Report No.: SA180830W001

TABLE OF CONTENTS

RF EXPOSURE REPORT	1
RELEASE CONTROL RECORD	3
1 CERTIFICATION	4
2 GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
3 RF EXPOSURE.....	6
3.1 CALCULATION RESULT	6
3.2 CONCLUSION.....	6



Test Report No.: SA180830W001

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA180830W001	Original release	Jan. 07, 2019



Test Report No.: SA180830W001

1 CERTIFICATION

PRODUCT: Remote Controller
BRAND NAME: NIU
MODEL NAME: R800
APPLICANT: Beijing Niu Technology Co., Ltd
TESTED: Dec. 04, 2018 ~ Jan. 04, 2019
TEST SAMPLE: Production Unit
STANDARDS: FCC Part 2 (Section 2.1093)
KDB 447498 D01 General RF Exposure Guidance v06
IEEE C95.1

The above equipment has been tested by **BV 7Layers Communications Technology (Shenzhen) Co. Ltd** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Roger, **DATE:** Jan. 07, 2019
(Roger Li / Engineer)

APPROVED BY : [Signature], **DATE:** Jan. 07, 2019
(Sam Tung / Manager)

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Remote Controller
MODEL NAME	D23
NOMINAL VOLTAGE	3Vdc (button battery)
OPERATING TEMPERATURE RANGE	-20 ~ 70°C
MODULATION TYPE	ASK
OPERATING FREQUENCY	ASK
ANTENNA GAIN	PCB Antenna with 1.5dBi gain
HW VERSION	HRXN-D23-2150L-FCC-C20180926
SW VERSION	HR-2150L-V1.0-C1CF
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	N/A

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

3 RF EXPOSURE

Per KDB 447498 D01, for 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR,

$f(\text{GHz})$ is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

3.1 CALCULATION RESULT

Frequency (MHz)	Max. Tune-up Power (dBm)	Test Position	Separation Distance (mm)	Max. Tune-up (mW)	$\sqrt{f}(\text{GHz})$	Calculation Result	limit:3.0(1g)
315	-1.0	Body	5	0.79	0.561	0.1	No

3.2 CONCLUSION

According to the KDB447498 D01, the RF exposure analysis concludes that the SAR test is not required, and compliant with the FCC Rule.

--END--