

FCC RF Exposure

EUT Description: Arrow Smartwatch

Model No.: sw88

FCC ID: 2AQA7-SW88

1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1 - g and 10 - g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
 $[(\text{max power of channel, including tune - up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1 - g SAR and ≤ 7.5 for 10 - g extremity SAR,

Where:

Result= $P \sqrt{F/D}$

F= the RF channel transmit frequency in GHz

P=Maximum turn - up power in mw

D=Min. test separation distance in mm

2. Test Result of RF Exposure Evaluation

	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit (mW/cm ²)	SAR Test Exclusion
802.11b	7.85	7±1	8/6.31	5	1.980	3.0	Pass
802.11g	7.03	7±1	8/6.31	5	1.980	3.0	Pass
802.11n(HT20)	6.84	7±1	8/6.31	5	1.980	3.0	Pass
802.11n(HT40)	5.96	5±1	6/3.98	5	1.247	3.0	Pass

Note:

PK Output power= conducted power.

Conducted power see the test report HK180628351-E, antenna gain=1.6dBi

Note: Exclusion Thresholds Results= $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Distance=5mm