

# FCC REPORT

**Applicant:** Zhejiang Yihe Sanitary Ware Co., Ltd.

**Address of Applicant:** District A, No. 102 East Taihe Road, Haimen street, Jiaojiang, Taizhou, Zhejiang, China

Equipment Under Test (EUT)

**Product Name:** Remote Control

**Model No.:** RC08

**FCC ID:** 2AQBG-RC08

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart C Section 15.249

**Date of sample receipt:** 15 Mar., 2019

**Date of Test:** 15 Mar., to 10 Apr., 2019

**Date of report issued:** 11 Apr., 2019

**Test Result:** PASS\*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang  
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

## 2 Version

Version No.	Date	Description
00	11 Apr., 2019	Original
01	16 Apr., 2019	Update 4&20&21

**Prepared By:**

*Mike.ou*

**Date:**

11 Apr., 2019

**Project Engineer**

**Check By:**

*Winner.Zhang*

**Date:**

11 Apr., 2019

**Reviewer**

### **3 Contents**

	Page
<b>1 COVER PAGE</b>	1
<b>2 VERSION</b>	2
<b>3 CONTENTS</b>	3
<b>4 TEST SUMMARY</b>	4
<b>5 GENERAL INFORMATION</b>	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF E.U.T	5
5.3 TEST MODE	5
5.4 DESCRIPTION OF SUPPORT UNITS	5
5.5 LABORATORY FACILITY	6
5.6 LABORATORY LOCATION	6
5.7 TEST INSTRUMENTS LIST	7
<b>6 TEST RESULTS AND MEASUREMENT DATA</b>	8
6.1 ANTENNA REQUIREMENT	8
6.2 RADIATED EMISSION	9
6.2.1 Field Strength Of The Fundamental Signal	11
6.2.2 Spurious Emissions	12
6.2.3 Band Edge	15
6.3 20DB OCCUPY BANDWIDTH	20
<b>7 TEST SETUP PHOTO</b>	22
<b>8 EUT CONSTRUCTIONAL DETAILS</b>	23

## 4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
Conducted Emission	15.207	N/A
Field strength of the fundamental signal	15.249 (a)(e)	Pass
Spurious emissions	15.249 (d)/15.209	Pass
20dB Occupy Bandwidth	15.215	Pass

*Pass: The EUT comply with the essential requirements in the standard.*

## 5 General Information

### 5.1 Client Information

Applicant:	Zhejiang Yihe Sanitary Ware Co., Ltd.
Address of Applicant:	District A, No. 102 East Taihe Road, Haimen street, Jiaojiang, Taizhou, Zhejiang
Factory:	WUXI DENVEL INTELLIGENT ELECNIC INC
Address of Factory:	Building A, NO.8 LianHe Road, WuXi, JiangSu, China

### 5.2 General Description of E.U.T.

Product Name:	Remote Control
Model No.:	RC08
Operation Frequency:	2407MHz~2477MHz
Channel numbers:	12
Modulation type:	GFSK
Antenna Type:	PCB antenna
Antenna gain:	0 dBi
Power supply:	DC 3V (2 x " AA" Battery)
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

Operation Frequency each of channel					
Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2407MHz	4	2421MHz	8	2460MHz
1	2410MHz	5	2428MHz	9	2469MHz
2	2412MHz	6	2435MHz	10	2467MHz
3	2414MHz	7	2442MHz	11	2477MHz

**Note:**  
In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test. Channel No. 0, 7 & 11 were selected as Lowest, Middle and Highest channel.

### 5.3 Test mode

Transmitting mode:	Keep the EUT in transmitting mode with modulation. (new battery is used during all test.)										
<b>Pre-Test Mode:</b> (highest channel=2477MHz)											
CCIS has verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report and defined as follows:											
<table border="1"> <thead> <tr> <th>Axis</th><th>X</th><th>Y</th><th>Z</th></tr> </thead> <tbody> <tr> <td>Field Strength(dBuV/m)</td><td>88.67</td><td>89.13</td><td>91.21</td></tr> </tbody> </table>				Axis	X	Y	Z	Field Strength(dBuV/m)	88.67	89.13	91.21
Axis	X	Y	Z								
Field Strength(dBuV/m)	88.67	89.13	91.21								
<b>Final Test Mode:</b>											
According to ANSI C63.4 standards, the test results are both the "worst case" and "worst setup": Z axis (see the test setup photo)											

### 5.4 Description of Support Units

N/A
-----

## 5.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Registration No.: 727551**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC (Federal Communications Commission). The Registration No. is 727551.

● **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

## 5.6 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,  
Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755-23118282, Fax: +86-755-23116366


Email: info@ccis-cb.com, Website: http://www.ccis-cb.com

## 5.7 Test Instruments list

Radiated Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-18-2019	03-17-2020
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-18-2019	03-17-2020
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-22-2017	06-21-2020
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-21-2018	11-20-2019
Loop Antenna	SCHWARZBECK	FMZB 1519 B	00044	03-18-2019	03-17-2020
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-18-2019	03-17-2020
Pre-amplifier	CD	PAP-1G18	11804	03-18-2019	03-17-2020
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-18-2019	03-17-2020
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-21-2018	11-20-2019
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-18-2019	03-17-2020
Simulated Station	Anritsu	MT8820C	6201026545	03-18-2019	03-17-2020
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-18-2019	03-17-2020
Cable	MICRO-COAX	MFR64639	K10742-5	03-18-2019	03-17-2020
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-18-2019	03-17-2020



## 6 Test results and Measurement Data

### 6.1 Antenna requirement:

Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: <i>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</i>	
E.U.T Antenna:	<p>The antenna is PCB antenna which cannot detachable . The best case gain of the antenna is 0 dBi.</p> 

## 6.2 Radiated Emission

Test Requirement:	FCC Part15 C Section 15.249 and 15.209									
Test Method:	ANSI C63.10: 2013									
Test Frequency Range:	30MHz to 25000MHz									
Test site:	Measurement Distance: 3m									
Receiver setup:	Frequency	Detector	RBW	VBW	Remark					
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value					
	Above 1GHz	Peak	1MHz	3MHz	Peak Value					
Limit: (Field strength of the fundamental signal)	Frequency		Limit (dBuV/m @3m)		Remark					
	2400-2483.5MHz		94.00		Average Value					
			114.00		Peak Value					
Limit: (Spurious Emissions)	Frequency	Limit (dBuV/m @3m)			Remark					
	30MHz-88MHz	40.00			Quasi-peak Value					
	88MHz-216MHz	43.50			Quasi-peak Value					
	216MHz-960MHz	46.00			Quasi-peak Value					
	960MHz-1GHz	54.00			Quasi-peak Value					
	Above 1GHz	54.00			Average Value					
		74.00			Peak Value					
Limit: (outside of the specified frequency band)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.									
Test Procedure:	<ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table 0.8m(below 1GHz)/1.5m(above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>									

<p>Test setup:</p>	<p>Below 1GHz</p>  <p>Above 1GHz</p> 
<p>Test Instruments:</p>	<p>Refer to section 5.7</p>
<p>Test mode:</p>	<p>Refer to section 5.3</p>
<p>Test results:</p>	<p>Passed</p>

### 6.2.1 Field Strength Of The Fundamental Signal

Peak value							
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2407	58.00	27.56	4.8	90.36	114.00	-23.64	Vertical
	56.76	27.56	4.8	89.12	114.00	-24.88	Horizontoal
2442	58.14	27.56	4.8	90.50	114.00	-23.50	Vertical
	57.87	27.56	4.8	90.23	114.00	-23.77	Horizontoal
2477	58.85	27.56	4.8	91.21	114.00	-22.79	Vertical
	55.82	27.56	4.8	88.18	114.00	-25.82	Horizontoal
Average value							
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2407	57.24	27.56	4.8	89.60	94.00	-4.40	Vertical
	55.34	27.56	4.8	87.70	94.00	-6.30	Horizontoal
2442	57.85	27.56	4.8	90.21	94.00	-3.79	Vertical
	56.84	27.56	4.8	89.20	94.00	-4.80	Horizontoal
2477	58.18	27.56	4.8	90.54	94.00	-3.46	Vertical
	54.24	27.56	4.8	86.60	94.00	-7.40	Horizontoal


NOTE: Field strength of the fundamental signal test, RBW >20dB BW, VBW>=3XRBW.

## 6.2.2 Spurious Emissions

Measurement Data (worst case):

Below 1GHz:

Product Name:	Remote Control	Product Model:	RC08
Test By:	Mike	Test mode:	2.4G Tx mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	DC 3V	Environment:	Temp: 24°C Huni: 57%




Freq MHz	Read	Antenna Level	Cable Loss	Preamp Factor	Limit Level dBuV/m	Line Level dBuV/m	Over Limit dB	Over Limit Remark
	Antenna Level dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 45.375	34.87	12.28	1.29	29.86	18.58	40.00	-21.42	QP
2 109.029	31.91	11.75	2.04	29.46	16.24	43.50	-27.26	QP
3 248.552	33.10	12.62	2.81	28.55	19.98	46.00	-26.02	QP
4 494.199	32.62	18.00	3.57	28.94	25.25	46.00	-20.75	QP
5 625.078	32.77	19.61	3.90	28.86	27.42	46.00	-18.58	QP
6 979.180	32.25	22.76	4.36	27.55	31.82	54.00	-22.18	QP

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

<b>Product Name:</b>	Remote Control	<b>Product Model:</b>	RC08
<b>Test By:</b>	Mike	<b>Test mode:</b>	2.4G Tx mode
<b>Test Frequency:</b>	30 MHz ~ 1 GHz	<b>Polarization:</b>	Horizontal
<b>Test Voltage:</b>	DC 3V	<b>Environment:</b>	Temp: 24°C Huni: 57%



Freq MHz	ReadAntenna Level Factor		Cable Loss Factor		Preamp Level dB	Limit Level dBuV/m	Over Line Limit dBuV/m	Over Line Limit dB	Remark
	MHz	dBuV	dB/m	dB					
1	49.533	34.50	12.12	1.26	29.82	18.06	40.00	-21.94	QP
2	113.714	33.73	11.38	2.10	29.43	17.78	43.50	-25.72	QP
3	205.675	34.94	10.84	2.86	28.79	19.85	43.50	-23.65	QP
4	326.740	35.99	14.17	3.02	28.51	24.67	46.00	-21.33	QP
5	750.108	33.57	20.60	4.36	28.48	30.05	46.00	-15.95	QP
6	989.536	33.06	22.77	4.41	27.49	32.75	54.00	-21.25	QP

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

## Above 1GHz


Test channel: Lowest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4814.00	55.10	31.62	6.81	41.82	51.71	74.00	-22.29	Vertical
4814.00	58.54	31.62	6.81	41.82	55.15	74.00	-18.85	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4814.00	45.66	31.62	6.81	41.82	42.27	54.00	-11.73	Vertical
4814.00	52.08	31.62	6.81	41.82	48.69	54.00	-5.31	Horizontal
Test channel: Middle channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4884.00	55.82	31.72	6.86	41.84	52.56	74.00	-21.44	Vertical
4884.00	57.31	31.72	6.86	41.84	54.05	74.00	-19.95	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4884.00	50.65	31.72	6.86	41.84	47.39	54.00	-6.61	Vertical
4884.00	52.51	31.72	6.86	41.84	49.25	54.00	-4.75	Horizontal
Test channel: Highest channel								
Detector: Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4954.00	53.23	31.84	6.91	41.87	50.11	74.00	-23.89	Vertical
4954.00	53.00	31.84	6.91	41.87	49.88	74.00	-24.12	Horizontal
Detector: Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4954.00	41.90	31.84	6.91	41.87	38.78	54.00	-15.22	Vertical
4954.00	45.98	31.84	6.91	41.87	42.86	54.00	-11.14	Horizontal

## Remark:


- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

### 6.2.3 Band Edge

#### Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.205 and 15.209										
Test Method:	ANSI C63.10: 2013										
Test Frequency Range:	2.3GHz to 2.5GHz										
Test Distance:	3m										
Receiver setup:	Frequency	Detector	RBW	VBW	Remark						
	Above 1GHz	Peak	1MHz	3MHz	Peak Value						
Limit:	Frequency	Limit (dBuV/m @3m)		Remark							
	Above 1GHz	54.00		Average Value							
Test Procedure:		<ol style="list-style-type: none"> <li>The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>									
Test setup:											
Test Instruments:	Refer to section 5.7 for details										
Test mode:	Refer to section 5.3 for details										
Test results:	Passed										

Product Name:	Remote Control	Product Model:	RC08
Test By:	Mike	Test mode:	2.4G-Tx mode
Test Channel:	Lowest channel	Polarization:	Vertical
Test Voltage:	DC 3V	Environment:	Temp: 24°C Huni: 57%




Freq MHz	Read Level dBuV	Antenna Factor dB/m	Cable Loss dB	Preamp Factor dB	Limit Line dBuV/m	Over Line dBuV/m	Over Line dB	Over Line Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB	
1 2400.000	17.15	27.11	4.70	0.00	48.96	74.00	-25.04	Peak
2 2400.000	10.86	27.11	4.70	0.00	42.67	54.00	-11.33	Average

## Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	Remote Control	Product Model:	RC08
Test By:	Mike	Test mode:	2.4G-Tx mode
Test Channel:	Lowest channel	Polarization:	Horizontal
Test Voltage:	DC 3V	Environment:	Temp: 24°C Huni: 57%




Freq	Read Antenna		Cable		Preamp Level	Limit Line	Over Line	Over Limit	Remark
	Level	Antenna Factor	Loss	Factor					
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	dB	
1	2400.000	17.80	27.11	4.70	0.00	49.61	74.00	-24.39	Peak
2	2400.000	11.27	27.11	4.70	0.00	43.08	54.00	-10.92	Average

## Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

<b>Product Name:</b>	Remote Control	<b>Product Model:</b>	RC08
<b>Test By:</b>	Mike	<b>Test mode:</b>	2.4G-Tx mode
<b>Test Channel:</b>	Highest channel	<b>Polarization:</b>	Vertical
<b>Test Voltage:</b>	DC 3V	<b>Environment:</b>	Temp: 24°C Huni: 57%




Freq MHz	Read		Antenna		Cable		Preamp		Limit Line dBuV/m	Over Line dB	Over Limit dB	Remark
	Freq MHz	Read Level dBuV	Antenna Level Factor	Antenna Loss dB/m	Cable Loss Factor	Preamp Level dB	Preamp Level dBuV/m	Limit Line dBuV/m				
1 2483.500	22.37	27.36	4.81	0.00	54.54	74.00	-19.46	Peak				
2 2483.500	8.69	27.36	4.81	0.00	40.86	54.00	-13.14	Average				

## Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

<b>Product Name:</b>	Remote Control	<b>Product Model:</b>	RC08
<b>Test By:</b>	Mike	<b>Test mode:</b>	2.4G-Tx mode
<b>Test Channel:</b>	Highest channel	<b>Polarization:</b>	Horizontal
<b>Test Voltage:</b>	DC 3V	<b>Environment:</b>	Temp: 24°C Huni: 57%




Freq MHz	Read Level dBuV	Antenna Factor dB/m	Cable Loss Factor dB	Preamp Level dB	Limit Line dBuV/m	Over Line dBuV/m	Over Line dB	Remark
1 2483.500	19.63	27.35	4.81	0.00	51.79	74.00	-22.21	Peak
2 2483.500	8.69	27.35	4.81	0.00	40.85	54.00	-13.15	Average

## Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

### 6.3 20dB Occupy Bandwidth

Test Requirement:	FCC Part 15 C Section 15.215
Test Method:	ANSI C63.10:2013
Receiver setup:	RBW=30 kHz, VBW=100 kHz, detector=Peak
Limit:	N/A
Test setup:	
Test Instruments:	Refer to section 5.7 for details
Test mode:	Transmitting mode
Test results:	Pass

#### Measurement Data:

20dB Occupy Bandwidth (MHz)		
Lowest channel	Middle channel	Highest
1.56	1.56	1.56

Test plot as follows:

