

裁切线 _____ 压痕线 _____ V槽线 _____ 半穿刀 _____	辅助线 _____ 牙 刀 _____ 画 线 _____
☒ 外表面视图	☐ 内表面视图

版本	变更描述	变更日期	结构工程师	设计者
A01	初始发行	2023/06/28	\	邓始景

UGREEN

HiTune Max5

Hybrid Active Noise-Cancelling Headphones

Model: HP202

Package Contents

1x HiTune Max5 Hybrid Active Noise-Cancelling Headphones
1x Carrying Case
1x 3.5mm Audio Cable
1x USB-C to USB-A Cable
1x User Manual

Product Overview

HiTune Max5 Hybrid Active Noise-Cancelling Headphones
1x HiTune Max5 Hybrid Active Noise-Cancelling Headphones
1x Carrying Case
1x 3.5mm Audio Cable
1x USB-C to USB-A Cable
1x User Manual

Specifications

Model: HP202
Frequency Response: 20Hz-20kHz
Impedance: 32Ω
Sensitivity: 105dB
Driver: 40mm
Weight: 250g
Charging Time: 2 hours
Battery Life: 30 hours

Wear and Adjust

Adjust the headband to properly fit your head, and make it comfortable with your head's shape.

Charging

Connect the USB-C cable to the charging port on the back of the headphones.

Powering On/Off

Press and hold the power button to turn the headphones on.

Pairing

Press and hold the power button to enter pairing mode.

Force Pairing

Press and hold the power button for 10 seconds to force pair the headphones.

[illegible]

备注:

1. 材质： 128g 哑粉
2. 印刷颜色： 四色+1专  PANTONE3415C
3. 展开尺寸： 840x240mm
4. 成型尺寸： 105x120mm
5. 成型工艺： 风琴折
6. 尺寸公差： +1mm
7. 印刷偏位： <=0.5mm
8. 套印偏位： <=0.35mm
9. 所有成品及辅料符合欧盟包装指令94/62/EC，美国TPCH，欧盟REACH
10. 印刷油墨（成品）矿物油含量需满足MOSH(C15-C36)小于0.1%；MOAH（1-7芳香环）小于0.1%；MOAH（3-7芳香环）小于0.0001%

SELECT			V							SCALE 1:1 SHEET 1/1 UNIT mm 	UGREEN 绿联 深圳市绿联科技股份有限公司		
Dim TOL.	A	B	C	EPS	EPE	EPP	BAG	CTN	LABEL		物料名称: 说明书		
0~6	0.05	0.05	0.10						0.20				
6~30	0.10	0.15	0.20	0.50	0.50	0.50	3.00		0.20				
30~120	0.15	0.20	0.30	0.50	0.50	0.50	5.00	1.00	0.25				
120~300	0.20	0.30	0.40	1.00	1.00	1.00	10.00	1.00	0.30				
300~450	0.25	0.40	0.50	2.00	2.00	2.00	15.00	2.00	0.50				
450~600	0.30	0.50	0.60	3.00	3.00	3.00	20.00	3.00	0.80				
DRAFT TOLERANCE			± 0.20"		CRITICAL DIM. MARK				*	产品名称 HiTune Max5 头戴式主动降噪蓝牙耳机			
										项目工程师 高玄英			
										核准 韦杰威			