



中国认可
国际互认
检测
TESTING
CNAS L6791

TEST REPORT

Applicant: Ugreen Group Limited
Address: URGEEN Building, Longcheng Industrial Park,
Longguanxi Road, Longhua, ShenZhen, China
Equipment Type: UGREEN Dots
Model Name: WS220
Brand Name: **UGREEN**
FCC ID: 2AQI5-WS220
Test Standard: 47 CFR Part 15 Subpart C
(refer to section 3.1)
Sample Arrival Date: Jun. 26, 2025
Test Date: Jul. 08, 2025 - Aug. 14, 2025
Date of Issue: Sep. 02, 2025

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Julie Zhu**Checked by:** Ye Hongji**Approved by:** Sunny Zou
(Technical Director)

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Sep. 02, 2025</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Test Location	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	Factory Information	5
2.4	General Description for Equipment under Test (EUT)	5
2.5	Technical Information	6
3	SUMMARY OF TEST RESULTS	8
3.1	Test Standards	8
3.2	Test Verdict	8
4	GENERAL TEST CONFIGURATIONS	9
4.1	Test Environments	9
4.2	Test Equipment List	9
4.3	Test Software List	9
4.4	Measurement Uncertainty	10
4.5	Description of Test Setup	10
4.6	Measurement Results Explanation Example	13
5	TEST ITEMS	14
5.1	Antenna Requirements	14
5.2	Frequency Hopping Systems	15
5.3	Number of Hopping Frequencies	17
5.4	Peak Output Power	19

5.5	Occupied Bandwidth	22
5.6	Carrier Frequency Separation	27
5.7	Time of Occupancy (Dwell time)	29
5.8	Conducted Spurious Emission & Authorized-band band-edge	33
5.9	Conducted Emission	41
5.10	Radiated Spurious Emission	44
5.11	Band Edge (Restricted-band band-edge).....	54
ANNEX A	TEST SETUP PHOTOS	56
1	Radiated Test Photo.....	56
2	Conducted Test Photo.....	58
3	Conducted Emission	59
ANNEX B	EUT EXTERNAL PHOTOS	60
ANNEX C	EUT INTERNAL PHOTOS	65

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☒ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Ugreen Group Limited
Address	UGREEN Building, Longcheng Industrial Park Longguanxi Road, Longhua, ShenZhen, China

2.2 Manufacturer Information

Manufacturer	Ugreen Group Limited
Address	UGREEN Building, Longcheng Industrial Park Longguanxi Road, Longhua, ShenZhen, China

2.3 Factory Information

Factory	Shenzhen Originality Technology Co., Ltd.
Address	501, Building 3, No. 59, Haoye Road, Zhancheng Community, Fuhai Street, Baoan District, Shenzhen

2.4 General Description for Equipment under Test (EUT)

EUT Name	UGREEN Dots
Model Name Under Test	WS220
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

Remark:

- Product Number (P/N) code in the below table, for marketing purpose, will be marked on the marking plate.

75627	75627EU	75627UK	75627US	75627JP	75627CN	75627KC	75627A	75627B	75627C	75627P	75627X	75627U	KC-75627
75628	75628EU	75628UK	75628US	75628JP	75628CN	75628KC	75628A	75628B	75628C	75628P	75628X	75628U	KC-75628

2.5 Technical Information

Network and Wireless connectivity	Bluetooth (BR+EDR+BLE)
-----------------------------------	------------------------

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	FHSS
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Product Type	☐ Mobile ☒ Portable ☐ Fix Location
Transfer Rate	DH5: 1 Mbps 2DH5: 2 Mbps 3DH5: 3 Mbps
Frequency Range	The frequency range used is 2400 MHz to 2483.5 MHz.
Number of Channel	79 (at intervals of 1 MHz)
Tested Channel	0 (2402 MHz), 39 (2441 MHz), 78 (2480 MHz)
Antenna Type	Ceramic Antenna
Antenna Gain	1.89 dBi
Antenna Impedance	50 Ω
Antenna System (MIMO Smart Antenna)	N/A

All channel was listed on the following table:

Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)
0	2402	21	2423	42	2444	63	2465
1	2403	22	2424	43	2445	64	2466
2	2404	23	2425	44	2446	65	2467
3	2405	24	2426	45	2447	66	2468
4	2406	25	2427	46	2448	67	2469
5	2407	26	2428	47	2449	68	2470
6	2408	27	2429	48	2450	69	2471
7	2409	28	2430	49	2451	70	2472
8	2410	29	2431	50	2452	71	2473
9	2411	30	2432	51	2453	72	2474
10	2412	31	2433	52	2454	73	2475
11	2413	32	2434	53	2455	74	2476
12	2414	33	2435	54	2456	75	2477
13	2415	34	2436	55	2457	76	2478
14	2416	35	2437	56	2458	77	2479
15	2417	36	2438	57	2459	78	2480
16	2418	37	2439	58	2460	-	-
17	2419	38	2440	59	2461	-	-
18	2420	39	2441	60	2462	-	-
19	2421	40	2442	61	2463	-	-
20	2422	41	2443	62	2464	-	-

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Intentional radiators of radio frequency equipment
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
3 ☆	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

3.2 Test Verdict

No.	Description	FCC Part No.	Channel	Test Result	Verdict	Remark
1	Antenna Requirement	15.203	N/A	--	Pass	Note ¹
2	Number of Hopping Frequencies	15.247(a)	Hopping Mode	5.3.4	Pass	Note ²
3	Peak Output Power	15.247(b)	Low/Middle/High	5.4.4	Pass	--
4	Occupied Bandwidth	15.247(a)	Low/Middle/High	5.5.4	Pass	--
5	Carrier Frequency Separation	15.247(a)	Hopping Mode	5.6.4	Pass	Note ²
6	Time of Occupancy (Dwell time)	15.247(a)	Hopping Mode	5.7.4	Pass	Note ²
7	Conducted Spurious Emission & Authorized-band band-edge	15.247(d)	Hopping Mode; Low/Middle/High	5.8.4	Pass	Note ²
8	Conducted Emission	15.207	Low/Middle/High	5.9.4	Pass	Note ²
9	Radiated Spurious Emission	15.209 15.247(d)	Low/Middle/High	5.10.4	Pass	Note ²
10	Band Edge(Restricted-band band-edge)	15.209 15.247(d)	Low/High	5.11.4	Pass	Note ²

Note ¹: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note ²: $\pi/4$ -DQPSK is the EDR 2M rate mode, 8-DPSK is the EDR 3M rate mode. The consistency of test results in $\pi/4$ -DQPSK and 8-DPSK is very high. So we chose 8-DPSK as a typical representative to appear on the report. Another we will show all the modes on the RF output power test item.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	39% to 65%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+21.7°C to +26.1°C
Working Voltage of the EUT	NV (Normal Voltage)	3.7 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	KEYSIGHT	N9020A	MY46471071	2025.06.16	2026.06.15
Spectrum Analyzer	KEYSIGHT	N9020A	MY52510065	2025.06.16	2026.06.15
Test Antenna-Horn	SCHWARZBECK	BBHA 9120D	01631	2025.02.22	2028.02.21
Test Antenna-Horn	A-INFO	LB-180400KF	J211060273	2024.06.15	2027.06.14
Anechoic Chamber	RAINFORD	9m*6m*6m	144	2022.02.19	2025.09.03
Amplifier	COM-MV	LSCX_LNA1-12G-01	180602	2025.06.17	2026.06.16
Amplifier	COM-MV	XKu_LNA7-18G-01	180601	2025.06.17	2026.06.16
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2025.06.16	2026.06.15
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9168	9168-01162	2023.08.04	2026.08.03
Test Antenna-Loop	SCHWARZBECK	FMZB 1519	1519-037	2024.01.23	2027.01.22
Amplifier	COM-MV	ZT30-1000M	B2018054558	2024.11.28	2025.11.27
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	130	2024.07.13	2027.07.12
EMI Receiver	KEYSIGHT	N9010B	MY57110309	2025.06.16	2026.06.15
LISN	SCHWARZBECK	NSLK 8127	8127-687	2025.04.29	2026.04.28
Shielded Enclosure	YiHeng Electronic Co., Ltd	3.5m*3.1m*2.8m	112	2025.02.14	2028.02.13

4.3 Test Software List

Description	Manufacturer	Software Version	Serial No.	Applicable test Setup
BL410R	BALUN	V2.1.1.488	N/A	The section 4.5.1
BL410E	BALUN	V22.930	N/A	The section 4.5.2&4.5.3&4.5.4&4.5.5

4.4 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Parameters	Uncertainty
Occupied Channel Bandwidth	2.8%
RF output power, conducted	1.28 dB
Power Spectral Density, conducted	1.30 dB
Unwanted Emissions, conducted	1.84 dB
All emissions, radiated	5.36 dB
Temperature	0.8°C
Humidity	4%


4.5 Description of Test Setup

4.5.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.5.2 For AC Power Supply Port Test




(Diagram 2)

4.5.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.5.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.5.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.6 Measurement Results Explanation Example

4.6.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Frequency Hopping Systems

5.2.1 Relevant Standards

FCC §15.247(a) (1) (i) (ii) (iii) (iv); FCC §15.247(g); FCC §15.247(h)

Describe how the hopping sequence is generated. Provide an example of the hopping sequence channels, to demonstrate that the sequence meets the requirement specified in the definition of an FHSS system. Per the definition in Section 2.1(c), the hop set shall appear as random in the near term, shall appear as evenly distributed in the long term, and sequential hops shall be randomly distributed in both direction and magnitude of change.

Describe how each individual EUT meets the requirement that each of its hopping channels is used equally on average (e.g., that each new transmission event begins on the next channel in the hopping sequence after the final channel used in the previous transmission event).

Describe how the associated receiver(s) complies with the requirement that the input bandwidth (either RF or IF) matches the bandwidth of the transmitted signal.

Describe how the associated receiver(s) has the ability to shift frequencies in synchronization with the transmitted signals.


For short burst systems, describe how the EUT complies with the requirement that it be designed to be capable of operating as a true frequency hopping system. Specifically, the device shall comply with the equal frequency use and pseudorandom hopping sequence requirement when transmitting in short bursts, and shall be designed to comply when presented with continuous data (or information) stream.

Describe how the EUT complies with the requirement that it not have the ability to be coordinated with other FHSS systems in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

5.2.2 Description of the systems

1. According to the preset procedure of the whole network, all the stations in the automatic control network synchronously change the frequency multiple times within one second, and temporarily stay on each frequency hopping channel. Periodic synchronization signaling is sent from the primary station, instructing all slaves to simultaneously change the operating frequency, then the hopping sequence is generated.
2. The hop set shall appear as random in the near term, shall appear as evenly distributed in the long term, and sequential hops shall be randomly distributed in both direction and magnitude of change.

Reference Documents



3. Channels are classified into two categories, used and unused, where used channels are part of the hopping sequence and unused channels are replaced in the hopping sequence by used channels in a pseudo-random way. Make each individual EUT meets the requirement that each of its hopping channels is used equally on average.
4. The input bandwidth and transmitted bandwidth are both 1MHz, the associated receiver(s) complies with the requirement that the input bandwidth matches the bandwidth of the transmitted signal.
5. Connected devices communicate on the same physical channel by synchronizing with a common clock and hopping sequence.
6. EUT isn't short burst systems.
7. EUT can't have the ability to be coordinated with other FHSS systems in an effort.

5.3 Number of Hopping Frequencies

5.3.1 Limit

FCC §15.247(a) (1) (iii)

Frequency hopping systems operating in the 2400 MHz to 2483.5 MHz bands shall use at least 15 hopping frequencies.

5.3.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.3.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = The frequency band of operation

RBW = To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize


5.3.4 Test Result

Test Data


Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Verdict
GFSK	2400 - 2483.5	79	15	Pass
8-DPSK	2400 - 2483.5	79	15	Pass

Test Plots


GFSK 2.4 GHz ~ 2.4415 GHz




GFSK 2.4415 GHz ~ 2.4835 GHz



8-DPSK 2.4 GHz ~ 2.4415 GHz



8-DPSK 2.4415 GHz ~ 2.4835 GHz



5.4 Peak Output Power

5.4.1 Test Limit

FCC § 15.247(b)

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

5.4.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.4.3 Test Procedure

The Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.


5.4.4 Test Result

Peak Power Test Data


Channel	Measured Output Peak Power						Limit		Verdict
	GFSK		π/4-DQPSK		8-DPSK		dBm	mW	
	dBm	mW	dBm	mW	dBm	mW			
Low	1.96	1.57	0.25	1.06	0.80	1.20	21	125	Pass
Middle	1.44	1.39	0.05	1.01	0.49	1.12			Pass
High	0.84	1.21	-0.45	0.90	0.02	1.00			Pass

Test Plots


GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL



$\pi/4$ -DQPSK LOW CHANNEL



$\pi/4$ -DQPSK MIDDLE CHANNEL




$\pi/4$ -DQPSK HIGH CHANNEL



8-DPSK LOW CHANNEL



8-DPSK MIDDLE CHANNEL



8-DPSK HIGH CHANNEL



5.5 Occupied Bandwidth

5.5.1 Limit

FCC §15.247(a)

Measurement of the 20dB bandwidth of the modulated signal.

5.5.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.5.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = in the range of 1% to 5% of the OBW

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate, Allow the trace to stabilize.

5.5.4 Test Result

Test Data

GFSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	0.960200	0.865850
Middle	0.960200	0.868010
High	0.960200	0.869220
$\pi/4$ -DQPSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.297400	1.172200
Middle	1.297400	1.173700
High	1.297400	1.173100
8-DPSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.290000	1.174900
Middle	1.290000	1.175900
High	1.290000	1.176200

Test Plots

20 dB Bandwidth

GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL

 $\pi/4$ -DQPSK LOW CHANNEL $\pi/4$ -DQPSK MIDDLE CHANNEL

$\pi/4$ -DQPSK HIGH CHANNEL



8-DPSK LOW CHANNEL



8-DPSK MIDDLE CHANNEL



8-DPSK HIGH CHANNEL




99% Bandwidth


GFSK LOW CHANNEL




GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL

 $\pi/4$ -DQPSK MIDDLE CHANNEL $\pi/4$ -DQPSK LOW CHANNEL

$\pi/4$ -DQPSK HIGH CHANNEL



8-DPSK LOW CHANNEL



8-DPSK MIDDLE CHANNEL



8-DPSK HIGH CHANNEL



5.6 Carrier Frequency Separation

5.6.1 Limit

FCC §15.247(a)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 2/3 of the 20 dB bandwidth of the hopping channel, whichever is greater.

5.6.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.6.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) $\geq 1\%$ of the span

Video (or Average) Bandwidth (VBW) $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.


5.6.4 Test Result

Test Data


Mode	Frequency separation (MHz)	2/3 of the 20 dB Bandwidth (MHz)	Verdict
GFSK	1.000	0.640	Pass
8-DPSK	1.000	0.860	Pass

Test Plots

GFSK



8-DPSK



5.7 Time of Occupancy (Dwell time)

5.7.1 Limit

FCC §15.247(a)

Frequency hopping systems in the 2400 MHz - 2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

5.7.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.7.3 Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

Span: Zero span, centered on a hopping channel

RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1/T$, where T is the expected dwell time per channel

Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel

Detector function: Peak

Trace: Max hold

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

The average time of occupancy on any channel within the Period can be calculated with formulas:

For GFSK and 8-DPSK:

For DH1 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 2) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For DH3 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 4) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For DH5 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 6) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For AFH Mode:

For DH1 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (800 / 2) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For DH3 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (800 / 4) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For DH5 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (800 / 6) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.


5.7.4 Test Result

Test Data


GFSK				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.38240	122.368	0.4	Pass
DH 3	1.64100	262.560	0.4	Pass
DH 5	2.88800	308.053	0.4	Pass
8-DPSK				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
3DH 1	0.39200	125.440	0.4	Pass
3DH 3	1.64300	262.880	0.4	Pass
3DH 5	2.88800	308.053	0.4	Pass
AFH Mode				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.38080	60.928	0.4	Pass
DH 3	1.63400	130.720	0.4	Pass
DH 5	2.87600	153.387	0.4	Pass

Test Plots


GFSK DH1




GFSK DH3




GFSK DH5




8-DPSK 3DH1




8-DPSK 3DH3




8-DPSK 3DH5




AFH Mode DH1



AFH Mode DH3



AFH Mode DH5



5.8 Conducted Spurious Emission & Authorized-band band-edge

5.8.1 Limit

FCC §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.8.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.8.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW = 300 kHz

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize


5.8.4 Test Result

Test Data


GFSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-40.09	1.73	-18.27	Pass
Middle	-40.28	1.22	-18.78	Pass
High	-40.38	0.54	-19.46	Pass
8-DPSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-40.60	-1.00	-21.00	Pass
Middle	-39.73	-1.10	-21.10	Pass
High	-39.77	-1.62	-21.62	Pass
Hopping Mode				
Mode	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
GFSK	-40.06	1.57	-18.43	Pass
8-DPSK	-36.98	1.28	-18.72	Pass

Test Plots


GFSK LOW CHANNEL, CARRIER LEVEL




GFSK LOW CHANNEL, BAND EDGE




GFSK LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




GFSK MIDDLE CHANNEL, CARRIER LEVEL




GFSK MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK MIDDLE CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



GFSK HIGH CHANNEL, CARRIER LEVEL




GFSK HIGH CHANNEL, BAND EDGE




GFSK HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK HIGH CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



8-DPSK LOW CHANNEL, CARRIER LEVEL



8-DPSK LOW CHANNEL, BAND EDGE




8-DPSK LOW CHANNEL, SPURIOUS

30 MHz ~ 3 GHz




8-DPSK LOW CHANNEL, SPURIOUS


3 GHz ~ 25 GHz




8-DPSK MIDDLE CHANNEL, CARRIER LEVEL




8-DPSK MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




8-DPSK MIDDLE CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



8-DPSK HIGH CHANNEL, CARRIER LEVEL




8-DPSK HIGH CHANNEL, BAND EDGE




8-DPSK HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




8-DPSK HIGH CHANNEL, SPURIOUS 3 GHz ~ 25 GHz






GFSK HOPPING, CARRIER LEVEL




GFSK HOPPING BAND EDGE (LOW)




GFSK HOPPING BAND EDGE (HIGH)

GFSK Hopping Mode, SPURIOUS
30 MHz ~ 3 GHzGFSK Hopping Mode, SPURIOUS
3GHz ~ 25 GHz




8-DPSK HOPPING, CARRIER LEVEL



8-DPSK Hopping BAND EDGE (LOW)



8-DPSK Hopping BAND EDGE (HIGH)

8-DPSK Hopping Mode, SPURIOUS
30 MHz ~ 3 GHz8-DPSK Hopping Mode, SPURIOUS
3GHz ~ 25 GHz

5.9 Conducted Emission

5.9.1 Limit

FCC §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.9.2 Test Setup

See section 4.5.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX A.

5.9.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.9.4 Test Result

Note ¹: The EUT was tested in Link mode and the charging.


Note ²: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Note ³: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)

Test Data and Plots

PHASE L


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.160	41.16	9.85	65.46	24.30	Peak	L	Pass
1**	0.160	27.86	9.85	55.46	27.60	AV	L	Pass
2	0.344	38.47	10.70	59.11	20.64	Peak	L	Pass
2**	0.344	25.73	10.70	49.11	23.38	AV	L	Pass
3	0.704	36.80	10.67	56.00	19.20	Peak	L	Pass
3**	0.704	26.16	10.67	46.00	19.84	AV	L	Pass
4	2.332	35.60	10.14	56.00	20.40	Peak	L	Pass
4**	2.332	23.99	10.14	46.00	22.01	AV	L	Pass
5	6.930	36.76	10.34	60.00	23.24	Peak	L	Pass
5**	6.930	23.61	10.34	50.00	26.39	AV	L	Pass
6	19.992	37.27	11.30	60.00	22.73	Peak	L	Pass
6**	19.992	24.94	11.30	50.00	25.06	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.176	40.79	9.85	64.67	23.88	Peak	N	Pass
1**	0.176	27.18	9.85	54.67	27.49	AV	N	Pass
2	0.294	39.33	9.82	60.41	21.08	Peak	N	Pass
2**	0.294	25.68	9.82	50.41	24.73	AV	N	Pass
3	1.390	35.69	9.84	56.00	20.31	Peak	N	Pass
3**	1.390	23.66	9.84	46.00	22.34	AV	N	Pass
4	4.290	36.24	10.45	56.00	19.76	Peak	N	Pass
4**	4.290	24.58	10.45	46.00	21.42	AV	N	Pass
5	12.380	36.56	10.88	60.00	23.44	Peak	N	Pass
5**	12.380	25.60	10.88	50.00	24.40	AV	N	Pass
6	24.508	36.91	10.97	60.00	23.09	Peak	N	Pass
6**	24.508	26.68	10.97	50.00	23.32	AV	N	Pass

5.10 Radiated Spurious Emission

5.10.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength (dBμV/m) = 20*log[Field Strength (μV/m)].
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.10.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.10.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.10.4 Test Result

Note ¹: The symbol of “--” in the table which means not application.

Note ²: For the test data above 1 GHz, according the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note ³: The EUT was tested in Link mode and the charging.


Note ⁴: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV/m) + Factor (dB)

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Test Data and Plots

30 MHz to 1 GHz, ANT H


10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	33.637	15.79	-26.96	29.5	13.71	Peak	0.00	200	Horizontal	Pass
2	55.214	14.17	-27.15	29.5	15.33	Peak	78.00	200	Horizontal	Pass
3	150.735	16.59	-26.22	33.0	16.41	Peak	214.00	200	Horizontal	Pass
4	303.957	30.90	-25.41	35.5	4.60	Peak	10.00	200	Horizontal	Pass
5	333.049	28.84	-24.82	35.5	6.66	Peak	358.00	200	Horizontal	Pass
6	949.088	30.12	-9.64	35.5	5.38	Peak	217.00	200	Horizontal	Pass

30 MHz to 1 GHz, ANT V

10m RE Test Case_FCC Certification_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	54.971	15.73	-27.15	29.5	13.77	Peak	7.00	200	Vertical	Pass
2	118.005	15.33	-28.29	33.0	17.67	Peak	319.00	100	Vertical	Pass
3	132.067	22.08	-27.19	33.0	10.92	Peak	0.00	200	Vertical	Pass
4	145.644	20.68	-26.36	33.0	12.32	Peak	62.00	100	Vertical	Pass
5	302.744	18.68	-25.41	35.5	16.82	Peak	192.00	100	Vertical	Pass
6	843.869	28.45	-11.81	35.5	7.05	Peak	273.00	100	Vertical	Pass

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 18GHz-25GHz is noise only, do not show on the report.

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1459.900	40.75	74.0	33.25	Peak	80.00	200	Horizontal	Pass
1**	1459.900	31.16	54.0	22.84	AV	80.00	200	Horizontal	Pass
2	2402.200	94.11	74.0	-20.11	Peak	63.00	200	Horizontal	N/A
2**	2402.200	93.55	54.0	-39.55	AV	63.00	200	Horizontal	N/A
3	4980.600	48.72	74.0	25.28	Peak	50.00	150	Horizontal	Pass
3**	4980.600	40.11	54.0	13.89	AV	50.00	150	Horizontal	Pass
4	6985.200	51.95	74.0	22.05	Peak	270.00	300	Horizontal	Pass
4**	6985.200	43.20	54.0	10.80	AV	270.00	300	Horizontal	Pass
5	12464.513	47.30	74.0	26.70	Peak	94.00	300	Horizontal	Pass
5**	12464.513	38.79	54.0	15.21	AV	94.00	300	Horizontal	Pass
6	17395.988	50.56	74.0	23.44	Peak	360.00	200	Horizontal	Pass
6**	17395.988	42.32	54.0	11.68	AV	360.00	200	Horizontal	Pass

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1332.500	46.53	74.0	27.47	Peak	112.00	400	Vertical	Pass
1**	1332.500	34.09	54.0	19.91	AV	112.00	400	Vertical	Pass
2	2402.100	89.69	74.0	-15.69	Peak	72.00	100	Vertical	N/A
2**	2402.100	89.36	54.0	-35.36	AV	72.00	100	Vertical	N/A
3	5315.400	52.67	74.0	21.33	Peak	96.00	100	Vertical	Pass
3**	5315.400	43.31	54.0	10.69	AV	96.00	100	Vertical	Pass
4	6993.200	52.43	74.0	21.57	Peak	360.00	150	Vertical	Pass
4**	6993.200	43.18	54.0	10.82	AV	360.00	150	Vertical	Pass
5	12894.375	48.07	74.0	25.93	Peak	120.00	400	Vertical	Pass
5**	12894.375	37.49	54.0	16.51	AV	120.00	400	Vertical	Pass
6	17386.275	51.47	74.0	22.53	Peak	0.00	100	Vertical	Pass
6**	17386.275	42.27	54.0	11.73	AV	0.00	100	Vertical	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1162.300	43.39	74.0	30.61	Peak	164.00	400	Horizontal	Pass
1**	1162.300	30.64	54.0	23.36	AV	164.00	400	Horizontal	Pass
2	2441.200	93.41	74.0	-19.41	Peak	53.00	200	Horizontal	N/A
2**	2441.200	93.16	54.0	-39.16	AV	53.00	200	Horizontal	N/A
3	4931.800	49.02	74.0	24.98	Peak	15.00	200	Horizontal	Pass
3**	4931.800	40.16	54.0	13.84	AV	15.00	200	Horizontal	Pass
4	6988.000	51.96	74.0	22.04	Peak	360.00	300	Horizontal	Pass
4**	6988.000	43.50	54.0	10.50	AV	360.00	300	Horizontal	Pass
5	11912.800	47.67	74.0	26.33	Peak	99.00	300	Horizontal	Pass
5**	11912.800	38.36	54.0	15.64	AV	99.00	300	Horizontal	Pass
6	17379.187	51.69	74.0	22.31	Peak	243.00	400	Horizontal	Pass
6**	17379.187	42.64	54.0	11.36	AV	243.00	400	Horizontal	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1330.000	45.98	74.0	28.02	Peak	102.00	200	Vertical	Pass
1**	1330.000	34.47	54.0	19.53	AV	102.00	200	Vertical	Pass
2	2441.100	92.80	74.0	-18.80	Peak	110.00	200	Vertical	N/A
2**	2441.100	92.55	54.0	-38.55	AV	110.00	200	Vertical	N/A
3	4965.800	48.83	74.0	25.17	Peak	106.00	150	Vertical	Pass
3**	4965.800	40.34	54.0	13.66	AV	106.00	150	Vertical	Pass
4	6988.800	52.49	74.0	21.51	Peak	185.00	100	Vertical	Pass
4**	6988.800	43.94	54.0	10.06	AV	185.00	100	Vertical	Pass
5	9764.312	45.20	74.0	28.80	Peak	291.00	150	Vertical	Pass
5**	9764.312	41.16	54.0	12.84	AV	291.00	150	Vertical	Pass
6	16972.575	50.62	74.0	23.38	Peak	26.00	100	Vertical	Pass
6**	16972.575	41.52	54.0	12.48	AV	26.00	100	Vertical	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1586.400	40.50	74.0	33.50	Peak	360.00	100	Horizontal	Pass
1**	1586.400	31.55	54.0	22.45	AV	360.00	100	Horizontal	Pass
2	2480.200	95.08	74.0	-21.08	Peak	329.00	200	Horizontal	N/A
2**	2480.200	94.72	54.0	-40.72	AV	329.00	200	Horizontal	N/A
3	4960.000	48.99	74.0	25.01	Peak	76.00	100	Horizontal	Pass
3**	4960.000	41.00	54.0	13.00	AV	76.00	100	Horizontal	Pass
4	7440.450	45.84	74.0	28.16	Peak	339.00	150	Horizontal	Pass
4**	7440.450	39.72	54.0	14.28	AV	339.00	150	Horizontal	Pass
5	12582.674	47.18	74.0	26.82	Peak	0.00	200	Horizontal	Pass
5**	12582.674	38.20	54.0	15.80	AV	0.00	200	Horizontal	Pass
6	17391.526	51.03	74.0	22.97	Peak	23.00	200	Horizontal	Pass
6**	17391.526	42.15	54.0	11.85	AV	23.00	200	Horizontal	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1329.900	46.63	74.0	27.37	Peak	102.00	200	Vertical	Pass
1**	1329.900	32.96	54.0	21.04	AV	102.00	200	Vertical	Pass
2	2480.100	94.96	74.0	-20.96	Peak	110.00	100	Vertical	N/A
2**	2480.100	94.75	54.0	-40.75	AV	110.00	100	Vertical	N/A
3	4986.200	49.22	74.0	24.78	Peak	218.00	150	Vertical	Pass
3**	4986.200	40.35	54.0	13.65	AV	218.00	150	Vertical	Pass
4	6982.000	52.15	74.0	21.85	Peak	313.00	400	Vertical	Pass
4**	6982.000	44.50	54.0	9.50	AV	313.00	400	Vertical	Pass
5	12732.750	47.36	74.0	26.64	Peak	146.00	200	Vertical	Pass
5**	12732.750	37.48	54.0	16.52	AV	146.00	200	Vertical	Pass
6	17382.339	50.98	74.0	23.02	Peak	132.00	300	Vertical	Pass
6**	17382.339	41.08	54.0	12.92	AV	132.00	300	Vertical	Pass

8-DPSK LOW CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1332.400	41.21	74.0	32.79	Peak	0.00	200	Horizontal	Pass
1**	1332.400	31.30	54.0	22.70	AV	0.00	200	Horizontal	Pass
2	2402.000	96.69	74.0	-22.69	Peak	156.00	200	Horizontal	N/A
2**	2402.000	94.07	54.0	-40.07	AV	156.00	200	Horizontal	N/A
3	4985.400	49.23	74.0	24.77	Peak	237.00	100	Horizontal	Pass
3**	4985.400	39.86	54.0	14.14	AV	237.00	100	Horizontal	Pass
4	6985.400	52.81	74.0	21.19	Peak	287.00	200	Horizontal	Pass
4**	6985.400	43.42	54.0	10.58	AV	287.00	200	Horizontal	Pass
5	9608.487	45.47	74.0	28.53	Peak	229.00	150	Horizontal	Pass
5**	9608.487	40.53	54.0	13.47	AV	229.00	150	Horizontal	Pass
6	17390.213	50.44	74.0	23.56	Peak	0.00	100	Horizontal	Pass
6**	17390.213	41.97	54.0	12.03	AV	0.00	100	Horizontal	Pass

8-DPSK LOW CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1327.300	44.18	74.0	29.82	Peak	24.00	300	Vertical	Pass
1**	1327.300	33.31	54.0	20.69	AV	24.00	300	Vertical	Pass
2	2402.000	93.75	74.0	-19.75	Peak	136.00	200	Vertical	N/A
2**	2402.000	91.87	54.0	-37.87	AV	136.00	200	Vertical	N/A
3	4978.000	49.48	74.0	24.52	Peak	25.00	100	Vertical	Pass
3**	4978.000	40.60	54.0	13.40	AV	25.00	100	Vertical	Pass
4	6156.400	51.66	74.0	22.34	Peak	360.00	400	Vertical	Pass
4**	6156.400	41.63	54.0	12.37	AV	360.00	400	Vertical	Pass
5	11895.550	47.23	74.0	26.77	Peak	159.00	300	Vertical	Pass
5**	11895.550	38.33	54.0	15.67	AV	159.00	300	Vertical	Pass
6	17390.213	51.38	74.0	22.62	Peak	72.00	200	Vertical	Pass
6**	17390.213	41.70	54.0	12.30	AV	72.00	200	Vertical	Pass

8-DPSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1571.500	40.86	74.0	33.14	Peak	171.00	300	Horizontal	Pass
1**	1571.500	31.19	54.0	22.81	AV	171.00	300	Horizontal	Pass
2	2440.800	97.23	74.0	-23.23	Peak	154.00	200	Horizontal	N/A
2**	2440.800	93.86	54.0	-39.86	AV	154.00	200	Horizontal	N/A
3	4693.400	48.71	74.0	25.29	Peak	360.00	200	Horizontal	Pass
3**	4693.400	39.12	54.0	14.88	AV	360.00	200	Horizontal	Pass
4	6518.600	52.38	74.0	21.62	Peak	70.00	400	Horizontal	Pass
4**	6518.600	42.46	54.0	11.54	AV	70.00	400	Horizontal	Pass
5	12585.838	47.52	74.0	26.48	Peak	48.00	100	Horizontal	Pass
5**	12585.838	37.84	54.0	16.16	AV	48.00	100	Horizontal	Pass
6	15566.888	50.97	74.0	23.03	Peak	110.00	300	Horizontal	Pass
6**	15566.888	40.77	54.0	13.23	AV	110.00	300	Horizontal	Pass

8-DPSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1332.600	43.85	74.0	30.15	Peak	110.00	300	Vertical	Pass
1**	1332.600	34.91	54.0	19.09	AV	110.00	300	Vertical	Pass
2	2441.000	94.51	74.0	-20.51	Peak	137.00	100	Vertical	N/A
2**	2441.000	91.31	54.0	-37.31	AV	137.00	100	Vertical	N/A
3	4968.800	48.95	74.0	25.05	Peak	298.00	200	Vertical	Pass
3**	4968.800	41.14	54.0	12.86	AV	298.00	200	Vertical	Pass
4	6988.600	52.27	74.0	21.73	Peak	265.00	300	Vertical	Pass
4**	6988.600	43.28	54.0	10.72	AV	265.00	300	Vertical	Pass
5	12773.363	47.65	74.0	26.35	Peak	139.00	100	Vertical	Pass
5**	12773.363	37.71	54.0	16.29	AV	139.00	100	Vertical	Pass
6	17396.251	50.78	74.0	23.22	Peak	27.00	300	Vertical	Pass
6**	17396.251	41.71	54.0	12.29	AV	27.00	300	Vertical	Pass

8-DPSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1330.400	44.10	74.0	29.90	Peak	152.00	300	Horizontal	Pass
1**	1330.400	33.07	54.0	20.93	AV	152.00	300	Horizontal	Pass
2	2479.800	98.88	74.0	-24.88	Peak	142.00	100	Horizontal	N/A
2**	2479.800	95.53	54.0	-41.53	AV	142.00	100	Horizontal	N/A
3	4991.400	49.05	74.0	24.95	Peak	0.00	150	Horizontal	Pass
3**	4991.400	38.75	54.0	15.25	AV	0.00	150	Horizontal	Pass
4	7440.450	47.34	74.0	26.66	Peak	324.00	150	Horizontal	Pass
4**	7440.450	41.28	54.0	12.72	AV	324.00	150	Horizontal	Pass
5	11196.349	47.09	74.0	26.91	Peak	360.00	150	Horizontal	Pass
5**	11196.349	37.78	54.0	16.22	AV	360.00	150	Horizontal	Pass
6	17407.275	51.31	74.0	22.69	Peak	307.00	100	Horizontal	Pass
6**	17407.275	41.83	54.0	12.17	AV	307.00	100	Horizontal	Pass

8-DPSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1163.300	45.73	74.0	28.27	Peak	35.00	300	Vertical	Pass
1**	1163.300	32.69	54.0	21.31	AV	35.00	300	Vertical	Pass
2	2480.100	96.84	74.0	-22.84	Peak	128.00	200	Vertical	N/A
2**	2480.100	93.55	54.0	-39.55	AV	128.00	200	Vertical	N/A
3	4972.600	49.17	74.0	24.83	Peak	328.00	150	Vertical	Pass
3**	4972.600	40.00	54.0	14.00	AV	328.00	150	Vertical	Pass
4	6990.600	51.76	74.0	22.24	Peak	263.00	400	Vertical	Pass
4**	6990.600	43.31	54.0	10.69	AV	263.00	400	Vertical	Pass
5	12466.813	47.65	74.0	26.35	Peak	24.00	200	Vertical	Pass
5**	12466.813	37.52	54.0	16.48	AV	24.00	200	Vertical	Pass
6	15901.838	50.93	74.0	23.07	Peak	194.00	400	Vertical	Pass
6**	15901.838	41.01	54.0	12.99	AV	194.00	400	Vertical	Pass

5.11 Band Edge (Restricted-band band-edge)

5.11.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.11.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.11.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.11.4 Test Result

Note ¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Note ²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note ³: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note ⁴: The Level (dBuV/m) has been corrected by factor.

Test Data

GFSK LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2326.000	55.91	74.0	18.09	Peak	299.00	150	Horizontal	Pass
1**	2326.000	43.62	54.0	10.38	AV	299.00	150	Horizontal	Pass
2	2389.833	55.59	74.0	18.41	Peak	46.00	100	Horizontal	Pass
2**	2389.833	43.48	54.0	10.52	AV	46.00	100	Horizontal	Pass

GFSK HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.550	54.88	74.0	19.12	Peak	330.00	150	Horizontal	Pass
1**	2483.550	43.94	54.0	10.06	AV	330.00	150	Horizontal	Pass
2	2491.850	55.62	74.0	18.38	Peak	190.00	100	Horizontal	Pass
2**	2491.850	43.48	54.0	10.52	AV	190.00	100	Horizontal	Pass

8-DPSK LOW CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2369.167	55.80	74.0	18.20	Peak	57.00	100	Horizontal	Pass
1**	2369.167	43.76	54.0	10.24	AV	57.00	100	Horizontal	Pass
2	2389.833	54.12	74.0	19.88	Peak	348.00	200	Horizontal	Pass
2**	2389.833	43.46	54.0	10.54	AV	348.00	200	Horizontal	Pass

8-DPSK HIGH CHANNEL

No.	Frequency (MHz)	Results (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.550	54.71	74.0	19.29	Peak	0.00	200	Horizontal	Pass
1**	2483.550	44.11	54.0	9.89	AV	0.00	200	Horizontal	Pass
2	2496.300	55.55	74.0	18.45	Peak	253.00	200	Horizontal	Pass
2**	2496.300	43.26	54.0	10.74	AV	253.00	200	Horizontal	Pass


ANNEX A TEST SETUP PHOTOS

1 Radiated Test Photo


Below 30MHz




30MHz-1GHz




Close-up



Above 1GHz




Close-up



2 Conducted Test Photo

Conducted Test



3 Conducted Emission

Photo 1



Photo 2



ANNEX B EUT EXTERNAL PHOTOS

FRONT VIEW OF EUT



REAR VIEW OF EUT



LEFT VIEW OF EUT



RIGHT VIEW OF EUT



TOP VIEW OF EUT




BOTTOM VIEW OF EUT



Accessory-Charging Case



Accessory-Type-C Cable






ANNEX C EUT INTERNAL PHOTOS


EUT UNCOVER VIEW 1




EUT UNCOVER VIEW 2



MAIN BOARD TOP VIEW



MAIN BOARD REAR VIEW



Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--