

FCC ID: 2AQJL-BL36

Frequency	Power density (mW/ cm ²)	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

[illegible]

Mode	CH	PK Output power(dBm)	Output power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
11b	CH1	12.87	19.36	1	1.2589	0.00485
	CH6	12.75	18.84	1	1.2589	0.00472
	CH11	12.24	16.75	1	1.2589	0.00420
11g	CH1	12.16	16.44	1	1.2589	0.00412
	CH6	11.48	14.06	1	1.2589	0.00352
	CH11	11.83	15.24	1	1.2589	0.00382
11n/HT20	CH1	11.37	13.71	1	1.2589	0.00344
	CH6	11.21	13.21	1	1.2589	0.00331
	CH11	10.79	11.99	1	1.2589	0.00301
11n/HT40	CH1	10.67	11.67	1	1.2589	0.00292
	CH4	10.48	11.17	1	1.2589	0.00280
	CH7	10.11	10.26	1	1.2589	0.00257
$Pd = \frac{P_{out} * G}{4\pi r^2} ;$						
Note:						
Note: The estimation distance is 20cm						
Note: PK Output power= conducted power. Conducted power see the test report HK1907161762-E, antenna gain=1dBi.						

-----The End-----