

FCC/IC TEST REPORT

Reference No. : G-45-2018-01873

Applicant : COMPACT.D

Equipment Under Test (EUT) :

Product Name : BTS OFFICIAL LIGHT STICK VER.3

Model Name : BTS X OFFICIAL 7718G

Applied Standards : FCC Part 15 Subpart B

ANSI C 63.4:2014

ICES-003, Issue 6

Date of Receipt : June 1, 2018

Date of Test : June 22, 2018

Date of Issue : July 13, 2018

Test Results : Complied

Tested by


:



Yongtae Yu

Reviewed by

:



Paul Kang

Remarks :

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full. This test report does not assure KOLAS accreditation.

Contents

1. General Information	4
1.1 Client Information.....	4
1.2 Test Laboratory.....	4
1.3 General Information of E.U.T.....	4
1.4 Operating Modes and Conditions	5
1.5 Auxiliary Equipments	5
1.6 Cable List.....	5
1.7 System Configurations.....	5
1.8 Test System Layout	5
1.9 Modifications.....	5
1.10 Applicable Standards for Testing	6
1.11 Summary of Test Results	6
2. Emission Test.....	7
2.1 Test Results.....	7
2.2 Test Method and Limits	7
2.2.1 Test Method.....	7
2.2.2 Test Limits	7
2.3 Radiated Emission	8
2.3.1 Test Equipments.....	8
2.3.2 Test Site	8
2.3.3 Environment Conditions and data	8
2.4 Photographs of Radiated Emission (Below 1 GHz).....	10
2.5 Photographs of Radiated Emission (Above 1 GHz)	11
3. Photographs of EUT	12
Appendix A: Radiated Emission	15



Revision History

Revision	Report Number	Description
0	F690501/RF-EMC003680(G)	Initial
1		
2		



1. General Information

1.1 Client Information

Applicant : COMPACT.D
- Address of Applicant : 2F, 703, Eonju-ro, Gangnam-gu, Seoul, Republic of Korea

Manufacturer : COMPACT.D
- Address of Manufacturer : 2F, 703, Eonju-ro, Gangnam-gu, Seoul, Republic of Korea.

1.2 Test Laboratory

Name and Address : SGS Korea Co., Ltd.
- Giheung 1 Laboratory : 35, Giheungdanji-ro 121beon-gil, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea
- Giheung 2 Laboratory : 23, Giheungdanji-ro 24beon-gil, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea
- Gunpo Laboratory : 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, 15807, Republic of Korea.

Phone : + 82 31 428 5700
Fax : + 82 31 427 2370
e-mail : paul.kang@sgs.com

1.3 General Information of E.U.T.

Classification	Description
Product Name	BTS OFFICIAL LIGHT STICK VER.3
Model Name	BTS X OFFICIAL 7718G
Serial No.	-
EMI Classification	Class B
Test Voltage	4.5 Vd.c
Rated Voltage	4.5 Vd.c., 160 mA
Operating Temperature	(-)10 °C ~ (+)50 °C
Description	The device is a battery-powered bluetooth light stick.

1.4 Operating Modes and Conditions

Operating Mode	Percussor
1) Operation mode	White LED Illuminated regularly

1.5 Auxiliary Equipments

Description	Model	Serial No.	Manufacturer
-	-	-	-


1.6 Cable List

Start		END		Cable Spec.		Used core
Name	I/O Port	Name	I/O Port	Length	Shield	
-	-	-	-	-	-	-

1.7 System Configurations

Description	Model	Serial No.	Manufacturer
Main Board	BTS ARMY Bong v2	-	-

1.8 Test System Layout



1.9 Modifications

- There was no modified item during the test.



1.10 Applicable Standards for Testing

Standards	Status	Deviation
FCC Part 15 Subpart B ICES-003 Issue 6: 2017	Applicable	No Deviation

1.11 Summary of Test Results

Test Item	Standards	Results
Radiated Emission	ANSI C 63.4:2014 FCC Part 15 Subpart B ICES-003 Issue 6: 2017	Complied

Note : Test methods of all test items are performed according to the basic standards in this table.

EMISSION

2.1 Test Results

Test Items	Basic Standards	Test Results
Radiated Emission	ANSI C 63.4:2014, FCC Part 15 Subpart B ICES-003 Issue 6: 2017	Complied

2.2 Test Method and Limits

2.2.1 Test Method

Test Items	Measuring Frequency Range	RBW	Measuring Distance
Radiated Emission	30 MHz ~ 1 GHz	120 kHz	3 m
	Above 1 GHz	1 MHz	3 m

2.2.2 Test Limits

-Radiated Emission Limits below 1 GHz

Frequency Range	Limits(dB(μ V/m))	Class
	Quasi-peak	
30 MHz ~ 88 MHz	39.1	Class A
88 MHz ~ 216 MHz	43.5	
216 MHz ~ 960 MHz	46.4	
960 MHz ~ 1 GHz	49.5	
30 MHz ~ 88 MHz	40	Class B
88 MHz ~ 216 MHz	43.5	
216 MHz ~ 960 MHz	46	
960 MHz ~ 1 GHz	54	

-Radiated Emission Limits above 1 GHz (3m method)

Frequency Range	Limits(dB(μ V/m))		Class
	Average	Peak	
Above 1 GHz	59.5	79.5	Class A
Above 1 GHz	54	74	Class B

2.3 Radiated Emission

The initial preliminary exploratory scans were performed at 3 m distance over the measuring frequency range(30 MHz to 13 GHz) using a max hold mode incorporating a Peak detector and using the software of EMC32(Version 8.50.0 from R&S) and EP5RE(Version Ver3.10.20 from TOYO). The final test data was measured using a Quasi-Peak detector below 1 GHz at 3 m distance and a Peak and Average detector above 1 GHz at 3 m distance. Measurements were made with the antenna positioned in both the horizontal and vertical planes of polarization. The antenna height was varied from 1 m to 4 m and the EUT was rotated 360° to find the maximum emitting point for each frequency.

2.3.1 Test Equipments

Description	Model No.	Manufacturer	S/N	Cal Due. Date
Horn Antenna (KOLAS)	HF906	R & S	100326	2020.02.14
Signal Conditioning Unit	SCU 18	R & S	102244	2018.09.22
Test Receiver	ESU26	R & S	100109	2019.02.07
Bilog Antenna (KOLAS)	VULB9163	SCHWARZBECK	01126	2020.03.26
Amplifier	8447F	HP	2944A03909	2018.08.11

Note : Only the calibration period of Antennas is 2 years but the period of every equipment is 1 year.

2.3.2 Test Site

3m SEMI-ANECHOIC CHAMBER Gunpo Laboratory (Below 1 GHz, Above 1 GHz)

2.3.3 Environment Conditions and data

- Below 1 GHz

Temperature : (minimum 20.7, maximum 21.3) °C

Humidity : (minimum 37.0, maximum 39.0) %R.H.

Atmospheric Pressure : (minimum 101.4, maximum 101.5) kPa

Test Date : June 22, 2018

- Above 1 GHz

Temperature : (minimum 20.7, maximum 21.3) °C

Humidity : (minimum 37.0, maximum 39.0) %R.H.

Atmospheric Pressure : (minimum 101.4, maximum 101.5) kPa

Test Date : June 22, 2018

- Below 1 GHz (3 m method)

Freq. (MHz)	Level (dB(μV))	Pol. (H/V)	A (°)	H (cm)	AF (dB/m)	CL (dB)	Amp. (dB)	Result (dB(μV/m))	Limit (dB(μV/m))	Margin (dB)
33.92	31.20	V	329	400	10.68	1.22	28.10	15.00	40.00	25.00
35.38	32.90	H	5	100	10.88	1.23	28.10	16.91	40.00	23.09
53.97	31.70	H	127	100	12.95	1.40	28.09	17.96	40.00	22.04
60.07	31.50	V	232	300	11.96	1.46	28.08	16.84	40.00	23.16
430.73	32.60	H	192	200	17.09	3.64	28.38	24.95	46.00	21.05
550.89	31.60	V	174	300	19.40	4.08	28.80	26.28	46.00	19.72

Measurement Uncertainty (Horizontal) : 5.31 dB (The confidential level is about 95%, k=2)

Measurement Uncertainty (Vertical) : 5.73 dB (The confidential level is about 95%, k=2)

Note 1: • AF = Antenna Factor • CL = Cable Loss • Amp = Amplifier Gain
• POL H = Horizontal • POL V = Vertical • A : Angle
• H : Height • Margin = Limit – Result • Result = Level + AF + CL – Amp

- Above 1 GHz (3 m method)

Freq. (MHz)	Level (dBμV)	Pol. (H/V)	A (°)	H (cm)	AF (dB)	CL (dB)	Amp. (dB)	CF (dB)	Result (dB μV/m)	Limit (dB μV/m)	Margin (dB)
Peak Detector											
1083.13	56.40	H	186	100	24.48	5.64	38.21	0.00	48.31	74.00	25.69
1529.58	54.40	H	186	100	25.52	6.68	37.92	0.00	48.68	74.00	25.32
1593.54	50.40	V	167	100	25.82	6.89	38.08	0.00	45.03	74.00	28.97
1593.75	54.60	H	186	100	25.82	6.90	38.08	0.00	49.24	74.00	24.76
1953.33	52.80	H	186	100	27.50	7.94	37.92	0.00	50.32	74.00	23.68
1961.46	52.00	H	186	100	27.54	7.98	37.92	0.00	49.60	74.00	24.40
1977.50	47.50	V	181	100	27.61	8.04	37.91	0.00	45.24	74.00	28.76
Average Detector											
1083.13	40.70	H	186	100	24.48	5.64	38.21	0.00	32.61	54.00	21.39
1529.58	40.90	H	186	100	25.52	6.68	37.92	0.00	35.18	54.00	18.82
1593.54	37.30	V	167	100	25.82	6.89	38.08	0.00	31.93	54.00	22.07
1593.75	41.50	H	186	100	25.82	6.90	38.08	0.00	36.14	54.00	17.86
1953.33	42.20	H	186	100	27.50	7.94	37.92	0.00	39.72	54.00	14.28
1961.46	41.50	H	186	100	27.54	7.98	37.92	0.00	39.10	54.00	14.90
1977.50	37.10	V	181	100	27.61	8.04	37.91	0.00	34.84	54.00	19.16

Measurement Uncertainty (Horizontal) : 5.73 dB (The confidential level is about 95%, k=2)


Measurement Uncertainty (Vertical) : 5.85 dB (The confidential level is about 95%, k=2)

Note 1: • AF = Antenna Factor • CL = Cable Loss • Amp = Amplifier Gain
• POL H = Horizontal • POL V = Vertical • A : Angle
• H : Height • Margin = Limit – Result • Result = Level + AF + CL – Amp


See Appendix B (Radiated Emission)

2.4 Photographs of Radiated Emission (Below 1 GHz)

[Front]




[Rear]




2.5 Photographs of Radiated Emission (Above 1 GHz)

[Front]



[Rear]



3. Photographs of EUT

[Front View of EUT]




[Rear View of EUT]




[Front View of Main Board]



[Rear View of Main Board]




[View of Inside]




Appendix A: Radiated Emission

Below 1 GHz



Above 1 GHz



- End of the Report -