



# FCC TEST REPORT

**Test report  
On Behalf of  
Electronic Design Solutions LLC  
For  
Smart AC controller  
Model No.: 00860293002309**

FCC ID: 2AQLRG1

Prepared for : **Electronic Design Solutions LLC**  
**331 east 83rd St #3, New York NY 10028**

Prepared By : **Shenzhen HUAK Testing Technology Co., Ltd.**  
**1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,**  
**Bao'an District, Shenzhen City, China**

**Date of Test:** Jul. 25, 2018 to Aug. 07, 2018  
**Date of Report:** Aug. 07, 2018  
**Report Number:** HUAK180803687E



## TEST RESULT CERTIFICATION

**Applicant's name** ..... : Electronic Design Solutions LLC  
Address ..... : 331 east 83rd St #3, New York NY 10028

**Manufacture's Name** ..... : Electronic Design Solutions LLC  
Address ..... : 331 east 83rd St #3, New York NY 10028

### Product description

Product name ..... Smart AC controller  
Brand name ..... Gidbo  
Test model ..... : 00860293002309

**Standards** ..... : FCC Rules and Regulations Part 15 Subpart C Section 15.247  
ANSI C63.10: 2013

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAK Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAK Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

### Date of Test .....

Date (s) of performance of tests ..... : Jul. 25, 2018 to Aug. 07, 2018  
Date of Issue ..... : Aug. 07, 2018  
Test Result ..... : **Pass**

Testing Engineer : 

(Gary Qian)

Technical Manager : 

(Eden Hu)

Authorized Signatory : 

(Jason Zhou)



## TABLE OF CONTENTS

<b>1. GENERAL INFORMATION .....</b>	<b>5</b>
1.1. PRODUCT DESCRIPTION .....	5
1.2. TABLE OF CARRIER FREQUENCYS .....	5
1.3. IEEE 802.11N MODULATION SCHEME.....	6
1.4. RELATED SUBMITTAL(S) / GRANT (S) .....	6
1.5. TEST METHODOLOGY.....	7
1.6. SPECIAL ACCESSORIES.....	7
1.7. EQUIPMENT MODIFICATIONS.....	7
<b>2. MEASUREMENT UNCERTAINTY .....</b>	<b>8</b>
<b>3. DESCRIPTION OF TEST MODES .....</b>	<b>9</b>
<b>4. SYSTEM TEST CONFIGURATION.....</b>	<b>10</b>
4.1. CONFIGURATION OF EUT SYSTEM.....	10
4.2. EQUIPMENT USED IN EUT SYSTEM .....	10
4.3. SUMMARY OF TEST RESULTS.....	10
<b>5. TEST FACILITY .....</b>	<b>11</b>
<b>6. OUTPUT POWER .....</b>	<b>12</b>
6.1. MEASUREMENT PROCEDURE.....	12
6.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	12
6.3. LIMITS AND MEASUREMENT RESULT .....	13
<b>7. dB BANDWIDTH.....</b>	<b>14</b>
7.1. MEASUREMENT PROCEDURE.....	14
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	14
7.3. LIMITS AND MEASUREMENT RESULTS.....	15
<b>8. CONDUCTED SPURIOUS EMISSION .....</b>	<b>18</b>
8.1. MEASUREMENT PROCEDURE.....	18
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	18
8.3. MEASUREMENT EQUIPMENT USED .....	18
8.4. LIMITS AND MEASUREMENT RESULT .....	19
<b>9. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY .....</b>	<b>25</b>
9.1. MEASUREMENT PROCEDURE.....	25
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	25
9.3. MEASUREMENT EQUIPMENT USED .....	25
9.4. LIMITS AND MEASUREMENT RESULT .....	26
<b>10. RADIATED EMISSION .....</b>	<b>29</b>
10.1. MEASUREMENT PROCEDURE.....	29



10.2. TEST SETUP .....	30
10.3. LIMITS AND MEASUREMENT RESULT .....	31
10.4. TEST RESULT .....	32
<b>11. BAND EDGE EMISSION .....</b>	<b>35</b>
11.1. MEASUREMENT PROCEDURE.....	35
11.2. TEST SET-UP .....	35
11.3. RADIATED TEST RESULT.....	36
11.4. CONDUCTED TEST RESULT .....	37
<b>12. FCC LINE CONDUCTED EMISSION TEST .....</b>	<b>38</b>
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST .....	38
12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST .....	38
12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST .....	39
12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST.....	40
12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST.....	41
<b>13. APPENDIX A: PHOTOGRAPHS OF TEST SETUP .....</b>	<b>43</b>



# 1. GENERAL INFORMATION

## 1.1. PRODUCT DESCRIPTION

The EUT is designed as “Smart AC controller”. It is designed by way of utilizing the DSSS and OFDM technology to achieve the system operation.

A major technical description of EUT is described as following

<b>Operation Frequency</b>	2.412 GHz ~ 2.462GHz
<b>Output Power</b>	IEEE 802.11b: <b>17.62</b> dBm, IEEE 802.11g: <b>16.23</b> dBm; IEEE 802.11n(20): <b>15.96</b> dBm
<b>Modulation</b>	DSSS(DBPSK/DQPSK/CCK);OFDM(BPSK/QPSK/16-QAM/64-QAM)
<b>Number of channels</b>	11 Channels (IEEE802.11b/g/n20)
<b>Hardware Version</b>	2.2
<b>Software Version</b>	1321
<b>Antenna Designation</b>	PCB Antenna
<b>Antenna Gain</b>	3.0dBi
<b>Power Supply</b>	DC5.0V

## 1.2. TABLE OF CARRIER FREQUENCYS

<b>Frequency Band</b>	<b>Channel Number</b>	<b>Frequency</b>
2400~2483.5MHZ	1	2412 MHZ
	2	2417 MHZ
	3	2422 MHZ
	4	2427 MHZ
	5	2432 MHZ
	6	2437 MHZ
	7	2442 MHZ
	8	2447 MHZ
	9	2452 MHZ
	10	2457 MHZ
	11	2462 MHZ

Note: For 20MHZ bandwidth system use Channel 1 to Channel 11



### 1.3. IEEE 802.11N MODULATION SCHEME

MCS Index	Nss	Modulation	R	NBPSC	NCBPS		NDBPS		Data rate(Mbps)	
					20MHz	40MHz	20MHz	40MHz	20MHz	40MHz
0	1	BPSK	1/2	1	52	108	26	54	6.5	13.5
1	1	QPSK	1/2	2	104	216	52	108	13.0	27.0
2	1	QPSK	3/4	2	104	216	78	162	19.5	40.5
3	1	16-QAM	1/2	4	208	432	104	216	26.0	54.0
4	1	16-QAM	3/4	4	208	432	156	324	39.0	81.0
5	1	64-QAM	2/3	6	312	648	208	432	52.0	108.0
6	1	64-QAM	3/4	6	312	648	234	489	58.5	121.5
7	1	64-QAM	5/6	6	312	648	260	540	65.0	135.0

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	Guard interval

### 1.4. RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: FFDD** filing to comply with the FCC Part 15 requirements.



## **1.5. TEST METHODOLOGY**

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

Others testing (listed at item 5.3) was performed according to the procedures in FCC Part 15.247 rules KDB 558074 D01 DTS Meas Guidance v04.

## **1.6. SPECIAL ACCESSORIES**

Refer to section 5.2.

## **1.7. EQUIPMENT MODIFICATIONS**

Not available for this EUT intended for grant.



## 2. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	$\pm 2.56\text{dB}$
2	RF power, conducted	$\pm 0.12\text{dB}$
3	Spurious emissions, conducted	$\pm 0.11\text{dB}$
4	All emissions, radiated(<1G)	$\pm 3.92\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.28\text{dB}$
6	Temperature	$\pm 0.1^\circ\text{C}$
7	Humidity	$\pm 1.0\%$



### 3. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel TX
2	Middle channel TX
3	High channel TX
4	Normal operating

**Note:**  
Transmit by 802.11b with Date rate (1/2/5.5/11)  
Transmit by 802.11g with Date rate (6/9/12/18/24/36/48/54)  
Transmit by 802.11n (20MHz) with Date rate (6.5/13/19.5/26/39/52/58.5/65)

**Note:**


1. The EUT has been set to operate continuously on the lowest, middle and highest operation frequency individually, and the eut is operating at its maximum duty cycle>or equal 98%
2. All modes under which configure applicable have been tested and the worst mode test data recording in the test report, if no other mode data.
3. For Radiated Emission, 3axis were chosen for testing for each applicable mode.



## 4. SYSTEM TEST CONFIGURATION

### 4.1. CONFIGURATION OF EUT SYSTEM

Configure:



### 4.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	Smart AC controller	00860293002309	FFDD	EUT
2	Adapter	A18A-050100U-US2	DC 5.0V 1A	Accessory
3	USB	N/A	N/A	Accessory

Note: All the accessories have been used during the test in conduction emission test.

### 4.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.247	Output Power	Compliant
§15.247	6 dB Bandwidth	Compliant
§15.247	Conducted Spurious Emission	Compliant
§15.247	Maximum Conducted Output Power SPECTRAL Density	Compliant
§15.209	Radiated Emission	Compliant
§15.247	Band Edges	Compliant
§15.207	Line Conduction Emission	Compliant



## 5. TEST FACILITY

Test Firm	Shenzhen HUAK Testing Technology Co., Ltd.
Address	1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen City, China
Designation Number	CN1229
Registration Number	616276

### ALL TEST EQUIPMENT LIST

Equipment	Manufacturer	Model	S/N	Cal. Due
Receiver	R&S	ESCI 7	HKE-010	Dec. 28, 2018
LISN	R&S	ENV216	HKE-002	Dec. 28, 2018
Conducted test software	Tonscend	TS+ Rev 2.5.0.0	HKE-081	N/A
Power meter	Agilent	E4417B	HKE-107	Dec. 28, 2018
Power Sensor	Agilent	E9327A	HKE-113	Dec. 28, 2018
RF cable	Times	1-40G	HKE-034	Dec. 28, 2018
RF automatic control unit	Tonscend	JS0806-2	HKE-060	Dec. 28, 2018
Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 28, 2018
RF Cable (9KHz-26.5GHz)	Tonscend	170660	N/A	Dec. 28, 2018
Signal generator	Agilent	N5183A	HKE-071	Dec. 28, 2018
Receiver	R&S	ESCI-7	HKE-010	Dec. 28, 2018
Preamplifier	EMCI	EMC051845SE	HKE-015	Dec. 28, 2018
Preamplifier	Agilent	83051A	HKE-016	Dec. 28, 2018
Loop antenna	Schwarzbeck	FMZB 1519 B	HKE-014	Dec. 28, 2018
Broadband antenna	Schwarzbeck	VULB 9163	HKE-012	Dec. 28, 2018
Horn antenna	Schwarzbeck	9120D	HKE-013	Dec. 28, 2018
Antenna Mast	Keleto	CC-A-4M	N/A	N/A
Position controller	Taiwan MF	MF7802	HKE-011	Dec. 28, 2018
RF cable (9KHz-1GHz)	Times	381806-001	N/A	N/A



## 6. OUTPUT POWER

### 6.1. MEASUREMENT PROCEDURE


For max average conducted output power test:

1. Connect EUT RF output port to power probe through an RF attenuator.
2. Connect the power probe to the PC.
3. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
4. Record the maximum power from the software.

**Note:** The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

### 6.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

#### AVERAGE POWER SETUP





### 6.3. LIMITS AND MEASUREMENT RESULT

<b>TEST ITEM</b>	OUTPUT POWER
<b>TEST MODE</b>	802.11b with data rate 1

Frequency (GHz)	Average Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.412	<b>17.62</b>	30	Pass
2.437	16.19	30	Pass
2.462	14.56	30	Pass

<b>TEST ITEM</b>	OUTPUT POWER
<b>TEST MODE</b>	802.11g with data rate 6

Frequency (GHz)	Average Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.412	<b>16.23</b>	30	Pass
2.437	15.97	30	Pass
2.462	11.56	30	Pass

<b>TEST ITEM</b>	OUTPUT POWER
<b>TEST MODE</b>	802.11n 20 with data rate 6.5

Frequency (GHz)	Average Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.412	<b>15.96</b>	30	Pass
2.437	15.68	30	Pass
2.462	11.35	30	Pass




## 7. dB BANDWIDTH

### 7.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 KHz, VBW  $\geq 3 \times$  RBW.
4. Set SPA Trace 1 Max hold, then View.

**Note:** The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

### 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)






### 7.3. LIMITS AND MEASUREMENT RESULTS

Mode	Channel	6dB Bandwidth [MHz]	Verdict
11b	LCH	9.056	PASS
	MCH	9.038	PASS
	HCH	8.107	PASS
11g	LCH	15.69	PASS
	MCH	15.69	PASS
	HCH	15.72	PASS
11nHT20	LCH	15.47	PASS
	MCH	15.46	PASS
	HCH	15.48	PASS




## Test Graph







11nHT20-LCH



11nHT20-MCH



11nHT20-HCH





## 8. CONDUCTED SPURIOUS EMISSION

### 8.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Trace 1 Max hold, then View.

**Note:** The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements. Owing to satisfy the requirements of the number of measurement points, we set the RBW=1MHz, VBW>RBW, scan up through 10th harmonic, and consider the tested results as the worst case, if the tested results conform to the requirement, we can deem that the real tested results(set the RBW=100KHz, VBW > RBW) are conform to the requirement.

### 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 8.2.

### 8.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.




#### 8.4. LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT		
Applicable Limits	Measurement Result	
	Test Data	Criteria
In any 100 KHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power. In addition, radiation emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in§15.209(a))	At least -20dBc than the limit Specified on the BOTTOM Channel	PASS
	At least -20dBc than the limit Specified on the TOP Channel	PASS




## Test Graph







## 11B-HCH




## 11B-HCH




## 11B-HCH




## 11G-LCH






## 11G-LCH




## 11G-LCH









## 11nHT20-LCH




## 11nHT20-LCH




## 11nHT20-LCH




## 11nHT20-MCH



## 11nHT20-MCH




## 11nHT20-MCH







## 11nHT20-HCH



## 11nHT20-HCH



## 11nHT20-HCH





## **9. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY**

### **9.1. MEASUREMENT PROCEDURE**

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set SPA Trace 1 Max hold, then View.

Note: The method of AVGPSD in the KDB 558074 item 10.3 was used in this testing.

### **9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)**

Refer To Section 8.2.

### **9.3. MEASUREMENT EQUIPMENT USED**

Refer To Section 6.





#### 9.4. LIMITS AND MEASUREMENT RESULT

Mode	Channel	PSD [dBm/20kHz]	Limit[dBm/3kHz]	Verdict
11b	LCH	4.159	8	PASS
	MCH	2.406	8	PASS
	HCH	1.147	8	PASS
11g	LCH	-0.781	8	PASS
	MCH	-1.062	8	PASS
	HCH	-5.308	8	PASS
11nHT20	LCH	0.017	8	PASS
	MCH	-0.312	8	PASS
	HCH	-4.838	8	PASS



## Test Graph








## 10. RADIATED EMISSION

### 10.1. MEASUREMENT PROCEDURE


1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.

## 10.2. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz





### 10.3. LIMITS AND MEASUREMENT RESULT

15.209(a) Limit in the below table has to be followed

<b>Frequencies (MHz)</b>	<b>Field Strength (micorvolts/meter)</b>	<b>Measurement Distance (meters)</b>
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested For restricted band radiated emission,  
the test records reported below are the worst result compared to other modes.




#### 10.4. TEST RESULT

##### RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

##### RADIATED EMISSION BELOW 1GHZ

##### RADIATED EMISSION TEST- (30MHZ-1GHZ) -HORIZONTAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dB <sub>UV</sub>	dB/m	dB <sub>UV</sub> /m	dB <sub>UV</sub> /m	dB		cm	degree	
1		41.3167	19.51	11.81	31.32	40.00	-8.68	peak			
2		115.6833	22.01	6.86	28.87	43.50	-14.63	peak			
3		319.3833	18.10	16.70	34.80	46.00	-11.20	peak			
4		479.4333	17.25	20.91	38.16	46.00	-7.84	peak			
5		799.5333	6.04	27.31	33.35	46.00	-12.65	peak			
6	*	907.8500	10.62	28.83	39.45	46.00	-6.55	peak			

**RESULT: PASS**



## RADIATED EMISSION TEST- (30MHZ-1GHZ) -VERTICAL

66.9 dBuV/m



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna	Table	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		Height	Degree	
1		41.3167	25.13	8.81	33.94	40.00	-6.06	peak			
2	*	80.1167	33.09	1.84	34.93	40.00	-5.07	peak			
3		131.8500	22.47	11.80	34.27	43.50	-9.23	peak			
4		319.3833	16.67	16.70	33.37	46.00	-12.63	peak			
5		479.4333	14.23	20.91	35.14	46.00	-10.86	peak			
6		799.5333	4.79	27.31	32.10	46.00	-13.90	peak			

**RESULT: PASS**

**Note:** 1. Factor=Antenna Factor + Cable loss, Margin= Result -Limit.  
2. The "Factor" value can be calculated automatically by software of measurement system.  
3. All test modes had been pre-tested. The 802.11b at low channel is the worst case and recorded in the report.



## RADIATED EMISSION ABOVE 1GHZ

Frequency (MHz)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Detector Type	Comment
TX 11b 2412MHz					
4824	48.29	74	-25.71	Pk	Horizontal
4824	42.13	54	-11.87	AV	Horizontal
7236	49.11	74	-24.89	pk	Horizontal
7236	41.03	54	-12.97	AV	Horizontal
4824	48.79	74	-25.21	Pk	Vertical
4824	40.78	54	-13.22	AV	Vertical
7236	47.99	74	-26.01	Pk	Vertical
7236	41.81	54	-12.19	AV	Vertical
TX 11b 2437MHz					
4874	48.33	74	-25.67	Pk	Horizontal
4874	42.17	54	-11.83	AV	Horizontal
7311	49.15	74	-24.85	Pk	Horizontal
7311	41.07	54	-12.93	AV	Horizontal
4874	48.83	74	-25.17	Pk	Vertical
4874	40.82	54	-13.18	AV	Vertical
7311	48.03	74	-25.97	Pk	Vertical
7311	41.85	54	-12.15	AV	Vertical
TX 11b 2462MHz					
4924	48.36	74	-25.64	Pk	Horizontal
4924	42.2	54	-11.8	AV	Horizontal
7386	49.18	74	-24.82	Pk	Horizontal
7386	41.1	54	-12.9	AV	Horizontal
4924	48.86	74	-25.14	Pk	Vertical
4924	40.85	54	-13.15	AV	Vertical
7386	48.06	74	-25.94	Pk	Vertical
7386	41.88	54	-12.12	AV	Vertical

**RESULT: PASS****Note:**

1. Margin = Emission Level - Limit
- 2.1GHz-25GHz(All test modes had been pre-tested. The 802.11b mode is the worst case and recorded in the report. No recording in the test report at least have 20dB margin).



## 11. BAND EDGE EMISSION

### 11.1. MEASUREMENT PROCEDURE

#### 1) Radiated restricted band edge measurements

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting


#### 2) Conducted Emissions at the band edge

- a) The transmitter output was connected to the spectrum analyzer
- b) Set RBW=100kHz, VBW=300kHz
- c) Suitable frequency span including 100kHz bandwidth from band edge

### 11.2. TEST SET-UP

Radiated same as 11.2

Conducted set up





### 11.3. RADIATED TEST RESULT

Frequency (MHz)	Emission Level (dB $\mu$ V/m)	Limits	Margin (dB)	Detector Type	Comment
TX 11b 2412MHz					
2399.9	52.35	74	-21.65	pk	Horizontal
2399.9	39.31	54	-14.69	AV	Horizontal
2400	52.71	74	-21.29	pk	Horizontal
2400	39.16	54	-14.84	AV	Horizontal
2399.9	52.28	74	-21.72	pk	Vertical
2399.9	39.29	54	-14.71	AV	Vertical
2400	53.36	74	-20.64	pk	Vertical
2400	39.68	54	-14.32	AV	Vertical
TX 11b 2462MHz					
2483.5	51.46	74	-22.54	pk	Horizontal
2483.5	37.59	54	-16.41	AV	Horizontal
2483.6	51.58	74	-22.42	pk	Horizontal
2483.6	39.43	54	-14.57	AV	Horizontal
2483.5	52.59	74	-21.41	pk	Vertical
2483.5	39.9	54	-14.1	AV	Vertical
2483.6	53.76	74	-20.24	pk	Vertical
2483.6	40.77	54	-13.23	AV	Vertical

### RESULT: PASS



**Note:** Scan with 11b,11g,11n, the worst case is 11b Mode

Margin= Emission Level -Limit.



## 11.4. CONDUCTED TEST RESULT

### Test Graph



## 12. FCC LINE CONDUCTED EMISSION TEST


### 12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P. ( dBuV)	Average( dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

### 12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





### 12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received charging voltage by adapter which received 120V/60Hz power by a LISN..
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.




#### **12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST**

1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.



## 12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

### LINE CONDUCTED EMISSION TEST LINE 1-L




NO.	Freq. [MHz]	Level [dBμV]	Factor [dB]	Limit [dBμV]	Margin [dB]	Detector
1	0.4740	40.55	10.04	56.60	16.05	PK
2	0.8925	39.36	10.06	56.00	16.64	PK
3	1.4910	37.36	10.10	56.00	18.64	PK
4	2.4405	35.22	10.18	56.00	20.78	PK
5	4.7265	32.40	10.26	56.00	23.60	PK
6	10.4280	32.21	10.04	60.00	27.79	PK

NO.	Freq. [MHz]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]
1	0.4706	10.04	38.72	56.50	17.78	31.38	46.50	15.12
2	0.9095	10.06	31.06	56.00	24.94	21.05	46.00	24.95
3	1.4538	10.10	29.89	56.00	26.11	22.85	46.00	23.15
4	2.3958	10.18	29.26	56.00	26.74	21.11	46.00	24.89
5	4.8247	10.26	25.67	56.00	30.33	19.41	46.00	26.59
6	10.5646	10.03	25.66	60.00	34.34	19.56	50.00	30.44



## Line Conducted Emission Test Line 2-N



NO.	Freq. [MHz]	Level [dB $\mu$ V]	Factor [dB]	Limit [dB $\mu$ V]	Margin [dB]	Detector
1	0.4695	37.40	10.04	56.60	19.20	PK
2	0.8970	31.69	10.06	56.00	24.31	PK
3	2.1975	32.85	10.17	56.00	23.15	PK
4	4.9920	34.10	10.26	56.00	21.90	PK
5	9.6225	31.44	10.08	60.00	28.56	PK
6	16.5885	31.40	9.99	60.00	28.60	PK


NO.	Freq. [MHz]	Factor [dB]	QP Value [dB $\mu$ V]	QP Limit [dB $\mu$ V]	QP Margin [dB]	AV Value [dB $\mu$ V]	AV Limit [dB $\mu$ V]	AV Margin [dB]
1	0.4742	10.04	35.95	56.44	20.49	28.97	46.44	17.47
2	0.9194	10.06	28.20	56.00	27.80	20.59	46.00	25.41
3	2.1640	10.16	27.50	56.00	28.50	21.23	46.00	24.77
4	5.1025	10.26	26.72	60.00	33.28	21.18	50.00	28.82
5	9.4763	10.09	25.24	60.00	34.76	19.47	50.00	30.53
6	16.6545	9.99	25.51	60.00	34.49	19.56	50.00	30.44

## 13. APPENDIX A: PHOTOGRAPHS OF TEST SETUP

### LINE CONDUCTED EMISSION TEST SETUP



### RADIATED EMISSION TEST SETUP





RADIATED EMISSION ABOVE 1G TEST SETUP



----END OF REPORT----