

MPE Calculation : GSM / WCDMA

RF function or Mode	Frequency range (MHz)			Max Target Power (dBm)	ANT Gain (dBi)	Maximum EIRP (dBm)	Maximum EIRP (mW)	Maximum power density (mW/cm ²)	Requirment (mW/cm ²)
GSM850	824.20	~	848.80	33.00	-5.64	27.36	544.503	0.1084	0.549
GSM1900	1850.20	~	1909.80	30.00	3.26	33.26	2118.362	0.4215	1.000
WCDMA850	826.40	~	846.60	23.50	-5.64	17.86	61.095	0.0122	0.550
WCDMA1900	1852.40	~	1907.60	23.50	3.26	26.76	474.242	0.0944	1.000
		~							
		~							
		~							
		~							

Note: Please refer to the tune-up procedure.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE sample calculation for this exposure is shown below.

$$\begin{aligned}
 S &= \text{EIRP} / (4 R^2 \pi) \\
 &= 544.503 / (4 \times 20^2 \times \pi) \\
 &= 0.1084 \text{ mW/cm}^2
 \end{aligned}$$

- Note

S= Maximum power density(mW/cm²)

EIRP= Equivalent Isotropic Radiated Power(mW)

R= Distance to the center of the radiation of the antenn

▪ Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)			Electric Field strength (V/m)	Magnetic field strength (A/m)	Power Density (mW/cm ²)	Averageing time (minutes)
0.3	~	1.34	614	1.63	*100	30
1.34	~	30	824/f	2.19 / f	*180 / f ²	30
30	~	300	27.5	0.073	0.2	30
300	~	1,500			f / 1500	30
1,500	~	100,000			1.0	30

Conclusion : The exposure condition of this device is compliant with FCC