

RADIO TEST REPORT

FCC ID: 2AQMY-ZR303RX

Product: Wireless baby monitor receiver

Trade Mark: N/A

Model No.: ZR303RX

ZR313RX, ZR323RX, ZR333RX,
ZR343RX, ZR353RX, ZR363RX,
ZR373RX, ZR383RX, ZR393RX,
ZR201RX, ZR202RX, ZR301RX,
ZR302RX, ZR601RX, ZR602RX,
ZR603RX, ZR650RX, ZR651RX,
ZR660RX, ZR870RX, ZR871RX,
ZR880RX

Report No.: SER180622702001E

Issue Date: Aug 06, 2018

Prepared for

Shenzhen ZhaofengweiTechnology Co. Ltd.
3 / F, Building B, No. 30 of Pingnan dongsheng Village, Zhongkai
high-tech zone, Huizhou city, Guangdong province,
P. R. China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community,
Xixiang Street Bao'an District, Shenzhen 518126 P.R. China
Tel.: +86-755-6115 6588
Fax.: +86-755-6115 6599
Website:<http://www.ntek.org.cn>

TABLE OF CONTENTS

1	TEST RESULT CERTIFICATION	3
2	SUMMARY OF TEST RESULTS.....	4
3	FACILITIES AND ACCREDITATIONS	5
3.1	FACILITIES.....	5
3.2	LABORATORY ACCREDITATIONS AND LISTINGS	5
3.3	MEASUREMENT UNCERTAINTY	5
4	GENERAL DESCRIPTION OF EUT	6
5	DESCRIPTION OF TEST MODES	8
6	SETUP OF EQUIPMENT UNDER TEST	9
6.1	BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM.....	9
6.2	SUPPORT EQUIPMENT.....	10
6.3	EQUIPMENTS LIST FOR ALL TEST ITEMS.....	11
7	TEST REQUIREMENTS.....	13
7.1	CONDUCTED EMISSIONS TEST	13
7.2	RADIATED SPURIOUS EMISSION	18
7.3	NUMBER OF HOPPING CHANNEL.....	27
7.4	HOPPING CHANNEL SEPARATION MEASUREMENT	29
7.5	AVERAGE TIME OF OCCUPANCY (DWELL TIME)	32
7.6	20DB BANDWIDTH TEST	35
7.7	PEAK OUTPUT POWER.....	38
7.8	CONDUCTED BAND EDGE MEASUREMENT.....	41
7.9	SPURIOUS RF CONDUCTED EMISSION.....	43
7.10	ANTENNA APPLICATION	47

1 TEST RESULT CERTIFICATION

Applicant's name	Shenzhen ZhaofengweiTechnology Co. Ltd.
Address	3 / F, Building B, No. 30 of Pingnan dongsheng Village, Zhongkai high-tech zone, Huizhou city, Guangdong province, P. R. China
Manufacturer's Name	Shenzhen ZhaofengweiTechnology Co. Ltd.
Address	3 / F, Building B, No. 30 of Pingnan dongsheng Village, Zhongkai high-tech zone, Huizhou city, Guangdong province, P. R. China
Product description	
Product name	Wireless baby monitor receiver
Model and/or type reference	ZR303RX
Serial Model	ZR313RX, ZR323RX, ZR333RX, ZR343RX, ZR353RX, ZR363RX, ZR373RX, ZR383RX, ZR393RX, ZR201RX, ZR202RX, ZR301RX, ZR302RX, ZR601RX, ZR602RX, ZR603RX, ZR650RX, ZR651RX, ZR660RX, ZR870RX, ZR871RX, ZR880RX

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD/ TEST PROCEDURE	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C KDB 174176 D01 Line Conducted FAQ v01r01 ANSI C63.10-2013	Complied


This device described above has been tested by Shenzhen NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.


This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK Testing Technology Co., Ltd., this document may be altered or revised by Shenzhen NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : 22 Jun. 2018 ~ 13 Jul. 2018

Testing Engineer : 
(Loren Luo)

Technical Manager : 
(Jason Chen)

Authorized Signatory : 
(Sam Chen)

2 SUMMARY OF TEST RESULTS**FCC Part15 (15.247), Subpart C**

Standard Section	Test Item	Verdict	Remark
15.207	Conducted Emission	PASS	
15.209 (a) 15.205 (a)	Radiated Spurious Emission	PASS	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(a)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

Remark:

1. "N/A" denotes test is not applicable in this Test Report.
2. All test items were verified and recorded according to the standards and without any deviation during the test.

3 FACILITIES AND ACCREDITATIONS

3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab.

: The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)
The Certificate Registration Number is L5516.

IC-Registration

The Certificate Registration Number is 9270A-1.

FCC- Accredited

Test Firm Registration Number: 463705.

Designation Number: CN1184

A2LA-Lab.

The Certificate Registration Number is 4298.01

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories.

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).

: Shenzhen NTEK Testing Technology Co., Ltd.

: 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 2.80\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(30MHz~1GHz)	$\pm 2.64\text{dB}$
5	All emissions, radiated(1GHz~6GHz)	$\pm 2.40\text{dB}$
6	All emissions, radiated(>6GHz)	$\pm 2.52\text{dB}$
7	Temperature	$\pm 0.5^\circ\text{C}$
8	Humidity	$\pm 2\%$

4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification	
Equipment	Wireless baby monitor receiver
Trade Mark	N/A
FCC ID	2AQMY-ZR303RX
Model No.	ZR303RX
Serial Model	ZR313RX, ZR323RX, ZR333RX, ZR343RX, ZR353RX, ZR363RX, ZR373RX, ZR383RX, ZR393RX, ZR201RX, ZR202RX, ZR301RX, ZR302RX, ZR601RX, ZR602RX, ZR603RX, ZR650RX, ZR651RX, ZR660RX, ZR870RX, ZR871RX, ZR880RX
Model Difference	All models are the same circuit and RF module, except the model name.
Operating Frequency	2407.5MHz~2471.625MHz
Modulation	GFSK
Number of Channels	20 Channels
Antenna Type	Cable Antenna
Antenna Gain	2 dBi
Power supply	<input checked="" type="checkbox"/> DC supply: DC 3.7V/600mAh from battery or DC 5V from adapter
	<input checked="" type="checkbox"/> Adapter supply: Model: G051U-050100B-1 Input: 100-240V~50-60Hz 0.25A Output: 5---1.0A
HW Version	EMGL-A20-V1.0
SW Version	V2.0.4

Note: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.

Revision History

5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

Carrier Frequency and Channel list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2407.5	11	2441.25
2	2410.875	12	2444.625
3	2414.25	13	2448
4	2417.625	14	2451.375
5	2421	15	2454.75
6	2424.375	16	2458.125
7	2427.75	17	2461.5
8	2431.125	18	2464.875
9	2434.5	19	2468.25
10	2437.875	20	2471.625

The following summary table is showing all test modes to demonstrate in compliance with the standard.

For AC Conducted Emission

Final Test Mode	Description
Mode 1	normal link mode

Note: AC power line Conducted Emission was tested under maximum output power.

For Radiated Test Cases

Final Test Mode	Description
Mode 1	normal link mode
Mode 2	CH01(2407.5MHz)
Mode 3	CH11(2441.25MHz)
Mode 4	CH20(2471.625MHz)

For Conducted Test Cases

Final Test Mode	Description
Mode 2	CH01(2407.5MHz)
Mode 3	CH11(2441.25MHz)
Mode 4	CH20(2471.625MHz)
Mode 5	Hopping mode


Note: The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.

1. AC power line Conducted Emission was tested under maximum output power.


6 SETUP OF EQUIPMENT UNDER TEST

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM


For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note: 1. The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

6.2 SUPPORT EQUIPMENT

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Wireless baby monitor receiver	N/A	ZR303RX	N/A	EUT
E-2	Wireless baby monitor transmitter	N/A	ZR303TX	N/A	
E-3	Adapter	N/A	G051U-050100B-1	N/A	
E-4	Adapter	N/A	G051U-050100B-1	N/A	

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	Power Cable	NO	NO	2.5m
C-2	Power Cable	NO	NO	2.5m
C-3	RF Cable	NO	NO	0.5m

Notes:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".

6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2018.05.19	2019.05.18	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2017.10.26	2018.10.25	1 year
3	EMI Test Receiver	Agilent	N9038A	MY53227146	2018.05.19	2019.05.18	1 year
4	Test Receiver	R&S	ESPI	101318	2018.05.19	2019.05.18	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2018.04.08	2019.04.07	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2018.05.19	2019.05.18	1 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2018.04.08	2019.04.07	1 year
8	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2018.05.19	2019.05.18	1 year
9	Amplifier	EMC	EMC051835 SE	980246	2017.08.09	2018.08.08	1 year
10	Amplifier	MITEQ	TTA1840-35-HG	177156	2018.05.19	2019.05.18	1 year
11	Loop Antenna	ARA	PLA-1030/B	1029	2018.05.19	2019.05.18	1 year
12	Power Meter	DARE	RPR3006W	15100041SN 084	2017.08.07	2018.08.06	1 year
13	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2017.04.21	2020.04.20	3 year
14	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2017.04.21	2020.04.20	3 year
15	High Test Cable(1G-40GHz)	N/A	R-03	N/A	2017.04.21	2020.04.20	3 year
16	High Test Cable(1G-40GHz)	N/A	R-04	N/A	2017.04.21	2020.04.20	3 year
17	Filter	TRILTHIC	2400MHz	29	2018.03.29	2019.03.28	1 year
18	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2018.05.19	2019.05.18	1 year
2	LISN	R&S	ENV216	101313	2018.04.18	2019.04.19	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2018.05.19	2019.05.18	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2018.05.19	2019.05.18	1 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2017.04.21	2020.04.20	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2017.04.21	2020.04.20	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2017.04.21	2020.04.20	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable which is scheduled for calibration every 3 years.

7 TEST REQUIREMENTS

7.1 CONDUCTED EMISSIONS TEST

7.1.1 Applicable Standard


According to FCC Part 15.207(a) and KDB 174176 D01 Line Conducted FAQ v01r01

7.1.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
 2. The lower limit shall apply at the transition frequencies
 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

7.1.3 Test Configuration



7.1.4 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

7.1.5 Test Results

Pass


7.1.6 Test Results

EUT:	Wireless baby monitor receiver	Model Name :	ZR303RX
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode:	Mode 1

Frequency (MHz)	Reading Level (dB μ V)	Correct Factor (dB)	Measure-ment (dB μ V)	Limits (dB μ V)	Margin (dB)	Remark
0.5220	36.75	9.74	46.49	56.00	-9.51	AVG
0.5220	26.99	9.74	36.73	46.00	-9.27	QP
1.1339	29.47	9.74	39.21	56.00	-16.79	QP
1.1699	20.58	9.74	30.32	46.00	-15.68	AVG
1.4539	30.05	9.76	39.81	56.00	-16.19	QP
1.4659	20.20	9.76	29.96	46.00	-16.04	AVG
1.7059	19.52	9.77	29.29	46.00	-16.71	AVG
1.7179	29.06	9.77	38.83	56.00	-17.17	QP
2.4700	24.62	9.79	34.41	46.00	-11.59	AVG
2.4780	34.44	9.79	44.23	56.00	-11.77	QP
4.2458	29.63	9.85	39.48	56.00	-16.52	QP
4.2819	19.71	9.86	29.57	46.00	-16.43	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	Wireless baby monitor receiver	Model Name :	ZR303RX
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode:	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dB μ V)	(dB)	(dB μ V)	(dB μ V)	(dB)	
0.5180	39.64	9.75	49.39	56.00	-6.61	QP
0.5180	30.33	9.75	40.08	46.00	-5.92	AVG
1.1180	32.75	9.75	42.50	56.00	-13.50	QP
1.1459	22.84	9.75	32.59	46.00	-13.41	AVG
1.4179	33.22	9.76	42.98	56.00	-13.02	QP
1.4179	23.80	9.76	33.56	46.00	-12.44	AVG
1.6699	21.89	9.78	31.67	46.00	-14.33	AVG
1.6819	32.35	9.78	42.13	56.00	-13.87	QP
2.5819	36.68	9.83	46.51	56.00	-9.49	QP
2.5819	25.42	9.83	35.25	46.00	-10.75	AVG
4.2138	21.98	9.92	31.90	46.00	-14.10	AVG
4.3098	31.74	9.93	41.67	56.00	-14.33	QP

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	Wireless baby monitor receiver	Model Name :	ZR303RX
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC 5V from Adapter AC 240V/60Hz	Test Mode:	Mode 1

Frequency (MHz)	Reading Level (dB μ V)	Correct Factor (dB)	Measure-ment (dB μ V)	Limits (dB μ V)	Margin (dB)	Remark
0.4179	22.97	9.74	32.71	47.49	-14.78	AVG
0.4339	31.76	9.74	41.50	57.18	-15.68	QP
0.5180	27.55	9.74	37.29	46.00	-8.71	AVG
0.5220	37.27	9.74	47.01	56.00	-8.99	QP
1.0020	33.09	9.74	42.83	56.00	-13.17	QP
1.0540	24.35	9.74	34.09	46.00	-11.91	AVG
1.5420	23.68	9.77	33.45	46.00	-12.55	AVG
1.5500	32.84	9.77	42.61	56.00	-13.39	QP
2.3420	26.47	9.79	36.26	46.00	-9.74	AVG
2.4100	34.30	9.79	44.09	56.00	-11.91	QP
4.1498	32.93	9.85	42.78	56.00	-13.22	QP
4.2019	24.28	9.85	34.13	46.00	-11.87	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	Wireless baby monitor receiver	Model Name :	ZR303RX
Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase :	N
Test Voltage :	DC 5V from Adapter AC 240V/60Hz	Test Mode:	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dB μ V)	(dB)	(dB μ V)	(dB μ V)	(dB)	
0.4420	24.36	9.75	34.11	47.02	-12.91	AVG
0.4460	34.50	9.75	44.25	56.95	-12.70	QP
0.5140	30.01	9.75	39.76	46.00	-6.24	AVG
0.5220	39.12	9.75	48.87	56.00	-7.13	QP
1.0100	35.23	9.75	44.98	56.00	-11.02	QP
1.0500	26.69	9.75	36.44	46.00	-9.56	AVG
1.5540	27.65	9.78	37.43	46.00	-8.57	AVG
1.5620	35.59	9.78	45.37	56.00	-10.63	QP
2.3380	36.61	9.81	46.42	56.00	-9.58	QP
2.3380	29.26	9.81	39.07	46.00	-6.93	AVG
4.0939	34.98	9.92	44.90	56.00	-11.10	QP
4.1539	26.79	9.92	36.71	46.00	-9.29	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



7.2 RADIATED SPURIOUS EMISSION

7.2.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and ANSI C63.10-2013

7.2.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μ V/m)	Field Strength (dB μ V/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (μ V/m)	300
0.490~1.705	2400/F(KHz)	20 log (μ V/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dB μ V/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dB μ V/m=20 log (μ V/m)


2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. Distance extrapolation factor =40log(Specific distance/ test distance)(dB);
Limit line=Specific limits(dB μ V) + distance extrapolation factor.

7.2.3 Measuring Instruments


The Measuring equipment is listed in the section 6.3 of this test report.

7.2.4 Test Configuration


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



7.2.5 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz]/\text{narrower RBW [kHz]})$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

7.2.6 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

EUT:	Wireless baby monitor receiver	Model No.:	ZR303RX
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Loren Luo

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $20 \log(\text{Specific distance} / \text{test distance})$ (dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission below 1GHz (30MHz to 1GHz)


All the modulation modes have been tested, and the worst result was report as below:

EUT:	Wireless baby monitor receiver	Model Name :	ZR303RX
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010hPa	Test Mode:	Mode 1
Test Voltage :	DC 5V from Adapter AC 120V/60Hz		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	122.4038	26.13	13.25	39.38	43.50	-4.12	QP
V	128.1128	27.81	13.40	41.21	43.50	-2.29	QP
V	133.1511	27.96	13.41	41.37	43.50	-2.13	QP
V	149.4857	26.61	12.81	39.42	43.50	-4.08	QP
V	170.7923	25.30	11.27	36.57	43.50	-6.93	QP
V	229.2931	28.32	12.11	40.43	46.00	-5.57	QP

Remark:


Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	128.1129	19.70	13.40	33.10	43.50	-10.40	QP
H	138.8735	20.50	13.32	33.82	43.50	-9.68	QP
H	207.8500	21.79	10.83	32.62	43.50	-10.88	QP
H	223.7333	23.63	12.02	35.65	46.00	-10.35	QP
H	234.9909	23.88	12.35	36.23	46.00	-9.77	QP
H	815.9678	10.25	27.41	37.66	46.00	-8.34	QP

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



■ Spurious Emission Above 1GHz (1GHz to 25GHz)

EUT:	Wireless baby monitor receiver	Model No.:	ZR303RX
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Loren Luo

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Read Level (dB μ V)	Cable loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Remark	Comment
Low Channel (2407.5 MHz)(GFSK)--Above 1G									
4815.236	59.63	5.21	35.59	44.30	56.13	74.00	-17.87	Pk	Vertical
4815.236	40.66	5.21	35.59	44.30	37.16	54.00	-16.84	AV	Vertical
7222.159	59.90	6.48	36.27	44.60	58.05	74.00	-15.95	Pk	Vertical
7222.159	41.69	6.48	36.27	44.60	39.84	54.00	-14.16	AV	Vertical
4815.636	61.97	5.21	35.55	44.30	58.43	74.00	-15.57	Pk	Horizontal
4815.636	41.71	5.21	35.55	44.30	38.17	54.00	-15.83	AV	Horizontal
7222.248	59.72	6.48	36.27	44.52	57.95	74.00	-16.05	Pk	Horizontal
7222.248	41.51	6.48	36.27	44.52	39.74	54.00	-14.26	AV	Horizontal
Mid Channel (2441.25 MHz)(GFSK)--Above 1G									
4882.572	62.28	5.21	35.66	44.20	58.95	74.00	-15.05	Pk	Vertical
4882.572	40.91	5.21	35.66	44.20	37.58	54.00	-16.42	AV	Vertical
7323.759	59.79	7.10	36.50	44.43	58.96	74.00	-15.04	Pk	Vertical
7323.759	42.12	7.10	36.50	44.43	41.29	54.00	-12.71	AV	Vertical
4882.538	60.25	5.21	35.66	44.20	56.92	74.00	-17.08	Pk	Horizontal
4882.538	42.14	5.21	35.66	44.20	38.81	54.00	-15.19	AV	Horizontal
7323.749	62.02	7.10	36.50	44.43	61.19	74.00	-12.81	Pk	Horizontal
7323.749	40.88	7.10	36.50	44.43	40.05	54.00	-13.95	AV	Horizontal
High Channel (2471.625 MHz)(GFSK)-- Above 1G									
4943.256	61.65	5.21	35.52	44.21	58.17	74.00	-15.83	Pk	Vertical
4943.256	40.19	5.21	35.52	44.21	36.71	54.00	-17.29	AV	Vertical
7414.873	61.98	7.10	36.53	44.60	61.01	74.00	-12.99	Pk	Vertical
7414.873	40.98	7.10	36.53	44.60	40.01	54.00	-13.99	AV	Vertical
4943.261	62.02	5.21	35.52	44.21	58.54	74.00	-15.46	Pk	Horizontal
4943.261	41.26	5.21	35.52	44.21	37.78	54.00	-16.22	AV	Horizontal
7414.877	61.24	7.10	36.53	44.60	60.27	74.00	-13.73	Pk	Horizontal
7414.877	40.31	7.10	36.53	44.60	39.34	54.00	-14.66	AV	Horizontal

Note: (1) All Readings are Peak Value (VBW=3MHz) and AV Value (VBW=10Hz).

(2) Emission Level= Antenna Factor + Cable Loss + Read Level - Preamp Factor

(3) All other emissions more than 20dB below the limit.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

EUT:	Wireless baby monitor receiver	Model No.:	ZR303RX
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4	Test By:	Loren Luo

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Meter Reading (dB μ V)	Cable Loss (dB)	Antenna Factor dB/m	Preamp Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector Type	Comment
(GFSK)- Non-hopping									
2310.00	59.61	2.97	27.80	43.80	46.58	74	-27.42	Pk	Horizontal
2310.00	42.67	2.97	27.80	43.80	29.64	54	-24.36	AV	Horizontal
2310.00	59.96	2.97	27.80	43.80	46.93	74	-27.07	Pk	Vertical
2310.00	41.91	2.97	27.80	43.80	28.88	54	-25.12	AV	Vertical
2390.00	61.89	3.14	27.21	43.80	48.44	74	-25.56	Pk	Vertical
2390.00	39.74	3.14	27.21	43.80	26.29	54	-27.71	AV	Vertical
2390.00	60.26	3.14	27.21	43.80	46.81	74	-27.19	Pk	Horizontal
2390.00	39.65	3.14	27.21	43.80	26.20	54	-27.80	AV	Horizontal
2483.50	60.33	3.58	27.70	44.00	47.61	74	-26.39	Pk	Vertical
2483.50	40.14	3.58	27.70	44.00	27.42	54	-26.58	AV	Vertical
2483.50	60.50	3.58	27.70	44.00	47.78	74	-26.22	Pk	Horizontal
2483.50	40.20	3.58	27.70	44.00	27.48	54	-26.52	AV	Horizontal
(GFSK)- hopping									
2310.00	59.82	2.97	27.80	43.80	46.79	74	-27.21	Pk	Horizontal
2310.00	42.64	2.97	27.80	43.80	29.61	54	-24.39	AV	Horizontal
2310.00	60.71	2.97	27.80	43.80	47.68	74	-26.32	Pk	Vertical
2310.00	42.95	2.97	27.80	43.80	29.92	54	-24.08	AV	Vertical
2390.00	60.97	3.14	27.21	43.80	47.52	74	-26.48	Pk	Vertical
2390.00	39.82	3.14	27.21	43.80	26.37	54	-27.63	AV	Vertical
2390.00	59.70	3.14	27.21	43.80	46.25	74	-27.75	Pk	Horizontal
2390.00	42.39	3.14	27.21	43.80	28.94	54	-25.06	AV	Horizontal
2483.50	62.13	3.58	27.70	44.00	49.41	74	-24.59	Pk	Vertical
2483.50	40.06	3.58	27.70	44.00	27.34	54	-26.66	AV	Vertical
2483.50	61.50	3.58	27.70	44.00	48.78	74	-25.22	Pk	Horizontal
2483.50	40.16	3.58	27.70	44.00	27.44	54	-26.56	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

■ Spurious Emission in Restricted Band 3260MMHz-18000MHz

EUT:	Wireless baby monitor receiver	Model No.:	ZR303RX
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4	Test By:	Loren Luo

All the modulation modes have been tested, and the worst result was report as below:

Frequency (MHz)	Reading Level (dB μ V)	Cable Loss (dB)	Antenna dB/m	Preamp Factor (dB)	Emission Level (dB μ V/m)	Limits (dB)	Margin (dB)	Detector Type	Comment
3260	61.62	4.04	29.57	44.70	50.53	74	-23.47	Pk	Vertical
3260	51.73	4.04	29.57	44.70	40.64	54	-13.36	AV	Vertical
3260	60.16	4.04	29.57	44.70	49.07	74	-24.93	Pk	Horizontal
3260	49.22	4.04	29.57	44.70	38.13	54	-15.87	AV	Horizontal
3332	60.45	4.26	29.87	44.40	50.18	74	-23.82	Pk	Vertical
3332	49.66	4.26	29.87	44.40	39.39	54	-14.61	AV	Vertical
3332	61.93	4.26	29.87	44.40	51.66	74	-22.34	Pk	Horizontal
3332	48.76	4.26	29.87	44.40	38.49	54	-15.51	AV	Horizontal
17797	41.47	10.99	43.95	43.50	52.91	74	-21.09	Pk	Vertical
17797	30.74	10.99	43.95	43.50	42.18	54	-11.82	AV	Vertical
17788	39.99	11.81	43.69	44.60	50.89	74	-23.11	Pk	Horizontal
17788	29.66	11.81	43.69	44.60	40.56	54	-13.44	AV	Horizontal

Note: (1) All other emissions more than 20dB below the limit.

7.3 NUMBER OF HOPPING CHANNEL

7.3.1 Applicable Standard

According to FCC Part 15.247(a)(1) (iii) and ANSI C63.10-2013

7.3.2 Conformance Limit

Frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

7.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.3.4 Test Setup

Please refer to Section 6.1 of this test report.

7.3.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.3

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW : To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW \geq RBW

Sweep = auto


Detector function = peak

Trace = max hold

7.3.6 Test Results

EUT:	Wireless baby monitor receiver	Model No.:	ZR303RX
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode 5(1Mbps)	Test By:	Loren Luo

Number of Hopping (Channel)	limit	Verdict
20	≥ 15	Pass



7.4 HOPPING CHANNEL SEPARATION MEASUREMENT

7.4.1 Applicable Standard

According to FCC Part 15.247(a)(1) and ANSI C63.10-2013

7.4.2 Conformance Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5MHz band shall have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

7.4.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.4.4 Test Setup

Please refer to Section 6.1 of this test report.

7.4.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.2

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = Measurement Bandwidth or Channel Separation

RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold


7.4.6 Test Results

EUT:	Wireless baby monitor receiver	Model No.:	ZR303RX
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Loren Luo


Modulation Mode	Channel Number	Channel Frequency (MHz)	Measured Channel Separation (kHz)	Limit (kHz)		Verdict
GFSK	01	2407.5	3373	>2371.333	2/3 of 20dB BW	PASS
	11	2441.25	3373	>2518.667	2/3 of 20dB BW	PASS
	20	2471.625	3373	>2527.333	2/3 of 20dB BW	PASS

Test Plot


(1Mbps) Channel Separation plot on channel 01



(1Mbps) Channel Separation plot on channel 11



(1Mbps) Channel Separation plot on channel 20



7.5 AVERAGE TIME OF OCCUPANCY (DWELL TIME)

7.5.1 Applicable Standard

According to FCC Part 15.247(a)(1)(iii) and ANSI C63.10-2013

7.5.2 Conformance Limit

The average time of occupancy on any channel shall not be greater than 0.4s within a period of 0.4s multiplied by the number of hopping channels employed.

7.5.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.5.4 Test Setup

Please refer to Section 6.1 of this test report.

7.5.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.4

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW \geq 1MHz

VBW \geq RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold

Measure the maximum time duration of one single pulse.

7.5.6 Test Results

EUT:	Wireless baby monitor receiver	Model No.:	ZR303RX
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode3	Test By:	Loren Luo

Modulation Mode	Channel Number	Accumulated Transmit Time per Hop	Accumulated Dwell Time	Limit	Verdict
		(ms)	(ms)		
GFSK	11	0.113	2.930	<400	PASS


Note:

A Period Time = (channel number)*0.4=20*0.4=8s


Accumulated Dwell Time=A Period Time hopping number* Single Burst Pulse Width

Test Plot

Single Burst Pulse Width



A Period Time hopping number



7.6 20DB BANDWIDTH TEST

7.6.1 Applicable Standard

According to FCC Part 15.247(a)(1) and ANSI C63.10-2013

7.6.2 Conformance Limit

No limit requirement.

7.6.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.6.4 Test Setup

Please refer to Section 6.1 of this test report.

7.6.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 6.9.2

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW \geq 1% of the 20 dB bandwidth

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

7.6.6 Test Results

EUT:	Wireless baby monitor receiver	Model No.:	ZR303RX
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Loren Luo

Test Channel	Frequency (MHz)	Measured Bandwidth (KHz)	Limit	Verdict
			(kHz)	
1Mbps				
01	2407.5	3557	N/A	PASS
11	2441.25	3778	N/A	PASS
20	2471.625	3791	N/A	PASS

Note: N/A (Not Applicable)

Test Plot


20dB Bandwidth plot on channel 01 (1Mbps)



20dB Bandwidth plot on channel 11 (1Mbps)



20dB Bandwidth plot on channel 20 (1Mbps)



7.7 PEAK OUTPUT POWER

7.7.1 Applicable Standard

According to FCC Part 15.247(b)(1) and ANSI C63.10-2013

7.7.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.

7.7.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.7.4 Test Setup

Please refer to Section 6.1 of this test report.

7.7.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.5.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW \geq the 20 dB bandwidth of the emission being measured

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

7.7.6 Test Results

EUT:	Wireless baby monitor receiver	Model No.:	ZR303RX
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Loren Luo


Test Channel	Frequency (MHz)	Power Setting	Peak Output Power	LIMIT (dBm)	Verdict
			(dBm)		
1Mbps					
01	2407.5	Default	0.54	20.97	PASS
11	2441.25	Default	1.15	20.97	PASS
20	2471.625	Default	1.72	20.97	PASS

Test Plot


Peak output Power plot on channel 01 (1Mbps)



Peak output Power plot on channel 11 (1Mbps)



Peak output Power plot on channel 20 (1Mbps)



7.8 CONDUCTED BAND EDGE MEASUREMENT

7.8.1 Applicable Standard

According to FCC Part 15.247(d) and ANSI C63.10-2013

7.8.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.8.4 Test Setup

Please refer to Section 6.1 of this test report.

7.8.5 Test Procedure

The testing follows ANSI C63.10-2013 clause 7.8.6.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = 100KHz

VBW = 300KHz

Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.

Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.


Repeat above procedures until all measured frequencies were complete.

7.8.6 Test Results


EUT:	Wireless baby monitor receiver	Model No.:	ZR303RX
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2 /Mode4/ Mode 5	Test By:	Loren Luo

Test Plot


GFSK: Band Edge-Low Channel




GFSK: Band Edge-High Channel



GFSK: Band Edge-Low Channel (Hopping Mode)



GFSK: Band Edge-High Channel (Hopping Mode)



7.9 SPURIOUS RF CONDUCTED EMISSION

7.9.1 Applicable Standard

According to FCC Part 15.247(d) and ANSI C63.10-2013.

7.9.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.9.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.9.4 Test Setup

Please refer to Section 6.1 of this test report.

7.9.5 Test Procedure

Establish an emission level by using the following procedure:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.


Then the limit shall be attenuated by at least 20 dB relative to the maximum amplitude level in 100 kHz.

7.9.6 Test Results


Remark: The measurement frequency range is from 9KHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandge measurement data.

Test Plot(GFSK)


GFSK on channel 01




GFSK on channel 01



GFSK on channel 01




GFSK on channel 01




Test Plot


GFSK on channel 11




GFSK on channel 11



GFSK on channel 11




GFSK on channel 11




Test Plot


GFSK on channel 20




GFSK on channel 20



GFSK on channel 20



GFSK on channel 20



7.10 ANTENNA APPLICATION

7.10.1 Antenna Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.10.2 Result

The EUT antenna is permanent attached Cable antenna (Gain:2dBi). It comply with the standard requirement.

END OF REPORT