

RF Exposure evaluation

FCC ID: 2AQQS-T1810

1. Reference

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}$

Where:

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

2. Test distance

As the plot exhibit below, the distance of body to the Antenna plane is 50mm.

3. Result

As the antenna EUT used was 2dBi and the Max field strength level measured with duty cycle $\geq 98\%$ in EMI test report, the sar exclusion value can obtained.

According to the formula described above:

The value is within the tune up $\pm 0.2\text{dB}$ stated by the manufacturer

Worse case is as below:

Frequency (MHz)	TX Power (mw)	TX Power with tune-up (mw)	Separation Distance (mm)	calculated value	exclusion thresholds
462.6125	510	533	50	7.25	7.5

4. Conclusion

The Extremity SAR evaluation is not required.