

FCC 47 CFR MPE REPORT

LEVO Oil Infusion Inc.

Oil Infuser

Model Number: LEVO II Alpine

Additional Model: LEVO II Cayenne, LEVO II Jet, LEVO II Robin,
LEVO II Meyer

FCC ID: 2AQQX857722

| | |
|--------------------------|---|
| Prepared for: | LEVO Oil Infusion Inc. |
| | 3000 Lawrence Street Suite #10, Denver, Colorado 80205, United States |
| | |
| Prepared By: | EST Technology Co., Ltd. |
| | Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China |
| Tel: 86-769-83081888-808 | |

| | |
|-----------------|-------------------------|
| Report Number: | ESTE-R1810014 |
| Date of Test: | Jul. 25 ~ Oct. 08, 2018 |
| Date of Report: | Oct. 09, 2018 |



Maximum Permissible Exposure

1、 Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、 Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength E (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Times E 2 , H 2 or S (minutes) |
|-----------------------|---------------------------------|-----------------------------------|---|--|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842/f | 4.89/f | (900/f)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | | | F/300 | 6 |
| 1500-10000 | | | 5 | 6 |

(b)、 Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength E (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Times E 2 , H 2 or S (minutes) |
|-----------------------|---------------------------------|-----------------------------------|---|--|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | | | F/1500 | 30 |
| 1500-10000 | | | 1.0 | 30 |

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、 MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

3、Conducted Power Result

| Mode | Frequency (MHz) | Peak output power (dBm) | Peak output power (mW) | Target power (dBm) | Antenna gain | |
|-------------------|-----------------|-------------------------|------------------------|--------------------|--------------|----------|
| | | | | | (dBi) | (Linear) |
| IEEE 802.11b | 2412 | 10.74 | 11.858 | 10±1 | 1.5 | 1.413 |
| | 2437 | 10.03 | 10.069 | 10±1 | 1.5 | 1.413 |
| | 2462 | 10.28 | 10.666 | 10±1 | 1.5 | 1.413 |
| IEEE 802.11g | 2412 | 5.78 | 3.784 | 5±1 | 1.5 | 1.413 |
| | 2437 | 5.53 | 3.573 | 5±1 | 1.5 | 1.413 |
| | 2462 | 5.59 | 3.622 | 5±1 | 1.5 | 1.413 |
| IEEE 802.11n HT20 | 2412 | 5.11 | 3.243 | 5±1 | 1.5 | 1.413 |
| | 2437 | 4.74 | 2.979 | 4±1 | 1.5 | 1.413 |
| | 2462 | 4.52 | 2.831 | 4±1 | 1.5 | 1.413 |

4、Calculated Result and Limit

| Mode | Target power (dBm) | Antenna gain | | Power Density (S) (mW/cm ²) | Limited of Power Density (S) (mW/cm ²) | Test Result |
|-------------------|--------------------|--------------|----------|---|--|-------------|
| | | (dBi) | (Linear) | | | |
| Wi-Fi | | | | | | |
| IEEE 802.11b | 11 | 1.5 | 1.413 | 0.00354 | 1 | Compiles |
| IEEE 802.11g | 6 | 1.5 | 1.413 | 0.00112 | 1 | Compiles |
| IEEE 802.11n HT20 | 6 | 1.5 | 1.413 | 0.00112 | 1 | Compiles |