

FCC 47 CFR MPE REPORT

LEVO Oil Infusion Inc.

Oil Infuser Lux

Model Number: Levo Lux

FCC ID: 2AQQX857722008

Prepared for:	LEVO Oil Infusion Inc.
	66 S Logan St. Denver, Colorado 80209, United States
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2108243
Date of Test:	May. 06~Aug. 26, 2021
Date of Report:	Aug. 27, 2021

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11b	2412	19.37	86.497	19 ± 1	1.5	1.413
	2437	19.08	80.910	19 ± 1	1.5	1.413
	2462	18.92	77.983	18 ± 1	1.5	1.413
IEEE 802.11g	2412	22.55	179.887	22 ± 1	1.5	1.413
	2437	22.23	167.109	22 ± 1	1.5	1.413
	2462	22.20	165.959	22 ± 1	1.5	1.413
IEEE 802.11n HT20	2412	22.22	166.725	22 ± 1	1.5	1.413
	2437	22.03	159.588	22 ± 1	1.5	1.413
	2462	21.98	157.761	21 ± 1	1.5	1.413

3. Calculated Result and Limit

Antenna 0

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
		(dBi)	(Linear)			
2.4G Band						
IEEE 802.11b	20	1.5	1.413	0.02810	1	Complies
IEEE 802.11g	23	1.5	1.413	0.05607	1	Complies
IEEE 802.11n HT20	23	1.5	1.413	0.05607	1	Complies

End of Test Report