

FCC CFR47 PART 22H, 24E, 27, CERTIFICATION TEST REPORT FCC ID: 2AQR9-PDA-GS0533W

Product: PDA-GS0533W

Trade Mark: N/A

Model No.: PDA-GS0533W

Family Model: N/A

Report No.: S23042405702006

Issue Date: May 24, 2023

Prepared for

Shenzhen Geshem Technology Co.,Ltd
2/F,Chuangye Building,No.5 North 2ndLane,Chuangye 2nd Road,28th Area
Bao'anDistrict,Shenzhen,Guangdong,China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community,
Xixiang Street Bao'an District, Shenzhen 518126 P.R. China
Tel. 400-800-6106, 0755-2320 0050, 0755-2320 0090
Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name : Shenzhen Geshem Technology Co.,Ltd

Address..... : 2/F,Chuangye Building,No.5 North 2nd Lane,Chuangye 2nd Road,28th Area Bao'an District,Shenzhen,Guangdong,China

Manufacturer's Name..... : Shenzhen Geshem Technology Co.,Ltd

Address..... : 2/F,Chuangye Building,No.5 North 2nd Lane,Chuangye 2nd Road,28th Area Bao'an District,Shenzhen,Guangdong,China

Product name..... : PDA-GS0533W

Model and/or type reference .. : PDA-GS0533W

Trade Mark..... : N/A

Family Model..... : N/A

Test Sample Number..... : S230424057002

Standards..... : FCC CFR 47 Part 22H, Part 24E, Part 27

Test procedure : ANSI C63.26:2015
ANSI/TIA-603-E-2016

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests..... Apr 25, 2023 ~ May 24, 2023

Date of Issue May 24, 2023

Test Result..... **Pass**

Testing Engineer : _____



(Allen Liu)

Authorized Signatory : _____



(Alex Li)

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	5
1. GENERAL INFORMATION.....	5
1.1 PRODUCT DESCRIPTION	5
1.2 RELATED SUBMITTAL(S) / GRANT (S)	6
1.3 TEST METHODOLOGY.....	6
1.4 TEST FACILITY.....	6
MEASUREMENT UNCERTAINTY	6
1.5 SPECIAL ACCESSORIES.....	6
1.6 WORST-CASE CONFIGURATION AND MODE.....	6
2. SYSTEM TEST CONFIGURATION	7
2.1 EUT CONFIGURATION.....	7
2.2 EUT EXERCISE	7
2.3 CONFIGURATION OF EUT SYSTEM.....	7
2.4 TEST SETUP	8
3.TEST AND MEASUREMENT EQUIPMENT	9
4. OUTPUT POWER.....	11
4.1 OUTPUT POWER MEASUREMENT	11
6. BANDEDGE AND EMISSION MASK.....	14
7. OUT OF BAND EMISSIONS	16
7.1 MEASUREMENT METHOD	16
8. RADIATED MEASUREMENT	17
8.1. RADIATED POWER (ERP & EIRP).....	17
8.2 LTE BAND 2.....	18

8.3 LTE BAND 4.....	22
8.4 LTE BAND 5.....	26
8.5 LTE BAND 12	28
8.6 LTE BAND 17	30
9. SPURIOUS RADIATION EMISSION	32
9.1 LTE BAND 2.....	34
9.2 LTE BAND 4.....	36
9.3 LTE BAND 5.....	38
9.4 LTE BAND 12	40
9.5 LTE BAND 17	42
10. FREQUENCY STABILITY	44
10.1 LTE BAND 2	45
10.2 LTE BAND 4	47
10.3 LTE BAND 5	49
10.4 LTE BAND 12	51
10.5 LTE BAND 17	53
11. PEAK-TO-AVERAGE RATIO.....	55
11.1 Description of the PAR Measurement.....	55
11.2 Measuring Instruments	55
11.3 Test Procedures.....	55
11.4 Test Setup.....	56

1. GENERAL INFORMATION

1.1 PRODUCT DESCRIPTION

A major technical description of EUT is described as following:

Product Designation:	PDA-GS0533W
Trade Mark	N/A
Model Name	PDA-GS0533W
Family Model	N/A
Model Difference	N/A
FCC ID:	2AQR9-PDA-GS0533W
Frequency Bands:	U.S. Bands: ☒ LTE FDD Band 2,4,5,12, 17
Frequency Range:	LTE FDD Band 2 Uplink: 1850MHz-1910MHz, Downlink: 1930MHz-1990MHz; LTE FDD Band 4 Uplink: 1710MHz-1755MHz, Downlink: 2110MHz-2155MHz; LTE FDD Band 5 Uplink: 824MHz-849MHz, Downlink: 869MHz-894MHz; LTE FDD Band 12 Uplink: 699MHz-716MHz, Downlink: 729MHz-746MHz; LTE FDD Band 17 Uplink: 704MHz-716MHz, Downlink: 734MHz-746MHz;
Type of Modulation:	QPSK/16QAM/64QAM(Only Downlink)
Power Class	Class 3
SIM CARD	SIM 1 and SIM 2 is a chipset unit and tested as a single chipset. The SIM 1 is chosen for test.
Antenna:	PIFA Antenna
Antenna gain:	Band2:0.64dBi; Band4:-1.42dBi; Band5:-1.92dBi; Band12:-1.92dBi; Band17:-1.92dBi;
Adapter	Model: JJY-0502000-US Input: 100-240V~50/60Hz 0.3A Output: 5.0V---2.0A
Battery	DC 3.8V, 4800mAh
Power supply	DC 3.8V from battery or DC 5V from Adapter.
Extreme Vol. Limits:	DC 3.4V to DC 4.2V (Nominal DC 3.87V) (Note 1)
HW Version	N/A
SW Version	N/A
** Note1: The High Voltage DC 4.2V and Low Voltage 3.4V was declared by manufacturer, The EUT couldn't be operate normally with higher or lower voltage.	

1.2 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2AQR9-PDA-GS0533W** filing to comply with the FCC Part 22H&24E&27.

1.3 TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI/TIA-603-E-2016, FCC CFR 47 Part 2, Part 22, Part 24, Part 27, ,ANSI C63.26:2015.

1.4 TEST FACILITY

The test site used to collect the radiated data is located at:

ShenZhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R.China.

The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.26:2015& ANSI C63.4: 2014.

FCC Registration No.:463705

IC Registration No.:9270A-1,

CNAS Registration No.:L5516

MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.5dB

1.5 SPECIAL ACCESSORIES

The battery and the charger, earphone supplied by the applicant were used as accessories and being tested with EUT intended for FCC grant together.

1.6 WORST-CASE CONFIGURATION AND MODE

The worst-case scenario for all measurements is based on the investigation results.

The device has LTE Bands of: Band 2/4/5/12/17

The RB Size was selected to measure for peak or average ERP and EIRP, which was based on the conducted power verification baseline data.

For the fundamental investigation of radiated emissions, the EUT is investigated for vertical and horizontal antenna orientations and X Y and Z orientations of the EUT alone. After the investigations the worst case was determined to be at X orientation for all LTE bands.

2. SYSTEM TEST CONFIGURATION

2.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT EXERCISE

The Transmitter was operated in the maximum output power mode through Communication Tester. The TX frequency was fixed which was for the purpose of the measurements.

2.3 CONFIGURATION OF EUT SYSTEM

Table 2-1 Equipment Used in EUT System

Item	Equipment	Model No.	ID or Specification	Note
1	PDA-GS0533W	PDA-GS0533W	FCC ID: 2AQR9-PDA-GS0533W	EUT


*Note: All the accessories have been used during the test.
the following "EUT" in setup diagram means EUT system.*

2.4 TEST SETUP


For Radiated Test Cases




For Conducted Output Power



For Peak-to Average Ratio, Occupied Bandwidth, Conducted Band edge and Conducted Spurious Emission



For Frequency Stability



Note: EUT built-in battery-powered, the battery is fully-charged.

3.TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	MXA Signal Analyzer	Agilent	N9020A	MY49100060	2022.06.17	2023.06.16	1 year
2	Test Receiver	R&S	ESPI	101318	2023.03.27	2024.03.26	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2023.03.27	2024.03.26	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2020.05.11 2023.05.06	2023.05.10 2026.05.05	3 year
5	Horn Antenna	EM	EM-AH-10180	2011071402	2023.03.27	2024.03.26	1 year
6	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2022.06.17	2023.06.16	1 year
7	Amplifier	EM	EM-30180	060538	2022.06.17	2023.06.16	1 year
8	Loop Antenna	ARA	PLA-1030/B	1029	2023.03.27	2024.03.26	1 year
9	Power Meter	R&S	NRVS	100696	2022.06.17	2023.06.16	1 year
10	Power Sensor	R&S	URV5-Z4	0395.1619.05	2023.03.27	2024.03.26	1 year
11	Test Cable	N/A	R-01	N/A	2022.06.17	2025.06.16	3 year
12	Test Cable	N/A	R-02	N/A	2022.06.17	2025.06.16	3 year
13	Test Cable	N/A	R-03	N/A	2022.06.17	2025.06.16	3 year
14	Test Receiver	R&S	ESCI	101160	2023.03.27	2024.03.26	1 year
15	LISN	R&S	ENV216	101313	2023.03.27	2024.03.26	1 year
16	LISN	EMCO	3816/2	00042990	2023.03.27	2024.03.26	1 year
17	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2023.03.27	2024.03.26	1 year
18	Passive Voltage Probe	R&S	ESH2-Z3	100196	2023.03.27	2024.03.26	1 year
19	Test Cable	N/A	C01	N/A	2020.05.11 2023.05.06	2023.05.10 2026.05.05	3 year
20	Test Cable	N/A	C02	N/A	2020.05.11 2023.05.06	2023.05.10 2026.05.05	3 year
21	Test Cable	N/A	C03	N/A	2020.05.11 2023.05.06	2023.05.10 2026.05.05	3 year
22	Attenuator	MCE	24-10-34	BN9258	2023.03.27	2024.03.26	1 year
23	Spectrum Analyzer	agilent	e4440a	us44300399	2023.03.27	2024.03.26	1 year
24	test receiver	R&S	ESCI	a0304218	2023.03.27	2024.03.26	1 year

25	Communication Tester	R&S	CMU200	A0304247	2022.06.16	2023.06.15	1 year
26	Thermal Chamber	Ten Billion	TTC-B3C	TBN-960502	2023.03.27	2024.03.26	1 year
27	DC Power Source	N/A	PS-6005D	20170402923	2020.05.11 2023.05.06	2023.05.10 2026.05.05	3 year
28	MXG Vector Signal Generator	Agilent	N5182A	MY47070317	2022.06.16	2023.06.15	1 year
29	Communication Tester	R&S	CMW500	148500	2022.06.16	2023.06.15	1 year

Note: Each piece of equipment is scheduled for calibration once a year except the Test Cable& DC Power Source which is scheduled for calibration every 3 years.

4. OUTPUT POWER

4.1 OUTPUT POWER MEASUREMENT

LTE Measurement Procedure:

All LTE bands conducted power peak and average are obtained from the CMW500 telecommunication test set. The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

The allowed A-MPR values specified below in Table 6.2.4.-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signaling Value of "NS_01".³

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	NA
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
			10, 15, 20	See Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10, 15, 20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	n/a
NS_07	6.6.2.2.3 6.6.3.3.2	13	10	Table 6.2.4-2	Table 6.2.4-2
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	Table 6.2.4-3
NS_11	6.6.2.2.1	23 ¹	1.4, 3, 5, 10	Table 6.2.4-5	Table 6.2.4-5
..					
NS_32	-	-	-	-	-

Note 1: Applies to the lower block of Band 23, i.e. a carrier placed in the 2000-2010 MHz region.

Test data reference attachment.

5. OCCUPIED BANDWIDTH

RULE PART(S)

FCC: §2.1049

LIMITS

For reporting purposes only

TEST PROCEDURE

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at the low, middle and high channel in each band. The -26dB bandwidth was also measured and recorded.

MODES TESTED

☐

Band 2/4/5/12/17

RESULTS

PASS

Test data reference attachment.

6. BANDEDGE AND EMISSION MASK

RULE PART(S)

FCC: §2.1051, §22.901, §22.917, §24.238, §27.53,
FCC: §22.359

LIMITS

FCC: §22.917, §24.238, §27.53

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

(m)(4) For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees. Show citation box.

(c)(4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;

TEST PROCEDURE

The transmitter output was connected to a CMW500 Test Set and configured to operate at maximum power. The band edge emissions were measured at the required operating frequencies in each band on the Spectrum Analyzer.

For each band edge measurement:

Set the spectrum analyzer span to include the block edge frequency

Set a marker to point the corresponding band edge frequency in each test case.

Set resolution bandwidth to at least 1% of emission bandwidth.

MODES TESTED

Band 2/4/5/12/17

RESULTS

Test data reference attachment.

7. OUT OF BAND EMISSIONS

RULE PART(S)

FCC: §2.1051, §22.901, §22.917, §24.238, §27.53

LIMITS

1. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.
2. The Band 7/41 emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $55 + 10 \log (P)$ dB.

TEST PROCEDURE

The RF output of the transmitter was connected to a spectrum analyzer through a calibrated coaxial cable. Sufficient scans were taken to show the out-of-band Emissions, if any, up to 10th harmonic. Multiple sweeps were recorded in maximum hold mode using a peak detector to ensure that the worst-case emissions were caught.

For each out of band emissions measurement:

- ☐
- ☐ Set RBW & VBW to 100 kHz for the measurement below 1 GHz, and 1 MHz for the measurement above 1 GHz.

MODES TESTED

- ☐ Band 2/4/5/12/17
- ☐

7.1 MEASUREMENT METHOD

The test set up and general procedure is similar to conducted peak output power test. Only different for setting the measurement configuration of the measuring instrument of Spectrum Analyzer.

Test data reference attachment.

8. RADIATED MEASUREMENT

8.1. RADIATED POWER (ERP & EIRP)

RULE PART(S)

FCC: §2.1046, §22.913, §24.232, §27.50

LIMITS:

22.913(a) - The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

27.50 (c) (10) the following power and antenna height requirements apply to stations transmitting in the 698–746 MHz band, the portable stations (hand-held devices) are limited to 3 watts ERP.

27.50 (b)(10) Portable stations (hand-held devices) transmitting in the 746–757 MHz, 758–763 MHz, 776–793 MHz, and 805–806 MHz bands are limited to 3 watts ERP.

27.50 (d)(4) The following power and antenna height requirements apply to stations transmitting in the 1710–1755 MHz and 2110–2155 MHz bands: Fixed, mobile, and portable (hand-held) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP.

27.50 (h)(2) Mobile and other user stations. Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

TEST PROCEDURE

ANSI/TIA-603-E Clause 2.2.17

KDB 971168 v02r01 RF power output using broadband peak and average power meter method.

KDB 971168 D01 Power Meas License Digital Systems v02r01, "Measurement Guidance for Certification of Licensed Digital Transmitters"

MODES TESTED

Band 2/4/5/12/17

RESULTS

Pass

8.2 LTE BAND 2

Radiated Power (EIRP) for Band 2									
Mode	RB/RB SIZE	Frequency	Result						Conclusion
			SG Level (dBm)	Cable Loss (dBm)	Antenna Factor (dB)	Max.	Max.	Polarization Of Max. ERP	
						EIRP Average (dBm)	EIRP Average (mW)		
1.4MHz	1/#Mid	1850.7	-2.53	3.76	28.24	21.95	156.675	Horizontal	Pass
Band		1880	-2.34	3.91	28.22	21.97	157.398	Horizontal	Pass
QPSK		1909.3	-2.25	3.93	28.20	22.02	159.221	Horizontal	Pass
3.0MHz	1/#Mid	1851.5	-2.59	3.77	28.23	21.87	153.815	Horizontal	Pass
Band		1880	-2.44	3.91	28.24	21.89	154.525	Horizontal	Pass
QPSK		1908.5	-2.31	3.94	28.25	22.00	158.489	Horizontal	Pass
5.0MHz	1/#Mid	1852.5	-2.48	3.77	28.31	22.06	160.694	Horizontal	Pass
Band		1880	-2.10	3.91	28.22	22.21	166.341	Horizontal	Pass
QPSK		1907.5	-2.03	3.94	28.20	22.23	167.109	Horizontal	Pass
10.0MHz	1/#Mid	1855	-2.34	3.79	28.33	22.20	165.959	Horizontal	Pass
Band		1880	-2.04	3.95	28.22	22.23	167.109	Horizontal	Pass
QPSK		1905	-1.93	3.97	28.19	22.29	169.434	Horizontal	Pass
15.0MHz	1/#Mid	1857.5	-2.30	3.79	28.34	22.25	167.880	Horizontal	Pass
Band		1880	-2.09	3.95	28.22	22.18	165.196	Horizontal	Pass
QPSK		1902.5	-1.95	3.97	28.18	22.26	168.267	Horizontal	Pass
20.0MHz	1/#Mid	1860	-2.29	3.81	28.35	22.25	167.880	Horizontal	Pass
Band		1880	-1.96	3.96	28.22	22.30	169.824	Horizontal	Pass
QPSK		1900	-1.90	4.00	28.16	22.26	168.267	Horizontal	Pass
1.4MHz	1/#Mid	1850.7	-3.71	3.76	28.24	20.77	119.399	Vertical	Pass
Band		1880	-2.71	3.91	28.22	21.60	144.544	Vertical	Pass
QPSK		1909.3	-3.03	3.93	28.20	21.24	133.045	Vertical	Pass
3.0MHz	1/#Mid	1851.5	-2.83	3.77	28.23	21.63	145.546	Vertical	Pass
Band		1880	-3.01	3.91	28.24	21.32	135.519	Vertical	Pass
QPSK		1908.5	-3.03	3.94	28.25	21.28	134.276	Vertical	Pass
5.0MHz	1/#Mid	1852.5	-3.20	3.77	28.31	21.34	136.144	Vertical	Pass
Band		1880	-3.43	3.91	28.22	20.88	122.462	Vertical	Pass
QPSK		1907.5	-3.42	3.94	28.20	20.84	121.339	Vertical	Pass
10.0MHz	1/#Mid	1855	-3.60	3.79	28.33	20.94	124.165	Vertical	Pass
Band		1880	-3.60	3.95	28.22	20.67	116.681	Vertical	Pass
QPSK		1905	-2.94	3.97	28.19	21.28	134.276	Vertical	Pass

15.0MHz		1857.5	-3.48	3.79	28.34	21.07	127.938	Vertical	Pass
Band	1/#Mid	1880	-2.81	3.95	28.22	21.46	139.959	Vertical	Pass
QPSK		1902.5	-2.65	3.97	28.18	21.56	143.219	Vertical	Pass
20.0MHz		1860	-3.10	3.81	28.35	21.44	139.316	Vertical	Pass
Band	1/#Mid	1880	-3.47	3.96	28.22	20.79	119.950	Vertical	Pass
QPSK		1900	-2.92	4.00	28.16	21.24	133.045	Vertical	Pass

Radiated Power (EIRP) for Band 2									
Mode	RB/RB SIZE	Frequency	Result						Conclusion
			SG Level (dBm)	Cable Loss (dBm)	Antenna Factor (dB)	Max. EIRP Average (dBm)	Max.	Polarization	
							EIRP	Of Max. ERP	
							Average		
							(mW)		
1.4MHz	1/#Mid	1850.7	-3.65	3.76	28.24	20.83	121.060	Horizontal	Pass
Band 16		1880	-3.12	3.91	28.22	21.19	131.522	Horizontal	Pass
QAM		1909.3	-3.05	3.93	28.20	21.22	132.434	Horizontal	Pass
3.0MHz	1/#Mid	1851.5	-3.15	3.77	28.23	21.31	135.207	Horizontal	Pass
Band 16		1880	-3.23	3.91	28.24	21.10	128.825	Horizontal	Pass
QAM		1908.5	-3.44	3.94	28.25	20.87	122.180	Horizontal	Pass
5.0MHz	1/#Mid	1852.5	-3.09	3.77	28.31	21.45	139.637	Horizontal	Pass
Band 16		1880	-3.00	3.91	28.22	21.31	135.207	Horizontal	Pass
QAM		1907.5	-2.68	3.94	28.20	21.58	143.880	Horizontal	Pass
10.0MHz	1/#Mid	1855	-3.14	3.79	28.33	21.40	138.038	Horizontal	Pass
Band 16		1880	-3.13	3.95	28.22	21.14	130.017	Horizontal	Pass
QAM		1905	-2.60	3.97	28.19	21.62	145.211	Horizontal	Pass
15.0MHz	1/#Mid	1857.5	-3.12	3.79	28.34	21.43	138.995	Horizontal	Pass
Band 16		1880	-2.91	3.95	28.22	21.36	136.773	Horizontal	Pass
QAM		1902.5	-2.87	3.97	28.18	21.34	136.144	Horizontal	Pass
20.0MHz	1/#Mid	1860	-3.01	3.81	28.35	21.53	142.233	Horizontal	Pass
Band 16		1880	-2.71	3.96	28.22	21.55	142.889	Horizontal	Pass
QAM		1900	-2.53	4.00	28.16	21.63	145.546	Horizontal	Pass
1.4MHz	1/#Mid	1850.7	-4.06	3.76	28.24	20.42	110.154	Vertical	Pass
Band 16		1880	-4.25	3.91	28.22	20.06	101.391	Vertical	Pass
QAM		1909.3	-3.73	3.93	28.20	20.54	113.240	Vertical	Pass
3.0MHz	1/#Mid	1851.5	-4.76	3.77	28.23	19.70	93.325	Vertical	Pass
Band 16		1880	-4.18	3.91	28.24	20.15	103.514	Vertical	Pass
QAM		1908.5	-4.24	3.94	28.25	20.07	101.625	Vertical	Pass
5.0MHz	1/#Mid	1852.5	-3.94	3.77	28.31	20.60	114.815	Vertical	Pass
Band 16		1880	-3.73	3.91	28.22	20.58	114.288	Vertical	Pass
QAM		1907.5	-3.99	3.94	28.20	20.27	106.414	Vertical	Pass
10.0MHz	1/#Mid	1855	-4.34	3.79	28.33	20.20	104.713	Vertical	Pass
Band 16		1880	-4.43	3.95	28.22	19.84	96.383	Vertical	Pass
QAM		1905	-4.50	3.97	28.19	19.72	93.756	Vertical	Pass
15.0MHz	1/#Mid	1857.5	-4.82	3.79	28.34	19.73	93.972	Vertical	Pass
Band 16		1880	-4.04	3.95	28.22	20.23	105.439	Vertical	Pass

QAM		1902.5	-3.75	3.97	28.18	20.46	111.173	Vertical	Pass
20.0MHz	1/#Mid	1860	-4.65	3.81	28.35	19.89	97.499	Vertical	Pass
Band 16		1880	-3.93	3.96	28.22	20.33	107.895	Vertical	Pass
QAM		1900	-3.63	4.00	28.16	20.53	112.980	Vertical	Pass

Note:

SG Level= Signal generator output

Max. EIRP Average (dBm)= Antenna Gain(dB)+ SG Level (dBm)- Cable Loss(dBm)

Factor Gain(dB)=Antenna Gain(dB) + Amplifier Factor (dB)

8.3 LTE BAND 4

Radiated Power (EIRP) for Band 4									
Mode	RB/RB SIZE	Frequency	Result						Conclusion
			SG	Cable	Antenna	Max.	Max.	Polarization	
			Level	Loss	Factor	EIRP	EIRP	Of Max. ERP	
			(dBm)	(dBm)	(dB)	Average	Average		
						(dBm)	(mW)		
1.4MHz	Band 1/#Mid QPSK	1710.7	-2.44	3.12	27.58	22.02	159.221	Horizontal	Pass
		1732.5	-2.43	3.27	27.61	21.91	155.239	Horizontal	Pass
		1754.3	-2.41	3.29	27.63	21.93	155.955	Horizontal	Pass
3.0MHz	Band 1/#Mid QPSK	1711.5	-2.61	3.13	27.61	21.87	153.815	Horizontal	Pass
		1732.5	-2.53	3.27	27.61	21.81	151.705	Horizontal	Pass
		1753.5	-2.45	3.30	27.62	21.87	153.815	Horizontal	Pass
5.0MHz	Band 1/#Mid QPSK	1712.5	-2.38	3.13	27.63	22.12	162.930	Horizontal	Pass
		1732.5	-2.28	3.27	27.61	22.06	160.694	Horizontal	Pass
		1752.5	-2.16	3.30	27.60	22.14	163.682	Horizontal	Pass
10.0MHz	Band 1/#Mid QPSK	1715	-2.32	3.15	27.64	22.17	164.816	Horizontal	Pass
		1732.5	-2.09	3.31	27.61	22.21	166.341	Horizontal	Pass
		1750	-2.11	3.33	27.59	22.15	164.059	Horizontal	Pass
15.0MHz	Band 1/#Mid QPSK	1717.5	-2.33	3.15	27.65	22.17	164.816	Horizontal	Pass
		1732.5	-2.17	3.31	27.61	22.13	163.305	Horizontal	Pass
		1747.5	-2.11	3.33	27.57	22.13	163.305	Horizontal	Pass
20.0MHz	Band 1/#Mid QPSK	1720	-2.27	3.17	27.66	22.22	166.725	Horizontal	Pass
		1732.5	-2.10	3.32	27.61	22.19	165.577	Horizontal	Pass
		1745	-2.04	3.36	27.56	22.16	164.437	Horizontal	Pass
1.4MHz	Band 1/#Mid QPSK	1710.7	-2.89	3.12	27.58	21.57	143.549	Vertical	Pass
		1732.5	-3.55	3.27	27.61	20.79	119.950	Vertical	Pass
		1754.3	-3.47	3.29	27.63	20.87	122.180	Vertical	Pass
3.0MHz	Band 1/#Mid QPSK	1711.5	-3.50	3.13	27.61	20.98	125.314	Vertical	Pass
		1732.5	-2.78	3.27	27.61	21.56	143.219	Vertical	Pass
		1753.5	-2.86	3.30	27.62	21.46	139.959	Vertical	Pass
5.0MHz	Band 1/#Mid QPSK	1712.5	-3.36	3.13	27.63	21.14	130.017	Vertical	Pass
		1732.5	-2.84	3.27	27.61	21.50	141.254	Vertical	Pass
		1752.5	-3.57	3.30	27.60	20.73	118.304	Vertical	Pass
10.0MHz	Band 1/#Mid QPSK	1715	-3.24	3.15	27.64	21.25	133.352	Vertical	Pass
		1732.5	-3.08	3.31	27.61	21.22	132.434	Vertical	Pass
		1750	-3.14	3.33	27.59	21.12	129.420	Vertical	Pass

15.0MHz		1717.5	-2.93	3.15	27.65	21.57	143.549	Vertical	Pass
Band	1/#Mid	1732.5	-3.15	3.31	27.61	21.15	130.317	Vertical	Pass
QPSK		1747.5	-3.18	3.33	27.57	21.06	127.644	Vertical	Pass
20.0MHz		1720	-3.79	3.17	27.66	20.70	117.490	Vertical	Pass
Band	1/#Mid	1732.5	-3.07	3.32	27.61	21.22	132.434	Vertical	Pass
QPSK		1745	-3.16	3.36	27.56	21.04	127.057	Vertical	Pass

Radiated Power (EIRP) for Band 4									
Mode	RB/RB SIZE	Frequency	Result						Conclusion
			SG	Cable	Antenna	Max. EIRP	Max. EIRP	Polarization	
			Level	Loss	Factor			Of Max.	
			(dBm)	(dBm)	(dB)	Average	Average	ERP	
						(dBm)	(mW)		
1.4MHz	Band 16 QAM	1710.7	-3.25	3.12	27.58	21.21	132.130	Horizontal	Pass
		1732.5	-3.10	3.27	27.61	21.24	133.045	Horizontal	Pass
		1754.3	-3.10	3.29	27.63	21.24	133.045	Horizontal	Pass
3.0MHz	Band 16 QAM	1711.5	-3.19	3.13	27.61	21.29	134.586	Horizontal	Pass
		1732.5	-3.32	3.27	27.61	21.02	126.474	Horizontal	Pass
		1753.5	-3.54	3.30	27.62	20.78	119.674	Horizontal	Pass
5.0MHz	Band 16 QAM	1712.5	-3.02	3.13	27.63	21.48	140.605	Horizontal	Pass
		1732.5	-2.98	3.27	27.61	21.36	136.773	Horizontal	Pass
		1752.5	-2.67	3.30	27.60	21.63	145.546	Horizontal	Pass
10.0MHz	Band 16 QAM	1715	-3.09	3.15	27.64	21.40	138.038	Horizontal	Pass
		1732.5	-3.28	3.31	27.61	21.02	126.474	Horizontal	Pass
		1750	-2.66	3.33	27.59	21.60	144.544	Horizontal	Pass
15.0MHz	Band 16 QAM	1717.5	-2.89	3.15	27.65	21.61	144.877	Horizontal	Pass
		1732.5	-2.95	3.31	27.61	21.35	136.458	Horizontal	Pass
		1747.5	-2.97	3.33	27.57	21.27	133.968	Horizontal	Pass
20.0MHz	Band 16 QAM	1720	-2.84	3.17	27.66	21.65	146.218	Horizontal	Pass
		1732.5	-2.85	3.32	27.61	21.44	139.316	Horizontal	Pass
		1745	-2.66	3.36	27.56	21.54	142.561	Horizontal	Pass
1.4MHz	Band 16 QAM	1710.7	-4.51	3.12	27.58	19.95	98.855	Vertical	Pass
		1732.5	-4.10	3.27	27.61	20.24	105.682	Vertical	Pass
		1754.3	-3.93	3.29	27.63	20.41	109.901	Vertical	Pass
3.0MHz	Band 16 QAM	1711.5	-4.28	3.13	27.61	20.20	104.713	Vertical	Pass
		1732.5	-4.05	3.27	27.61	20.29	106.905	Vertical	Pass
		1753.5	-4.42	3.30	27.62	19.90	97.724	Vertical	Pass
5.0MHz	Band 16 QAM	1712.5	-4.54	3.13	27.63	19.96	99.083	Vertical	Pass
		1732.5	-4.06	3.27	27.61	20.28	106.660	Vertical	Pass
		1752.5	-4.44	3.30	27.60	19.86	96.828	Vertical	Pass
10.0MHz	Band 16 QAM	1715	-4.53	3.15	27.64	19.96	99.083	Vertical	Pass
		1732.5	-4.59	3.31	27.61	19.71	93.541	Vertical	Pass
		1750	-3.78	3.33	27.59	20.48	111.686	Vertical	Pass
15.0MHz	Band 16	1717.5	-4.30	3.15	27.65	20.20	104.713	Vertical	Pass
		1732.5	-4.18	3.31	27.61	20.12	102.802	Vertical	Pass

QAM		1747.5	-3.87	3.33	27.57	20.37	108.893	Vertical	Pass
20.0MHz		1720	-4.52	3.17	27.66	19.97	99.312	Vertical	Pass
Band 16	1/#Mid	1732.5	-4.14	3.32	27.61	20.15	103.514	Vertical	Pass
QAM		1745	-3.83	3.36	27.56	20.37	108.893	Vertical	Pass

Note:

SG Level= Signal generator output

Max. EIRP Average (dBm)= Antenna Gain(dB)+ SG Level (dBm)- Cable Loss(dBm)

Factor Gain(dB)=Antenna Gain(dB) + Amplifier Factor (dB)

8.4 LTE BAND 5

Radiated Power (ERP) for Band 5										
Mode	RB/RB SIZE	Frequency	Result							Conclusion
			SG Level	Cable Loss	Antenna Factor	Correction	Max. EIRP	Max. EIRP	Polarization	
			(dBm)	(dBm)	(dB)	(dB)	Average	Average	Of Max. ERP	
							(dBm)	(mW)		
1.4MHz	3/#Mid	824.7	6.86	2.01	19.68	2.15	22.38	172.982	Horizontal	Pass
Band		836.5	6.74	2.01	19.77	2.15	22.35	171.791	Horizontal	Pass
QPSK		848.3	6.54	2.02	19.82	2.15	22.19	165.577	Horizontal	Pass
3.0MHz	1/#Mid	825.5	6.63	2.01	19.70	2.15	22.17	164.816	Horizontal	Pass
Band		836.5	6.53	2.01	19.77	2.15	22.14	163.682	Horizontal	Pass
QPSK		847.5	6.40	2.02	19.81	2.15	22.04	159.956	Horizontal	Pass
5.0MHz	1/#Mid	826.5	6.91	2.01	19.71	2.15	22.46	176.198	Horizontal	Pass
Band		836.5	6.79	2.01	19.77	2.15	22.40	173.780	Horizontal	Pass
QPSK		846.5	6.63	2.02	19.79	2.15	22.25	167.880	Horizontal	Pass
10.0MHz	1/#Mid	829	6.93	2.01	19.73	2.15	22.50	177.828	Horizontal	Pass
Band		836.5	6.88	2.01	19.77	2.15	22.49	177.419	Horizontal	Pass
QPSK		844	6.78	2.02	19.78	2.15	22.39	173.380	Horizontal	Pass
1.4MHz	1/#Mid	824.7	5.45	2.01	19.68	2.15	20.97	125.026	Vertical	Pass
Band		836.5	5.93	2.01	19.77	2.15	21.54	142.561	Vertical	Pass
QPSK		848.3	5.25	2.02	19.82	2.15	20.90	123.027	Vertical	Pass
3.0MHz	1/#Mid	825.5	5.18	2.01	19.70	2.15	20.72	118.032	Vertical	Pass
Band		836.5	5.62	2.01	19.77	2.15	21.23	132.739	Vertical	Pass
QPSK		847.5	5.81	2.02	19.81	2.15	21.45	139.637	Vertical	Pass
5.0MHz	1/#Mid	826.5	5.38	2.01	19.71	2.15	20.93	123.880	Vertical	Pass
Band		836.5	5.44	2.01	19.77	2.15	21.05	127.350	Vertical	Pass
QPSK		846.5	5.29	2.02	19.79	2.15	20.91	123.310	Vertical	Pass
10.0MHz	1/#Mid	829	5.97	2.01	19.73	2.15	21.54	142.561	Vertical	Pass
Band		836.5	5.75	2.01	19.77	2.15	21.36	136.773	Vertical	Pass
QPSK		844	5.12	2.02	19.78	2.15	20.73	118.304	Vertical	Pass

Radiated Power (ERP) for Band 5										
Mode	RB/RB SIZE	Frequency	Result							Conclusion
			SG	Cable	Antenna	Correction	Max.	Max.	Polarization	
			Level	Loss	Factor		EIRP	EIRP	Of Max.	
			(dBm)	(dBm)	(dB)		Average	Average	ERP	
						(dB)	(dBm)	(mW)		
1.4MHz Band 16 QAM	3/#Mid	824.7	6.01	2.01	19.68	2.15	21.53	142.233	Horizontal	Pass
		836.5	5.94	2.01	19.77	2.15	21.55	142.889	Horizontal	Pass
		848.3	5.78	2.02	19.82	2.15	21.43	138.995	Horizontal	Pass
3.0MHz Band 16 QAM	1/#Mid	825.5	6.09	2.01	19.70	2.15	21.63	145.546	Horizontal	Pass
		836.5	5.80	2.01	19.77	2.15	21.41	138.357	Horizontal	Pass
		847.5	5.28	2.02	19.81	2.15	20.92	123.595	Horizontal	Pass
5.0MHz Band 16 QAM	1/#Mid	826.5	6.41	2.01	19.71	2.15	21.96	157.036	Horizontal	Pass
		836.5	6.18	2.01	19.77	2.15	21.79	151.008	Horizontal	Pass
		846.5	5.93	2.02	19.79	2.15	21.55	142.889	Horizontal	Pass
10.0MHz Band 16 QAM	1/#Mid	829	6.41	2.01	19.73	2.15	21.98	157.761	Horizontal	Pass
		836.5	6.13	2.01	19.77	2.15	21.74	149.279	Horizontal	Pass
		844	5.67	2.02	19.78	2.15	21.28	134.276	Horizontal	Pass
1.4MHz Band 16 QAM	1/#Mid	824.7	4.84	2.01	19.68	2.15	20.36	108.643	Vertical	Pass
		836.5	4.17	2.01	19.77	2.15	19.78	95.060	Vertical	Pass
		848.3	5.42	2.02	19.82	2.15	21.07	127.938	Vertical	Pass
3.0MHz Band 16 QAM	1/#Mid	825.5	5.51	2.01	19.70	2.15	21.05	127.350	Vertical	Pass
		836.5	4.24	2.01	19.77	2.15	19.85	96.605	Vertical	Pass
		847.5	6.03	2.02	19.81	2.15	21.67	146.893	Vertical	Pass
5.0MHz Band 16 QAM	1/#Mid	826.5	4.50	2.01	19.71	2.15	20.05	101.158	Vertical	Pass
		836.5	5.97	2.01	19.77	2.15	21.58	143.880	Vertical	Pass
		846.5	5.50	2.02	19.79	2.15	21.12	129.420	Vertical	Pass
10.0MHz Band 16 QAM	1/#Mid	829	4.94	2.01	19.73	2.15	20.51	112.460	Vertical	Pass
		836.5	4.20	2.01	19.77	2.15	19.81	95.719	Vertical	Pass
		844	5.62	2.02	19.78	2.15	21.23	132.739	Vertical	Pass

Note:

SG Level= Signal generator output

Max. EIRP Average (dBm)= Antenna Gain(dB)+ SG Level (dBm)- Cable Loss(dBm)

Factor Gain(dB)=Antenna Gain(dB) + Amplifier Factor (dB)

8.5 LTE BAND 12

Radiated Power (ERP) for Band 12										
Mode	RB/RB SIZE	Frequency	Result							Conclusion
			SG	Cable	Antenna	Correction	Max.	Max.	Polarization	
			Level	Loss	Factor		EIRP	EIRP	Of Max.	
			(dBm)	(dBm)	(dB)		Average	Average	ERP	
						(dB)	(dBm)	(mW)		
1.4MHz	1/#Mid	699.7	7.23	1.91	19.21	2.15	22.38	172.982	Vertical	Pass
Band		707.5	7.15	1.91	19.26	2.15	22.35	171.791	Vertical	Pass
QPSK		715.3	6.93	1.93	19.34	2.15	22.19	165.577	Vertical	Pass
3.0MHz	1/#Mid	700.5	7.02	1.91	19.21	2.15	22.17	164.816	Vertical	Pass
Band		707.5	6.94	1.91	19.26	2.15	22.14	163.682	Vertical	Pass
QPSK		714.5	6.78	1.93	19.34	2.15	22.04	159.956	Vertical	Pass
5.0MHz	1/#Mid	701.5	7.29	1.91	19.23	2.15	22.46	176.198	Vertical	Pass
Band		707.5	7.20	1.91	19.26	2.15	22.40	173.780	Vertical	Pass
QPSK		713.5	6.99	1.92	19.33	2.15	22.25	167.880	Vertical	Pass
10.0MHz	1/#Mid	704	7.31	1.91	19.25	2.15	22.50	177.828	Vertical	Pass
Band		707.5	7.29	1.91	19.26	2.15	22.49	177.419	Vertical	Pass
QPSK		711	7.14	1.92	19.32	2.15	22.39	173.380	Vertical	Pass
1.4MHz	1/#Mid	699.7	5.96	1.91	19.21	2.15	21.11	129.122	Horizontal	Pass
Band		707.5	6.37	1.91	19.26	2.15	21.57	143.549	Horizontal	Pass
QPSK		715.3	5.90	1.93	19.34	2.15	21.16	130.617	Horizontal	Pass
3.0MHz	1/#Mid	700.5	6.03	1.91	19.21	2.15	21.18	131.220	Horizontal	Pass
Band		707.5	6.15	1.91	19.26	2.15	21.35	136.458	Horizontal	Pass
QPSK		714.5	5.69	1.93	19.34	2.15	20.95	124.451	Horizontal	Pass
5.0MHz	1/#Mid	701.5	6.31	1.91	19.23	2.15	21.48	140.605	Horizontal	Pass
Band		707.5	5.95	1.91	19.26	2.15	21.15	130.317	Horizontal	Pass
QPSK		713.5	5.63	1.92	19.33	2.15	20.89	122.744	Horizontal	Pass
10.0MHz	1/#Mid	704	5.75	1.91	19.25	2.15	20.94	124.165	Horizontal	Pass
Band		707.5	5.80	1.91	19.26	2.15	21.00	125.893	Horizontal	Pass
QPSK		711	6.35	1.92	19.32	2.15	21.60	144.544	Horizontal	Pass

Radiated Power (ERP) for Band 12										
Mode	RB/RB SIZE	Frequency	Result							Conclusion
			SG	Cable	Antenna	Correction	Max.	Max.	Polarization	
			Level	Loss	Factor		EIRP	EIRP	Of Max.	
			(dBm)	(dBm)	(dB)		Average	Average	ERP	
						(dB)	(dBm)	(mW)		
1.4MHz Band 16 QAM	1/#Mid	699.7	7.28	1.91	19.21	2.15	22.43	174.985	Vertical	Pass
		707.5	7.20	1.91	19.26	2.15	22.40	173.780	Vertical	Pass
		715.3	6.98	1.93	19.34	2.15	22.24	167.494	Vertical	Pass
3.0MHz Band 16 QAM	1/#Mid	700.5	7.07	1.91	19.21	2.15	22.22	166.725	Vertical	Pass
		707.5	6.99	1.91	19.26	2.15	22.19	165.577	Vertical	Pass
		714.5	6.83	1.93	19.34	2.15	22.09	161.808	Vertical	Pass
5.0MHz Band 16 QAM	1/#Mid	701.5	7.34	1.91	19.23	2.15	22.51	178.238	Vertical	Pass
		707.5	7.25	1.91	19.26	2.15	22.45	175.792	Vertical	Pass
		713.5	7.04	1.92	19.33	2.15	22.30	169.824	Vertical	Pass
10.0MHz Band 16 QAM	1/#Mid	704	7.36	1.91	19.25	2.15	22.55	179.887	Vertical	Pass
		707.5	7.34	1.91	19.26	2.15	22.54	179.473	Vertical	Pass
		711	7.19	1.92	19.32	2.15	22.44	175.388	Vertical	Pass
1.4MHz Band 16 QAM	1/#Mid	699.7	5.93	1.91	19.21	2.15	21.08	128.233	Horizontal	Pass
		707.5	5.91	1.91	19.26	2.15	21.11	129.122	Horizontal	Pass
		715.3	5.52	1.93	19.34	2.15	20.78	119.674	Horizontal	Pass
3.0MHz Band 16 QAM	1/#Mid	700.5	6.48	1.91	19.21	2.15	21.63	145.546	Horizontal	Pass
		707.5	5.66	1.91	19.26	2.15	20.86	121.899	Horizontal	Pass
		714.5	5.68	1.93	19.34	2.15	20.94	124.165	Horizontal	Pass
5.0MHz Band 16 QAM	1/#Mid	701.5	6.21	1.91	19.23	2.15	21.38	137.404	Horizontal	Pass
		707.5	6.28	1.91	19.26	2.15	21.48	140.605	Horizontal	Pass
		713.5	5.83	1.92	19.33	2.15	21.09	128.529	Horizontal	Pass
10.0MHz Band 16 QAM	1/#Mid	704	6.32	1.91	19.25	2.15	21.51	141.579	Horizontal	Pass
		707.5	6.24	1.91	19.26	2.15	21.44	139.316	Horizontal	Pass
		711	6.26	1.92	19.32	2.15	21.51	141.579	Horizontal	Pass

Note:

SG Level= Signal generator output

Max. EIRP Average (dBm)= Antenna Gain(dB)+ SG Level (dBm)- Cable Loss(dBm)

Factor Gain(dB)=Antenna Gain(dB) + Amplifier Factor (dB)

8.6 LTE BAND 17

Radiated Power (ERP) for Band 17										
Mode	RB/RB SIZE	Frequency	Result							Conclusion
			SG	Cable	Antenna	Correction	Max.	Max.	Polarization	
			Level	Loss	Factor		EIRP	EIRP	Of Max.	
			(dBm)	(dBm)	(dB)		Average	Average	ERP	
5.0MHz Band QPSK	1/#Mid	706.5	7.74	1.91	19.23	2.15	22.91	195.434	Vertical	Pass
		710	7.60	1.91	19.26	2.15	22.80	190.546	Vertical	Pass
		713.5	7.50	1.92	19.33	2.15	22.76	188.799	Vertical	Pass
10.0MHz Band QPSK	1/#Mid	709	7.75	1.91	19.25	2.15	22.94	196.789	Vertical	Pass
		710	7.70	1.91	19.26	2.15	22.90	194.984	Vertical	Pass
		711	7.66	1.92	19.32	2.15	22.91	195.434	Vertical	Pass
5.0MHz Band QPSK	1/#Mid	706.5	5.81	1.91	19.23	2.15	20.98	125.314	Horizontal	Pass
		710	7.20	1.91	19.26	2.15	22.40	173.780	Horizontal	Pass
		713.5	6.51	1.92	19.33	2.15	21.77	150.314	Horizontal	Pass
10.0MHz Band QPSK	1/#Mid	709	7.51	1.91	19.25	2.15	22.70	186.209	Horizontal	Pass
		710	5.63	1.91	19.26	2.15	20.83	121.060	Horizontal	Pass
		711	6.61	1.92	19.32	2.15	21.86	153.462	Horizontal	Pass

Radiated Power (ERP) for Band 17										
Mode	RB/RB SIZE	Frequency	Result							Conclusion
			SG Level	Cable Loss	Antenna Factor	Correction	Max. EIRP	Max. EIRP	Polarization	
			(dBm)	(dBm)	(dB)		Average	Average	Of Max. ERP	
							(dBm)	(mW)		
5.0MHz	1/#Mid	706.5	7.09	1.91	19.23	2.15	22.26	168.267	Vertical	Pass
Band 16		710	7.00	1.91	19.26	2.15	22.20	165.959	Vertical	Pass
QAM		713.5	6.80	1.92	19.33	2.15	22.06	160.694	Vertical	Pass
10.0MHz	1/#Mid	709	6.63	1.91	19.25	2.15	21.82	152.055	Vertical	Pass
Band 16		710	7.16	1.91	19.26	2.15	22.36	172.187	Vertical	Pass
QAM		711	6.89	1.92	19.32	2.15	22.14	163.682	Vertical	Pass
5.0MHz	1/#Mid	706.5	5.74	1.91	19.23	2.15	20.91	123.310	Horizontal	Pass
Band 16		710	5.68	1.91	19.26	2.15	20.88	122.462	Horizontal	Pass
QAM		713.5	5.79	1.92	19.33	2.15	21.05	127.350	Horizontal	Pass
10.0MHz	1/#Mid	709	5.90	1.91	19.25	2.15	21.09	128.529	Horizontal	Pass
Band 16		710	6.23	1.91	19.26	2.15	21.43	138.995	Horizontal	Pass
QAM		711	6.35	1.92	19.32	2.15	21.60	144.544	Horizontal	Pass

Note:

ERP=EIRP-2.15

SG Level= Signal generator output

Max. EIRP Average (dBm)= Antenna Factor (dB)+ SG Level (dBm)- Cable Loss(dBm)

9. SPURIOUS RADIATION EMISSION

RULE PART(S)

FCC: §2.1053, §22.917, §24.238, §27.53

LIMIT

§22.917 (e) and §24.238 and §90.691 (a): Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.

§27.53 (g) For operations in the 698–746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB.

§27.53 (h) For operations in the 1710–1755 MHz and 2110–2155 MHz bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB.

TEST PROCEDURE

For Cellular equipment - Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 100 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

For PCS equipment - Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

The unwanted emission power shall be measured with a resolution bandwidth of at least 1% of the occupied bandwidth in the 1 MHz band immediately outside and adjacent to the channel edge of the equipment. Beyond the 1 MHz band immediately outside the channel edge of the equipment, a resolution bandwidth of 1 MHz shall be employed. A narrower resolution bandwidth is allowed to be used provided that the measured power is integrated over the full required measurement bandwidth of 1 MHz or 1% of the occupied bandwidth as applicable.

The power of any unwanted emissions measured from the channel edge of the equipment shall be attenuated below the transmitter power, P (dBW), as follows:

- a. for base station and subscriber equipment, other than mobile subscriber equipment, the attenuation shall not be less than $43 + 10 \log_{10}(p)$, dB; and
- b. for mobile subscriber equipment, the attenuation shall not be less than $43 + 10 \log_{10}(p)$, dB at the channel edges and $55 + 10 \log_{10}(p)$ at 5.5 MHz away and beyond the channel edges where p in (a) and (b) is the transmitter power measured in watts.

MODES TESTED

LTE Band 2/4/5/12/17

RESULTS

PASS

9.1 LTE BAND 2

QPSK EIRP POWER FOR LTE BAND 2 (1.4MHZ BANDWIDTH)

Test Results for Low Channel 1850.7MHz							
Frequency(MHz)	SG Level(dBm)	Cable Loss(dB)	Antenna Factor(dB)	Absolute Level(dBm)	Limit (dBm)	Margin(dBm)	Polarity
3701.4	-46.63	4.04	33.51	-17.16	-13	-4.16	Horizontal
3701.4	-44.80	4.04	33.51	-15.33	-13	-2.33	Vertical
5552.1	-46.85	5.24	35.84	-16.25	-13	-3.25	Vertical
5552.1	-49.16	5.24	35.84	-18.56	-13	-5.56	Horizontal
195.8	-39.84	1.43	16.02	-25.25	-13	-12.25	Vertical
436.0	-39.57	1.30	17.99	-22.88	-13	-9.88	Horizontal
Test Results for Mid Channel 1880MHz							
3760.0	-48.66	4.04	33.56	-19.14	-13	-6.14	Horizontal
3760.0	-50.25	4.04	33.56	-20.73	-13	-7.73	Vertical
5640.0	-46.62	5.24	35.91	-15.95	-13	-2.95	Vertical
5640.0	-53.79	5.24	35.91	-23.12	-13	-10.12	Horizontal
211.7	-39.74	1.62	16.97	-24.39	-13	-11.39	Vertical
391.9	-34.91	1.74	15.98	-20.68	-13	-7.68	Horizontal
Test Results for High Channel 1909.3MHz							
3818.6	-47.24	4.04	34.00	-17.28	-13	-4.28	Horizontal
3818.6	-50.18	4.04	34.00	-20.22	-13	-7.22	Vertical
5727.9	-47.85	5.24	36.04	-17.05	-13	-4.05	Vertical
5727.9	-50.20	5.24	36.04	-19.40	-13	-6.40	Horizontal
203.2	-35.68	1.42	17.29	-19.81	-13	-6.81	Vertical
341.9	-37.02	1.50	17.90	-20.61	-13	-7.61	Horizontal

QPSK EIRP POWER FOR LTE BAND 2 (20.0MHZ BANDWIDTH)

Test Results for Low Channel 1860MHz							
Frequency(MHz)	SG Level(dBm)	Cable Loss(dB)	Antenna Factor(dB)	Absolute Level(dBm)	Limit (dBm)	Margin(dBm)	Polarity
3720.0	-53.47	4.07	33.54	-24.00	-13	-11.00	Horizontal
3720.0	-49.78	4.07	33.54	-20.31	-13	-7.31	Vertical
5580.0	-48.86	5.28	35.86	-18.28	-13	-5.28	Vertical
5580.0	-53.09	5.28	35.86	-22.51	-13	-9.51	Horizontal
196.5	-40.56	1.58	16.89	-25.24	-13	-12.24	Vertical
326.2	-42.21	1.76	17.26	-26.71	-13	-13.71	Horizontal
Test Results for Mid Channel 1880MHz							
3760.0	-50.55	4.04	33.56	-21.03	-13	-8.03	Horizontal
3760.0	-51.19	4.04	33.56	-21.67	-13	-8.67	Vertical
5640.0	-48.64	5.24	35.91	-17.97	-13	-4.97	Vertical
5640.0	-51.69	5.24	35.91	-21.02	-13	-8.02	Horizontal
203.6	-40.94	1.46	16.27	-26.13	-13	-13.13	Vertical
320.4	-41.26	1.59	15.15	-27.70	-13	-14.70	Horizontal
Test Results for High Channel 1900MHz							
3800.0	-49.13	4.04	34.00	-19.17	-13	-6.17	Horizontal
3800.0	-53.74	4.04	34.00	-23.78	-13	-10.78	Vertical
5700.0	-47.54	5.24	36.04	-16.74	-13	-3.74	Vertical
5700.0	-51.03	5.24	36.04	-20.23	-13	-7.23	Horizontal
190.1	-36.62	1.36	17.39	-20.58	-13	-7.58	Vertical
264.8	-34.09	1.66	15.39	-20.36	-13	-7.36	Horizontal

Note: P_{Mea}(dBm)= Power(dBm)+ AR_{pl} (dBm)

. Over Limit= : P_{Mea}(dBm)-Limit(dBm)

. Both QPSK and 16QAM has been tested, the worst case is QPSK mode, the report just reported the worst case.

9.2 LTE BAND 4

QPSK EIRP POWER FOR LTE BAND 4 (1.4MHZ BANDWIDTH)

Test Results for Low Channel 1710.7MHz							
Frequency(MHz)	SG Level(dBm)	Cable Loss(dB)	Antenna Factor(dB)	Absolute Level(dBm)	Limit (dBm)	Margin(dBm)	Polarity
3421.4	-45.18	4.02	29.80	-19.40	-13	-6.40	Horizontal
3421.4	-48.36	4.02	29.80	-22.58	-13	-9.58	Vertical
5132.1	-50.23	5.24	35.84	-19.63	-13	-6.63	Vertical
5132.1	-50.15	5.24	35.84	-19.55	-13	-6.55	Horizontal
187.5	-42.38	1.68	16.04	-28.02	-13	-15.02	Vertical
307.5	-44.54	1.78	17.74	-28.58	-13	-15.58	Horizontal
Test Results for Mid Channel 1732.5MHz							
3465.0	-53.98	4.03	30.00	-28.01	-13	-15.01	Horizontal
3465.0	-51.89	4.03	30.00	-25.92	-13	-12.92	Vertical
5197.5	-51.66	5.25	35.86	-21.05	-13	-8.05	Vertical
5197.5	-53.16	5.25	35.86	-22.55	-13	-9.55	Horizontal
196.5	-37.78	1.72	17.69	-21.81	-13	-8.81	Vertical
392.8	-42.06	1.62	16.02	-27.65	-13	-14.65	Horizontal
Test Results for High Channel 1754.3MHz							
3508.6	-53.09	4.05	30.01	-27.13	-13	-14.13	Horizontal
3508.6	-51.17	4.05	30.01	-25.21	-13	-12.21	Vertical
5262.9	-48.07	5.26	35.86	-17.47	-13	-4.47	Vertical
5262.9	-50.60	5.26	35.86	-20.00	-13	-7.00	Horizontal
182.9	-38.50	1.80	16.69	-23.61	-13	-10.61	Vertical
338.9	-41.57	1.75	16.66	-26.67	-13	-13.67	Horizontal

QPSK EIRP POWER FOR LTE BAND 4 (20.0MHZ BANDWIDTH)

Test Results for Low Channel 1720MHz							
Frequency(MHz)	SG Level(dBm)	Cable Loss(dB)	Antenna Factor(dB)	Absolute Level(dBm)	Limit (dBm)	Margin(dBm)	Polarity
3440.0	-47.09	4.02	29.80	-21.31	-13	-8.31	Horizontal
3440.0	-46.11	4.02	29.80	-20.33	-13	-7.33	Vertical
5160.0	-49.75	5.24	35.84	-19.15	-13	-6.15	Vertical
5160.0	-49.75	5.24	35.84	-19.15	-13	-6.15	Horizontal
180.4	-39.88	1.57	17.26	-24.19	-13	-11.19	Vertical
272.9	-42.64	1.78	16.35	-28.07	-13	-15.07	Horizontal
Test Results for Mid Channel 1732.5MHz							
3465.0	-50.40	4.03	30.00	-24.43	-13	-11.43	Horizontal
3465.0	-48.46	4.03	30.00	-22.49	-13	-9.49	Vertical
5197.5	-53.32	5.25	35.86	-22.71	-13	-9.71	Vertical
5197.5	-50.88	5.25	35.86	-20.27	-13	-7.27	Horizontal
193.6	-35.02	1.44	17.95	-18.51	-13	-5.51	Vertical
323.4	-39.59	1.65	16.09	-25.15	-13	-12.15	Horizontal
Test Results for High Channel 1745MHz							
3490.0	-53.92	2.91	27.68	-29.15	-13	-16.15	Horizontal
3490.0	-45.95	2.91	27.68	-21.18	-13	-8.18	Vertical
5235.0	-47.11	5.26	35.86	-16.51	-13	-3.51	Vertical
5235.0	-53.45	5.26	35.86	-22.85	-13	-9.85	Horizontal
194.3	-41.53	1.61	16.85	-26.29	-13	-13.29	Vertical
397.1	-34.85	1.61	15.19	-21.27	-13	-8.27	Horizontal

Note: P_{Mea}(dBm)= Power(dBm)+ AR_{pl} (dBm)

. Over Limit= : P_{Mea}(dBm)-Limit(dBm)

. Both QPSK and 16QAM has been tested, the worst case is QPSK mode, the report just reported the worst case.

9.3 LTE BAND 5

QPSK EIRP POWER FOR LTE BAND 5 (1.4MHZ BANDWIDTH)

Test Results for Low Channel 824.7MHz							
Frequency(MHz)	SG Level(dBm)	Cable Loss(dB)	Antenna Factor(dB)	Absolute Level(dBm)	Limit (dBm)	Margin(dBm)	Polarity
1649.4	-49.18	2.78	27.50	-24.46	-13	-11.46	Horizontal
1649.4	-52.28	2.78	27.50	-27.56	-13	-14.56	Vertical
2474.1	-51.44	2.90	27.80	-26.54	-13	-13.54	Vertical
2474.1	-50.26	2.90	27.80	-25.36	-13	-12.36	Horizontal
190.2	-39.96	1.76	17.59	-24.13	-13	-11.13	Vertical
439.3	-38.24	1.63	15.87	-24.00	-13	-11.00	Horizontal
Test Results For Mid Channel 836.5MHz							
1673.0	-45.71	2.80	27.48	-21.03	-13	-8.03	Horizontal
1673.0	-53.10	2.80	27.48	-28.42	-13	-15.42	Vertical
2509.5	-53.74	2.91	27.70	-28.95	-13	-15.95	Vertical
2509.5	-53.49	2.91	27.70	-28.70	-13	-15.70	Horizontal
203.4	-43.19	1.61	15.68	-29.12	-13	-16.12	Vertical
399.3	-37.70	1.59	17.52	-21.78	-13	-8.78	Horizontal
Test Results for High Channel 848.3MHz							
1696.6	-47.16	2.82	27.43	-22.55	-13	-9.55	Horizontal
1696.6	-48.25	2.82	27.43	-23.64	-13	-10.64	Vertical
2544.9	-52.25	2.92	27.74	-27.43	-13	-14.43	Vertical
2544.9	-50.92	2.92	27.74	-26.10	-13	-13.10	Horizontal
199.4	-38.91	1.69	16.67	-23.92	-13	-10.92	Vertical
240.0	-41.72	1.70	17.18	-26.24	-13	-13.24	Horizontal

QPSK EIRP POWER FOR LTE BAND 5 (10MHZ BANDWIDTH)

Test Results for Low Channel 829MHz							
Frequency(MHz)	SG Level(dBm)	Cable Loss(dB)	Antenna Factor(dB)	Absolute Level(dBm)	Limit (dBm)	Margin(dBm)	Polarity
1658.0	-51.50	2.78	27.50	-26.78	-13	-13.78	Horizontal
1658.0	-53.86	2.78	27.50	-29.14	-13	-16.14	Vertical
2487.0	-44.76	2.90	27.80	-19.86	-13	-6.86	Vertical
2487.0	-49.56	2.90	27.80	-24.66	-13	-11.66	Horizontal
209.3	-39.94	1.71	15.57	-26.08	-13	-13.08	Vertical
379.7	-41.20	1.34	16.40	-26.14	-13	-13.14	Horizontal
Test Results for Mid Channel 836.5MHz							
1673.0	-46.47	2.80	27.48	-21.79	-13	-8.79	Horizontal
1673.0	-46.39	2.80	27.48	-21.71	-13	-8.71	Vertical
2509.5	-47.99	2.91	27.70	-23.20	-13	-10.20	Vertical
2509.5	-53.24	2.91	27.70	-28.45	-13	-15.45	Horizontal
191.4	-35.30	1.44	17.04	-19.70	-13	-6.70	Vertical
374.6	-38.84	1.76	17.62	-22.98	-13	-9.98	Horizontal
Test Results for High Channel 844MHz							
1688.0	-48.82	2.82	27.43	-24.21	-13	-11.21	Horizontal
1688.0	-48.53	2.82	27.43	-23.92	-13	-10.92	Vertical
2532.0	-53.90	2.92	27.74	-29.08	-13	-16.08	Vertical
2532.0	-53.85	2.92	27.74	-29.03	-13	-16.03	Horizontal
180.9	-37.52	1.74	17.70	-21.56	-13	-8.56	Vertical
258.2	-44.80	1.41	17.46	-28.74	-13	-15.74	Horizontal

Note: P_{Mea}(dBm)= Power(dBm)+ AR_{pl} (dBm)

. Over Limit= : P_{Mea}(dBm)-Limit(dBm)

. Both QPSK and 16QAM has been tested, the worst case is QPSK mode, the report just reported the worst case.

9.4 LTE BAND 12

QPSK EIRP POWER FOR LTE BAND 12 (1.4MHZ BANDWIDTH)

Test Results for Low Channel 699.7MHz							
Frequency(MHz)	SG Level(dBm)	Cable Loss(dB)	Antenna Factor(dB)	Absolute Level(dBm)	Limit (dBm)	Margin(dBm)	Polarity
1399.4	-47.51	2.60	27.20	-22.91	-13	-9.91	Horizontal
1399.4	-51.41	2.60	27.20	-26.81	-13	-13.81	Vertical
2099.1	-49.85	2.85	27.54	-25.16	-13	-12.16	Vertical
2099.1	-49.26	2.85	27.54	-24.57	-13	-11.57	Horizontal
207.2	-35.65	1.49	17.78	-19.36	-13	-6.36	Vertical
266.9	-41.21	1.36	17.33	-25.24	-13	-12.24	Horizontal
Test Results For Mid Channel 707.5MHz							
1415.0	-44.65	2.61	27.28	-19.98	-13	-6.98	Horizontal
1415.0	-52.44	2.61	27.28	-27.77	-13	-14.77	Vertical
2122.5	-50.14	2.87	27.59	-25.42	-13	-12.42	Vertical
2122.5	-53.32	2.87	27.59	-28.60	-13	-15.60	Horizontal
190.9	-43.90	1.73	15.74	-29.89	-13	-16.89	Vertical
423.9	-40.78	1.62	15.79	-26.61	-13	-13.61	Horizontal
Test Results for High Channel 715.3MHz							
1430.6	-53.84	2.63	27.28	-29.19	-13	-16.19	Horizontal
1430.6	-46.75	2.63	27.28	-22.10	-13	-9.10	Vertical
2145.9	-51.27	2.88	27.60	-26.55	-13	-13.55	Vertical
2145.9	-53.53	2.88	27.60	-28.81	-13	-15.81	Horizontal
202.2	-35.48	1.61	18.00	-19.09	-13	-6.09	Vertical
279.3	-34.12	1.45	15.49	-20.09	-13	-7.09	Horizontal

QPSK EIRP POWER FOR LTE BAND 12 (10MHZ BANDWIDTH)

Test Results for Low Channel 704MHz							
Frequency(MHz)	SG Level(dBm)	Cable Loss(dB)	Antenna Factor(dB)	Absolute Level(dBm)	Limit (dBm)	Margin(dBm)	Polarity
1408.0	-47.18	2.61	27.26	-22.53	-13	-9.53	Horizontal
1408.0	-50.49	2.61	27.26	-25.84	-13	-12.84	Vertical
2112.0	-44.91	2.87	27.58	-20.20	-13	-7.20	Vertical
2112.0	-52.30	2.87	27.58	-27.59	-13	-14.59	Horizontal
203.5	-37.13	1.31	16.97	-21.47	-13	-8.47	Vertical
416.2	-42.46	1.65	16.70	-27.41	-13	-14.41	Horizontal
Test Results for Mid Channel 707.5MHz							
1415.0	-46.73	2.61	27.28	-22.06	-13	-9.06	Horizontal
1415.0	-47.56	2.61	27.28	-22.89	-13	-9.89	Vertical
2122.5	-44.28	2.87	27.59	-19.56	-13	-6.56	Vertical
2122.5	-51.06	2.87	27.59	-26.34	-13	-13.34	Horizontal
205.5	-39.73	1.72	17.99	-23.46	-13	-10.46	Vertical
382.6	-44.94	1.73	17.94	-28.73	-13	-15.73	Horizontal
Test Results for High Channel 711MHz							
1422.0	-50.98	2.62	27.28	-26.32	-13	-13.32	Horizontal
1422.0	-52.87	2.62	27.28	-28.21	-13	-15.21	Vertical
2133.0	-51.50	2.87	27.60	-26.77	-13	-13.77	Vertical
2133.0	-49.39	2.87	27.60	-24.66	-13	-11.66	Horizontal
200.4	-35.97	1.58	15.93	-21.62	-13	-8.62	Vertical
273.5	-36.67	1.36	15.59	-22.44	-13	-9.44	Horizontal

Note: P_{Mea}(dBm)= Power(dBm)+ AR_{pl} (dBm)

. Over Limit= : P_{Mea}(dBm)-Limit(dBm)

. Both QPSK and 16QAM has been tested, the worst case is QPSK mode, the report just reported the worst case.

9.5 LTE BAND 17

QPSK EIRP POWER FOR LTE BAND 17 (5MHZ BANDWIDTH)

Test Results for Low Channel 706.5MHz							
Frequency(MHz)	SG Level(dBm)	Cable Loss(dB)	Antenna Factor(dB)	Absolute Level(dBm)	Limit (dBm)	Margin(dBm)	Polarity
1413.0	-49.40	2.61	27.28	-24.73	-13	-11.73	Horizontal
1413.0	-44.88	2.61	27.28	-20.21	-13	-7.21	Vertical
2119.5	-48.05	2.87	27.59	-23.33	-13	-10.33	Vertical
2119.5	-49.08	2.87	27.59	-24.36	-13	-11.36	Horizontal
207.9	-34.80	1.71	16.15	-20.36	-13	-7.36	Vertical
290.3	-39.82	1.41	17.32	-23.91	-13	-10.91	Horizontal
Test Results For Mid Channel 710MHz							
1420.0	-45.12	2.62	27.30	-20.44	-13	-7.44	Horizontal
1420.0	-51.03	2.62	27.30	-26.35	-13	-13.35	Vertical
2130.0	-52.71	2.87	27.62	-27.96	-13	-14.96	Vertical
2130.0	-53.10	2.87	27.62	-28.35	-13	-15.35	Horizontal
186.2	-34.48	1.42	15.25	-20.66	-13	-7.66	Vertical
454.7	-35.00	1.36	17.19	-19.17	-13	-6.17	Horizontal
Test Results for High Channel 713.5MHz							
1427.0	-46.18	2.66	27.28	-21.56	-13	-8.56	Horizontal
1427.0	-53.90	2.66	27.28	-29.28	-13	-16.28	Vertical
2140.5	-51.31	2.88	27.60	-26.59	-13	-13.59	Vertical
2140.5	-50.12	2.88	27.60	-25.40	-13	-12.40	Horizontal
187.9	-41.97	1.32	17.29	-26.00	-13	-13.00	Vertical
461.3	-34.64	1.72	16.89	-19.47	-13	-6.47	Horizontal

QPSK EIRP POWER FOR LTE BAND 17 (10MHZ BANDWIDTH)

Test Results for Low Channel 709MHz							
Frequency(MHz)	SG Level(dBm)	Cable Loss(dB)	Antenna Factor(dB)	Absolute Level(dBm)	Limit (dBm)	Margin(dBm)	Polarity
1418.0	-45.33	2.62	27.30	-20.65	-13	-7.65	Horizontal
1418.0	-47.63	2.62	27.30	-22.95	-13	-9.95	Vertical
2127.0	-48.44	2.87	27.62	-23.69	-13	-10.69	Vertical
2127.0	-50.31	2.87	27.62	-25.56	-13	-12.56	Horizontal
179.2	-34.16	1.35	16.91	-18.60	-13	-5.60	Vertical
336.5	-36.58	1.62	16.31	-21.89	-13	-8.89	Horizontal
Test Results for Mid Channel 710MHz							
1420.0	-53.25	2.62	27.30	-28.57	-13	-15.57	Horizontal
1420.0	-48.05	2.62	27.30	-23.37	-13	-10.37	Vertical
2130.0	-53.40	2.87	27.62	-28.65	-13	-15.65	Vertical
2130.0	-50.49	2.87	27.62	-25.74	-13	-12.74	Horizontal
193.9	-42.33	1.51	17.14	-26.70	-13	-13.70	Vertical
331.0	-44.69	1.77	16.88	-29.58	-13	-16.58	Horizontal
Test Results for High Channel 711MHz							
1422.0	-45.98	2.62	27.30	-21.30	-13	-8.30	Horizontal
1422.0	-52.80	2.62	27.30	-28.12	-13	-15.12	Vertical
2133.0	-50.98	2.87	27.62	-26.23	-13	-13.23	Vertical
2133.0	-53.72	2.87	27.62	-28.97	-13	-15.97	Horizontal
208.5	-44.12	1.78	15.95	-29.95	-13	-16.95	Vertical
432.6	-40.31	1.34	17.95	-23.71	-13	-10.71	Horizontal

Note: Spurious Emission Level = Spectrum Analyzer Read Value + Cable Loss+ Antenna Factor + 11.74

. Margin = Spurious Emission Level - Limit

. Both QPSK and 16QAM has been tested, the worst case is QPSK mode, the report just reported the worst case.

10. FREQUENCY STABILITY

RULE PART(S)

FCC: §2.1055, §22.355, §24.235, §27.54,

LIMITS

§22.355 - The carrier frequency shall not depart from the reference frequency in excess of ± 2.5 ppm for mobile stations.

§24.235 - The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

TEST PROCEDURE

Use CMW 500 with Frequency Error measurement capability.

- ☐ Temp. = -30° to $+50^{\circ}\text{C}$
- ☐ Voltage = low voltage, DC 3.4V, Normal, DC 3.8V and High voltage, DC 4.2V.

Frequency Stability vs Temperature:

The EUT is placed inside a temperature chamber. The temperature is set to -30°C and allowed to stabilize. After sufficient soak time, the transmitting frequency error is measured. The temperature is increased by 10 degrees, allowed to stabilize and soak, and then the measurement is repeated. This is repeated until $+50^{\circ}\text{C}$ is reached.

Frequency Stability vs Voltage:

The peak frequency error is recorded (worst-case).

MODES TESTED

LTE Band 2/4/5/12/17

RESULTS

See the following pages.

10.1 LTE BAND 2

Band 2 QPSK, (20MHz BANDWIDTH RB size 100 RB Offset 0)

Frequency error vs. Voltage

Voltage [Vdc]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
3.40	1880	13.1	0.006962	2.5
3.80	1880	14.0	0.007423	2.5
4.20	1880	13.8	0.007331	2.5

Frequency error vs. Temperature

Temperature [°C]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
Normal (25C)	1880	12.2	0.006510	2.5
Extreme (50C)	1880	11.6	0.006153	2.5
Extreme (40C)	1880	14.2	0.007542	2.5
Extreme (30C)	1880	13.8	0.007342	2.5
Extreme (10C)	1880	14.1	0.007492	2.5
Extreme (0C)	1880	11.7	0.006240	2.5
Extreme (-10C)	1880	13.4	0.007149	2.5
Extreme (-20C)	1880	14.4	0.007666	2.5
Extreme (-30C)	1880	15.0	0.007969	2.5

Band 2 16QAM, (20MHz BANDWIDTH RB size 100 RB Offset 0)

Frequency error vs. Voltage

Voltage [Vdc]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
3.40	1880	9.9	0.005267	2.5
3.80	1880	8.9	0.004753	2.5
4.20	1880	8.6	0.004565	2.5

Frequency error vs. Temperature

Temperature [°C]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
Normal (25C)	1880	10.0	0.005328	2.5
Extreme (50C)	1880	8.6	0.004592	2.5
Extreme (40C)	1880	7.8	0.004127	2.5
Extreme (30C)	1880	9.2	0.004890	2.5
Extreme (10C)	1880	8.5	0.004495	2.5
Extreme (0C)	1880	8.0	0.004264	2.5
Extreme (-10C)	1880	9.2	0.004881	2.5
Extreme (-20C)	1880	9.4	0.004988	2.5
Extreme (-30C)	1880	7.6	0.004054	2.5

***Note:** Frequency error measurements were made by using the build-in capability of the Wireless Communication Test Set.

10.2 LTE BAND 4

Band 4 QPSK, (20MHz BANDWIDTH RB size 100 RB Offset 0)

Frequency error vs. Voltage

Voltage [Vdc]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
3.40	1732.5	8.9	0.005121	2.5
3.80	1732.5	8.7	0.005005	2.5
4.20	1732.5	8.7	0.005017	2.5

Frequency error vs. Temperature

Temperature [°C]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
Normal (25C)	1732.5	8.2	0.004757	2.5
Extreme (50C)	1732.5	8.5	0.004883	2.5
Extreme (40C)	1732.5	7.2	0.004141	2.5
Extreme (30C)	1732.5	5.6	0.003223	2.5
Extreme (10C)	1732.5	7.3	0.004226	2.5
Extreme (0C)	1732.5	9.5	0.005489	2.5
Extreme (-10C)	1732.5	8.4	0.004870	2.5
Extreme (-20C)	1732.5	6.9	0.003973	2.5
Extreme (-30C)	1732.5	8.5	0.004918	2.5

Band 4 16QAM, (20MHz BANDWIDTH RB size 100 RB Offset 0)

Frequency error vs. Voltage

Voltage [Vdc]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
3.40	1732.5	10.3	0.005922	2.5
3.80	1732.5	8.9	0.005110	2.5
4.20	1732.5	7.6	0.004412	2.5

Frequency error vs. Temperature

Temperature [°C]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
Normal (25C)	1732.5	9.2	0.005337	2.5
Extreme (50C)	1732.5	8.6	0.004975	2.5
Extreme (40C)	1732.5	7.9	0.004577	2.5
Extreme (30C)	1732.5	8.5	0.004927	2.5
Extreme (10C)	1732.5	9.2	0.005320	2.5
Extreme (0C)	1732.5	8.3	0.004772	2.5
Extreme (-10C)	1732.5	9.2	0.005318	2.5
Extreme (-20C)	1732.5	9.2	0.005317	2.5
Extreme (-30C)	1732.5	7.6	0.004413	2.5

***Note:** Frequency error measurements were made by using the build-in capability of the Wireless Communication Test Set.

10.3 LTE BAND 5

Band 5 QPSK, (10MHz BANDWIDTH RB size 50 RB Offset 0)

Frequency error vs. Voltage

Voltage [Vdc]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
3.40	836.5	5.5	0.006580	2.5
3.80	836.5	6.8	0.008182	2.5
4.20	836.5	4.9	0.005803	2.5

Frequency error vs. Temperature

Temperature [°C]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
Normal (25C)	836.5	6.0	0.007139	2.5
Extreme (50C)	836.5	5.7	0.006856	2.5
Extreme (40C)	836.5	5.9	0.007078	2.5
Extreme (30C)	836.5	6.2	0.007461	2.5
Extreme (10C)	836.5	5.2	0.006195	2.5
Extreme (0C)	836.5	5.2	0.006183	2.5
Extreme (-10C)	836.5	5.3	0.006371	2.5
Extreme (-20C)	836.5	6.4	0.007660	2.5
Extreme (-30C)	836.5	6.3	0.007517	2.5

Band 5 16QAM, (10MHz BANDWIDTH RB size 50 RB Offset 0)

Frequency error vs. Voltage

Voltage [Vdc]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
3.40	836.5	5.5	0.006625	2.5
3.80	836.5	6.6	0.007857	2.5
4.20	836.5	5.2	0.006228	2.5

Frequency error vs. Temperature

Temperature [°C]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
Normal (25C)	836.5	6.1	0.007330	2.5
Extreme (50C)	836.5	6.1	0.007340	2.5
Extreme (40C)	836.5	6.1	0.007308	2.5
Extreme (30C)	836.5	6.8	0.008118	2.5
Extreme (10C)	836.5	5.7	0.006765	2.5
Extreme (0C)	836.5	5.2	0.006190	2.5
Extreme (-10C)	836.5	6.0	0.007180	2.5
Extreme (-20C)	836.5	6.4	0.007623	2.5
Extreme (-30C)	836.5	6.7	0.007956	2.5

***Note:** Frequency error measurements were made by using the build-in capability of the Wireless Communication Test Set.

10.4 LTE BAND 12

Band 12 QPSK, (10MHz BANDWIDTH RB size 50 RB Offset 0

Frequency error vs. Voltage

Voltage [Vdc]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
3.40	707.5	9.0	0.012673	2.5
3.80	707.5	10.3	0.014561	2.5
4.20	707.5	8.3	0.011676	2.5

Frequency error vs. Temperature

Temperature [°C]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
Normal (25C)	707.5	9.0	0.012689	2.5
Extreme (50C)	707.5	7.3	0.010378	2.5
Extreme (40C)	707.5	7.5	0.010533	2.5
Extreme (30C)	707.5	8.0	0.011357	2.5
Extreme (10C)	707.5	7.8	0.011063	2.5
Extreme (0C)	707.5	9.1	0.012857	2.5
Extreme (-10C)	707.5	8.4	0.011888	2.5
Extreme (-20C)	707.5	8.5	0.012024	2.5
Extreme (-30C)	707.5	8.2	0.011634	2.5

Band 12 16QAM, (10MHz BANDWIDTH RB size 50 RB Offset 0)

Frequency error vs. Voltage

Voltage [Vdc]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
3.40	707.5	7.5	0.010614	2.5
3.80	707.5	7.8	0.011046	2.5
4.20	707.5	7.1	0.010079	2.5

Frequency error vs. Temperature

Temperature [°C]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
Normal (25C)	707.5	6.5	0.009175	2.5
Extreme (50C)	707.5	5.5	0.007765	2.5
Extreme (40C)	707.5	6.4	0.009110	2.5
Extreme (30C)	707.5	-7.7	-0.010912	2.5
Extreme (10C)	707.5	-8.2	-0.011590	2.5
Extreme (0C)	707.5	2.9	0.004100	2.5
Extreme (-10C)	707.5	-5.2	-0.007292	2.5
Extreme (-20C)	707.5	-8.7	-0.012302	2.5
Extreme (-30C)	707.5	-10.2	-0.014350	2.5

***Note:** Frequency error measurements were made by using the build-in capability of the Wireless Communication Test Set.

10.5 LTE BAND 17

Band 17 QPSK, (10MHz BANDWIDTH RB size 50 RB Offset 0)

Frequency error vs. Voltage

Voltage [Vdc]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
3.40	710.0	9.4	0.013302	2.5
3.80	710.0	8.7	0.012294	2.5
4.20	710.0	8.2	0.011609	2.5

Frequency error vs. Temperature

Temperature [°C]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
Normal (25C)	710.0	9.6	0.013569	2.5
Extreme (50C)	710.0	9.0	0.012707	2.5
Extreme (40C)	710.0	7.9	0.011170	2.5
Extreme (30C)	710.0	9.4	0.013244	2.5
Extreme (10C)	710.0	9.0	0.012648	2.5
Extreme (0C)	710.0	8.0	0.011210	2.5
Extreme (-10C)	710.0	9.0	0.012663	2.5
Extreme (-20C)	710.0	8.6	0.012122	2.5
Extreme (-30C)	710.0	7.8	0.010941	2.5

Band 17 16QAM, (10MHz BANDWIDTH RB size 50 RB Offset 0)

Frequency error vs. Voltage

Voltage [Vdc]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
3.40	710.0	10.3	0.014468	2.5
3.80	710.0	8.9	0.012594	2.5
4.20	710.0	8.4	0.011770	2.5

Frequency error vs. Temperature

Temperature [°C]	Frequency [MHz]	Frequency* Error[Hz]	Frequency Error[ppm]	Limit [ppm]
Normal (25C)	710.0	9.7	0.013626	2.5
Extreme (50C)	710.0	9.2	0.013009	2.5
Extreme (40C)	710.0	8.7	0.012313	2.5
Extreme (30C)	710.0	8.5	0.011987	2.5
Extreme (10C)	710.0	8.0	0.011207	2.5
Extreme (0C)	710.0	8.1	0.011343	2.5
Extreme (-10C)	710.0	8.9	0.012570	2.5
Extreme (-20C)	710.0	8.9	0.012545	2.5
Extreme (-30C)	710.0	8.4	0.011762	2.5

***Note:** Frequency error measurements were made by using the build-in capability of the Wireless Communication Test Set.

11. Peak-to-Average Ratio

11.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


11.2 Measuring Instruments

See list of measuring instruments of this test report.

11.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. For LTE operating modes:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.

11.4 Test Setup



MODES TESTED

LTE Band 2/4/5/12/17

Test data reference attachment.

-----END OF REPORT-----