


TEST REPORT

FCC ID.	2AQRM-G1
Test Report No.	TCT241217E040
Date of issue	Feb. 14, 2025
Testing laboratory	SHENZHEN TONGCE TESTING LAB
Testing location/ address:	2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China
Applicant's name	FOXX Development Inc.
Address	3480 Preston Ridge Road, Suite500, Alpharetta, GA 30005, USA
Manufacturer's name	FOXX Development Inc.
Address	3480 Preston Ridge Road, Suite500, Alpharetta, GA 30005, USA
Standard(s)	FCC CFR Title 47 Part 2 FCC CFR Title 47 Part 22 FCC CFR Title 47 Part 24 FCC CFR Title 47 Part 27
Product Name	Smart Phone
Trade Mark	FOXX, MIRO, FOXXD
Model/Type reference	G1
Rating(s)	Rechargeable Li-ion Battery DC 3.87V Power Adapter: Model: 805A-018B-1A Input: AC 100-240V, 50/60Hz, 0.5A Output: DC 5.0V, 3.0A or DC 9.0V, 2.0A or DC 12.0V, 1.5A MAX
Date of receipt of test item	Dec. 17, 2024
Date (s) of performance of test	Dec. 18, 2024 ~ Feb. 10, 2025
Tested by (+signature)	Brews XU
Check by (+signature)	Beryl ZHAO
Approved by (+signature) :	Tomsin



General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Table of Contents

1. General Product Information	3
1.1. EUT description	3
1.2. Model(s) list.....	4
1.3. Operation Frequency.....	4
2. Test Result Summary	5
3. General Information.....	6
3.1. Test environment and mode	6
3.2. Description of Support Units	7
3.3. Configuration of Tested System.....	8
3.4. Measurement Results Explanation Example.....	8
4. Facilities and Accreditations	9
4.1. Facilities	9
4.2. Location.....	9
4.3. Measurement Uncertainty	9
5. Test Results and Measurement Data.....	10
5.1. Conducted Output Power Measurement.....	10
5.2. Peak to Average Ratio	11
5.3. 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	12
5.4. Band Edge and Conducted Spurious Emission Measurement.....	13
5.5. Field Strength of Spurious Radiation Measurement	14
5.6. Frequency Stability Measurement.....	23

Appendix A: Test Result of Conducted Test

Appendix B: Photographs of Test Setup

Appendix C: Photographs of EUT

1. General Product Information

1.1. EUT description

Product Name	Smart Phone
Model/Type reference	G1
Sample Number	TCT241217E035-0102
3G Version	WCDMA: R9 HSDPA: Release 5 HSUPA: Release 6
Tx Frequency	GSM/GPRS/EGPRS 850: 824.2MHz ~ 848.8MHz GSM/GPRS/EGPRS 1900: 1850.2MHz ~ 1909.8MHz WCDMA Band V: 826.4MHz ~ 846.6MHz WCDMA Band IV: 1712.4MHz ~ 1752.6MHz WCDMA Band II: 1852.4MHz ~ 1907.6MHz
Rx Frequency	GSM/GPRS/EGPRS 850: 869.2MHz ~ 893.8MHz GSM/GPRS/EGPRS 1900: 1930.2MHz ~ 1989.8MHz WCDMA Band V: 871.4MHz ~ 891.6MHz WCDMA Band IV: 2112.4MHz ~ 2152.6MHz WCDMA Band II: 1932.4MHz ~ 1987.6MHz
Maximum Output Power to Antenna	GSM850: 31.66dBm GSM1900: 29.01dBm GPRS850: 31.51dBm GPRS1900: 29.13dBm EGPRS850: 25.71dBm EGPRS1900: 24.48dBm WCDMA Band V: 23.44dBm WCDMA Band IV: 21.81dBm WCDMA Band II: 21.77dBm
99% Occupied Bandwidth	GSM850: 250KGXW GSM1900: 250KGXW GPRS850 Class 8: 250KGXW GPRS1900 Class 8: 250KGXW EGPRS850 Class 8: 247KG7W EGPRS1900 Class 8: 263KG7W WCDMA Band V RMC 12.2Kbps: 4M22F9W WCDMA Band IV RMC 12.2Kbps: 4M24F9W WCDMA Band II RMC 12.2Kbps: 4M21F9W
Type of Modulation	GSM/GPRS: GMSK EGPRS: 8PSK WCDMA/HSDPA/HSUPA: QPSK
Antenna Type	Inside Antenna
Antenna Gain	GSM/GPRS/EGPRS 850: -4.55dBi GSM/GPRS/EGPRS 1900: -1.66dBi WCDMA Band V: -4.55dBi WCDMA Band IV: -2.55dBi WCDMA Band II: -1.66dBi

Rating(s).....	Rechargeable Li-ion Battery DC 3.87V Power Adapter: Model: 805A-018B-1A Input: AC 100-240V, 50/60Hz, 0.5A Output: DC 5.0V, 3.0A or DC 9.0V, 2.0A or DC 12.0V, 1.5A MAX
----------------	--

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. Model(s) list

None.

1.3. Operation Frequency

GSM 850		PCS1900	
Channel:	Frequency (MHz)	Channel:	Frequency (MHz)
128	824.20	512	1850.20
129	824.40	513	1850.40
....
189	836.40	660	1879.80
190	836.60	661	1880.00
191	836.80	662	1880.20
...
250	848.60	809	1909.60
251	848.80	810	1909.80

WCDMA Band IV		WCDMA Band V		WCDMA Band II	
Channel:	Frequency (MHz)	Channel:	Frequency (MHz)	Channel:	Frequency (MHz)
1312	1712.4	4132	826.40	9262	1852.40
....	4133	826.60	9263	1852.60
....
....	4182	836.40	9399	1879.80
1413	1732.6	4183	836.60	9400	1880.00
....	4184	836.80	9401	1880.20
....
1513	1752.6	4233	846.60	9538	1907.60

2. Test Result Summary

Requirement	CFR 47 Section	Result
Conducted Output Power	§22.913; §2.1046 §24.232; §27.50(d)	PASS
Peak-to-Average Ratio	§2.1046; §24.232(d) §22.913; §27.50(d)	PASS
Effective Radiated Power	§2.1046; §22.913(a) §24.232; §27.50(d)	PASS
Equivalent Isotropic Radiated Power	§2.1046; §22.913(a) §24.232; §27.50(d)	PASS
Occupied Bandwidth	§2.1049	PASS
Band Edge	§2.1051 §22.917(a) §24.238(a) §27.53(g)	PASS
Conducted Spurious Emission	§2.1051; §22.917 §24.238; §27.53(h)	PASS
Field Strength of Spurious Radiation	§2.1053; §22.917(a) §24.238; §27.53(g)	PASS
Frequency Stability for Temperature & Voltage	§2.1055; §22.355 §24.235; §27.54	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

3. General Information

3.1. Test environment and mode

Operating Environment:	
Temperature:	23.9°C
Humidity:	48 % RH
Atmospheric Pressure:	1010 mbar

Remark: This product has a built-in rechargeable battery, so in an independent test, the EUT battery was fully-charged.

Test Mode		
Band	Radiated TCs	Conducted TCs
GSM 850	GSM Link GPRS class 12 Link EGPRS class 12 Link	GSM Link GPRS class 12 Link EGPRS class 12 Link
PCS 1900	GSM Link GPRS class 12 Link EGPRS class 12 Link	GSM Link GPRS class 12 Link EGPRS class 12 Link
WCDMA Band V	RMC 12.2Kbps Link	RMC 12.2Kbps Link
WCDMA Band IV	RMC 12.2Kbps Link	RMC 12.2Kbps Link
WCDM Band II	RMC 12.2Kbps Link	RMC 12.2Kbps Link

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power. Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission. The sample was placed (0.8m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarization. The emissions worst-case (Z axis) are shown in Test Results of the following pages.

3.2. Description of Support Units


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

3.3. Configuration of Tested System



3.4. Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level. The spectrum analyzer offset is derived from RF cable loss and attenuator factor.
Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 3 dB and a 5dB attenuator.

Example: $\text{Offset (dB)} = \text{RF cable loss (dB)} + \text{attenuator factor (dB)}$.
= 8(dB)

4. Facilities and Accreditations

4.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Innovation, Science and Economic Development Canada for radio equipment testing.

4.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

4.3. Measurement Uncertainty


The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	± 3.10 dB
2	RF power, conducted	± 0.12 dB
3	Spurious emissions, conducted	± 0.11 dB
4	All emissions, radiated(<1 GHz)	± 4.56 dB
5	All emissions, radiated(1 GHz - 18 GHz)	± 4.22 dB
6	All emissions, radiated(18 GHz- 40 GHz)	± 4.36 dB
7	Temperature	$\pm 0.1^\circ\text{C}$
8	Humidity	$\pm 1.0\%$

5. Test Results and Measurement Data

5.1. Conducted Output Power Measurement

5.1.1. Test Specification

Test Requirement:	FCC part 22.913(a) and FCC part 24.232(b) FCC part 27.50(d)
Test Method:	FCC KDB 971168 D01 v03r01
Operation mode:	Refer to item 3.1
Limits:	GSM 850: 7W PCS 1900: 2W WCDMA Band V:7W WCDMA Band II: 2W WCDMA Band IV:1W
Test Setup:	 <p>System Simulator EUT</p>
Test Procedure:	<ol style="list-style-type: none"> 1. The transmitter output port was connected to the system simulator. 2. Set EUT at maximum power through system simulator. 3. Select lowest, middle, and highest channels for each band and different modulation. 4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.
Test Result:	PASS

5.1.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Wideband Radio Communication Tester	R&S	CMW500	165017	Jan. 20, 2026

5.2. Peak to Average Ratio

5.2.1. Test Specification

Test Requirement:	FCC part 24.232(d); FCC part 22.913; FCC part 27.50(d);
Test Method:	ANSI C63.26:2013
Operation mode:	Refer to item 3.1
Limit:	The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.
Test Setup:	<p>The diagram illustrates the test setup. A 'System Simulator' (represented by a purple box with a screen and buttons) and a 'Spectrum Analyzer' (represented by a green box with a screen and buttons) are connected to a 'Power Divider' (represented by a black rectangle). The Power Divider splits the signal into two paths: one leading to the 'EUT' (represented by a yellow box) and another leading to a load (represented by an open circle).</p>
Test Procedure:	<ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 D01v03r01 Section 5.7.1. 2. The EUT was connected to spectrum analyzer and system simulator via a power divider. 3. Set EUT to transmit at maximum output power. 4. For GSM/EGPRS operating modes, signal gating is implemented on the spectrum analyzer by triggering from the system simulator. 5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer. Record the maximum PAPR level associated with a probability of 0.1%.
Test Result:	PASS

5.2.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Wideband Radio Communication Tester	R&S	CMW500	165017	Jan. 20, 2026
Spectrum Analyzer	Agilent	N9020A	MY50101018	Jun. 26, 2025

5.3. 99% Occupied Bandwidth and 26dB Bandwidth Measurement

5.3.1. Test Specification

Test Requirement:	FCC part 2.1049
Test Method:	FCC KDB 971168 D01v03r01
Operation mode:	Refer to item 3.1
Limit:	N/A
Test Setup:	<p>The diagram illustrates the test setup. A 'System Simulator' (represented by a purple box with a blue screen) and a 'Spectrum Analyzer' (represented by a green box with a blue screen) are connected to a 'Power Divider' (represented by a black rectangle). The 'Power Divider' then connects to the 'EUT' (represented by a yellow box with a circular port). The connections are shown as lines with arrows indicating the direction of signal flow.</p>
Test Procedure:	<ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 D01v03r01 Section 4.2. 2. The EUT was connected to the spectrum analyzer and system simulator via a power divider. 3. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 4. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, sample detector, trace maximum hold. 5. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.
Test Result:	PASS

5.3.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Wideband Radio Communication Tester	R&S	CMW500	165017	Jan. 20, 2026
Spectrum Analyzer	Agilent	N9020A	MY50101018	Jun. 26, 2025

5.4. Band Edge and Conducted Spurious Emission Measurement

5.4.1. Test Specification



Test Requirement:	FCC part22.917(a) and FCC part24.238(a) FCC part27.53(g)
Test Method:	FCC KDB 971168 D01v03r01
Operation mode:	Refer to item 3.1
Limit:	-13dBm
Test Setup:	<p>The diagram shows a 'System Simulator' (purple box) and a 'Spectrum Analyzer' (green box) connected to a 'Power Divider' (black rectangle). The 'Power Divider' is connected to the 'EUT' (yellow box).</p>
Test Procedure:	<ol style="list-style-type: none"> The testing follows FCC KDB 971168 D01v03r01 Section 6.0. The EUT was connected to the spectrum analyzer and system simulator via a power divider. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement. The band edges of low and high channels for the highest RF powers were measured. The conducted spurious emission for the whole frequency range was taken. The RF fundamental frequency should be excluded against the limit line in the operating frequency band. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power $P(\text{Watts}) = P(\text{W}) - [43 + 10\log(P)] \text{ (dB)} = [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13\text{dBm}$.
Test Result:	PASS

5.4.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Wideband Radio Communication Tester	R&S	CMW500	165017	Jan. 20, 2026
Spectrum Analyzer	Agilent	N9020A	MY50101018	Jun. 26, 2025

5.5. Field Strength of Spurious Radiation Measurement

5.5.1. Test Specification

Test Requirement:	FCC part 22.917(a) and FCC part 24.238(a) FCC part 27.53(g)
Test Method:	FCC KDB 971168 D01v03r01
Operation mode:	Refer to item 3.1
Limit:	-13dBm
Test setup:	<p>For 30MHz~1GHz</p>  <p>Above 1GHz</p> 
Test Procedure:	<ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 D01v03r01 Section 6 and ANSI / TIA-603-D-2010 Section 2.2.12. 2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground. 3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower. 4. The table was rotated 360 degrees to determine the position of the highest spurious emission. 5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations. 6. Make the measurement with the spectrum analyzer's

	<p>RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.</p> <p>7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.</p> <p>8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.</p> <p>9. Taking the record of output power at antenna port.</p> <p>10. Repeat step 7 to step 8 for another polarization.</p> <p>11. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain</p> <p>12. ERP (dBm) = EIRP - 2.15</p> <p>13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.</p> <p>14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)</p> $= P(W) - [43 + 10\log(P)] \text{ (dB)}$ $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$ $= -13 \text{ dBm.}$
Test results:	PASS
Remark:	All modulations have been tested, but only the worst modulation show in this test item.

5.5.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Universal Radio Communication Tester	R&S	CMU200	110188	Jun. 26, 2025
Spectrum Analyzer	R&S	FSQ40	200061	Jun. 26, 2025
Signal Generator	Agilent	N5173B	MY58108823	Jan. 20, 2026
Broadband Antenna	Schwarzbeck	VULB9163	340	Jun. 28, 2025
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Jun. 28, 2025
Broadband Antenna	Schwarzbeck	VULB9163	412	Jun. 28, 2025
Horn Antenna	Schwarzbeck	BBHA 9120D	1201	Jun. 28, 2025
Horn Antenna	Schwarzbeck	BBHA 9170	00956	Jan. 22, 2026
Coaxial cable	SKET	RE-03-D	/	Jun. 26, 2025
Coaxial cable	SKET	RE-03-M	/	Jun. 26, 2025
Coaxial cable	SKET	RE-03-L	/	Jun. 26, 2025
Coaxial cable	SKET	RE-04-D	/	Jun. 26, 2025
Coaxial cable	SKET	RE-04-M	/	Jun. 26, 2025
Coaxial cable	SKET	RE-04-L	/	Jun. 26, 2025
Antenna Mast	Keleto	RE-AM	/	/
EMI Test Software	EZ_EMC	FA-03A2 RE+	1.1.4.2	/

5.5.3. Test Data

Frequency Range (9 kHz-30MHz)

Frequency (MHz)	Level@3m (dB μ V/m)	Limit@3m (dB μ V/m)
--	--	--
--	--	--
--	--	--
--	--	--

Note: 1. Emission Level=Reading + Cable loss + Antenna factor - Amp factor

2. The emission levels are 20 dB below the limit value, which are not reported. It is deemed to comply with the requirement

Band	GSM 850			Test channel:	Lowest
Test mode:				Temperature:	24°C
				Relative Humidity:	50%

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
1648.4	Vertical	-37.96	-6.47	-44.43	-13	PASS
2472.6	V	-46.90	-2.89	-49.79		
3296.8	V	-59.39	-0.48	-59.87		
1648.4	Horizontal	-38.17	-6.29	-44.46		
2472.6	H	-45.48	-2.99	-48.47		
3296.8	H	-57.08	-0.10	-57.18		
Band	GSM 850				Test channel:	Middle
Test mode:					Temperature:	24°C
					Relative Humidity:	50%

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
1673.2	Vertical	-39.35	-6.46	-45.81	-13.00	PASS
2509.8	V	-50.71	-2.75	-53.46		
3346.4	V	-59.00	-0.47	-59.47		
1673.2	Horizontal	-37.70	-6.32	-44.02		
2509.8	H	-46.83	-2.85	-49.68		
3346.4	H	-59.63	-0.10	-59.73		
Band	GSM 850				Test channel:	Highest
Test mode:					Temperature:	24°C
					Relative Humidity:	50%

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
1697.6	Vertical	-40.94	-6.44	-47.38	-13.00	PASS
2546.4	V	-50.83	-2.58	-53.41		
3395.2	V	-58.46	-0.47	-58.93		
1697.6	Horizontal	-36.14	-6.35	-42.49		
2546.4	H	-45.76	-2.65	-48.41		
3395.2	H	-60.92	-0.10	-61.02		

Band	PCS 1900			Test channel:	Lowest
Test mode:				Temperature:	24°C
				Relative Humidity:	50%

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission			Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)		
3700.4	Vertical	-45.28	0.91	-13.00	PASS
5550.6	V	-53.73	6.87		
7400.8	V	-61.62	10.39		
3700.4	Horizontal	-42.16	1.89		
5550.6	H	-48.04	7.38		
7400.8	H	-58.22	10.01		
Band	PCS 1900			Test channel:	Middle
Test mode:				Temperature:	24°C
				Relative Humidity:	50%

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission			Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)		
3760	Vertical	-45.39	1.32	-13.00	PASS
5640	V	-55.28	7.21		
7520	V	-54.20	10.43		
3760	Horizontal	-41.97	2.48		
5640	H	-54.97	7.63		
7520	H	-60.47	10.03		
Band	PCS 1900			Test channel:	Highest
Test mode:				Temperature:	24°C
				Relative Humidity:	50%

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission			Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)		
3819.6	Vertical	-43.90	1.72	-13.00	PASS
5729.4	V	-52.93	7.54		
7639.2	V	-59.48	10.58		
3819.6	Horizontal	-42.56	3.07		
5729.4	H	-48.27	7.89		
7639.2	H	-60.26	10.33		

Band	WCDMA Band V			Test channel:	Lowest
Test mode:	RMC 12.2Kbps Link (QPSK)			Temperature:	24°C
				Relative Humidity:	50%

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
1652.8	Vertical	-52.95	-6.47	-59.42	-13.00	PASS
2479.2	V	-59.95	-2.84	-62.79		
3305.6	V	-58.50	-0.48	-58.98		
1652.8	Horizontal	-49.90	-6.30	-56.20		
2479.2	H	-60.29	-2.95	-63.24		
3305.6	H	-59.98	-0.10	-60.08		

Band **WCDMA Band V** **Test channel:** **Middle**

Test mode:	RMC 12.2Kbps Link (QPSK)			Temperature:	24°C
				Relative Humidity:	50%

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
1673.2	Vertical	-49.70	-6.46	-56.16	-13.00	PASS
2509.8	V	-59.28	-2.75	-62.03		
3346.4	V	-61.18	-0.47	-61.65		
1673.2	Horizontal	-48.36	-6.32	-54.68		
2509.8	H	-61.50	-2.86	-64.36		
3346.4	H	-59.07	-0.10	-59.17		

Band **WCDMA Band V** **Test channel:** **Highest**

Test mode:	RMC 12.2Kbps Link (QPSK)			Temperature:	24°C
				Relative Humidity:	50%

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
1693.2	Vertical	-54.22	-6.45	-60.67	-13.00	PASS
2539.8	V	-60.72	-2.65	-63.37		
3386.4	V	-63.87	-0.47	-64.34		
1693.2	Horizontal	-50.03	-6.35	-56.38		
2539.8	H	-59.58	-2.74	-62.32		
3386.4	H	-63.31	-0.11	-63.42		

Band	WCDMA Band IV			Test channel:	Lowest
Test mode:	RMC 12.2Kbps Link (QPSK)			Temperature:	24°C
				Relative Humidity:	50%

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
2452.3	Vertical	-61.33	-2.96	-64.29	-13.00	PASS
3424.8	V	-60.37	-0.46	-60.83		
5137.2	V	-61.97	6.11	-55.86		
2452.3	Horizontal	-59.51	-2.99	-62.50		
3424.8	H	-59.51	-0.11	-59.62		
5137.2	H	-58.85	6.55	-52.30		

Band **WCDMA Band IV** **Test channel:** **Middle**

Test mode:	RMC 12.2Kbps Link (QPSK)			Temperature:	24°C
				Relative Humidity:	50%

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
2641.3	Vertical	-60.95	-2.15	-63.10	-13.00	PASS
3465.2	V	-58.11	-0.46	-58.57		
5197.8	V	-63.15	6.21	-56.94		
2641.3	Horizontal	-59.13	-2.11	-61.24		
3465.2	H	-62.02	-0.11	-62.13		
5197.8	H	-62.09	6.66	-55.43		

Band **WCDMA Band IV** **Test channel:** **Highest**

Test mode:	RMC 12.2Kbps Link (QPSK)			Temperature :	24°C
				Relative Humidity:	50%

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
3102.2	Vertical	-60.54	-2.15	-62.69	-13.00	PASS
3505.2	V	-60.07	-0.41	-60.48		
5257.8	V	-58.09	6.3	-51.79		
3102.2	Horizontal	-60.24	-0.09	-60.33		
3505.2	H	-60.38	-0.06	-60.44		
5257.8	H	-63.33	6.77	-56.56		

Band	WCDMA Band II			Test channel:	Lowest
Test mode:	RMC 12.2Kbps Link (QPSK)			Temperature:	24°C
				Relative Humidity:	50%

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
3704.8	Vertical	-48.63	0.94	-47.69	-13.00	PASS
5557.2	V	-60.70	6.89	-53.81		
7409.6	V	-62.82	10.39	-52.43		
3704.8	Horizontal	-50.88	1.93	-48.95		
5557.2	H	-58.40	7.39	-51.01		
7409.6	H	-63.05	10.01	-53.04		

Band **WCDMA Band II** **Test channel:** **Middle**

Test mode:	RMC 12.2Kbps Link (QPSK)			Temperature:	24°C
				Relative Humidity:	50%

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
3760	Vertical	-58.54	1.32	-57.22	-13.00	PASS
5640	V	-62.34	7.21	-55.13		
7520	V	-51.98	10.43	-41.55		
3760	Horizontal	-57.78	2.48	-55.30		
5640	H	-62.09	7.63	-54.46		
7520	H	-60.14	10.03	-50.11		

Band **WCDMA Band II** **Test channel:** **Highest**

Test mode:	RMC 12.2Kbps Link (QPSK)			Temperature:	24°C
				Relative Humidity:	50%

Note: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Frequency (MHz)	Spurious Emission				Limit (dBm)	Result
	Polarization	Level (dBm)	Correction Factor (dB)	Spurious emissions (dBm)		
3815.2	Vertical	-51.84	1.69	-50.15	-13.00	PASS
5722.8	V	-63.26	7.52	-55.74		
7630.4	V	-63.98	10.57	-53.41		
3815.2	Horizontal	-50.97	3.03	-47.94		
5722.8	H	-58.69	7.87	-50.82		
7630.4	H	-63.16	10.31	-52.85		

5.6. Frequency Stability Measurement

5.6.1. Test Specification

Test Requirement:	FCC Part 2.1055 ; FCC Part 22.355 ; FCC Part 24.235 FCC Part 27.54
Test Method:	FCC KDB 971168 D01v03r01
Operation mode:	Refer to item 3.1
Limit:	FCC Part 22.355 : ± 2.5 ppm FCC Part 24.235 : The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.
Test Setup:	<p>The diagram illustrates the test setup. A 'System Simulator' (represented by a purple rectangular box with a small screen and two buttons) is connected to an 'EUT' (represented by a yellow rectangular box with a circular port). The 'EUT' is placed inside a 'Thermal Chamber' (represented by a blue rectangular box). A line connects the 'System Simulator' to the 'EUT'.</p>
Test Procedure:	<p>Test Procedures for Temperature Variation</p> <ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 D01v03r01 Section 9.0. 2. The EUT was set up in the thermal chamber and connected with the system simulator. 3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute. 4. With power OFF, the temperature was raised in 10°C steps up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute. <p>Test Procedures for Voltage Variation</p> <ol style="list-style-type: none"> 1. The testing follows FCC KDB 971168 D01v03r01 Section 9.0. 2. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator. 3. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT. 4. The variation in frequency was measured for the worst case.
Test Result:	PASS
Remark:	All three channels of all modulations have been tested, but only the worst channel and the worst modulation show in this test item.

5.6.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Wideband Radio Communication Tester	R&S	CMW500	165017	Jan. 20, 2026
Programable temprature and humidity chamber	JQ	JQ-2000	/	Jun. 26, 2025
DC power supply	Kingrang	KR3005K	/	Jun. 26, 2025

Appendix A: Test Result of Conducted Test

please refer to appendix document of test date.

Appendix B: Photographs of Test Setup

Please refer to document Appendix No.: TCT241217E035-A

Appendix C: Photographs of EUT

Please refer to document Appendix No.: TCT241217E035-B & TCT241217E035-C

*******END OF REPORT*******