





F. 3D Image



23-Head with front position in dist. 0mm on Channel 26740 in LTE band 26 part 90

SAR Measurement at LTE band 26 (Cheek, Right)

Date of measurement: 4/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.15
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 26
Channels/Frequency	Lower (26740)/ frequency 819.000 Mhz
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	814.590
Relative permittivity (real part)	42.037
Relative permittivity (imaginary part)	20.891
Conductivity (S/m)	0.887

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.091
SAR 1g (W/Kg)	0.118
Variation (%)	0.840
Horizontal validation criteria: minimum distance (mm)	23.973
Vertical validation criteria: SAR ratio M2/M1 (%)	74.797%

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.142	0.123	0.092	0.083	0.069	0.054	0.043



F. 3D Image



24-Body with back position in dist. 10mm on Channel 26740 in LTE band 26 part 90

SAR Measurement at LTE band 26 (Body, Validation Plane)

Date of measurement: 4/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.15
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 26
Channels/Frequency	Lower (26740)/ frequency 819.000 Mhz
Signal	LTE FDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	814.590
Relative permittivity (real part)	42.037
Relative permittivity (imaginary part)	20.891
Conductivity (S/m)	0.887

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.261
SAR 1g (W/Kg)	0.465
Variation (%)	-2.000
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	60.606

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.728	0.495	0.300	0.183	0.114	0.094	0.061



F. 3D Image



25-Head with front position in dist. 0mm on Channel 26965 in LTE band 26 part 22

SAR Measurement at LTE band 26 (Cheek, Right)

Date of measurement: 4/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.15
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 26
Channels/Frequency	Higher (26965)/ frequency 841.500 Mhz
Signal	LTE FDD
Cell Bandwidth	15 Mhz
Modulation	SC-OFDM - QPSK
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	834.840
Relative permittivity (real part)	41.982
Relative permittivity (imaginary part)	20.747
Conductivity (S/m)	0.892

C. SAR Surface and Volume



Maximum location: X=-48.00, Y=-48.00 ; SAR Peak: 0.19 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.109
SAR 1g (W/Kg)	0.147
Variation (%)	-3.680
Horizontal validation criteria: minimum distance (mm)	23.832
Vertical validation criteria: SAR ratio M2/M1 (%)	76.821


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.173	0.151	0.116	0.110	0.090	0.073	0.060


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China



F. 3D Image



26-Body with back position in dist. 10mm on Channel 26965 in LTE band 26 part 22

SAR Measurement at LTE band 26 (Body, Validation Plane)

Date of measurement: 4/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.15
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 26
Channels/Frequency	Higher (26965)/ frequency 841.500 Mhz
Signal	LTE FDD
Cell Bandwidth	15 Mhz
Modulation	SC-OFDM - QPSK
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	834.840
Relative permittivity (real part)	41.982
Relative permittivity (imaginary part)	20.747
Conductivity (S/m)	0.892

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.085
SAR 1g (W/Kg)	0.120
Variation (%)	-1.550
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	71.545

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.258	0.123	0.088	0.080	0.054	0.026	0.015



F. 3D Image



27-Head with front position in dist. 0mm on Channel 38750 in LTE band 40a

SAR Measurement at LTE band 40 (Cheek, Right)

Date of measurement: 13/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.38
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 40
Channels/Frequency	Lower (38750)/ frequency 2310.000 Mhz
Signal	LTE TDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	25
RB size	1
Subframe configuration	0
Special subframe configuration	0
Cyclic prefix	Normal
Duty Cycle (%)	0.61

B. Permittivity

Middle TX Frequency (MHz)	2310.090
Relative permittivity (real part)	39.065
Relative permittivity (imaginary part)	13.803
Conductivity (S/m)	1.652

C. SAR Surface and Volume




Maximum location: X=-27.00, Y=2.00 ; SAR Peak: 1.65 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.400
SAR 1g (W/Kg)	0.883
Variation (%)	-2.790
Horizontal validation criteria: minimum distance (mm)	11.314
Vertical validation criteria: SAR ratio M2/M1 (%)	49.231

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.646	0.975	0.480	0.244	0.124	0.073	0.038



F. 3D Image



28-Body with back position in dist. 10mm on Channel 38750 in LTE band 40a

SAR Measurement at LTE band 40 (Body, Validation Plane)

Date of measurement: 13/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.38
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 40
Channels/Frequency	Lower (38750)/ frequency 2310.000 Mhz
Signal	LTE TDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	25
RB size	1
Subframe configuration	0
Special subframe configuration	0
Cyclic prefix	Normal
Duty Cycle (%)	0.61

B. Permittivity

Middle TX Frequency (MHz)	2310.090
Relative permittivity (real part)	39.065
Relative permittivity (imaginary part)	13.803
Conductivity (S/m)	1.652

C. SAR Surface and Volume




Maximum location: X=-1.00, Y=48.00 ; SAR Peak: 0.17 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.042
SAR 1g (W/Kg)	0.094
Variation (%)	-1.310
Horizontal validation criteria: minimum distance (mm)	11.314
Vertical validation criteria: SAR ratio M2/M1 (%)	54.639

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.163	0.097	0.053	0.029	0.020	0.014	0.006



F. 3D Image



29-Head with front position in dist. 0mm on Channel 39200 in LTE band 40b

SAR Measurement at LTE band 40 (Cheek, Right)

Date of measurement: 13/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.38
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 40
Channels/Frequency	Lower (39200)/ frequency 2355.000 Mhz
Signal	LTE TDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	25
RB size	1
Subframe configuration	0
Special subframe configuration	0
Cyclic prefix	Normal
Duty Cycle (%)	0.61

B. Permittivity

Middle TX Frequency (MHz)	2355.090
Relative permittivity (real part)	38.960
Relative permittivity (imaginary part)	13.659
Conductivity (S/m)	1.681

C. SAR Surface and Volume




Maximum location: X=-3.00, Y=11.00 ; SAR Peak: 0.88 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.223
SAR 1g (W/Kg)	0.493
Variation (%)	-3.970
Horizontal validation criteria: minimum distance (mm)	11.313
Vertical validation criteria: SAR ratio M2/M1 (%)	50.947

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.874	0.528	0.269	0.141	0.075	0.040	0.021



F. 3D Image



30-Body with back position in dist. 10mm on Channel 39200 in LTE band 40b

SAR Measurement at LTE band 40 (Body, Validation Plane)

Date of measurement: 13/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.38
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 40
Channels/Frequency	Lower (39200)/ frequency 2355.000 Mhz
Signal	LTE TDD
Cell Bandwidth	10 Mhz
Modulation	SC-OFDM - QPSK
RB offset	25
RB size	1
Subframe configuration	0
Special subframe configuration	0
Cyclic prefix	Normal
Duty Cycle (%)	0.61

B. Permittivity

Middle TX Frequency (MHz)	2355.090
Relative permittivity (real part)	38.960
Relative permittivity (imaginary part)	13.659
Conductivity (S/m)	1.681

C. SAR Surface and Volume




Maximum location: X=-2.00, Y=30.00 ; SAR Peak: 0.21 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.063
SAR 1g (W/Kg)	0.124
Variation (%)	-2.380
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	54.478

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.213	0.134	0.073	0.039	0.022	0.013	0.005



F. 3D Image



31-Head with front position in dist. 0mm on Channel 41490 in LTE band 41

SAR Measurement at LTE band 41 (Cheek, Right)

Date of measurement: 15/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.27
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 41
Channels/Frequency	Higher (41490)/ frequency 2680.000 Mhz
Signal	LTE TDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1
Subframe configuration	0
Special subframe configuration	0
Cyclic prefix	Normal
Duty Cycle (%)	0.61

B. Permittivity

Middle TX Frequency (MHz)	2680.090
Relative permittivity (real part)	38.465
Relative permittivity (imaginary part)	12.976
Conductivity (S/m)	2.003

C. SAR Surface and Volume




Maximum location: X=-24.00, Y=8.00 ; SAR Peak: 0.54 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.109
SAR 1g (W/Kg)	0.271
Variation (%)	1.530
Horizontal validation criteria: minimum distance (mm)	11.313
Vertical validation criteria: SAR ratio M2/M1 (%)	42.568

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.540	0.296	0.126	0.060	0.028	0.010	0.007



F. 3D Image



32-Body with back position in dist. 10mm on Channel 41490 in LTE band 41

SAR Measurement at LTE band 41 (Body, Validation Plane)

Date of measurement: 15/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.27
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 41
Channels/Frequency	Higher (41490)/ frequency 2680.000 Mhz
Signal	LTE TDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	50
RB size	1
Subframe configuration	0
Special subframe configuration	0
Cyclic prefix	Normal
Duty Cycle (%)	0.61

B. Permittivity

Middle TX Frequency (MHz)	2680.090
Relative permittivity (real part)	38.465
Relative permittivity (imaginary part)	12.976
Conductivity (S/m)	2.003

C. SAR Surface and Volume




Maximum location: X=-9.00, Y=-18.00 ; SAR Peak: 1.15 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.404
SAR 1g (W/Kg)	0.723
Variation (%)	-3.860
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	60.411

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.137	0.771	0.466	0.283	0.176	0.085	0.043



F. 3D Image



33-Head with front position in dist. 0mm on Channel 132572 in LTE band 66

SAR Measurement at LTE band 66 (Cheek, Right)

Date of measurement: 7/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.20
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 66
Channels/Frequency	Higher (132572)/ frequency 1770.000 Mhz
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	1761.090
Relative permittivity (real part)	40.188
Relative permittivity (imaginary part)	16.542
Conductivity (S/m)	1.354

C. SAR Surface and Volume



Maximum location: X=-30.00, Y=-2.00 ; SAR Peak: 0.87 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.307
SAR 1g (W/Kg)	0.558
Variation (%)	-4.660
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	62.458


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.858	0.602	0.376	0.233	0.141	0.085	0.052


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China



F. 3D Image



34-Body with back position in dist. 10mm on Channel 132572 in LTE band 66

SAR Measurement at LTE band 66 (Body, Validation Plane)

Date of measurement: 7/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.20
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 66
Channels/Frequency	Higher (132572)/ frequency 1770.000 Mhz
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	1761.090
Relative permittivity (real part)	40.188
Relative permittivity (imaginary part)	16.542
Conductivity (S/m)	1.354

C. SAR Surface and Volume




Maximum location: X=-2.00, Y=-23.00 ; SAR Peak: 0.31 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.108
SAR 1g (W/Kg)	0.195
Variation (%)	0.560
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	59.903

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.309	0.207	0.124	0.076	0.048	0.029	0.018



F. 3D Image



35-Head with front position in dist. 0mm on Channel 133222 in LTE band 71

SAR Measurement at LTE band 71 (Cheek, Right)

Date of measurement: 2/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.24
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	LTE band 71
Channels/Frequency	Lower (133222)/ frequency 673.000 Mhz
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	664.090
Relative permittivity (real part)	42.446
Relative permittivity (imaginary part)	21.956
Conductivity (S/m)	0.852

C. SAR Surface and Volume



Maximum location: X=-49.00, Y=-47.00 ; SAR Peak: 0.11 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.074
SAR 1g (W/Kg)	0.092
Variation (%)	-4.140
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	79.787


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.111	0.094	0.075	0.069	0.059	0.047	0.039


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China



F. 3D Image



36-Body with back position in dist. 10mm on Channel 133222 in LTE band 71

SAR Measurement at LTE band 71 (Body, Validation Plane)

Date of measurement: 2/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.24
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	LTE band 71
Channels/Frequency	Lower (133222)/ frequency 673.000 Mhz
Signal	LTE FDD
Cell Bandwidth	20 Mhz
Modulation	SC-OFDM - QPSK
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	664.090
Relative permittivity (real part)	42.446
Relative permittivity (imaginary part)	21.956
Conductivity (S/m)	0.852

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.090
SAR 1g (W/Kg)	0.114
Variation (%)	2.430
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	77.778

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.136	0.117	0.091	0.079	0.064	0.034	0.018



F. 3D Image



37-Head with front position in dist. 0mm on Channel 376000 in NR band 2

SAR Measurement at NR band 2 (Cheek, Right)

Date of measurement: 7/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.31
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	NR band 2
Channels/Frequency	Middle (376000)/ frequency 1880.000 Mhz
Signal	NR FDD
Cell Bandwidth	20 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	1871.000
Relative permittivity (real part)	40.049
Relative permittivity (imaginary part)	15.482
Conductivity (S/m)	1.386

C. SAR Surface and Volume



Maximum location: X=-31.00, Y=0.00 ; SAR Peak: 1.04 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.357
SAR 1g (W/Kg)	0.655
Variation (%)	-2.330
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	62.714

E. Z Axis Scan


Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
--------	------	------	------	-------	-------	-------	-------

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

SAR (W/Kg)	0.997	0.700	0.439	0.275	0.167	0.100	0.062
------------	-------	-------	-------	-------	-------	-------	-------



F. 3D Image



38-Body with back position in dist. 10mm on Channel 376000 in NR band 2

SAR Measurement at NR band 2 (Body, Validation Plane)

Date of measurement: 7/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.31
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	NR band 2
Channels/Frequency	Middle (376000)/ frequency 1880.000 Mhz
Signal	NR FDD
Cell Bandwidth	20 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	1871.000
Relative permittivity (real part)	40.049
Relative permittivity (imaginary part)	15.482
Conductivity (S/m)	1.386

C. SAR Surface and Volume




D. SAR 1g & 10g

SAR 10g (W/Kg)	0.188
SAR 1g (W/Kg)	0.341
Variation (%)	-4.610
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	60.440


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
--------	------	------	------	-------	-------	-------	-------

SAR (W/Kg)	0.534	0.364	0.220	0.134	0.079	0.048	0.029
------------	-------	-------	-------	-------	-------	-------	-------



F. 3D Image



39-Head with front position in dist. 0mm on Channel 166800 in NR band 5

SAR Measurement at NR band 5 (Cheek, Right)

Date of measurement: 4/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.15
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	NR band 5
Channels/Frequency	Lower (166800)/ frequency 834.000 Mhz
Signal	NR FDD
Cell Bandwidth	20 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	834.000
Relative permittivity (real part)	41.985
Relative permittivity (imaginary part)	20.753
Conductivity (S/m)	0.892

C. SAR Surface and Volume



Maximum location: X=-49.00, Y=-49.00 ; SAR Peak: 0.09 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.058
SAR 1g (W/Kg)	0.075
Variation (%)	-1.870
Horizontal validation criteria: minimum distance (mm)	23.973
Vertical validation criteria: SAR ratio M2/M1 (%)	78.205

E. Z Axis Scan


Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
--------	------	------	------	-------	-------	-------	-------

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

SAR (W/Kg)	0.090	0.078	0.061	0.055	0.044	0.036	0.028
------------	-------	-------	-------	-------	-------	-------	-------



F. 3D Image



40-Body with back position in dist. 10mm on Channel 166800 in NR band 5

SAR Measurement at NR band 5 (Body, Validation Plane)

Date of measurement: 4/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.15
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	NR band 5
Channels/Frequency	Lower (166800)/ frequency 834.000 Mhz
Signal	NR FDD
Cell Bandwidth	20 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	834.000
Relative permittivity (real part)	41.985
Relative permittivity (imaginary part)	20.753
Conductivity (S/m)	0.892

C. SAR Surface and Volume




D. SAR 1g & 10g

SAR 10g (W/Kg)	0.029
SAR 1g (W/Kg)	0.046
Variation (%)	1.970
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	67.391


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
--------	------	------	------	-------	-------	-------	-------

SAR (W/Kg)	0.068	0.046	0.031	0.026	0.019	0.015	0.009
------------	-------	-------	-------	-------	-------	-------	-------



F. 3D Image



41-Head with front position in dist. 0mm on Channel 511000 in NR band 7

SAR Measurement at NR band 7 (Cheek, Right)

Date of measurement: 15/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.40
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	NR band 7
Channels/Frequency	Higher (511000)/ frequency 2555.000 Mhz
Signal	NR FDD
Cell Bandwidth	30 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	2555.140
Relative permittivity (real part)	38.594
Relative permittivity (imaginary part)	13.025
Conductivity (S/m)	1.869

C. SAR Surface and Volume



Maximum location: X=-31.00, Y=0.00 ; SAR Peak: 0.64 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.239
SAR 1g (W/Kg)	0.417
Variation (%)	-1.970
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	63.575

E. Z Axis Scan


Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
--------	------	------	------	-------	-------	-------	-------

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

SAR (W/Kg)	0.639	0.442	0.281	0.179	0.120	0.072	0.046
------------	-------	-------	-------	-------	-------	-------	-------



F. 3D Image



42-Body with back position in dist. 10mm on Channel 511000 in NR band 7

SAR Measurement at NR band 7 (Body, Validation Plane)

Date of measurement: 15/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.40
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	NR band 7
Channels/Frequency	Higher (511000)/ frequency 2555.000 Mhz
Signal	NR FDD
Cell Bandwidth	30 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	2555.140
Relative permittivity (real part)	38.594
Relative permittivity (imaginary part)	13.025
Conductivity (S/m)	1.869

C. SAR Surface and Volume



D. SAR 1g & 10g

SAR 10g (W/Kg)	0.160
SAR 1g (W/Kg)	0.298
Variation (%)	3.750
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	59.813

E. Z Axis Scan


Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
--------	------	------	------	-------	-------	-------	-------

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

SAR (W/Kg)	0.477	0.321	0.192	0.114	0.068	0.040	0.023
------------	-------	-------	-------	-------	-------	-------	-------



F. 3D Image



43-Head with front position in dist. 0mm on Channel 376500 in NR band 25

SAR Measurement at NR band 25 (Cheek, Right)

Date of measurement: 7/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.31
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	NR band 25
Channels/Frequency	Middle (376500)/ frequency 1882.500 Mhz
Signal	NR FDD
Cell Bandwidth	20 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	1873.500
Relative permittivity (real part)	40.047
Relative permittivity (imaginary part)	15.451
Conductivity (S/m)	1.386

C. SAR Surface and Volume



Maximum location: X=-34.00, Y=0.00 ; SAR Peak: 1.44 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.417
SAR 1g (W/Kg)	0.742
Variation (%)	-1.800
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	61.523

E. Z Axis Scan


Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
--------	------	------	------	-------	-------	-------	-------

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

SAR (W/Kg)	1.413	0.985	0.606	0.367	0.214	0.126	0.077
------------	-------	-------	-------	-------	-------	-------	-------



F. 3D Image



44-Body with back position in dist. 10mm on Channel 376500 in NR band 25

SAR Measurement at NR band 25 (Body, Validation Plane)

Date of measurement: 7/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.31
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	NR band 25
Channels/Frequency	Middle (376500)/ frequency 1882.500 Mhz
Signal	NR FDD
Cell Bandwidth	20 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	1873.500
Relative permittivity (real part)	40.047
Relative permittivity (imaginary part)	15.451
Conductivity (S/m)	1.386

C. SAR Surface and Volume




D. SAR 1g & 10g

SAR 10g (W/Kg)	0.238
SAR 1g (W/Kg)	0.427
Variation (%)	1.750
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	60.619


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
--------	------	------	------	-------	-------	-------	-------

SAR (W/Kg)	0.664	0.452	0.274	0.165	0.100	0.059	0.036
------------	-------	-------	-------	-------	-------	-------	-------



F. 3D Image



45-Head with front position in dist. 0mm on Channel 462000 in NR band 40a

SAR Measurement at NR band 40 (Cheek, Right)

Date of measurement: 13/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.38
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	NR band 40
Channels/Frequency	Middle (462000)/ frequency 2310.000 Mhz
Signal	NR TDD
Cell Bandwidth	10 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1
Duty Cycle (%)	1.00

B. Permittivity

Middle TX Frequency (MHz)	2310.860
Relative permittivity (real part)	39.063
Relative permittivity (imaginary part)	13.801
Conductivity (S/m)	1.652

C. SAR Surface and Volume



Maximum location: X=-54.00, Y=-49.00 ; SAR Peak: 0.16 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.110
SAR 1g (W/Kg)	0.140
Variation (%)	1.980
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	78.912


E. Z Axis Scan

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.163	0.147	0.116	0.105	0.083	0.071	0.057



F. 3D Image



46-Body with back position in dist. 10mm on Channel 462000 in NR band 40a

SAR Measurement at NR band 40 (Body, Validation Plane)

Date of measurement: 13/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.38
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	NR band 40
Channels/Frequency	Middle (462000)/ frequency 2310.000 Mhz
Signal	NR TDD
Cell Bandwidth	10 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1
Duty Cycle (%)	1.00

B. Permittivity

Middle TX Frequency (MHz)	2310.860
Relative permittivity (real part)	39.063
Relative permittivity (imaginary part)	13.801
Conductivity (S/m)	1.652

C. SAR Surface and Volume



D. SAR 1g & 10g

SAR 10g (W/Kg)	0.118
SAR 1g (W/Kg)	0.159
Variation (%)	-4.150
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	79.245


E. Z Axis Scan

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.188	0.159	0.126	0.101	0.079	0.059	0.047



F. 3D Image



47-Head with front position in dist. 0mm on Channel 471000 in NR band 40b

SAR Measurement at NR band 40 (Cheek, Right)

Date of measurement: 13/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.38
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	NR band 40
Channels/Frequency	Middle (471000)/ frequency 2355.000 Mhz
Signal	NR TDD
Cell Bandwidth	10 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1
Duty Cycle (%)	1.00

B. Permittivity

Middle TX Frequency (MHz)	2350.860
Relative permittivity (real part)	38.970
Relative permittivity (imaginary part)	13.673
Conductivity (S/m)	1.678

C. SAR Surface and Volume



Maximum location: X=-55.00, Y=-54.00 ; SAR Peak: 0.16 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.108
SAR 1g (W/Kg)	0.136
Variation (%)	-1.980
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	79.856


E. Z Axis Scan

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.161	0.139	0.111	0.098	0.082	0.068	0.055



F. 3D Image



48-Body with back position in dist. 10mm on Channel 471000 in NR band 40b

SAR Measurement at NR band 40 (Body, Validation Plane)

Date of measurement: 13/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.38
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	NR band 40
Channels/Frequency	Middle (471000)/ frequency 2355.000 Mhz
Signal	NR TDD
Cell Bandwidth	10 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1
Duty Cycle (%)	1.00

B. Permittivity

Middle TX Frequency (MHz)	2350.860
Relative permittivity (real part)	38.970
Relative permittivity (imaginary part)	13.673
Conductivity (S/m)	1.678

C. SAR Surface and Volume



Maximum location: X=23.00, Y=55.00 ; SAR Peak: 0.22 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.138
SAR 1g (W/Kg)	0.184
Variation (%)	-0.380
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	77.174


E. Z Axis Scan

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.214	0.184	0.142	0.121	0.095	0.076	0.060



F. 3D Image



49-Head with front position in dist. 0mm on Channel 528000 in NR band 41

SAR Measurement at NR band 41 (Cheek, Right)

Date of measurement: 15/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.27
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	NR band 41
Channels/Frequency	Higher (528000)/ frequency 2640.000 Mhz
Signal	NR TDD
Cell Bandwidth	100 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1
Duty Cycle (%)	1.00

B. Permittivity

Middle TX Frequency (MHz)	2640.860
Relative permittivity (real part)	38.498
Relative permittivity (imaginary part)	12.931
Conductivity (S/m)	1.964

C. SAR Surface and Volume



Maximum location: X=-33.00, Y=-2.00 ; SAR Peak: 0.65 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.241
SAR 1g (W/Kg)	0.427
Variation (%)	-0.420
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	63.834


E. Z Axis Scan

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.650	0.459	0.293	0.182	0.113	0.070	0.042



F. 3D Image



50-Body with back position in dist. 10mm on Channel 528000 in NR band 41

SAR Measurement at NR band 41 (Body, Validation Plane)

Date of measurement: 15/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.27
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	NR band 41
Channels/Frequency	Higher (528000)/ frequency 2640.000 Mhz
Signal	NR TDD
Cell Bandwidth	100 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1
Duty Cycle (%)	1.00

B. Permittivity

Middle TX Frequency (MHz)	2640.860
Relative permittivity (real part)	38.498
Relative permittivity (imaginary part)	12.931
Conductivity (S/m)	1.964

C. SAR Surface and Volume



Maximum location: X=-6.00, Y=-22.00 ; SAR Peak: 0.50 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.166
SAR 1g (W/Kg)	0.311
Variation (%)	0.720
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	58.982


E. Z Axis Scan

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.501	0.334	0.197	0.122	0.071	0.039	0.022



F. 3D Image



51-Head with front position in dist. 0mm on Channel 344000 in NR band 66

SAR Measurement at NR band 66 (Cheek, Right)

Date of measurement: 7/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.20
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	NR band 66
Channels/Frequency	Lower (344000)/ frequency 1720.000 Mhz
Signal	NR FDD
Cell Bandwidth	20 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	1720.000
Relative permittivity (real part)	40.268
Relative permittivity (imaginary part)	16.728
Conductivity (S/m)	1.333

C. SAR Surface and Volume



Maximum location: X=-32.00, Y=2.00 ; SAR Peak: 0.44 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.158
SAR 1g (W/Kg)	0.282
Variation (%)	-3.480
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	65.789

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
--------	------	------	------	-------	-------	-------	-------


Total or partial reproduction of this document without permission of the Laboratory is not allowed.

Page 328 of 378


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

SAR (W/Kg)	0.415	0.304	0.200	0.126	0.078	0.048	0.030
------------	-------	-------	-------	-------	-------	-------	-------



F. 3D Image



52-Body with back position in dist. 10mm on Channel 344000 in NR band 66

SAR Measurement at NR band 66 (Body, Validation Plane)

Date of measurement: 7/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.20
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	NR band 66
Channels/Frequency	Lower (344000)/ frequency 1720.000 Mhz
Signal	NR FDD
Cell Bandwidth	20 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	1720.000
Relative permittivity (real part)	40.268
Relative permittivity (imaginary part)	16.728
Conductivity (S/m)	1.333

C. SAR Surface and Volume




D. SAR 1g & 10g

SAR 10g (W/Kg)	0.087
SAR 1g (W/Kg)	0.154
Variation (%)	1.740
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	60.976


E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
--------	------	------	------	-------	-------	-------	-------

SAR (W/Kg)	0.241	0.164	0.100	0.062	0.037	0.023	0.014
------------	-------	-------	-------	-------	-------	-------	-------



F. 3D Image



53-Head with front position in dist. 0mm on Channel 136100 in NR band 71

SAR Measurement at NR band 71 (Cheek, Right)

Date of measurement: 2/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.24
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	NR band 71
Channels/Frequency	Middle (136100)/ frequency 680.500 Mhz
Signal	NR FDD
Cell Bandwidth	20 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	671.500
Relative permittivity (real part)	42.426
Relative permittivity (imaginary part)	21.904
Conductivity (S/m)	0.854

C. SAR Surface and Volume



D. SAR 1g & 10g

SAR 10g (W/Kg)	0.023
SAR 1g (W/Kg)	0.031
Variation (%)	0.160
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	66.667

E. Z Axis Scan


Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
--------	------	------	------	-------	-------	-------	-------

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

SAR (W/Kg)	0.050	0.033	0.022	0.023	0.015	0.016	0.010
------------	-------	-------	-------	-------	-------	-------	-------



F. 3D Image



54-Body with back position in dist. 10mm on Channel 136100 in NR band 71

SAR Measurement at NR band 71 (Body, Validation Plane)

Date of measurement: 2/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.24
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	NR band 71
Channels/Frequency	Middle (136100)/ frequency 680.500 Mhz
Signal	NR FDD
Cell Bandwidth	20 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1

B. Permittivity

Middle TX Frequency (MHz)	671.500
Relative permittivity (real part)	42.426
Relative permittivity (imaginary part)	21.904
Conductivity (S/m)	0.854

C. SAR Surface and Volume



Maximum location: X=23.00, Y=54.00 ; SAR Peak: 0.09 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.056
SAR 1g (W/Kg)	0.075
Variation (%)	-1.140
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	77.632

E. Z Axis Scan


Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
--------	------	------	------	-------	-------	-------	-------

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

SAR (W/Kg)	0.096	0.076	0.059	0.049	0.039	0.031	0.025
------------	-------	-------	-------	-------	-------	-------	-------



F. 3D Image



55-Head with front position in dist. 0mm on Channel 650000 in NR band 77a

SAR Measurement at NR band 77 (Cheek, Right)

Date of measurement: 16/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.11
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	NR band 77
Channels/Frequency	Lower (650000)/ frequency 3750.000 Mhz
Signal	NR TDD
Cell Bandwidth	100 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1
Duty Cycle (%)	1.00

B. Permittivity

Middle TX Frequency (MHz)	3750.260
Relative permittivity (real part)	37.568
Relative permittivity (imaginary part)	14.203
Conductivity (S/m)	3.077

C. SAR Surface and Volume



Maximum location: X=-31.00, Y=0.00 ; SAR Peak: 0.64 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.229
SAR 1g (W/Kg)	0.440
Variation (%)	-1.670
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	59.050


E. Z Axis Scan

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.615	0.442	0.261	0.179	0.120	0.072	0.046



F. 3D Image



56-Body with back position in dist. 10mm on Channel 650000 in NR band 77a

SAR Measurement at NR band 77 (Body, Validation Plane)

Date of measurement: 16/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.11
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	NR band 77
Channels/Frequency	Lower (650000)/ frequency 3750.000 Mhz
Signal	NR TDD
Cell Bandwidth	100 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1
Duty Cycle (%)	1.00

B. Permittivity

Middle TX Frequency (MHz)	3750.260
Relative permittivity (real part)	37.568
Relative permittivity (imaginary part)	14.203
Conductivity (S/m)	3.077

C. SAR Surface and Volume



D. SAR 1g & 10g

SAR 10g (W/Kg)	0.162
SAR 1g (W/Kg)	0.311
Variation (%)	-0.850
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	58.282


E. Z Axis Scan

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.503	0.326	0.190	0.114	0.068	0.040	0.023



F. 3D Image



57-Head with front position in dist. 0mm on Channel 633334 in NR band 77d

SAR Measurement at NR band 77 (Cheek, Right)

Date of measurement: 16/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.17
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	NR band 77
Channels/Frequency	Middle (633334)/ frequency 3500.000 Mhz
Signal	NR TDD
Cell Bandwidth	100 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1
Duty Cycle (%)	1.00

B. Permittivity

Middle TX Frequency (MHz)	3500.260
Relative permittivity (real part)	37.777
Relative permittivity (imaginary part)	13.916
Conductivity (S/m)	2.826

C. SAR Surface and Volume



Maximum location: X=-8.00, Y=2.00 ; SAR Peak: 0.70 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.257
SAR 1g (W/Kg)	0.439
Variation (%)	1.300
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	59.653


E. Z Axis Scan

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.702	0.461	0.275	0.161	0.109	0.070	0.045



F. 3D Image



58-Body with back position in dist. 10mm on Channel 633334 in NR band 77d

SAR Measurement at NR band 77 (Body, Validation Plane)

Date of measurement: 16/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.17
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	NR band 77
Channels/Frequency	Middle (633334)/ frequency 3500.000 Mhz
Signal	NR TDD
Cell Bandwidth	100 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1
Duty Cycle (%)	1.00

B. Permittivity

Middle TX Frequency (MHz)	3500.260
Relative permittivity (real part)	37.777
Relative permittivity (imaginary part)	13.916
Conductivity (S/m)	2.826

C. SAR Surface and Volume



D. SAR 1g & 10g

SAR 10g (W/Kg)	0.110
SAR 1g (W/Kg)	0.158
Variation (%)	-3.610
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	78.528


E. Z Axis Scan

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.195	0.163	0.128	0.102	0.081	0.061	0.050



F. 3D Image



59-Head with front position in dist. 0mm on Channel 650000 in NR band 78a

SAR Measurement at NR band 78 (Cheek, Right)

Date of measurement: 16/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.11
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	NR band 78
Channels/Frequency	Middle (650000)/ frequency 3750.000 Mhz
Signal	NR TDD
Cell Bandwidth	100 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1
Duty Cycle (%)	1.00

B. Permittivity

Middle TX Frequency (MHz)	3750.000
Relative permittivity (real part)	37.568
Relative permittivity (imaginary part)	14.203
Conductivity (S/m)	3.077

C. SAR Surface and Volume



Maximum location: X=-40.00, Y=1.00 ; SAR Peak: 1.31 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.244
SAR 1g (W/Kg)	0.637
Variation (%)	-2.030
Horizontal validation criteria: minimum distance (mm)	11.313
Vertical validation criteria: SAR ratio M2/M1 (%)	44.145


E. Z Axis Scan

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.335	0.743	0.328	0.145	0.065	0.035	0.013



F. 3D Image



60-Body with back position in dist. 10mm on Channel 650000 in NR band 78a

SAR Measurement at NR band 78 (Body, Validation Plane)

Date of measurement: 16/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.11
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	NR band 78
Channels/Frequency	Middle (650000)/ frequency 3750.000 Mhz
Signal	NR TDD
Cell Bandwidth	100 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1
Duty Cycle (%)	1.00

B. Permittivity

Middle TX Frequency (MHz)	3750.000
Relative permittivity (real part)	37.568
Relative permittivity (imaginary part)	14.203
Conductivity (S/m)	3.077

C. SAR Surface and Volume



Maximum location: X=0.00, Y=14.00 ; SAR Peak: 0.12 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.038
SAR 1g (W/Kg)	0.070
Variation (%)	-2.340
Horizontal validation criteria: minimum distance (mm)	11.313
Vertical validation criteria: SAR ratio M2/M1 (%)	48.571


E. Z Axis Scan

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.121	0.070	0.034	0.015	0.008	0.005	0.002



F. 3D Image



61-Head with front position in dist. 0mm on Channel 633334 in NR band 78e

SAR Measurement at NR band 78 (Cheek, Right)

Date of measurement: 16/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.17
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	NR band 78
Channels/Frequency	Middle (633334)/ frequency 3500.000 Mhz
Signal	NR TDD
Cell Bandwidth	100 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1
Duty Cycle (%)	1.00

B. Permittivity

Middle TX Frequency (MHz)	3500.260
Relative permittivity (real part)	37.777
Relative permittivity (imaginary part)	13.916
Conductivity (S/m)	2.826

C. SAR Surface and Volume



Maximum location: X=-15.00, Y=9.00 ; SAR Peak: 0.82 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.202
SAR 1g (W/Kg)	0.449
Variation (%)	-3.410
Horizontal validation criteria: minimum distance (mm)	11.314
Vertical validation criteria: SAR ratio M2/M1 (%)	50.507


E. Z Axis Scan

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.819	0.493	0.249	0.132	0.068	0.036	0.019



F. 3D Image



62-Body with back position in dist. 10mm on Channel 633334 in NR band 78e

SAR Measurement at NR band 78 (Body, Validation Plane)

Date of measurement: 16/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.17
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	NR band 78
Channels/Frequency	Middle (633334)/ frequency 3500.000 Mhz
Signal	NR TDD
Cell Bandwidth	100 Mhz
Modulation	DFT-s-OFDM - QPSK
subcarrier spacing (SCS)	30 kHz
RB offset	0
RB size	1
Duty Cycle (%)	1.00

B. Permittivity

Middle TX Frequency (MHz)	3500.260
Relative permittivity (real part)	37.777
Relative permittivity (imaginary part)	13.916
Conductivity (S/m)	2.826

C. SAR Surface and Volume



Maximum location: X=-16.00, Y=6.00 ; SAR Peak: 0.40 W/kg

D. SAR 1g & 10g

SAR 10g (W/Kg)	0.119
SAR 1g (W/Kg)	0.240
Variation (%)	1.600
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	54.762


E. Z Axis Scan

Total or partial reproduction of this document without permission of the Laboratory is not allowed.


BTF Testing Lab (Shenzhen) Co., Ltd.

101/201/301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Subdistrict, Bao'an District, Shenzhen, China

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.402	0.252	0.138	0.078	0.044	0.024	0.012



F. 3D Image



63-Head with front position in dist. 0mm on Channel 11 in IEEE 802.11b ISM

SAR Measurement at ISM (Cheek, Right)

Date of measurement: 14/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.40
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	ISM
Channels/Frequency	Higher (11)/ frequency 2462.000 Mhz
Signal	IEEE 802.11 b

B. Permittivity

Middle TX Frequency (MHz)	2462.000
Relative permittivity (real part)	38.722
Relative permittivity (imaginary part)	13.316
Conductivity (S/m)	1.756

C. SAR Surface and Volume




Maximum location: X=-33.00, Y=-43.00 ; SAR Peak: 0.33 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.113
SAR 1g (W/Kg)	0.211
Variation (%)	-2.470
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	63.889

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.299	0.216	0.138	0.088	0.051	0.031	0.018



F. 3D Image



64-Body with back position in dist. 10mm on Channel 11 in IEEE 802.11b ISM

SAR Measurement at ISM (Body, Validation Plane)

Date of measurement: 14/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.40
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	ISM
Channels/Frequency	Higher (11)/ frequency 2462.000 Mhz
Signal	IEEE 802.11 b

B. Permittivity

Middle TX Frequency (MHz)	2462.000
Relative permittivity (real part)	38.722
Relative permittivity (imaginary part)	13.316
Conductivity (S/m)	1.756

C. SAR Surface and Volume




Maximum location: X=-2.00, Y=5.00 ; SAR Peak: 0.35 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.097
SAR 1g (W/Kg)	0.200
Variation (%)	-3.030
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	52.778

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.345	0.216	0.114	0.055	0.029	0.014	0.010



F. 3D Image



65-Head with front position in dist. 0mm on Channel 36 in IEEE 802.11n U-NII

SAR Measurement at U-NII-1 (Cheek, Right)

Date of measurement: 17/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.18
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	U-NII-1
Channels/Frequency	Lower (36)/ frequency 5180.000 Mhz
Signal	IEEE 802.11 n

B. Permittivity

Middle TX Frequency (MHz)	5180.000
Relative permittivity (real part)	36.369
Relative permittivity (imaginary part)	15.842
Conductivity (S/m)	4.512

C. SAR Surface and Volume




Maximum location: X=-10.00, Y=-25.00 ; SAR Peak: 0.44 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.053
SAR 1g (W/Kg)	0.142
Variation (%)	1.930
Horizontal validation criteria: minimum distance (mm)	8.000
Vertical validation criteria: SAR ratio M2/M1 (%)	41.429

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	0.239	0.140	0.058	0.028	0.030	0.013	0.005	0.005	0.006	0.003	0.004	0.006



F. 3D Image



66-Body with back position in dist. 10mm on Channel 36 in IEEE 802.11n U-NII

SAR Measurement at U-NII-1 (Body, Validation Plane)

Date of measurement: 17/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.18
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	U-NII-1
Channels/Frequency	Lower (36)/ frequency 5180.000 Mhz
Signal	IEEE 802.11 n

B. Permittivity

Middle TX Frequency (MHz)	5180.000
Relative permittivity (real part)	36.369
Relative permittivity (imaginary part)	15.842
Conductivity (S/m)	4.512

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.271
SAR 1g (W/Kg)	0.582
Variation (%)	-2.430
Horizontal validation criteria: minimum distance (mm)	12.000
Vertical validation criteria: SAR ratio M2/M1 (%)	78.627

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	1.003	0.772	0.607	0.432	0.353	0.260	0.206	0.150	0.107	0.090	0.063	0.057



F. 3D Image



67-Head with front position in dist. 0mm on Channel 64 in IEEE 802.11n U-NII

SAR Measurement at U-NII-2a (Cheek, Right)

Date of measurement: 17/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.14
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	U-NII-2a
Channels/Frequency	Higher (64)/ frequency 5320.000 Mhz
Signal	IEEE 802.11 n

B. Permittivity

Middle TX Frequency (MHz)	5320.000
Relative permittivity (real part)	36.113
Relative permittivity (imaginary part)	16.085
Conductivity (S/m)	4.756

C. SAR Surface and Volume




Maximum location: X=-7.00, Y=-30.00 ; SAR Peak: 0.58 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.062
SAR 1g (W/Kg)	0.166
Variation (%)	-0.420
Horizontal validation criteria: minimum distance (mm)	8.000
Vertical validation criteria: SAR ratio M2/M1 (%)	40.000

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	0.276	0.175	0.070	0.067	0.033	0.023	0.010	0.012	0.006	0.008	0.004	0.012



F. 3D Image



68-Body with back position in dist. 10mm on Channel 64 in IEEE 802.11n U-NII

SAR Measurement at U-NII-2a (Body, Validation Plane)

Date of measurement: 17/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.14
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	U-NII-2a
Channels/Frequency	Higher (64)/ frequency 5320.000 Mhz
Signal	IEEE 802.11 n

B. Permittivity

Middle TX Frequency (MHz)	5320.000
Relative permittivity (real part)	36.113
Relative permittivity (imaginary part)	16.085
Conductivity (S/m)	4.756

C. SAR Surface and Volume




Maximum location: X=-5.00, Y=1.00 ; SAR Peak: 1.12 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.277
SAR 1g (W/Kg)	0.564
Variation (%)	2.230
Horizontal validation criteria: minimum distance (mm)	12.641
Vertical validation criteria: SAR ratio M2/M1 (%)	79.778

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	1.026	0.811	0.647	0.479	0.341	0.278	0.203	0.156	0.118	0.101	0.081	0.064



F. 3D Image



69-Head with front position in dist. 0mm on Channel 120 in IEEE 802.11n U-NII

SAR Measurement at U-NII-2c (Cheek, Right)

Date of measurement: 18/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.12
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2.0mm,Complete
Phantom	Right head
Device Position	Cheek
Band	U-NII-2c
Channels/Frequency	Middle (120)/ frequency 5600.000 Mhz
Signal	IEEE 802.11 n

B. Permittivity

Middle TX Frequency (MHz)	5600.000
Relative permittivity (real part)	35.363
Relative permittivity (imaginary part)	16.241
Conductivity (S/m)	5.112

C. SAR Surface and Volume




Maximum location: X=-7.00, Y=-24.00 ; SAR Peak: 0.55 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.067
SAR 1g (W/Kg)	0.178
Variation (%)	0.090
Horizontal validation criteria: minimum distance (mm)	11.313
Vertical validation criteria: SAR ratio M2/M1 (%)	43.103

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	0.289	0.174	0.075	0.058	0.032	0.020	0.017	0.018	0.014	0.009	0.004	0.013



F. 3D Image



70-Body with back position in dist. 10mm on Channel 120 in IEEE 802.11n U-NII

SAR Measurement at U-NII-2c (Body, Validation Plane)

Date of measurement: 18/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.12
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	U-NII-2c
Channels/Frequency	Middle (120)/ frequency 5600.000 Mhz
Signal	IEEE 802.11 n

B. Permittivity

Middle TX Frequency (MHz)	5600.000
Relative permittivity (real part)	35.363
Relative permittivity (imaginary part)	16.241
Conductivity (S/m)	5.112

C. SAR Surface and Volume




Maximum location: X=-7.00, Y=0.00 ; SAR Peak: 0.80 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.106
SAR 1g (W/Kg)	0.278
Variation (%)	-3.070
Horizontal validation criteria: minimum distance (mm)	11.313
Vertical validation criteria: SAR ratio M2/M1 (%)	52.804

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	0.697	0.428	0.226	0.118	0.077	0.036	0.018	0.007	0.010	0.010	0.010	0.009



F. 3D Image



71-Head with front position in dist. 0mm on Channel 149 in IEEE 802.11n U-NII

SAR Measurement at U-NII-3 (Cheek, Right)

Date of measurement: 18/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.11
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	U-NII-3
Channels/Frequency	Lower (149)/ frequency 5745.000 Mhz
Signal	IEEE 802.11 n

B. Permittivity

Middle TX Frequency (MHz)	5745.000
Relative permittivity (real part)	35.188
Relative permittivity (imaginary part)	16.374
Conductivity (S/m)	5.249

C. SAR Surface and Volume




Maximum location: X=3.00, Y=-17.00 ; SAR Peak: 0.59 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.061
SAR 1g (W/Kg)	0.169
Variation (%)	1.620
Horizontal validation criteria: minimum distance (mm)	11.313
Vertical validation criteria: SAR ratio M2/M1 (%)	48.171

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	0.277	0.164	0.079	0.035	0.030	0.006	0.010	0.010	0.004	0.009	0.013	0.013



F. 3D Image



72-Body with back position in dist. 10mm on Channel 149 in IEEE 802.11n U-NII

SAR Measurement at U-NII-3 (Body, Validation Plane)

Date of measurement: 18/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.11
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	7x7x12, dx=4mm dy=4mm dz=2.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	U-NII-3
Channels/Frequency	Lower (149)/ frequency 5745.000 Mhz
Signal	IEEE 802.11 n

B. Permittivity

Middle TX Frequency (MHz)	5745.000
Relative permittivity (real part)	35.188
Relative permittivity (imaginary part)	16.374
Conductivity (S/m)	5.249

C. SAR Surface and Volume




D. SAR 1g & 10g


SAR 10g (W/Kg)	0.116
SAR 1g (W/Kg)	0.291
Variation (%)	1.660
Horizontal validation criteria: minimum distance (mm)	14.422
Vertical validation criteria: SAR ratio M2/M1 (%)	53.696

E. Z Axis Scan

Z (mm)	0.00	2.00	4.00	6.00	8.00	10.00	12.00	14.00	16.00	18.00	20.00	22.00
SAR (W/Kg)	0.776	0.460	0.247	0.124	0.063	0.037	0.031	0.009	0.011	0.010	0.004	0.005



F. 3D Image



73-Head with front position in dist. 0mm on Channel 39 in Bluetooth

SAR Measurement at Bluetooth (Cheek, Right)

Date of measurement: 14/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.40
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Right head
Device Position	Cheek
Band	Bluetooth
Channels/Frequency	Middle (39)/ frequency 2441.000 Mhz
Signal	Bluetooth

B. Permittivity

Middle TX Frequency (MHz)	2441.000
Relative permittivity (real part)	38.759
Relative permittivity (imaginary part)	13.383
Conductivity (S/m)	1.735

C. SAR Surface and Volume




Maximum location: X=-27.00, Y=7.00 ; SAR Peak: 0.10 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.038
SAR 1g (W/Kg)	0.066
Variation (%)	-0.180
Horizontal validation criteria: minimum distance (mm)	16.000
Vertical validation criteria: SAR ratio M2/M1 (%)	65.714

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.098	0.070	0.046	0.029	0.019	0.010	0.005



F. 3D Image



74-Body with back position in dist. 10mm on Channel 39 in Bluetooth

SAR Measurement at Bluetooth (Body, Validation Plane)

Date of measurement: 14/6/2025


A. Experimental conditions.

Probe	0125-EPGO-445
ConvF	1.40
Area Scan	dx=8mm dy=8mm, Complete
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5.0mm, Complete
Phantom	Validation plane
Device Position	Body
Band	Bluetooth
Channels/Frequency	Middle (39)/ frequency 2441.000 Mhz
Signal	Bluetooth

B. Permittivity

Middle TX Frequency (MHz)	2441.000
Relative permittivity (real part)	38.759
Relative permittivity (imaginary part)	13.383
Conductivity (S/m)	1.735

C. SAR Surface and Volume




Maximum location: X=8.00, Y=-43.00 ; SAR Peak: 0.03 W/kg

D. SAR 1g & 10g


SAR 10g (W/Kg)	0.013
SAR 1g (W/Kg)	0.020
Variation (%)	0.540
Horizontal validation criteria: minimum distance (mm)	22.627
Vertical validation criteria: SAR ratio M2/M1 (%)	66.667

E. Z Axis Scan

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.028	0.021	0.014	0.010	0.007	0.003	0.001



F. 3D Image




ANNEX D SAR Test Setup Photos


Reference Photo: simulation liquid depth 15.9cm




Reference Photos




Left Head - Cheek



Left Head - Tilt



Right Head - Cheek



Right Head - Tilt



ANNEX E EUT External and Internal Photos

Please refer to RF Report.

ANNEX F Calibration Information

Please refer to the document "Calibration.pdf".



BTF Testing Lab (Shenzhen) Co., Ltd.

F101, 201 and 301, Building 1, Block 2, Tantou Industrial Park, Tantou Community, Songgang Street,
Bao'an District, Shenzhen, China

www.btf-lab.com

--END OF REPORT--